

#### VOLUME XI.

NEW-YORK, DECEMBER 23, 1855.

WEISSENBORN'S PATENT WATER PURIFIER FOR

### NUMBER 15.

#### THE Scientific American, PUBLISHED WEEKLY

At 128 Fulton Street, N. Y. (Sun Buildings.) BY MUNN & COMPANY.

UNN, S. H. WALES, Federhen & Co., Boston. Dexter & Bro., New York A. Winch, Philadelphia. E.E. Fuller, Halifax, N S. A. G. Courtenay, Charleston. S. W. Pease, Cincinnati, O. Avery, Bellford & Co., London MM.Gardissal & Co., Paris

Responsible Agents may also be found in all the princi pal cities and towns in the United States. Single copies of the paper are on sale at all the periodi

cal stores in this city, Brooklyn, and Jersey City. TERMS--S2 a-year,--S1 in advance and the remain der in six months.

#### Water Purifler for Steam Boilers.

The accompanying engravings represent the apparatus for depositing the mineral and other matter contained in water, for which a patent was granted to Gustavus Weissenborn, of this city, on the 16th of January last.

Fig. 1 is a longitudinal vertical section of the apparatus. Fig. 2 is a horizontal section through the large cylinder, A B, and fig. 3 is a plan view of the spiral exhaust chamber. The nature of the invention consists in the method of depositing mineral or other foreign matter held in solution in water, by heating the hard water by steam, and causing it to trickle or flow over an extensive surface of stones, twigs, and similar substances, and thus deposit the earthy or mineral substances in the water by the agency of heat, and the great extent of surface over which the water is made to flow.

b, fig. 3, is a pipe for introducing the steam. eis a pipe through which the hard water to be purified is injected in fine jets. fff is the spiral channel through which the commingled water and steam pass to the center, 2, where they enter, in a fine shower, into the large cylinder, A B, and through brushwood, H, in fig. 1, between which and the sides of the cylinder, an open space is preserved, by four upright pieces of wood, at equal distances apart, and kept in their position by iron rings, 2'. The heated water flows from the brushwood into a sheet iron case, K, containing horse manure, through which it passes into the nterior cylinder, which is a brass sieve, K', thence to the lower receptacle, which is placed in the ground, and can be made of wood. In this the water ascends from the bottom through pebbles or small stones, L, as shown by the arrows, fig. 1, then falls and rises again through pebbles in separate compartments, from which it passes to the reservoir, and is thence drawn off by a feed pump attached to the pipe, M. C is an exhaust relief pipe; g is the cover of the apparatus, and v represents a float to regulate the admission of water.

This is a close apparatus, and it will be un derstood that it is connected with a steam engine, the exhaust steam of which is injected into it, to heat the cold hard water which is admitted through the pipe, e, as has been described. The object of it is to deposit all the matter held in solution in hard water, on the brushwood, pebbles, &c., so as to render it pure previous to its being used in the steam boiler, and thus prevent it forming incrustations therein, the very principle recommended some years since in our columns to be employed in the limestone districts of our country for steam boilers, and which Mr. Weissenborn has here ingeniously carried out into practice. The annexed engravings represent an apparatus, designed for Messrs. Stillman Allen, & Co., of the Novelty Works, this city for an engine of about 100-horse power, and is about 2 feet 8 inches in diameter, and 5 feet high. with a tank or reservoir below ground of 5 feet long, 3 feet wide, and 2 feet deep.

The pumps force the hard water into the purifier, and steam from a boiler, or the exhaust steam from the engine is admitted, in sufficient



point. These come in contact in the upper | contained in a coarse mat or sack, then falls part of the apparatus, at the entrance to a coil of pipe, which may be of 20 to 40 feet in length, and is arranged in the spiral form, to it flows freed of its mineral matter, as deeconomise space, and afford greater friction scribed, into the reservoir, and thence by the than a straight smooth channel. The wateris admitted through a sliding strainer, which di- plus steam from the apparatus is carried off to vides the stream into numerous fine jets, thus insuring a more complete commingling with the steam, the force of which drives it with the salts contained in the water is set free, and great velocity through this winding channel; thence it runs to the perforated basin, where it channel, and upon the twigs and stones, or is showered over and trickles through the whatever substitutes for them it may be most brush; from this it filters through horse manure, charcoal, or other suitable substances itate at the bottom.

and rises through the pebbles, L, placed in two or three compartments of the tank, from which feed pump is conveyed to the boiler. Any surthe air, or to a condenser.

At each stage of the process, a portion of deposited in the purifier, chiefly in the spiral convenient to use, and also as a muddy precip-



Due provision is of course made for opening | ime and magnesia. Heat expels from water the different parts of the apparatus, to remove its free carbonic acid, without the presence of the mineral and earthy matter from time to which the carbonates of lime, &c., are insolutime-about every three or four months, we are | ble, consequently, when the acid is expelled, told.

quantity to heat the water to about boiling steam boilers are of carbonate and sulphate of tration of these salts, likewise brings them in for home consumption."

these matters are precipitated. The evapora-The most common incrustations formed in tion of the heated water, causing a concen-

excess of the power of the water to hold them in solution, and also tends to the same results -their deposition. This is the philosophy of the process. But these agencies alone are insufficient to effect the separation of all the mineral matter before the water enters the boiler. To complete the process, the violent agitation of the water, its subdivision into small streams, and, in this state, meeting with, and percolating or trickling through, a mass of material presenting a great extent of surfaces for contact; all have to perform their part. As a further security for the desired result, horse manure, charcoal, or other matter, may be used, the object being, by the operation of their chemical affinities, to precipitate any solid matter which may chance still to have remained in solution.

The joint action of these principles purifies the water of its incrusting salts before it comes to be used in the boiler, leaving them deposited in the apparatus, where they are of no detriment.

This Incrustation Preventor requires but little space and attention, and it may be made quite a neat and ornamental attachment to the engine, while its utility as a heater is also selfevident. The impracticability of using the ordinary heaters for hard water, on account of the frequent bursting of the feed pipes from incrustations, renders this apparatus very valuable for some districts in our country. At the same time its services as a condenser are also deserving of attention. The form of this apparatus can be varied to suit the requirements of parties using it. The manifold evils resulting from the formation of incrustations in steam boilers, are well-known to all our readers, and need not be further alluded to at present. An efficient and simple remedy has long been a desideratum. Mr. Weissenbornwho is a mechanical draughtsman and engineer-has devoted much attention to the subject, and has invented this apparatus, and practically tested it. It is now attracting considerable attention in this city, and is here presented so that the public may have an opportunity of judging for themselves of its merits. More information may be obtained of E. W

Sargent, Delmonico's Hotel, Broadway, N. Y. Saltpeter.

Dr. A. A. Hayes, in a communication to the Boston Atlas, suggests a plan by which the present scarcity and high price of saltpeter may be in a great measure obviated. He proposes to import nitrate of soda, which is a natural product, found in the district of Atacama, South Peru. He says, "As the price of nitrate of soda at the port of shipment, is to a large extent made up from the cost of fuel consumed in refining (the country is a desert,) and the expense of transportation, it is apparent to every one, that under judicious arrangement, these charges might be much reduced, and either the crude or refined article delivered at the shipping port, at a cost much less than at present. During the last ten years, the cargo price of nitrate of soda at this port has not much exceeded two-thirds the price of the first quality of saltpeter, and it is now less than half that price. Nitrate of soda, in its dry and pure state, is composed of anhydrous nitric acid 63.53, and anhydrous soda 36.47 parts in a 100. As the nitric acid in 100 parts of saltpeter weighs 53,21, one hundred parts of nitrate of soda should afford nearly one hundred and nineteen parts of saltpeter, by exchanging its soda base for an equivalent of potash. This change can be easily effected by means of salts of potash, when salts of soda are produced on one hand, and saltpeter on the other. Salts of potash abound in wood ashes, and where wood ashes can be obtained, or any salt of potash cheaply, we may at once compete with India in the production of saltpeter

# Scientific American.

COURCESSION CONTRACTOR CONTRACTOR SHARE THE SHARE THE SHARE

114

[Reported Officially for the Scientific American.] LIST OF PATENT CLAIMS Issued from the United States Patent Office FOR THE WEEK ENDING DEC. 11, 1855.

For the week ending bec. 11, 1835. BLEACHING lyong-Wm. M. Welling, of Brooklyn, N. Y., I claim the method described and shown, of bleach-ing ivory plates, by so placing and sustaining them on their edges, in a suitable case, that the sun's rays shall act with uniform power and bleach said plates equally on loth sides, in the manner and as specified, thereby dis-i e .sing with the usual method of turning the plates over, to expose, alternately, the flat sides to the action of the light, and prevening warping ordamage to the ivory, and ar on light ing said bleaching operation in far less time. and .nore perfectly.

FOLDING AND MEASURING CLOTH—James Baxendale, of Providen e, R. 1. 1 claim, first, the employment of separate rods, b, b' b', for the several folds of the cloth, the said rods being arranged and operated to fallacross the successive layers of the cloth, as they are laid, by the movements of a suitable reciprocating carriage over the fuding table, and to remain within the folds till the fold-ing of the whole piece is completed, substantially as set for the substantial the reciproced substantially as set

forth. Second, the manner of operating the said rods, b b, b' b', to throw hem from their upright positions, across and upon the cicth, by means of the nut, JJ, and the screws, IT, which are actuated by the movements of the recipro-caung carriage, substantially as described. [Fhe cloth passes from a roller on which it is wound through a reciprocating carriage; the latter moves back

and forth over a horizontal table which receives the cloth; at each movement of the carriage a hinged rod drops from the machine into the fold made and remains in the crease until the whole piece is finished; there is a rod for each crease; when the piece is all finished it is drawn off from the rods, and the latter thrown back for use again. The machine works with certainty : it is quite simple in its operations and might we think be introduced with great success in all establishments where large quantities of goods are to be put up. By the attachment of a register-ing a part is the exact length of the cloth folded might be unerringly exhibited. B. B. Babbitt, Esq., of Provi

be interingly exhibited. B. B. Babolit, Esd., of Frovi dence, is assignee of one half of this patent.] BOOT AND SHOE PEG CUTTERS—H. E. Chapman, of Albany, N. Y.: I claim the making of shoemakers' floats or peg cutters with plaining cutters, substantially as the same is set forth and described.

same is set forth and described. FOUNTAIN INKSTAND—C. T. Close, of New York City. I clain the arrangement and combination, substantially as specified, of the upper tute or passage, b, connecting the top or air space of the reservoir with the pen cup at or mmediately below the level the ink is designed to stand in said cup, the latter heing convected with the re-servoir, in manner shown or equivalently thereto, and the ink in the pen cup, forming a fluid valve, that upon the insertion of the pen, and withdrawal thereo; alter-nately opens and closes the lower end of the upper con-fresh air, at intervals, in the reservoir, as required.

fresh air, at intervals, in the reservoir, as required. WATER GAUGES FOR STEAM BOILERS.—Josephus Echols, of Columbus, Ga.: Although I have described the glasses on each side as being attached to nuts in frames, which can be removed, I do not wish to limit myself to this, as glasses on one side may be secured directly to the gaugetube and be got at for the purpose of cleaning, when the glass or glasses are removed on the other side. Nor do I wish to be understood as limiting myself to the special mode of construction specified, as other equivalent modes may be substituted. I claim making gauge tubes for indicting the hight of water in steam boilers with an aperture provided with convex glass, presenting the convex or arched surface to the pressure in the tube, substantially as, and for the pur-pose specified.

GAS APPARATUS—John S. Gallaher, Jr., & John W. Smith, of Washington, D. C. Disclaiming all and every part of our apparatus taken individually, we claim, solely, the arrangement of the said parts, and specifically of the retort, X, with Hooke's blow-pipe, C, combined with the furnace, a aa a, the water reservoir, b b, the strain-er, K K, the receiver, m m, in the mainter as specified, and for the purpose of constituting a compact and portable gas generating and purifying apparatus.

RAILROAD CAR SPRINGS-P. G. Gardiner, of New York City: 1 claim my improved car spring composed of a coiled plate spring combined with a segmental base, and a movable segmental cap, substantially as set forth. [This invention consists, first, in a volute spring com-

posed of a flatstrip of metal arranged to receive the force or weight in a direction parallel with the axis of the vo lute A weaker spring of any suitable form and materia is introduced into the center of the volute spring, for the purpose of giving a support to both ends of the volute at t e same time, and thereby effectually preventing the occurrence of a fracture through any sudden coc us; ion

The invention consists, secondly, in encasing the volute spring within a double bed, which, while it yields to every movement (f the spring, forms an efficient guide to preventany lateral movement, and also protects the spring from dust. At the late fair at the Crystal Palace, we saw some tests of this invention made, which satisfied us that it was an important and valuable improvement.]

TILE ROOFING --Gottlieb Graessle, of Hamilton, O.; I claim the construction substantially as described, of tile roofing, having each over-lapping edge, a., resting by an angle only, upon the flat subjying surface, b, b:tween the ridges, c d, of the adjacent tile, and having two transverse ridges, e, n, projecting from the suberjacent under sur-faces of the tier next above, for the purposes explained,

faces of the tier next above, for the purposes explained, RAKING AND LOADING HAY—John K. Harris, of Al-lensville, Ind.: I do not claim any form of attachment to the wagon, or the manner of forming the spring of the rake teek, or any continued erdless tell motion, with an ordinary rake attached behind, to save the hay, passed over by the endless bit lelevator. But I claim, in combination with the rake, for the pur-pose of taking the hay from the rake in regular succes-sive intervals of time, and in separate parcels, and ele-vating and delivering it on the wagon, substantially in the manner and for the purpose as described.

BEDSTEADS-Benjn. Hinkley, of Troy, N. Y.: I do not

claim the cross springs as a means of support. Hut I claim the cross bars, whether springs or not, for the support of a bedstead frame, when the same are mounted upon a pedestal and stand, as set forth.

ATTACHING EXTINGUISHERS TO LAMPS—F. A. Jew-ett, of Abington, Mass. I claim attaching the cap or ex-tinguisher to the lamp by means of a spiral syving, coiled around the wick tube, and secured at one each to the cap, and at the other to the screw plate, c, or in any other con-venient locality, where's the cap is tightly drawn down over the wick, as described.

User the wick, as described. Locks for F PEIGHT CARS—Henry C. Jones, of New-ark, N. J.: I c aim combining with the double jaw spring bolts of a lock, and with the levers, by which the jaws are opened, by the action of the key, as specified, a stop tumbler, substantially such as described. Operated by the key, after the jaw bolts have been opened, to hold and keep them opart, after the key is taken out of the lock, that the lock may be employed as a stop or dead bolt lock, as specified.

IMPACT WATER WHEEL—Athison Queal, of Plymouth, N.Y.: I claim the sliding buckets. H II, placed on the head, D, of the wheel, and operated by the inclined semi-circular rod, J, in comination with the partition, L, ar-ranged as shown and described. If urther claim attaching the wheel, C, to the shaft, G, by means of the pins, c c, fitting in the hub, h, the pins being attached to a ball, d, on the shaft, for the purpose set forth.

[The above is a horizontal water wheel, the buckets of which are movable, being made to rise and fall, alternately, on the reception and discharge of the water. The novel feature consists in the peculiar method of causing the buckets to move instantly and at the proper moment. An engraving would be required to exhibit the moving parts correctly. The inventor states that in this wheel the full force of the water is brought against the buckets sud denly, at the right time, without any back pressure, and that the force is continued until the moment of discharge. The exit of the water, which is permitted by the raising of the buckets, is free and quick, without any drag. It is te-lieved that the wheel will afford a greater per centage of power than any other of its class. Its construction is no expensive.]

CORN SHELLERS-James J. Johnston, of Alleghany City, Pa., I claim the secondary cleaners or pickers, f, revolved around the cob, as the cob is projected by the main cylinder, c, through the opening in the case, a, of the machine, substantially in the manuer and for the pur-pose described.

SAND FAPER MAKING MACHINES-Gilbert D. Jones, of Jersey City, N. J. 1 claim, first, applying the sand or grit in a heated state, to the glued surface of the paper, for the purpose set forth. Necond, the method of depositing the sand upon the glued surface, that is to say by projecting it forcibly against said surface, while insuch reversed position that the ex-cess shall fall off by gravity, as described. Third, the combination of the stationary pieces, or their equivalent, with the moving dram, the paper, and the glueing roller, for the purpose set forth.

the glueing roller, for the purpose set forth. CUTFING OUT, PUNCHING, AND STAMPING THE SOLES AND HEELS OF BOOTS AND SNORS—Jean Pierre Molliere, of Lyons, France. Patented in France, July 22, 1353 i claim the cutting out of soles and heels by the blades, a a a ad bb, from strips of hammered or other leath-er, sliding between the guide pieces, rr, and the'd in place by the stoppers,  $\mathbf{x}$ , the pricking and stamping of the heels and soles, so cut out by the awls, d, and the stamp, e, at the same time, the three operations being performed at one stroke, the detaching from the blades and awls of the pieces cut out, pricked, and stamped, by the detach-ing rods, m m and o, and the adjustment of the eccentrics upon the shaft, L, in such manner that two of the punch-structed and operated substantially as described.

structed and operated substantially as described. PROCESSES FOR CALICO PRINTING—Robt. Prince, of Lowell, Mass., and Ambrose Lovis, of Boston, Mass. We are aware that pure silicate of soda alone, or with pure carbonate of soda, has been used herebore in dunging; and we are also aware that silicate or lime has been used for the same purpose. We disclaim the use of these sub-stances. Confining ourselves to the use of the silicate, in mixture with neutral and alkaline saits. We claim the manufacture of silicate of soda, or potash containing foreign neutral salts, and the use of this com-pound with carbonate of soda and neutral salts, in dung-ing operations, substantially asset forth.

SAWING MARDLE, &C., IN TAPER FORM-Geo. T. Pearsall, of Apalachin, N.Y.: I do not claim the adjust-able bars, II, irrespective of the mode of operating them nor do I claim the laterally moving saws placed within a reciprocating saw frame, for they have been previously used

But I claim the employment or use of the levers, C K. But I claim the employment or use of the levers, C K. the levers, K, being connected to the sockets. I, of the bars, H, and the uprights, f, of the framing, A, and the levers, C, being attached to the frame, B, and the framing, A, substantially as shown, for the purpose specified.

[The nature of this invention consists in the employ ment of cross levers attached to the saw frame guides, and also to the horizontal frame on which the saw frame works, for the purpose of causing the saw frame guides to be moved laterally in a perfectly vertical position, and at the same time enabling the horizontal frame to work up

and down in a horizontal position. The machine is intended for simultaneously sawing two sides of a block of mar ble on a taper.] BUCKLES—Sheldon S. Hartshorn, of Orange, Conn. : I claim constructing the tongue, s, and loop of the buckle in one part, and at one operation, in such a manner thuit the socket, a fig. 3, will firmly secure the joint b, in the other part, fig. 2, so as to need no other fastening, as described.

MOSQUITO CURTAINS—John S. Martin, of Boston, Mass.: I claim the mosquito curtain, as made of two bars, a sheet of cloth or netti g, and a series of elastic bands, arranged and applied, and so as to operate together, substantially as set forth.

ADJUSTING CIRCULAR SAWS OBLIQUELY TO THEIR SHAFTS-AMOS D. Highfield, of Philadelphia, Pa, as signorto himself and Wm. H. Harrison, of same place : I do not desire to claim the exclusive use of oblique circu-lar saws for cutting grooves, as such are well known. But I claim the employment of two beveled washers between a fixed collar on the spindle and the circular saw, in the manner and for the purpose specified.

CORN SHELLERS-J. P. Smith, of Hummelstown, Pa.: I claim the construction of the frustums, D and C, with their winding wings, d d, upon both and cross projections, c c, upon one, substantially in the manner and for the pur-poses set forth.

CARVING WOOD, &c.-I. M. Sinzer, of New York City: Ido not limit myself to the special construction or ar-rangement of parts specified, as these may be varied with-out changing the mode of operation of my invention. I do not claim the combination of the tracer with the tracer which carries the block of wood to be carred, by means of one system of pentagraph levers, as this is de-scribed in a patent granted me on the luth day of April, 1319. But I claim combinization

1319. But I claim combining the tracer with the table which carries the block of wood to be carved, by means of two systems of pentagraph levers operating at right angles with each other, substantially as described, whereby the block to be carved will be directed and presented to the action of the cutter, in such manner as to determine the configuration as well in a vertical as in a horizontal direc-tion, as set forth.

tion, as set torth. SLIDE VALVES FOR STEAM EWGINES—E. D. Leavitt, Jr., of Lowell, Mass. : I claim making the valve and the corresponding parts of the steam ch.\*st, between which it works, of tapering form laterally, and fitting the valve to its rod, in such a manner as to be capable of lateral move-ment, sub-tantially as descrified; whereby the valve is al-ways kept tight between the seat and the back of the steam chest, by the pre-sure of the steam, and the wear-ing of the rubbing surfaces is always compensated for.

[In carrying out this invention the back of the valve is fitted to the cover of the steam chest, between which and its seat it works steam tight. The improvement consists in a certain method of compensating for the wear of the valve and the two faces between which it works. There is an arrangement whereby the valve is more perfectly balanced than by the ordinary method. The valve is made tapering in a transverse direction, but in a longitudinal direction its two faces are parallel. By thus taper-ing the valve, one of its sides is caused to have a greater area than the other, and the steam, by exerting a greater pressure on the larger area, tends to force the valve be tween the faces in which it moves, and thus keeps it always tight. It is a good improvement.]

MANUFACTURE OF CANNON.—Daniel Treadwell, of London, Eng. : I do not claim using hoops generally, it making can on, as the earliest cannon known were form-ed, in part, by hoops brazed upon them. But my invention consists in constructing cannon with hoops around, and shrunk upon a body, in which the cal-iser is formed, in the manner described

CARRIAGE HUBS-S. W. Reed, of Berkshire, N. Y.: I am aware that a loose di-k brace, or flange, has been used to support the spoiles of a wheel, mounted on and sup-ported between theiwo flanges of a hud, and having re-cesses to receive the lorked tenon of a spoke, formed by a saw cut, into which the disk is fitted, such a hub I do not claim, as that has been patented by J. B. Haydon. But I claim the arrangement of the dodg: d morti-es, D. formed on both ides of the perma: ent projecting flange or brace, C. by the triangularly-shaped projectio.s. A. radiating from the tule, B, for the reception of the spoke tenon, S, where y a douller row of spokes may be insert-ed in the hub, and supported by the flange, U, in combi-nation which the nuts, H, to tighten or lock the -pokes, a d by which a Lr. ken or worn-out spoke may be removed and a new one inserted in its place, without uniting the wheel, as described.

Wheel, as described. CUTTING ARTICLES FROM LEATHER—Chas. Rice, of Boston, Mass., and S. H. Whorf, of Roxbury, Mass. We lay no claim to any of the devices or comlinations co-tained in the machines described in patents Nos. 6,055 and 12,128. But we claim combining the cutting die with the platen by means of a rotary and adjustable plate, L, in combina-tion with so applying ite pack clamp to its pitman, that it may turn thereon when the die or cutter is revolved in the manner and tor the purpose as specified. We also claim the descri.ed arrang, ment of the opera-tive mechanism of the pack clamp, and that by which the cutter is either depressed or elevated.

cutter is either depressed or elevated. ATOGER HANDLES—Guillaume Henri Talb't, of Boston, Mass. Patented in England Aug. 25, 1355 : I do not claim the man.er described of giving a revolving action, in either direction, to the auger bit, or bori.g tool, by revre-sible pawls and ratchets, opera.ing i.a connection with a vibrating hundle apart from the relait we arrangement and form of handle specified, as such is common to drill stocks. Ibut I claim in gimlet or auger ha.dies, the arrangement substantially as specified, within the body of the said handle, which crosses the lit of the ratchets, a b, and pawls, a'b', wich their reversing gear, for o, ceration of the bit, or bit socket, in either direction, either by a revolving or vibratory action of the gimlet handle, on pre-sure of the hand, applied on both sides of the axial line of the bit and under the usual clutch of the handl on the handle over the center line of the lit, and whereby the actuating pawls, ratchets, and accompanying devices, form no ob-struction, and prisected from injury or derangement, es-sentially as set torth. [In this improvement there is a double ratchet move-

[In this improvement there is a double ratchet move-ment, contained within the handle of the tool, which enables the operator to revolve the gimblet without removing hishand from the handle. In confined places, where here is not room for turning the handle, and, is deed, in allplaces and positions this improvement will be found very convenient. There is a reversing catch, by pressing which the direction in which the tool turns is changed. All the moving parts are contained within the handle, which, in external appearance is the same as those in ordinary use. The invention is applicable to augers, screw drivers, and a variety of tools. Patented in the United States and Europe through the SCIENTIFIC AMERICAN Patent Agency.]

Distribution of the second second

with the velocity of the rollers and pich of the spiral grooves. Pith, I claim the carrier, x, operating substantially as described, first, to move forward to receive the ring in its fork, then moving quickly upwards, to snatch the ring from the box, and alterwards dragging the rig along the plate, which contains the elongating mechanism, till it comes in contact with one of the elongating posts, or its equivalent, as is thereby taken from the fork of the car-rier.

to the second se

[The chain made by this machine is not like that in common use, but is of a peculiar kind, which may le called "double link chain;" it is made, not of pairs of links, but strictly of double links, each consisting of only one piece of metal. The links are faggoted and welded lefore being put into the chain, and to make them enclose each other, only require to be bent. It is in a great measure owing to the manner of making the links which gives this chain the superiority which it is claimed to possess over the common kind of chain. This machine performs the whole of the process of making the chain from the forging of the links to putting them together. The first operation which takes place at one end of the machine, is that of winding up a small piece of small flat iron rod till it forms a coil of several thicknesses of metal This coil is taken to a proper fire and heated to a welding heat, and then put in another part of the machine, by which it is welded into a ring which is equally strong at all points. From the last-named part of the ma chine the ring is taken by automatic devices to another part, where it is elongated in one direction and closed in a direction at right angles to it, till it forms a link which resembles the figure 8, except that the two sides do not cross in the middle. It is then taken by other devices and bent at the middle of its length, and then, by hand, put through another link and placed in another part of the machine, by which its looped extremities are drawn close together, which finishes it. The next link passing through these looped ends secures them, and thus the chain is formed All the operations are performed with great rapidity. The invention is regarded as one of great value and im portance. American and European patents have been secured through the Scientific American Agency.]

Емвоззер Leather—Israel Amies, of Philadelphia Pa.: I wish it to be understood that although I have de-Pa. I wish it to be understood that although I have de-scribed one particular process of treating veneers, before my improved art of embossing is practiced thereon, I do not desire to confine myself to that process in every mi-nutia, as the same may be modified, or equivalents sub-stituted. But I claim the employment of embossing veneers, in the construction of furniture, and for other ornamental purposes, in the manner set forth.

PIANOFORTE ACTION-Fran' is Taylor, of New York City I do not c aim the button, m taking the second knuckle of the hammer but, as this has been used as an attachment to the key. But I am notaware that this button, m, has ever before been made as a permanent attachment to and movi. g with the fly of the jack in the man.er, a.d as specified, whereby the fly of the jack is held to the knuckle; 3, by the tutton, m, to clear the knuckle, 2, and also replaces the said fly of the jack beneath said knuckle; 4, imme-diately that the key is released and the hnumer de-cends but a short distance, producing an instantai.eous and uni-form repeating action. There.ore, i claim the regulating button, m, permanent-ly connected to moving with and governing the fly of the jack in its action on the lutt of the hammer, the whole arranged and operating substantially as specified. PACKING PISTONS FOR STEAM ENGINES-Joel W.

arranged a.d operating substantially as specified. PACKING PISTONS FOR STEAM ENGINES-Joel W. Pettis, of lillsdale, Mich.; I do not claim the forcing out of the racking ty means of radial arms within the piston, when the said arms have only a sliding rectilinear move-mei.t produced by cones at the center, as such have here-tfore been used, a: I consider that arrangement i.fe-rior to, or more likely to get out of order than, and not so easily adjusted, as the arrangement of the arms to work, as descrift ed. But I claim the arrangement and application of the arrus, F F, substantially as described, between the pack-ing rings and a movable center bearing, whether the said center bearing be movable, to adjust or tighten the pack-ing by means of a ce.tral rod passing through a hollow rod, or by other means.

[Mr. Pettis' improvement is intended to enable the engineer to tighten the packing of the piston, without going to the trouble of removing the cylinder head and various other appurtenances. This is done by making the piston rod hollow and passing a solid rod down its center to the piston head. The packing is metallic; wi hin the head are four arms, connected by joints at one end with the packing, and at the other with tho central rod before named by raising or lowering the rod the packing will be loosened or tightened; the engineer, therefore, when he desires to move the packing, merely turns a nut at the top of the pis<sup>2</sup> ton rod. The advantages of this improvement are obvious.]

CUTTING CLOAKS—A. S. Thompson, of Albion, Pa. : I claim cutting a cloak from a seamless cloth, without sleeves, but so that by making four cuts of the proper length for the sleeves, the cloak may le worn as a sleeved sack or overcoat, by merely chan ging the buttonings, sub-stantially in the manner described.

HARVESTER RAKERS-John W. Haggard & Geo. Bull, of Bloomington, Ill., assignors to Bull, flaggard, & News-teter, of same place. We claim the plate o, having its in-cil. ed and par. Hel planes on the same sides, in combina-tion with the pin, z, bar, J, spring, I, and pin, R, the whole being constructed, arranged, and operating as described.

Leing constructed, arranged, and operating as described. ROTARY PUMPS-C. D. Wright, of Fort Atkinson, Wis. : l claim the construction of the pump as show., viz., having the hollow sphere, C. placed within an inclined or oblique shell, B, which forms the body of the pump, the sphere being attached to a hollow shaft, E, at one wide, and communicating with a section pile, A, at its opposite side, two opposite sides of the sphere leing also divided into two compartments, b c. one of which, c. com-municates with the suction pipe, A, and the other, t. with the force pipe or hollow shell, E, the sphere having a flanch, D, attached to it, which divides the shell or body, B, into two compartments, e f, and the flanch having a piston, G', working in it, at each side of which, a gertures, B, are made in the sphere, C, the above parts being ar-ranged substantially as shown, and for the purposes speci-fied. In this improvement a hollow shere having two

[In this improvement a hollow sphere having two compartments is fitted within a shell placed in an oblique position, the shell being attached to a hollow shaft, which serves as a suction pipe, the sphere also attached to an-other hollow shaft, which serves as an exit pipe. The sphere has a flanch around it; which divides the shell into two compartments, and the flanch is provided with a piston operating in such a manner that as the hollow sphere rotates, the water is drawn through the suction pipe into one compartment of the sphere and forced into the other compartment, and through the exit pipe. The pump of crates with but little friction, is simple, and may be cheaply manufactured.]

promp operates with but little friction, is simple, and may be cheaply manufactured.] RUBBING TYPES- Daniel Moore, of Brooklyn, N. Y., assignor to Geo. S. Cameron, of Charleston, S. C., James H. MCWilliams, of New York City, and Daniel Moore, aforesald: 1 claim, first, constructing the since, i, with openings to receive the type at such an angle, relatively, with the direction which said slices move, that the cut-ters shall commence to act at the latter end of the type, carried by said slices and that the cutting operation shall end to force the type in the latter end of the type, carried by said slices and that the cutting operation slices and thereby relain the type in place in said slice in the man-ner and for the purposesspecified. Second, 1 claim constructing the slice, i, in such a man-ner, as at v, that the power to torce the type in an end-ways direction, or nearly so, through the cutters, shall be applied to, or near the middle of the Lottom end of the type, in the manner and as specified. Tourth, 1 claim the iollower of slides, 8, and holding plate, 9, to supply the machine with a like of type, in the manner, and as specified. Fourth, 1 claim the ifter, 12, combined with the gauge fingers, i, and end of the plate, 9, or other stop, for the purpose of elevating one type at a time, to be taken by the sices as specified.

VARIANLE CUT-OFF GEAR FOR STEAM ENGINES-Wm. W. Wade, of Springfield, Mass, assignor to Wad. & Burnham, of same place: 1 claim the arrangement of the induction and cut-off cams upon two parailel shalts, to operate in a yoke frame containing two separate yokes, one tefore the other, substantially as described.

[This invention consists in certain improved mechanism by which such a movement may be given to a common single slide value as to make it cut off the steam at any point, from one-eighth to seven-eighths of the stroke. It is a very good improvement, and reflects credit on the inventor. Without drawings its parts cannot be well deinventor. scribed.]

RE-ISSUES. RE-ISUES. MORTISING MACHINES-Jos. Guild, of Cincinnati, O., Patented originally Nov. 30, 1852: 1 claim, first, the slid-ing wrist, o, connected with the chisel, and also with the driving power, in the manner descrit ed, in comtinati an with the mechanism descrited, or its equivalent for slid-ing said wrist, so that the operator can, during the motion of the machine, vary the depth of cut of the chisel, or cause it to be suspended without disconnecting the driv ing power.

cause it to be suspended without disconnecting the driv ing power. Secondly, the combination in a mortising machine, substantially as described, of treadle and opposig spring, or weight, connected to a toggle, one end of which Leing pivote dto the frame, the other is pivoted to a sliding wrist upon a vibrating arm actuated by the power, the said wrist being slid out and in upon the arm with varying power and speed by the action of said toggle and its at-tached weight, or spring, and treadle, as explained, or their equivalents.

There equivalents. REAPING AND MOWING MACHINES—Saml. Rockafel-low. of Coatsville, Pa. Patented July 3, 1355: I claim raising and depressing the finger bar, K. and consequent-ly the cutter, ef, by means of the vertical bars, M. M. hav-ing wheels, oo, at their lower ends, arm. P. attached to the cross piece, N, of the lars, M. M. lever, Q, and shaft, R, with its arm. S, attached, the above parts being ar-ranged substantially as shown and described. I also claim supporting the ends of the stationary cut-ters, e, by means of the sockets or their equivalents in the knobs or projections, d, of the fingers, c, substantially, and for the purpose set forth and described. DESIGNS.

DESIGNS. PARLOR STOVES-Conrad Harris & Paul W. Zoiner, of Cincinnati, O. : Design for wood stove named "Parlor Gem."

CLOCK FRAMES—Jonathan C. Brown, of Bristol, Conn. : I claim the combination of the octagon form with the oval corner, as distinguished from some other form.

Sec.

PARLOR STOVES-Conrad Harris & Paul W. Zoiner, of Cincinnati, O. : Design for a parlor stove named "Car-SIX PLATE BOX STOVES-Conrad Harris & Paul W. Zoiner, of Cincinnati, O.

COOKING STOVE-Conrad Harris & Paul W. Zoiner, of Cinoinnati, O. Design named "Kanzas." STRAP HINGES-Enoch Woolman, of Damascoville, O.

NOTE-About one-third of all the American patents granted last week were obtained through the Sci ntific American Patent Agency. Several of the grants are for inventions of a very valuable and important nature, from which rapid fortunes will be made. To those who are longing to elevate themselves in the world, pecuniarily, we say invent, invent! There is not a surer way to business and fortune for individuals who are without capital, than patents. A good invention generally yields a cash return, and is often of more value than a California gold mine.

The present is an unusually favorable time for applying for pa ents. The Hon. Charies Mason is again in power, and the business of the Patent Office is being once more conducted with promptness and vigor. Applicants will not have to wait so long as formerly, before the result of their cases is made known

#### Prince Albert on Science and Common Sense

On the 22d of last month, at the laying of the corner-stone of the new edifice of the Birmingham Institute, England, Prince Albertwho was present, and whose health was drank at the dinner given on the occasion-made a speech, in which he, very sensibly, never alluded to the war, nor to political matters, but exclusively to the objects for which the building was designed, namely, scientific instruction. He said it was a pleasure for him to participate in a work of worldly wisdom in that great town, because it was one of the first public acway among the people of Britain, and destined to play an important part in its future developement (and the world in general,) viz., the introduction of science and art as the conscious regulators of human industry. The following short extracts from his speech are worthy of being engraved in letters of gold :

"In all our operations, whether agricultural or manufacturing, it is not we who operate, but the laws of nature, which we have set in operation. It is, then, of the highest importance that we should know these laws, in order to know what we are about, and the reason why certain things are, which occur daily under our hands, and what course we are to pursue in regard to them. Without such knowledge we merely go on to do things just as our fathers did, and for no better reason than because they did so-or improve upon certain processes by an experience hardly earned and dearly bought, and which, after all, can only embrace a comparatively short space of time, and a small number of experiments. From none of these causes can we hope for much progress; for the mind however ingenious, has no materials to work with, and remains in presence of phenomena, the cause of which are hidden from it. . . . . . . . . . .

But these laws of nature-these Divine laws-are capable of being discovered and understood, and of being taught and made our own. This is the task of science; and while science discovers and teaches these laws, art teaches their application. No pursuit is, therefore, too insignificant not to be capable of becoming the subject both of a science and and art. . . . . . . . . . . . . . .

No human pursuits make any material progress until science be brought to bear upon them. We have seen many of them slumber for centuries; but from the moment that science has touched them with her magic wand, they have sprung forward and taken strides which amaze and almost awe the beholder. Look at the transformation which has gone on around us since the laws of gravitation, electricity, magnetism, and the expansive power of heat have become known to us! It has altered our whole state of existence-one might say the whole face of the globe! We owe this each other. The eccentric is molded upon a to science, and science alone; and she has other treasures in store for us, if we will but call moved backwards and forwards across the quarries at Northbridge, Mass., a few days her to our assistance. It is sometimes object- axle by means of a handle, answering to the since, I had a conversation with the workmen ed by the ignorant that science is uncertain and changeable; and they point to the many through the medium of a pair of racks and the dust that they were rapping off with a flat exploded theories which have been superseded by others, as a proof that the present knowledge may be also unsound, and after all not worth having. But they are not aware that while they think to cast blame upon science, they bestow, in fact, the highest praise upon her. For that is precisely the difference between science and prejudice; that the latter keeps stubbornly to its position, whether disproved or not, while the former is an unarrest-

able movement toward the fountain of truthcaring little for cherished authorities or sen no false shame at her shortcomings, but, on the contrary, the highest pleasure when freed from an error, at having advanced another step towards the attainment of Divine truth. .

We also hear, not unfrequently, science and practice, scientific knowledge and common sense, contrasted as antagonistic. A strange error! For science is eminently practical, and must be so, as she sees and knows what she is doing; while mere common practice is condemned to work in the dark, applying natural ingenuity to unknown powers, to obtain a known result. Far be it from me to undervalue the creative power of genius, or to trea rewd common wose as thousenwihle ttrss st knowledge. But nobody will tell me that the same genius would not take an incomparably higher flight if supplied with all the means which knowledge can impart, or that common sense does not become only truly powerful when in possession of the materials upon which judgment is to be exercised. . .

No pursuit is too insignificant not to be capable of becoming the subjects both of a science and an art. The fine arts, as far as they relate to painting and sculpture (which are sometimes confounded with art in general,) rest on the application of the laws of form and labor, and what may be called the science of knowledgments of a principle daily forcing its the beautiful. They do not rest on any arbitrary theory on the modes of producing pleasurable emotions, but follow fixed laws, more difficult, perhaps, to seize than those regulating the material world, because belonging partly to the sphere of the ideal and our spiritual essence, yet perfectly appreciable and teachable, both abstractly and historically, from the works of different ages and nations." (Cheers.)

### **Recent Foreign Inventions.**

JOINING SLABS OF SHEET-IRON-A patent has been granted to Mr. Bertram, a practical engineer, employed in Woolwich Dockyard, Eng. as foreman. His invention consists of a process of firmly joining together slabs of sheetiron work for the purpose of making boilers, building ships, and erecting bridges, &c., without the use of rivets. This novel method of welding the iron instead of joining it by the rough means hitherto in use-that of riveting -is carried out by fusing the two edges of the plates to be adhered, and striking them simultaneously on both sides. By this means the structure is rendered materially lighter, and much stronger. Some experiments have been tested by order of the Lords of the Admiralty, in presence of the officers of the Dockyard, who are authorized to report thereon. The result of their deliberations will shortly be made known. It has been hitherto considered impossible to make an unlimited surface of iron; hence the system of riveting has been so far perpetuated.

A NEW EXPANSIVE VALVE MOTION FOR STEAM ENGINES was lately described at the Institution of Mechanical Engineers, by Mr. G. M. Miller, of Dublin. In this motion a single eccentric only is used on the driving axle; this works the rod of one of the valves direct, and the rod of the second value is worked by the eccentric through the intervention of a loose ring on the driving axle, having two arms projecting at right angles to each other, to one of which the second valve-rod is attached, the other arm being connected with the eccentric. huge proportions. The Vanderbilt is the larg-By this means a similar motion is given to both valves, but corresponding to the relative positions of the two cranks at right angles to transverse slide, which is capable of being gencer says :--- "While examining the granite ordinary reversing handle or lever, and acting who were dressing out the stone, in reference to pinions. By moving the transverse slides the piece of board from the face of the stone they ent. The patent was assigned to Mr. John throw of the eccentric is altered or reversed, were hammering. The dust is reduced in the thereby enabling the engine to be worked ex- hammering of the stone to an impalpable powpansively or reversed. A model of the new der, and will float in the air. I said to them motion was exhibited, showing it as applied to that it would be well to try the vegetating a locomotive engine; and the particulars were powers of this granite dust in a hill of corn. given of the successful working of the new They replied that it had been used in gardens motion in two engines upon the Great South- and on grass lands with great success, and ern and Western Railway of Ireland.-[Rail- that it was equal to the best manure. The way Gazette, London.

of Nowcastle-on-Tyne, has patented some imtiments, but continually progressing-feeling provements in steam engines, which consist of therefore be supposed to possess extraordinary an arrangement of trunk-engines in which the steam from the boiler is only admitted under the piston to perform the up-stroke, while it is  $\mathbf{m}$  d) to enter through a slide of a particular construction into the upper part of the cylinder, there to work expansively and perform the down-stroke.

> FURNACES-T. R. Crampton, C. E., of London, has patented an improvement in locomotive and other boiler furnaces, which consists in employing a series of flat bars arranged transversely in a furnace of a steam boiler, one bar below another, and somewhat forward of each other, thus producing a shelving grat ing, with spaces for the passage of air horizontally between the bars. At the lower part of such series of shelving bars is a series of ordinary fire bars, which receive the well-ignited fuel descending down the shelving bars, and which are so connected with an axis as to allow fire to be dropped upon them when desired.

#### Bursting of Krupp's Steel and Iron Cannon.

On page 98, in our list of claims of the 27th ult., two of the claims were embraced in a patent granted to Alfred Krupp, of Essen, Prussia. The first was for the manufacture of cannons from solid pieces of steel, and the second was for the surrounding of cannons made of cast steel with cast, or wrought iron, or gun metal.

We have learned, by recent foreign exchanges, that on the 19th of last month, at the Royal Arsenal, Woolwich, England, a number of scientific gentlemen assembled to witness the testing of one of these guns, a 68 pounder, manufactured by Krupp, in Prussia, for Capt. Creuse, royal engineer. It was supposed to be the largest piece of cast steel ever manufactured, and weighed between three and four tuns. The chemise, or outward covering of cast iron brought its weight to nine tuns. The proof charge was 25 lbs. of gunpowder, one wad, and one of the projectiles made by the inventor. and intended for service with the gun. This shot was of a conical shape, about two feet in length, weighing 2 cwt., 1 quarter, and 7 lbs. The quantity of powder used was less than the proof charge of an ordinary 68 pounder by 3 pounds. At the first discharge the gun burst, scattering the fragments high into the air. The sensation of the result was very great, as some supposed it capable of resisting any amount of powder. Its declared value was £1500-\$7500

#### Great Steamship Launched,

On the morning of the 10th inst. the new steamship C. Vanderbilt was launched from the yard of R. Simonson, at Greenpoint, amid the acclamations of a dense crowd numbering some thousands of persons, some of whom had come from a great distance to witness the descent of this noble vessel into the briny element. The launch was very successful. The  $\mathbf{v}$  ast size of this new leviathan of the deep was not properly appreciated because of her fine lines, until she was about to be towed down to the dockto get on her sheathing. Four tolerable sized "tugs"-two on each side-appeared beside her, like dog-fish beside a whale. The C. Vanderbilt is designed for the Atlantic trade between this port and Havre. She is built very strong, and of a capacity amounting to five thousand tuns. Her engines will be of the common over-head beams. They are nearly finished, at the Allaire Works, and are of est steamship yet launched on our continent

#### Granite Dust.

A correspondent of the Washington Intelligranite rocks may be ground to an impalpable

STEAM ENGINES-Mr. T. W. Bunning, C. E., powder and used as a fertilizer. Feldspar, a component of granite, yields notash, and may fertilizing power."

French Single Horizontal Steam Engines.

Wm. Fairbairn, of Manchester, Eng.,-the famous engineer-in his report of the steam engines on exhibition in Paris, states that the horizontal single cylinder engine is gaining ground on the double cylinder vertical engine. He attributes this to its being both cheaper and more compact. At one time the great objection to horizontal engines was the excessive unequal wear of the piston upon the lower side of the cylinder; but owing to the accuracy with which pistons, are now made, the wear and tear upon cylinders is greatly reduced. In France, Mr. Fairbairn states, the consumption of coal per horse power, in the most common steam engines, is very low-only about three pounds, and the makers of them guarantee that they will not exceed that amount. The steam is used at about fifty pounds pressure on the square inch, and is cut off at one-fifth of the stroke, and so far as economy of fuel is concerned they are equal to an engine with twocylinders, the one for high pressure, and the other for expansion-the well known Wolfe principle, which has been held to be the most economical of all. Mr. Fairbairn states that the improvements in French engines, although well known in England have not been carried out to the same extent as in the former country. He therefore awards high praise to the French engineers, and certainly, when we consider the economy of fuel-3 lbs. of coal per horse power an hour-in their engines, we must call upon our own engineers to spur up and use less fuel than they heretofore have been accustomed to do.

#### Encli h Scientific Journal.

We understand from undoubted sources that a new scientific and mechanical journal is about to be established in London, adopting the SCIENTIFIC AMERICAN as the standard. We are not permitted to announce the names of its projectors, but they are men of enterprise, and occupy high positions in the scientific circles of London, with almost unequalled advantages for a work of this character. So far as we know-and we believe we understand the subject thoroughly-there is not a first-class journal of the kind in London. They are generally monthlies or weeklies, without force or energy, and the opening for a good journal is, no doubt, very encouraging.

#### Terrible Effects of Conical Balls.

An English surgeon-Mr. Longmore-writing to the London Daily News from the Crimea, savs :-

"The experience of French practice, as well as our own is, that patients scarcely ever recover with compound fractures of the thigh, caused by rifle shots in the upper part of the limb, whether amputation be performed or not. This has led both the French and ourselves to make some experiments in cutting out some portions of the bone broken and killed by the injury, leaving the limb on; hoping that while one source of irritation is thus removed, and a less severe shock to the frame is caused than by lopping off the whole limb near the hip, nature may in time restore the continuality of the detached ends by throwing out new bones. There have not been sufficient cases to warrant conclusions on the propriety of this proceeding in the thigh. In no previous war has the human frame been shattered by missiles projected with such force as in this, and the conical form in the balls has caused a considerable difference in the kind of fissuring and splitting p of the hones."

#### Frantz's Wind Mill.

In the description of the Wind Mill in No. 13, SCIENTIFIC AMERICAN, it was stated that Phillips & Tritle were the assignces of the pat-Phillips solely, by the inventor,-Phillips & Tritle manufacture the Wind Mills.

#### Fermentation.

French grape juice, which ferments spontaneously in contact with the atmosphere, if put up in a glass jar, free from contact with the air, will not ferment. This was discovered by Gay Lussac.

## 116

# New Inventions.

#### Improvement in Billiard Tables.

The accompanying engravings illustrate an improvement in Billiard Tables, invented by Michael Phelan, No. 39 Chambers St., this city, who has taken measures to secure a patent.

Fig. 1 is a perspective view of the model table and combination cushions, partly showing the improvements-their construction, and the shape of the pocket irons-"jaws "-and sights, and the inventor would take this opportunity of calling the attention of all disciples of the beautiful and scientific game of billiards to the inspection of these diagrams and the brief explanations accompanying them. He feels confident that he has accomplished that which has occupied the attention of billiard table manufacturers, on the one hand, and all scientific players on the other-an improved model for the table, with cushions possessing the requisite elasticity to produce correct angles when played on.

Fig. 2 is a diagram, showing a top view of the bed, cushions, and pockets of a billiard table; this diagram illustrates the angles produced by a "stroke" of equal strength when played on the "combination" cloth and india rubber cushions. The example is, a ball played from the center of the side pocket over line ato the point on the opposite cushion with sufficient strength to make it rebound to the side from which it started, and back again. On the combination cushions it will describe the angles marked A A A, on the diagram, which evidently are correct angles, the base of both being equal. But on the india rubber cushions. the ball, if played with the same force, produces angles to correspond with the dotted lines marked B B, and if played with an increased force it will finally return in a direct line parallel with the end cushions, when, if correct angles had been produced, the ball would have returned to the corner pocket opposite to the ball marked a at the termination of the line, A

The second example is intended to illustrate the difference of the angles produced by a stroke on the cloth combination and india rubber cushions; play ball a against the cushion as represented in diagram, with a moderate degree of strength and the angles produced on the different cushions named will correspond with those lines marked "cloth," " combination," and "india rubber," the cloth cushion will produce an angle too obtuse, the india rubber an angle too acute, while the combination cushion will produce a correct right angle; this can can be proved by actual demonstration on the different tables. For the purpose of illustrating the cause of this, the reader is referred to figs. 4, 5, and 6 which are sectional views of the different cushions named.

Fig. 3 is a view of one corner of the model table, showing the improvements introduced in the shape of pockets, pocket irons, and "sights" or "nails" by which the great inconvenience of the "old school " tables are entirely obviated; also the improvements in the shape of cushions. a shows the shape of the jaws. bis the cue in a horizontal position, and c shows the shape of the jaws in old style. In fig. 4, ashows the manner the cue has to be elevated on the old style of cushions; b is the sight; cthe india rubber tube, and d the ball. a, fig 5, is the cue in a horizontal position. b is the sight inserted level with the cushion. c exhibits the manner in which the cushion is secured; e is the ball.

The combination cushions are half an inch lower than the old style cushions; this is of the greatest importance, for when the ball is at rest close to it, it can be struck and played with almost the same facility as if it were at any other part of the table, enabling the player to play with his cue in nearly a horizontal position, (fig. 5) and not be obliged to elevate it as the cue is represented by a in fig. 4. Another improvement is the nails or sights marked b b. In the old style (fig. 4) they project above the cushion and interfere with many strokes during the play. In fig. 5 they are inserted in, and level with the surface of the cushion; the pocket irons, also, are level with

allowing the player to strike the ball when in pockets in this style there is an additional sur- | tages of the "combination cushions" become the position represented in fig. 3, with the cue face of some thirty inches more of correct generally known. will be obvious to all good billiard players. The most important, perhaps, of all, is the difintended to show the difference between the tables. By constructing the "jaws" of the "take" a ball as easily as these on the model

b perfectly horizontal. These improvements cushions added to the space to be played on, over and above that on the old style tables, and many strokes can be made that would be ference in the shape of the pockets. The dotted | impossible on the old ones. Again, there is no lines, c c, at each side of the pocket, fig. 3, are | deceptive appearance presented to the player when playing a ball at a pocket as there is on shape on the old style, and those on the model the old wide gaping "jaws," which do not

### IMPROVED BILLIARD TABLES AND CUSHIONS.

Scientific American.



tables. c c, fig. 3, therefore, shows the old ] style shape of the pocket, and a the new style on the combination cushion. There is at least five inches more cushion on each pocket of the new, or thirty inches on the whole. Fig. 4 is a sectional view of the india rubber cushion, less, according to the degree of force with known amongst the billiard table makers as which it may be impelled; the greater the the "pipe" or "tube" cushion. It is composed of a long round strip of rubber, some- the more the ball is embedded, and this sinking

imes hollow and sometimes solid, as they wish to increase or diminish the degree of elasticity. The ball, d, is represented in contact with it. When the ball comes in contact with the rubber it sinks in, or is embedded in it more or force the more the rubber is compressed, and



the angle produced by the rebound, being angles. Fig. 5 is a sectional view, representing the new "combination" cushion, in which



the inventor, after a series of experiments, has the surface of the combination cushions, thus succeeded in producing an article in which the English pattern will be as soon as the advan- known in this and other cities of the Union.

in or embedding of the ball, together with the | objections referred to in the old table are extreme elasticity of the rubber is the cause of entirely obviated, and in which other important improvements are introduced. The "combinaacute, and so much at variance with correct tion" cushion, that is, the portion of it which causes the rebound of the ball after contact with it, is composed of three different materials, (not including the cloths for covers) by which a cushion elastic at its back and comparatively solid, yet pliable at its face, is produced, thus preventing the ball sinking in, and yet retaining the elasticity of the substance marked d. These three substances are of different degrees of elasticity, and are so combined and graduated as to produce angles in accordance with scientific principles. Fig. 6 is a sectional view of another india rubber cushion called the "English pattern." d is the ball, cthe india rubber, and b the sight. Some persons engaged in the manufacture of what they call billiard tables are using it, and talk about correct angles without well knowing what they mean. This cushion is simply a strip of rubber of the shape represented; and the same objections exist in this as in the "pipe" or "tube" cushion, viz., an embedding of the ball, and too much elasticity; at all events, the test is the angles, and they are found to give angles at variance with all known geometrical principles. This figure also serves to illustrate the shape of the old-fashioned cloth cushion, composed of long strips or layers of cloth stretched parallel with the cushion rail; they are now nearly out of use, as the "pipe," "tube," and



It is a well-known fact among scientific billiard players, that speed and truth cannot be obtained in a cushion. Beyond a certain degree of elasticity in a cushion, the more incorrect it becomes. When we say speed, we mean the ridiculous railroad pace lately brought into use in public billiard rooms, and which meet the approval of those only who are advocates for chance hazards or canon; while to the player who calculates upon, and who is accustomed to geometrical demonstration, it is painful to see the beautiful and scientific properties of the game disgraced.

The "combination cushions" are fast enough for every purpose of scientific play, and by playing on a table constructed as just described a knowledge of the game would be more easily acquired, whilst a greater number of points could be made from the balls; by using them, the proprietors of billiard rooms, would, we think, find players of merit more anxious to contend and test the strength of their games. More information may be obtained by letter adressed to Mr. Phelan, who is a distinguished

### Colt's Pistols.

billiard player.

At the trial of Baker in this city, last week, Edward N. Dickerson, attorney and counsellor at law, gave some valuable testimony relative to the manufacture of Colt's pistols. He was at one time a practical mechanic, and is Col. Colt's counsellor. He stated that he was familiar with every part of the manufacture of such pistols. The average number of menemployed in Colt's factory at Hartford, Conn., from 1848 till the present time has been about 200. The whole number manufactured up to the 1st of last February, was 200,000. These pistols are all made by machinery, all the parts of one size are alike, and fit one another. The number marked on each is the only way to distinguish one from another. He stated that the expanded gas of the powder rushed out of a pistol with a velocity of 7,000 feet per second.

#### Explosion of a Steam Fire Engine

The new steam fire engine Joe Ross, constructed by A. B. Latta, exploded its boiler on the 6th inst., at Cincinnati, while its powers were being tested. The engineer, John Winterbottom, we are sorry to say, was killed, and a number of others standing around were severely wounded. While the engine was working rapidly the hose-pipe burst; some person called to the engineer to stop the engine, which he did, although not instantly; almost as soon as it stopped working the explosion took place. The steam was at 180 lbs. pressure.

#### Sugar Crust in Pans.

A correspondent writing from Donaldsville, La., states that one of the greatest troubles experienced in sugar boiling is the crust which forms on the copper worm or pipe in the pan. It takes from three to four hours labor to scrape it off, and during this time the "dunder " in the mill, and the juice should at once, when pressed out of the cane, be run into the boiling pan, become rapidly sour, and entails a considerable loss. If there were any way to keep the steam pipe or worm perfectly free of crust in sugar boiling, so that the expressed cane juice could always be run rapidly into the pan, a great benefit would be conferred on sugar planters.

## Death of A. H. Simmons, of the Philadelphia Ledger.

Azariah A. Simmons, one of the proprietors of the Ledger, died, after a short illness, on the morning of the 9th inst. He was distinguished for his genial social qualities, strict business integrity and enterprise. In connection with his surviving partners, he, twenty years since, commenced the publication of the first success ful penny paper in Philadelphia. The deceased was 49 years of age, a native of Norwich, Conn., and was extensively and favorably

# Scientific American.

## Scientific American.

#### NEW-YORK, DECEMBER 22, 1855.

A Candidate for Public Charity. The owners of the Woodworth Planing Machine patent have reproduced a pamphlet of everything but that. eighty pages, setting forth the poverty and incapacity of William W. Woodworth, son, heir, and administrator of Woodworth the inventor. and humbly asking the charity of Congress, to save the heir from the poor-house. The real object in view is to procure the perpetuation of their monstrous monopoly, to wit. : the planing of all the lumber produced in the country.

Poor William is made to say in his present memorial, that when the last extension was granted, he was having a terrible time with the lawyers. Suits without number were instigated and carried on by a "combination of wealthy parties, deeply interested in the defeat of this patent, and against whom the unfortunate heirs to the estate of an inventor, embarrassed by expenditures to perfect this machine, could oppose but feeble resistance." "Your Memorialist and sisters had not the means to litigate them, and they were compelled either to dispose of the term which had thus been granted them by Congress, at the best price they could obtain for it, or to abandon to more wealthy infringers the profits due by law and justice to them." "While these questions were thus pending and thus situated, your Memorialist sold the extended term of said patent for \$50,000, in notes payable at long date, &c. At least 25 per cent of this amount was deducted by your Memorialist from the amount so to be received, in order to convert these notes into available means, and your Memorialist was compelled to pay debts of the estate of exceeding \$20,000, created by reason of his inventions of the planing machine."

If the foregoing statement is true, Mr. William W. Woodworth must be, by this time, on the verge of poverty. But is he the impoverished alms-seeker that he pretends ?

When Woodworth submitted his Memorial to Congress in 1852, his claims were most thoroughly examined by the Committee on Patents. They had power to send for persons and papers. They examined many witnesses, and the conclusion they reached was that Woodworth's representations were, in several important particulars, destitute of truth. Mr. Carter, the chairman of the Committee, in his scorching report, tells us that "when the last grant was given, there remained to the administrator an unexpired term of nearly five years, and the extension then granted for seven years in addition, was equal, u pon his own showing, to a tribute of three millions per annum, or a direct grant of twenty-one millions of dollars. If," continues the report, "he chose to part with this for \$50,000 or \$100,000 without reserving to himself some further equivalents beyond those which appear upon the face of the recorded papers, it was an act of strange improvidence, with which the Government has nothing to do. If the terms on which he afterwards parted with the re-issued patent were equally unfavorable—and upon that point the Committee have no information-the Government has no share in the responsibility. It neither imposes upon Congress the obligation nor invests them with the right to fasten upon the country, for his benefit, an immense burden of taxation for another term of fourteen years. The Committee, however, are not able to believe that the Memorialist has not profited amply by the precious bounty of Congress. Be that as it may, the debt has been *paid* by the country. and overpaid many hundred-fold. The invention of William Woodworth has no claim to further remuneration."

The Committee are not alone in thinking that the Memorialist has been amply profited by the bounty of Congress. It is difficult to believe that the administrator actually sold the entire extension of seven years, for a smaller sum than the patent was then netting in a single week. At the rate of \$3.009.000 per annum, the profits were fifty-seven thousand dollars a week.

The Woodworth memorial contains several other prominent features that are as wide there is but little carriage travel, but it is a motion by the engineer, who presses against it knowledging their reception.

publish the whole of the Carter report .---That document is entirely unanswerable by the Woodworth memorialists; we believe they have never made any attempt to refute it; indeed, in their present pamphlet, they attack

The Congressional Committee of 1852 effectually silenced them for three years, and unless we greatly misunderstand the signs of the times, the Committee for 1855-6 will silence them forever. But the most desperate efforts are being made, we understand, to subsidize and bring over the Senate, the House of Representatives, and all persons having political influence. The extension, if obtained, will be worth, to the grantees, not less than seventy millions of dollars! They can afford to spend a million or two in its obtaining, and they mean to do so. The most vigorous efforts. therefore, must be made to insure their defeat. Once more we call upon the people to make their sentiments on this subject known through their Representatives. We urge them to act

earnestly and with determination. One more vigorous blow and this hydra of wrong and corruption will be laid low in the dust. Petitions adverse to the monopoly can be had by writing to the SCIENTIFIC AMERICAN Office. We hope they will be generally circulated, signed, and promptly transmitted to Washington. Those who take charge of memorials must work hard and incessantly. Not a single opportunity for obtaining a name should be omitted. Petitions should be addressed to the Member of Congress representing the district where the petitioners reside.

In our own office we have posted conspicuonsly a memorial against the extension; it has already received a large number of signatures, William Woodworth, deceased, to an amount | but many thousands more are wanted. Walk up, gentlemen, and leave your autographs.

#### Defects of the Granite Pavement.

Under this head the Daily Times of the 13th inst. condemns all the granite pavement in this city. The objections which it has presented against the large block pavement, known by the name of "Russ," are correct, but it did not judiciously discriminate between that kind of pavement and the Belgian (how came it to get this name ?) or small granite block pavement. The Russ pavement,-the old Romanis composed of large granite cubes about eighteen inches square, laid on a bed of concrete and cemented in the joints. The first sample of this pavement laid down in this city was in Broadway, about eight years ago, and for a period it gave great satisfaction, because it vas such an improvement on the miserable old cobble stone pavement. Large sections of the same and other streets were soon afterwards paved in the same manner. This was while the face of the stones was rough, and afforded a good foothold for horses. About the time it was laid down we pointed out its defects, and stated that when the surface of the blocks be- $\operatorname{came}\operatorname{worn}$  and  $\operatorname{smooth}$  the street would become like a field of smooth steel, and the consequence would be that horses could not travel but with the utmost difficulty on it. This has actually taken place. Another defect pointed out was the difficuly it would always present in obtaining access to sewers, water and gas pipes, owing to its being laid in a bed of hard cement. These evils have now become apparent to all; hence the crv of condemnation has now become somewhat general, and justly so. But why does the *Times* condemn the small granite block pavement as follows?

"The recommendation of the Mayor to the Common Council to groove the Russ pavement is a very sensible one, as far as it goes; but grooves are of but little benefit, as the experience of the grooved and Belgian pavements proves."

What does it mean by saying "the grooves are of but little benefit, as the experience of the Belgian pavement proves ?" There are no grooves cut in the Belgian pavement blocks, consequently the above is not correct. Grooving the large blocks of the Russ pavement as is done in some of the old cities of Europe, is ning beneath the cars, the entire length of the an expensive and indifferent system. It may train. Attached to the engine is a reel, on do very well for an old city, over whose streets

of the real truth as the one we have dis- system altogether unsuited for Broadway-the by means of a convenient lever, a clutch friccussed. We shall probably allude to them hardest traveled street in the world, with the tion pulley, rotated by the engine. The chain, again, and perhaps in a future number re- exception, perhaps, of one or two in London. as it winds up, operates all the brakes simul-The hard cement between the joints, and the taneously. The engineer has the most perfect hard bottom of the grooves in large blocks, can | control of the brakes, being able to increase or never afford a sufficient foothold for the shoes diminish their pressure by the simple moveof horses. On the other hand, the smallblock pavement has soft sandy interstics; the blocks are so small and the joints so numerous that it the blocks are smooth. What, then, is the objection to it, seeing that it affords an easy access to drains. &c.? It is the best stone pavement, we believe, yet tried by our city, and we hope that mere declamation will not be allowed to lead our city authorities to condemn it.

#### Porter's Stone Dressing Machine.

Our constant readers will remember the illustrated description of the above machine, which appeared on page 57, volume 10, Sci-ENTIFIC AMERICAN. Since the period of that publication, a Company with a large capital, called the Porter Stone Dressing Machine Co. has been formed in this city, for the purpose of improving and constructing such machines for general use, and we had the pleasure last week of seeing one of their new machines in operation, at their works in Fourteenth street, near the North River. This new machine embraces a number of judicious and excellent improvements. In comparison with the first machine which we saw in operation, its performance was altogether superior. It has been greatly simplified; the number of parts have been reduced, and it is constructed in a most solid and approved manner. It was driven by a neat, but very small steam engine, of 5-horse power, at the rate of 300 strokes per minute, operating four hammers of 450 lbs. each, actuating four sets of cutter's tools in exact line, and which cut a surface of three feet broad on a brown free stone, six feet long, reducing it from a rough to a smooth surface, going over it three times, in a very few minutes. The machine can cut 800 feet of stone per day, from the rough as it comes from the quarry, to a smooth surface, of course changing the tools once from pointed groovers to smoothing or drove chisels for the finishing operation. One good stone cutter can face about sixteen feet of brown stone in a day; this machine, therefore, can do the work of fifty men  $(800 \div 16 = 50.)$ 

Quite a number of stone cutting machines have been invented, both at home and abroad, but it is a remarkable fact that none but Wilson's and this one are in operation in this city. There is something peculiar in the nature of stone cutting, which appears to be very difficult to accomplish successfully by machinery. Stone cutting by hand is a laborious and an expensive operation. At first sight it would really appear as if stones could easily be dressed by huge cutters, driven by that mighty agent "steam," in the same manner as planing timber, as the work is but a repetition of certain defined motions. But the nature of stone is peculiar; it must be struck with the chisel in a peculiar manner, and at a certain angle, or the face of the stone will be bruised and injured, because it is a crystalline, and not a fibrous substance like wood. This has been a great difficulty with stone cutting machines; the wrist of the stone cutter has a peculiar motion given to it while handling his tool.-This wrist motion of the tools is embraced in the stone cutting machine of Mr. Porter, and its principle of operation is the same as that of the hand of the human stone cutter. It 100 feet long, by the same makers, and on the therefore produces excellent work, and contains same principle, was submitted to a severe orwithin it the principles of success. It is worthy of a visit to see it in operation, by all who 31,142 lbs. 8 oz. was placed upon the track are interested in stone dressing. The Office of and rolled to different points. The greatest he Company is at No. 37 Wall chine is running daily at their works in 14th street, between 9th and 10th Avenues.

#### Loughridge's Patent Car Brake.

An interesting trial of this highly important invention took place Dec. 11th, on the Hudson River Railroad, between New York and Sing Sing. The apparatus was attached to a special train of five passenger cars; the ordinary brakes were also in place, but independent. The invention consists in having a chain runwhich the chain winds. The reel is put in

ment of the lever.

Running at 35 miles an hour the train was brought to a stop within 500 feet. At this affords a proper foothold for horses even when stage of the experiment, some portion of the apparatus gave way, and the train returned to the city without further exercise, save the following :

> The same speed was put upon the train, and the brakemen placed on the qui vive, in order to compete with Loughridge. The signal to brake was given, and they instantly did so. The result was, that the cars stopped in as short a distance as when Loughridge's apparatus operated. This proves, we think, that with the common brakes, if properly manned, and the brakemen at their posts, a large proportion of all accidents might be avoided. It also proves the existence of a shocking degree of carelessness on the part of brakemen and other officials in this respect. It likewise proves the great necessity for some invention which shall place the brakes under the instant control of the engineer.

> Mr. Loughridge's invention has been before noticed in our columns. It was patented in the United States and Europe through the Scientific American Patent Agency.

#### New Year's Presents.

In accordance with our custom for several years past, we shall distribute, on the 1st of January next, among our patrons, a number of highly valuable presents. They consist of money prizes, in sums varying from \$100 down. These presents will not be distributed by favoritism; they are open to all who choose to apply for them. We simply require that those who seek them shall obtain for us a few subscribers. For more full explanations of the conditions, see prospectus on the last age of this sheet.

New Year's day is close at hand, but there s still an opportunity for the highest success, f vigorous exertion be made. Several lists have been already sent in; some of them are equal, and in others there is only a difference of one or two names. We would suggest to competitors who have already entered, the propriety of further effort. The addition to their ists of even a single name may save them rom defeat, or gain a higher prize. Governors have been elected by the cast of a single vote.

#### Test of the Vergennes Scales.

We witnessed, last week, at the Crystal Palace, a test of one of the platform weighing apparatuses made by the Vergennes (Vermont) Scale Co., (Sampson's patent.) This scale requires no pit, and is portable; can be taken up and moved about from place to place with facility. The scale on trial had a capacity of even tuns. The test was made with a large chunk of iron weighing two tuns. This was moved about from end to end on the platform, but in no case was there a variation of over two ounces. So accurately adjusted was the apparatus that the addition of a copper cent to the weight made a sensible difference in the movement of the weighing beam !

Subsequently a trial was made before the Committee of Arts and Sciences of the American Institute, when the great railroad scale, deal. A truck containing a dead weight of difference of weight between any two tests wa 10 lbs. This was close shaving for a gross sum of over fifteen tuns. The invention has been before fully described and illustrated in the Scientific American.

At St. Louis, on the 7th, three steamboats were burned at the levee. The loss is estimated at \$70,000. The boats were named Parhenia, Twin City, and Prairie City; the fire caught on the first named.

Notwithstanding our admonitions, we continue to receive models without the inventor's names attached. This prevents us from ac-

# Scientific American.

#### British Association for the Advancement of Science.-No. 4

118

THEORY OF THE AURORA BOREALIS-Admiral Ross read a paper on this subject. He said: "It having occurred to me that, if my theory was true, namely, 'that the phenomena of Australia, and America are accessible by telethe aurora borealis were occasioned by the action of the sun, when below the pole, on the those commonly employed in submarine casurrounding masses of colored ice, by its rays bles? being reflected from the points of incidence to clouds above the pole which were before invisible,' the phenomena might be artificially produced; to accomplish this, I placed a powerful lamp to represent the sun, having a lens, at the focal distance of which I placed a rectified terrestrial globe, on which bruised glass, of the various colors we have seen in Baffin's Bay, was placed, to represent the colored icebergs we had seen in that locality, while the space between Greenland and Spitzbergen was left blank, to represent the sea. To represent the clouds above the pole, which were to receive the refracted rays, I applied a hot iron to a sponge; and, by giving the globe a regular diurnal motion, I produced the phenomena vulgarly called "The Merry Dancers," and every other appearance, exactly as seen in the natural sky, while it disappeared as the globe turned, as being the part representing the sea to the points of incidence. In corroboration of my theory, I have to remark that, during my last voyage to the Arctic Regions (1850-1) we never, among the numerous icebergs, saw any that were colored, but all were a yellowish white; and, during the following winter, the aurora was exactly the same color; and, when that part of the globe was covered with bruised glass of that color, the phenomena produced in my experiment was the same, as was, also, the Aurora Australis, in the Antarctic regions, where no colored icebergs were ever seen. I regret that it is out of my power to exhibit the experiments I have described, owing to the peculiar manner in which the room must be darkened, even if I had the necessary apparatus with me; but it is an experiment so simple that it can easily be accomplished by any person interested in the beautiful phenomena of

the aurora borealis." ON OCEAN TELEGRAPH CABLES-By Mr Wildman Whitehouse-After referring to the rapid progress in submarine telegraphy which the last four years have witnessed, Mr. Whitehouse said that he regarded it as an established fact that the nautical and engineering difficulties which at first existed had been already overcome, and that the experience gained in submerging the shorter lengths had enabled the projectors to provide for all contingencies affecting the greater. He then drew the attention to a series of experimental observations which he had made upon the Mediterranean and Newfoundland cables, before they sailed for their respective destinations. These cables contained an aggregate of 1,125 miles of insulated electric wire-and the experiments were conducted chiefly with reference to the problem of the practicability of establishing electric communications with India, Australia, and America. The results of all the experiments were recorded by a steel "style" upon electro-chemical paper by the action of the current itself, while the paper was at the same time divided into seconds and fractional parts of a second by the use of a pendulum. This mode of operating admits of great delicacy in the determination of the results, as the seconds can afterwards be divided into hundredths by the use of a "vernier," and the result read off with the same facility as a barometric observation. Enlarged fac-similes of these electric autographs were exhibited. The well-known effects of induction upon the current were accurately displayed. No less than eight currents-four positive and four negative-were transmitted in a single second of time through the same length of wire (1,125 miles) through which a single current required a second and a half to discharge itself spontaneously upon the paper. Having stated the precautions adopted to guard against error in the observations, the details of the experiments were then concisely given, including those for "velocity," which howed a much higher rate attainable by the magneto-electric than by the voltaic current. The author stated his conviction that it appeared from these experiments, as well as from trials which he had made with an instrument above-named Association.

of the simplest form, actuated by magnetoelectric currents, that the working speed attainable in a submarine wire of 1,125 miles was ample for commercial success. And may we not, he added, fairly conclude also that India. graph without the use of wires larger than

ON SOLAR REFRACTION-By Prof. Piazzi Smyth-Amongst other interesting and important consequences of the dynamical theory of heat, Prof. W. Thomson having deduced the necessity of a resisting medium, the condensation of this about the sun, and a consequent refraction of the stars seen in that neighborhood, Prof. Piazzi Smyth had endeavored to ascertain by direct astronomical observation whether any such effect was visible to our best instruments. Owing to atmospheric obstructions, only three observations, yielding two results, had been yet obtained; but both these indicated a sensible amount of solar refraction.-Should this effect be confirmed by more numerous observations it must have important bearings on every branch of astronomy; and as the atmosphere at all ordinary observatories presents almost insuperable obstacles, the author pointed out the advantage of stationing a telescope for this purpose on the summit of a high mountain.

THE INDIA RUBBER TREE AND ITS FRUIT-Chevalier D. Claussen, inventor of the flax cotton, read a paper on the above subject. He stated, that in the course of his travels in South America, he had occasion to examine the different trees which produce the india rubber, and of which the Hancornia speciosa is one.-It grows on the high plateaux of South America, between the tenth and twentieth degrees of latitude south, at a hight from three to five thousand feet above the level of the sea. It is of the family of the Sapotaca, the same to which belongs the tree which produces gutta percha It bears a fruit, in form, not unlike a bergamot pear, and full of a milky juice, which is liquid india rubber. To be eatable, the fruit must be kept two or three weeks after being gathered, in which time all the india rubber disappears, or is converted into sugar, and is then in taste one of the most delicious fruits known, and regarded by the Brazilians (who call it Mangava) as superior to all other fruits of their country. The change of india rubber into sugar, led him to suppose that gutta percha, india rubber, and similar compounds contained starch. He therefore tried to mix it with resinous or oily subtances, in combination with tannin, and succeeded in making compounds which can be mixed in all proportions with gutta percha or india rubber without altering their characters. By the foregoing it will be understood that a great number of compounds of the gutta percha and india rubber class may be formed by mixing starch, gluten, or flour with tannin and resinous or oily substances. By mixing some of these compounds with gutta percha or india rubber, he can so increase its hardness that it will be like horn, and may be used as shields to protect the soldiers from the effect of the Minie balls, and some of these compounds in combination with iron, may be useful in floating batteries and many other purposes, such as the covering the electric telegraph wires, imitation of wood, ship-building, &c.

SOAP PLANTS-The Chevalier also read a paper on this subject. When he was experimenting on several plants for the purpose of discovering fibers for paper pulp, he accidentally treated some common sea weeds with alkalies, and found they were entirely dissolved, and formed a soapy compound which could be employed in the manufacture of soap. The making of soaps directly from sea-weeds must be more advantageous than burning them for the purpose of making kelp, because the fucusoid and glutinous matter they contain are saved and converted into soap. The Brazilians use a malvaceous plant (Sida) for washing instead of soap, and the Chinese use flour of beans in the scouring of their silk; and he had found that not alone sea weed, but also many other glutinous plants, and gluten, may be used in the manufacture of soap.

[This concludes our extracts from some of the papers read before the last meeting of the

#### Pure and Impure City Water.

MESSRS. EDITORS-In the SCIENTIFIC AMERI-CAN of the 24th of Nov., I noticed an aticle entitled "Impure City Water," which, without further elucidation, is calculated to detract from the popularity of the gravitation system for supplying towns with water.

As a Commissioner under the English Drainage Acts; as one of the parties conferred with by the Government on the public Health Act; as having taken an active part in the promotion of these important measures; and, moreover, from a tolerably extensive experience, having a practical acquaintance with the most approved modern plans of sanatary works, which have been my special study and professional occupation for some years past. I feel more than an ordinary interest in impressing on the public mind a right appreciation of those more perfect and efficient plans which, after a long and costly probation, have, in England, attained a degree of completeness that it is my object to introduce on this continent .--Wherever it is attainable, even by going many miles for the purpose, there can be no question but that the gravitation system is the one to be adopted for a water supply. It has everything to commend it to public favor-cheapness of first cost, simplicity, durability, uniformity of supply, with the annual charge for repairs and management reduced to the lowest possible point. As compared with a pumping system, in almost every instance, it will save the entire first cost of the work in twenty years -the period over which it is usual to spread the outlay.

With reference to Boston and Albany, where the water is said to have acquired a fishy taste, it seems to me that the several circumstances have been too superficially examined. In the common course of nature it is simply impossible that opposite causes should produce similar effects; and hence the true reason must be looked for in the existence of the same defect in both places. And I am inclined to think that this will be found in an imperfect circulation in the distributing pipes, or technically speaking, in an excess of dead ends, which invariably produce a deleterious effect on the water. I have also known instances in which a fish has, by some means or other, got into the supply pipe, and being killed therein, has impregnated the water for some time. But, supposing the cause to be what is assumed, by the water being impregnated at its source either by animalculæ or weeds, there is a simple and effectual remedy by means of a properly constructed and adjusted screen filter filled with charcoal, &c., at the mouth of the supply pipe.

The low standard of public health, confirmed by the sad experience of daily reality, shows the pressing necessity which exists on this continent for a more stringent attention to sanatary matters; and that would be a wise and beneficent measure which should oblige (if need were) all municipalites to take prompt and efficient steps for the improvement of the public health.

If any evidence were needed beyond what almost every man's individual feelings can bear testimony to of the comfort, and even monetary benefit to be derived from perfect sewerage, and an ample water supply, it can be found in truthful abundance in the periodical reports of the English Registrar General, which, in recording the health of London, distinctly mark, step by step, the progressive advance in the duration of life exactly proportioned to the progress made in the sewerage of the metropolis, and its more perfect supply of water, and consequent general cleanliness.

Drainage and Sanatory Engineer, Hamilton, Canada West, Dec. 4, 1855.

JOHN H. CHARNOCK

#### A Fact for Farmers.

Every inch of rain that falls on a roof yields two barrels to every space ten feet square; and seventy-two barrels are yielded by the annual rain in this climate on a similar surface. A barn thirty by forty feet yields annually 864 barrels; this is enough for more than two barrels a day for every day in the year. Many have, however, at least five times that amount of roofing on their dwellings and other buildings, yielding annually more than four thousand barrels of rain water or about twelve be placed upon it.

barrel sor one hundred and fifty ordinary pailsful daily.- [Ger: Telegraph.

#### Artificial Manures.

At a meeting of the National Institute, held in Washington, Dec. 3rd, Dr. Gale in the chair a verbal communication was made by Dr. Breed, of the Patent Office, respecting the poisonous effluvia arising from the decomposition of night soil, &c., and the remedies for the same. These effluvia are a producing cause of disease, and, but for their diffusion, would generate pestilence in all cities. The remedies are simple and of easy application. Paris illustrates this fact; its former condition being such as to attract the attention of the scientific, their labors had resulted in an entire reform of the evil. The need of this reform in American cities and towns was presented, and the products of the process of putrefaction stated with their deleterious effects upon the air and upon walls. Not only does public health require the immediate abolition of this nuisance, but the wants of agriculture second the demand, as thereby an excellent fertilizer might be abundantly and cheaply supplied. It would be necessary so to treat the mass as to retain its most valuable constituent, nitrogen. The modes of so doing were given in detail-showing how to effect the last-mentioned object and likewise complete deodorization and disintection. The present process of making pou drette in Paris was then described; and, in conclusion, it was shown that the nitrogen of the annual night soil of London and New York is about equal to the nitrogen of the 180,000 tuns of guano annually imported into Great Britain and the United States, and that, if estimated by the cost of nitrogen in guano, it would amount to nearly ten millions of dollars per annum.

### Ari hmetical Improvement.

MESSRS. EDITORS-Knowing you to be advocates of improvements, whether mechanical or otherwise, I herewith present an improved plan of multiplying mixed numbers, by which one-half of the usual amount of figuring is saved.

Let us take for an example 866  $1-8 \times 4222-3$ , 866 1-8 422 2-3 1-3 of 866 1-8=288 17-24 2-3 of 866 1-8=577 10-24 1732866×422= 173234641-8 of 422= 52 6 - 8

Total amount 366082 4-24

By the old method the two numbers would be reduced to improper fractions, multiplied, and the numerator divided by the denominator, producing the same result, but involving double the figures.

This I consider of great importance, as the multiplication of long mixed numbers by the old process is excessively tedious. Mr. E. Robbins, a practical mathematician of New Haven, Ct., is, I believe, the discoverer of this improvement. **WM.** Y. BEACH.

### Wallingford, Ct., Dec., 1855.

#### New Shoal near New York Harbor.

Professor A. D. Bache, the able Superintendent of the U.S. Coast Survey, in a letter to the Secretary of the Treasury, dated the 21st ult., says that in the progress of the hydrographic work of the present season, in the vicinity of the Narrows' entrance to New York harbor, by the Coast Survey party, headed by Lieut. Com. T. A. Craven, U. S. N., a shoal spot has been discovered, existing in the main ship channel, located 2,067 yards S. 30 degrees E. from the lighthouse on Staten Island, lying north and south, with a length of 503 yards in that direction, and a breadth of 164 yards from east to west. The soundings show a depth of eighteen feet, at low water. The shoal is composed of sand and shells, or more strictly is a shell bank. The steamer Baltic struck on it a few months since, and it was reported that she had struck upon a wreck. Some of the pilots claim to have had a knowledge of the existenc of the shoal, though none of them could give the ranges for it. The Lieutenant and the Superintendent both recommend that a buoy

#### TO CORRESPONDENTS.

J. B. C., of Tenn.-We are awaiting the report of Mr. Co, eland on the Cloud Engine. It is true, as you observe, that the great amount of power required to inject the nec assary quantity of air for hot-air engines, is the cause, a ad always will be the cause of their failure.

E. B. F., of Ill.—A centrifugal gun for shooting balls by mechanical force, is not new; such a gun was experi mented with in this city about ten years ago. The ex pense of working such a gun would be greater than to discharge the balls with gunpowder. G. C. S., of N. Y.-We know nothing of a work called

Grier's Mechanic's Calculator. W. O. G., of Ct.-If you putone coil of pipe around the bottom of your tub, and have it perforated with holes, you

can boilyour water quicker than by the large coil without perforations. The use of one coil is preferable for the reason that it distributes the heat much better, and pre vents the shock attending the letting in of steam in a large volume. W. V., of N. J.-We can furnish you no information

about turning calender rolls used in the manufacture of puper. We do not remember to have published any thing on this su! ject. Cannot account for the tardy deliv-e vof your paper. It it regularly mailed from our office and ought to get 12 miles in less time than a week, but the Post Office Department is sometimes sadly out of joint in its postal operations.

S. H., of Iowa -The sketches of your method of tight-ening up bed cords have been examined. We do not remember to have seen the same thing before, although you must bear in mind that applications for such devices a ways attended with much doubt, owing to the fact that s much has been done in this line.

application our fee for preparing it would be \$25. The ent fee is \$20. See circular about model, etc. W. J. L., of Mass.-The experiment of producing spark

of electricity, accompanied by a crackling noise, by rub-bin; down a cat's back, isknown, we presume, to every one at all familiar with this feline quadruped. It was one of the curiosities of our juvenile days. J.P.A., of Ga.—Blackie & Son, 117 Fulton st., N.Y., sell

"ReidsHorology," which describes the machinery of watch and clock making. The art of polishing steel, sil-ver, and gold cannot be learned but by actual observation Emery wheels and buff leather wheels are used in polishing, as well as buff and emery straps. The burnishing or finishing operation is performed by a fine agate bur

C H. R., of Me.-Your arrangement for admitting steam through a puppet valve appears to be new and patentable Should you decide to make an application send us a mod el.

J. A., of Pa.-Models sent to the Patent Office canno e permanently withdrawn. The notice to which you allude has reference to models sent to our office, and upon which no applications are made for patents. Yours does not come within this category.

J. C. R., of Mich.—We have paid no attention to the pretensions set up by the reputed discoverer of a new language. The subject is scarcely worth a serious consid

eration, as it is wholly impracticable. J. J., of Mich.-We can understand how a log may be made to float, as you have described it, by chaining it to a lighter timber, but that is not an exact disposal of the question

Phillip Gross, Boonville, Mo., is a cooper and has heard a good deal about a shaving machine driven by one horse ower, which costs from \$75 to \$300. Mr. Gross wishes to hear directly from the mani, facturer of suca a machine.

J: C. R., of Pa.-Minie, the inventor and patentee of the celebrated fire-arm which bears his name, is a lieutenant in the French army, and is stationed in command of the fortress of Vincennes, near Paris. He is continually try-ing experiments for the benefit of his country. His rifle cannot be obtained in this country that we are aware of.

G. II. D., of N. Y.-During the holidays, from Thanks-gi ing till after New Years, patent business is always sluck with us, and but little is generally done at the Patent  $O_{\rm eff}$  c in acting upon cases. It is an excellent time however, for you to presen your several investion, for the pas pers can be prepared by us this month without any delay. If your friend should come down with his model, you can send your models, with the Government fees—\$3.0 on each -by him, and the papers we will prepare at once, and pr baily be able to send them for execution by Mr. H. where he returns. Assure Mr. II. that we will prepare his specifications and drawings so that we can execute

them at our office while he remains in the city. L. A. B., of N. Y.—We have examined the sketch and description of your improved wheel for ascending inclines, and we are of the opinion that it embraces patentable features, as we never saw or heard of anything like it, but as to its practicability we are by no means certain. We should doubt somewhat, and yet it may possibly prove to le free from objection. All we can say in regard to it is that we think it patentable.

J. M. H., of N. H.-A cupping apparatus constructed in the manner proposed by you, could not in our opinion be patented. It is the mere application of the air pump prln ciple to cupping, without involving anything novel in its contrivance. The idea, however, is not new, as the same thing has been done before. J. O. M., of N. Y.—A cheap and simple water measured

would be a desirable improvement.

L. Q., of Canada-No provision is made in our laws fo a foreign subject securing an invention in this country, by

a caveat P. & Co., of O -Fairbanks & Co., Broadway, this city, sell two kinds of coin scales-Fromnei's and Allander'sthe first is retailed at \$4,50, the latter at \$1,50, and we perceive no superiority in one over the other

W. F., of Tenn.-If you put in a good turbine water wheel, you will be able to get more work out of it than from your flutrer wheel. You have plenty of water to get eight horse power out of a good wheel. Any of those illustrated in our columns will answer your purpose

B. A. A., of Ind.—So far as we can learn, the chief dif-ficulty with the wire fences that have been put up is their mi erable construction. Being badly erected, a prejudice has grown up against their use. The expansion and contraction is a small item of disadvantage. Your device for preventing the same is good, and probably patentable .-You must determine as to the propriety of applying for a patent. Water will rise of itself in a pump stalk out of which the air is exhausted, to a hight of thirty-three feet. In pumping, the power spent is in exh using the air.— The water follows the piston as fast as it rises. For every foot above thirty-three the column of water must be raised bodily, like any other weight, and the power must be in accordance.

の記念

W. S. S., of Mass.-It would not be patentalle to fit up the interior of a car in the manner yom propose. It has been before suggested to us, but aside from this, the mere futroduction of saloons or state rooms for sleeping on cars could not le viewed in the light of a patentable invention. O. F. S., of N.H.—The raperon glycerine made as de-scribed, was read before the British Scientific Association, and was taken from the Report of their proceedings. In all likelihood, the steam required must be surchargeddry steam\_not wet steam.

E. H. H. of Ind.-Your governor is what is known as a chronom tric governor, and was invented mainy years ago by a Frenchman, whose name we forget. We have had the same thing submitted to us more than once with in a year or two.

Money received at the SCIENTIFIC AMERICAN Office of account of Patent Office business for the week ending Saturday, Dec. 15, 1855 :-

J. S., of Ind., \$15; W. P., of Ct., \$30; C. G., of Ky., \$25; C. B., of Pa.. \$30; J. II., Jr., of Wis., \$25); W. A., of N. Y., \$40; J. H. P., of N. Y., \$25; E. H., of N. Y., \$30; C. G. G., of N. Y., \$10; L. B. P., of O., \$25; E. T., of Ct., \$25; P. McM., of N. Y., \$20; S. I. T., of N. Y. \$25; J. W. H., of R. I., \$55; C. B., of Ind., \$25.
 Specifications and drawings belonging to parties with

the following initials have been forwarded to the Patent Office during the week ending Saturday, Dec. 15 -L. B. P., of O. ; J. W. H., of R. I. ; J. S., of Ind. ; C.

#### G., of Ky.; J. H. P., of N. Y.; S. I, T., of N. Y.; W. A., of N. Y.; E. T., of Ct.; C. B., of Ind. -

#### Important Items.

BACK NUMBERS AND VOLUMES-The following numbers and volumes of the SCIENTIFIC AMERICAN, are for sale at this office, at the annexed prices -- Volume VI Vol. VII, Vol. IX, and Vol. X, complete. PRICE, bound, per Volume, \$2,75. Numbers in sheets, complete, \$2. Of Volumes IX. and X., we have also about 40 numberseach. not consecutive, which will be sent by mail on receipt of \$1.

RECEIPTS—When money is paid at the office for subscrip tion, a receipt for it will always be given; but when subscribers remit their money by mail, they may consider the arrival of the first paper a bona fide acknowledgment of the receipt of their funds.

BINDING-We would suggest to those who desire to have theirvolumes bound, that they had better send their numbers to this office, and have them executed in a uni-

form style with their previous volumes. Price of bind ing 75 cents.

#### Literary Notices.

Literary Notices. GHLESPIE'S LAND SURVEYING—Prof. Gillespie, C. E., of Union College, is the author of a new work just pub-lished on the above su ject, by D. Appleton & Co. of this City. .t is a full and be treather on land surveying, comprising the theory developed from five elementary principles, and the practice with the chain, the compass, the theodolite, the plans, taile, dc. this illustrated with four hundred engravings and a magnetic chart of the U.ited States. While te whing surveying is preliminary to a course of Civil Engineering, he found that none of the books in use suited his purpose, and he was compelled to teach the subject iy a continati n of familiar lectures on its principles, and as exemplifications of its practice. Hishotes condinuely swelled in bulk, and gradually te-trasted, emily acting and the public, which has teen highly prized. The present volume is a full and complete treaties, emi-racing all contai, ed in his previous work, and does honor to its author for its completeness, and the perspicuity of its demonstrations. The publishers deserver credit for he neathers of the typography, and the general contour of the book--it is well printed, and the matter ar-ranged with great care.

The KNICKERDOCKER—Old Knick, for this month, is sentimental, practical, historical, graphical, satirical and nusical, as uval. It con ains a friendly criticism of Longfellow's recent poem 'I liawatha,'' which has caused and is causing so much criticism, *pro* a.d core, among the literati. "The Last Seize of Jesusalem,'' by Rachael A. Ackerman, is a fine poem. The Lediver's Table smokes cheerfully with a time feast of wit and humor.

cheerfully with a fine feast of wit and humor. FRANK LESLIE'S ILLUSTRATED NEWSPAPER—This is the name of a new weekly illustrated journal on the plan of the London illustrated News. It is a newspaper re-cord of all the principal occurrences of the day, the most prominent incidents Leing pictured to the eye by o. grav-max. In the number belore us there is, for example, an incressing printed description of Dr. Kane's exploits in the Polar r gions, illustrated by hands one pictures of Arctic scenery. Hare's Spiritual Machinery, as shown by him at the Broadway Talernacle, during his recert. lecture, is also engravings. The whole specimen, both in arristic, literary, and typographical appearance, is splendid. Sing e copies 10 cents; \$4 a year. Leslie, pub-lisher, 14 Spruce st., N. Y.

THE COACH MAKER'S MAGAZINE—For December, by C. W. Saladee, of Columtus, Ohio, contains three large plates of illustrations, besides a number of wood cuts...-With this number the first volume is conclud. We are happy to see that Mr. Saladee hts be n cheered by its success, and that he goes forward with animation in pre-paring for his next volume.

4	lines,	Ter for each	insertion,	ver	usin	g.		\$1
8								\$2
12	••					-		\$3
16	**	••		•	-		-	\$4
Ad7	ertisen	nents ex	ceeding 16	lin	es ca	nnot	be a	dmitted
neithe	r can e	engravin	gs be inser	ted	in th	e ad	verti	sing col

umns at any price. All advertisements must be paid for before insert ing.

**TYECHVICAL DIGTIONARY**—In the English, Fre. ch. and German Languares; by Messrs. TOL-HAUSEN & GARDISSAL, Civil Ibngineers. Ready (first part.) Freich, Freglish, German, price \$1.50. These ond part) English, French, German, price \$1.50. These volumes ar: designed for the general use of Engineer. Artists, Manufacturers, Foremen, Artizans, in short, of all those who, in some way or other, are concer ed in Arts those who, in some way or other, are concer ed in Arts and Manufactures. The present work is the key through which the foreign reader may penstrate into a language which he may know but imperfectly, it is the instanta-neous translator of the corresponding technical term, or its equivalent, in the three great industrial languages.— Forsale at the SCIENTIFIC AMERICAN Office

**DREAST WATER WHFELS**—For sale, three bed diameter and 3 feet vide, the other two about 12 feet diameter and 2 feet wide, be other two about 12 feet diameter and 2 1-2 feet wide. Fither can be made into breast or over-shot whice's at little exyense. Terms mod-erate. Apply to E. WHITNEY, New Haven, Ct. 15 6\*

**THE AGENT** for the sale of the English patent right of C. Cornell Brick Making Machine, the most su-perior machine in use, may be seen, together with the model, at Lovejoy's Hotel, N. Y. Prompt attention given to any communication addressed to the Agent, S. T. MA-THE WS, Lovejoy's Hotel.

WANTED-Four or five traveling and stationary agents, to sell patents and machines of several late improved agricultural implements needed by every far-mer. For particulars apply to JESSE URMY, wil-mington, Del.

#### **IMPORTANT TO INVENT-**ORS.

IMPORTANT TO INVENT-ORS.
THE UNDERSIGND having had Tex years' practical experience in soliciting PATENTS in this and foreign commiss, beg to give notice that they con-time to olfer their services to all who may desire to se-cure Patents at home or abroad. Over *three chousecend* Letters. Patent have been issued, whose papers were prepared at this Office, and on an average *effective*, or *view*. Arrif of all the Patents issued each week, are on cases which are prepared at our Agency. An able corps of Exignneers, Examiners, Draughtsmen, and Specification writers are in constant employment, which renders us able to prepare applications on the shortest notice, while the experience of a long practice, and facilities which few others possess, we are able to give the most cornect counsels to inventors in regard to the patentability of inventions placed before us for ex-amination. Privace consultations respecting the patentability of in-ventions are held free of charge, while inventors, at our office, from 9.4 M., until 4 P. M. Parties residing at a distance are informed that it is generally unnecessary for them to incur the expense of attending in person, as all the steps necessary to secure a patent can be arranged by lietter. A rough sketch and description of the improve-ment should be first forwarded, which we will examine and give an opinion as to patentability, without charge. Models and fees can be sent with safety from any part of the country by express. In this respect New York is more accessible than any other city in our country. Circulars of information will be sent free of postage to any one wishing to learn the preliminary steps towards mading an application. The addition to the advantages which the long experience and great success of our farm in obtaining patents present to inventors, they are informed that all inventions pat-ient divention our etablishment, are noticed, at the prop-er time, in the Scinny price Askencas. This paper is rountries are secured

LARM ATTACHMENT LOCK—Patented May, 1955—This Lock is manufactured in Rochester. N. Y., 19 the 1 atentee himself, and under his own directions, a di swillable for Trunks, Doors, Iron Safes, or any other place where a lock is needed—is made in the very best style and workmanlike manner—is perfectly safe to the owner, but rather dimerons for the thief. Responsible Agents are wanted for the safe of the same; and also the right in the United States. Anyiody wishing to invest capital in a profitat le 1 usiness, will do well to apply, ly mail or otherwise, to M ssrs. SCHINE, DER & SCHU-BERS, Glove Building, Bochester, N. Y. 1\*

Fig. S. C. LTPLE, 33 and 34 Fulton st., N. Y. 1\*

THIREE GOOD JOURNALS FOR 18561--Well adapted to all read-rs is every family. LIFE IL-LUSTRATED - a First-class Pamily Paper, devoted to News, Literature, Science, the Arts, to Entertainmet, Improvement, and Progress. Published weekly at \$2 a

Improvement, and Progress. Published weekly at \$2 a year. THE WATER-CURE JOURNAL-Hydropathy, its Philosophy and Practice. Physiology, Anaiomy, and the Laws of Life and Health. \$1 a year. THE PHRENOLO-HCAL JOURNAL-Devoted to all those Progressive measures for the Elevation and im-proveme to of Mankind. Hilburtated. \$1 a year. For \$3 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be sent a year. For \$2 ill three Papers will be year three \$2 ill three \$2 ill three Papers will be year three \$2 ill thre

**PROF. ROBERT HARD**?S Great Book-with en-gravings illustrating the Drs. is genicus mechanical inventions to detect deception, and scientifically demon-strate the true agent involved in the so-called spiritual manifestations. Price S1.75, postage 25 cents, just pub-lished iy PARTRIDGE & BUTTAAN, fronting the Tab-ernacle, No. 342 Broadway, N. Y. 142\*

RAILROAD SHUTTERS FOR STORES-An improvement in the allove line was patented August 23th, 1355. Those wishing to use this improvement can be accommodated on reaso, able terms i y applying to the patentee and manufacturer, D. ROHAN, No.7 Jackson st. Cincinnati. Ohio. 114

TE HAVE ALWAYS ON HAND and manufac-timp the to order, with the news of and most practical improvements, Surveyor's Compasses, Transits, Theodo-lites, &c., warranted to give stitulation. Also Swiss drawing instruments. Catalogues gratis on application. AMSLER & WIRZ, 211 Chestnut st., PLi.adelphia. 14 Geow

D. BARNETT, Malleable and Gray Iron Works Hamilton, corner McWhorter street, Newark, N J. Orders promptly attended to. 910\*

AULARD MACHINES—With Harness complete of and ready to receive the warps, I uit on the most im-proved plan, for the manufacturing of Finired Goods of every description. Also Ribbon Looms and Uard Punch-ing Machines made to order. W. P. UHLLINGER & CO., 124\* Germaniown Road and Oxford st., Phila.

CIRCULAR SAWS-We respectfully call the atten-tion of manufacturers of lumber to the great improve ments recently introduced in the manufacture of our Circular Saws. Being sole proprietors of Southwell's patent for grinding saws, we are enailed to grind circular saw. from six in chos to six fet with the greatest accuracy and precision. The imposful ity of grinding a saw with out leaving it un even in thickness has always been ac-knowl dg d ty practical saw makers. This cause the aw to expand as soon as it becomes slightly heated in work-ing. When thist kees place the saw loose its stiffness, and will not cut in a direct line. We will warrant our saws to be free from these delects they are made perfectly even in thickness, or gradually increase in thickness from the edge to the center, as may be desired. As there are no thick or thin places, the friction on the surf ce of the saw is uniform, consequently it will remain stiff and are no thick or thin places. the friction on the surf ce of the saw is uniform, consequently it will remain stiff and true, and will require less set and less power. Will saw smooth, saw e lumber, and will not be liable to be come un-true. This is the oldest etablishment now in existence for the manufacture of circular saws in the United States, having been established in the year 1330. Orders re-ceived at our Warehouse, No. 48 Congress st., Poston. 12 3m\* WELCH & GRIFFITHS.

WELLS, & CO., Florence, Hampshire Co., gle Mass. will furnish toorder, Morrison's Patent Shin-gle Machines. This is the only machine extant that will rive with the grain of the wood, and produce perfect shaved and join ed shingles. The machine will work any kind of timier that can be worked by hand, and will make 25.000 shingles in 10 hours regardless of width, with 4-horse power. Child's Circular Saw Minls constantly on hand. 116 eow\*

**DORTARI, E STEAM EVGINES**.-S. C. HILLS, No. 12 Platt st., N. Y., offers for sale these Engines, with Boilers, Pumps, Heaters, etc., all complete, and very compact, from 2 to 10 horse power, suitable for print-ers, carpenters, farmers, planters, &c. A 2 1-2 horse can be seen in store, it occupies a space 5 by 3 feet, weighs 1500 lbs., price \$240, other sizes in proportion. 3 e3w

10 JOTICE TO PLOW MANUFACTUREFS. JOSIUA GIBBS, of Canton, O., has invented a na-chie e for Grinding and Polishing plows. Ty addressing the patentee, a cut and directions for making and using will be forward d. also the term of three months will be granted to to sit its utility a d advantages. Cost for erect ing the machine will not exceed \$15. 128\*

Oli, SAVER-Save 75 per cent of your oil by using Devlan, Wood, & Hancock's Patent Oil Saver. For particulars and right to use in machine shors, factories, sc., and on railroads, apply to S. C. HILLS, 12 Platt st., New York. 1210

VAIL'S C. LEBRATED PORTABLE STRAM Engines and Saw Mills, Bogardus' Horsepowers, Smut Machines, Saw and Grist Mill irons and Gearing, Saw Gummers, Ratchet Drills, &c. Orders for light and heavy forging and castings executed with dispatch. VAIL & LIDGERWOOD, 13 1y\* 9 Gold st., N.Y.

MPORTANT INVENTION – Patented August 14th, 1355. "Garratt's Metal" for Journa, Boxes of all kinds, it is anti-friction, absorts the oil, not liabile to break, it can be made cheaper than either brass or Babbitt metal, and after many long and severe tests, has been found to surpass all other metals ever used for the purpose. For the purchase of either State, county, or shop rights under this patent, apply to JOS. GARRATT, Sen., Madison, Indiana. 133m\*

**5500** TO \$10,000-GREAT INVEST. Barge or small smount in patent right, that the profits of which will clear the whole cost in one month's silles. Can find an opportunity by addressing Box 2,027 this city. 14 4\*

ACHINISTS' TOOLS.-Meriden Machine Co the have on hand at their New York Office, 15 Gold street, a great variety of Machinists' Tools, Hand and Power Punching Presses, Forcing Pumps, Machine I elt-ing, &c., all of the best quality. Factory West Meriden, Conn. 2 13\*

Conn. P. N. FITZGERALD, Counsellor at Law-late Principal Examiner in the U. S. Patent Of-fice-has removed from Washington, D. C. to the city of New York, 271 Lroadway, (corner of Chamlers St.) As heretofore his practice is confined to Patent Cases, which he will rosecute or defend, as counsel, lefore the Su-preme and Circuit Courts of the United States, also Lefore the Patent Office, or the Judges having jurisdiction of ap-peals therefrom. 11f

ATER POWER FOR SALE-8 hours' ride from the city of New York, near the beautiful and thriving village of Owego, on the New York and Frie kairoad. The wheel is 14 feet diameter, 5 foot bucket, building 75 by 25, two stories high. For particulars apply to HARVEN CHURCH, Troy, N. Y., or H. H. NASH, Owego, N. Y. 88\*

MACHINISTS, TOOLS- Manufacturers, Mechanics and Railroad Supplies, Locomotive and Stationary Engines, Ashcroft's Steam Gauges, Foilers, Trip Ham-mers, Belting, Cotton and Woolen Machinery, Waier Wheels, Pumps, Blowers, Wrought fron Tackle Blocks, &c. FOSTER & LEACH, 313\* 23 Broadway, N. Y.,

OIL : OIL : OIL : For railroads, steamers, and for machinery and hurning-Dease's improved Machine-ry and Eurning Oil wills ave fifty per cent. and will not gum. This oil possesses qualities vitally essential for tubri-cating and burning, and found in no other oil. It is of fered to the pullic upon the most reliable, thorough, and practical test. Our most kellful engineers and machinists pronounce its uperior and cheaper than any other, and the only oil that is in all cases reliable and will not gum. The Scientific American, after several tests, pronounced it "superior to any other they have ever used for machin-ery." For sale only by the inventor and manufacturer. F. S. PEASE, (il Mainst., Buffalo, N. Y. N. B.,-Reliable orders filled for any part of the United States and Europe.

**75 (FeW 2018) (FeW 2018)**

**TRULE NEW YORK DAILY SUN-1s** forwarded by the early mails to country subscribers at \$4 per an-num, or \$1 per quarter, payable in advance. The postage under the present law is as follows: to any postofice in the State of New York, 74 cents per year, payable quar-terly in advance. Out of New York State, but within the United States, \$1,60 per year, payable quarterly in ad-vance. MOSES S. BEACH, Publisher, 4 Corner of Fulton and Nassau sts.

MPORTANT TO ENGINEERS AND MACHIN BISTS-NOTICE-Those withing to obtain the senu-inters of Metallic Oil and Grease, should send their orders direct to the manufacturer. AUGUSTUS 100K-NE), Office 67 Exchange Place, New York. No Agonts employed. 16m\*

NORCROSS ROTARY PLANING MACHINE. The Supreme Court of the U.S., at the Term of 1853 and 1854, having decided that the patent granted to Nich-olas G. Norcross, of date Feb. 2, 1850, for a Rotary Pla-ning Machine for Planing Boards and Planks is not an infringement of the Woodworth Patent. Rights to use the N.G. Norcross's patented machine can be purchased on application to N.G. NORCROSS, 203 Braadway, New York. Office for sale of rights at 208 Eroadway, New York. Boston, 27 State street, and Lowell, Mass. 42 6m\*

GRAIN MILLS - EDWARD HARRISON, of New Haven, Conn., has on hand for sale, and is constantly manufacturing to order, a great variety of his approved Flour and Grain Mills, including Bolting Machinery, Ele-vators, complete with Mills ready for use. Orders ad-dressed as above to the patentee, who is the exclusive manufacturer, will be supplied with the latest improve-ments. Cut sent to applications, and all mills warranted to give satisfaction. 10th

**BOWES: PLANER** – Persons wanting Iron Planers of superior wormanship, and that always give satis faction, are recommended to the New Haven Manufactur ing Company, New Haven, Conn. 4007

A NDREWS & JESUP-Commission Merchants Cotton and Woolen Machinery, Steam Engines Machinists' Tools Belting & c., Importers and Dealers in Machinists' Tools, Belting, &c., Importers and Dealers in Manufacturers' Articles; No' 67 Pine street, N. Y. 23 ly

NEW HAVEN MFG. CO.-Machinists' Tools, Iron Planers, Engine and Hand Lathes, Drills, Jolt Cut-ters, Gear Cutters, Chucks, &c., on hand and finishing. These Tools are of superior quality, and are for sale low for cash or approved paper. For cuts giving full descrip-tion and prices, address, "New Haven Manufacturing Co." New Haven, Conn. 40 tf

ARRISON'S GRAIN MILLS-Latest Patent... \$1000 reward offered by the patentee for their equal. A supply constantly on hand. Liberal Commis-sions paid to agents. For further information address New Haven Manufacturing Co., New Haven, Conn., or to S. C. HILLS, our agent, 12 Platt street, New York.13tf

THE EUROPEAN MINING JOUENAL, RAIL-way and Commercial Gazette. A weekly newspa-per, forming a complete history of the Commercial and Scientific Progress of Mines and Railways, and a carefuily collated Synopsis, with numerous Illustrations, of all New Inventions and Improvements in Mechanics and Givil Fragineering. Office 25 Fleet street, London. Price 85 50 per annum. 36 H \$6 50 per annum. 36 tf

Â

De No

# Science and Art.

120

## Purifying Cotton Seed for the Manufacture of Oil and Oil Cake.

Heretofore the efforts made to render the seed of the cotton plant available for the production of oil, or for the purpose of feeding man or domestic animals, have not been productive of perfect results, owing to the nature of the shell, by which the kernel of the seed is enclosed, as some fibers of the cotton adhere to it, and both the shell and the fibers of cotton absorb a considerable portion of the oil. and also render the cake unsuitable for feeding purposes. On the 24th of July last, a patent was granted to Daniel W. Messer, of Boston, Mass., for an improvement in preparing cotton seed, having for its object the removal of the above evils. The nature of this improvement consists in the separation of the shell of the seed from the kernel, previous to expressing the oil, by which a greater quantity of oil is obtained from the same amount of seed, whilst the residuum, or oil cake, is left free from shell and cotton fiber, and is therefore rendered much superior for feeding cattle. This he accomplishes as follows :-

The shell of the cotton seed is first softened by soaking it in water, or by subjecting it to the action of low steam. When boiling water is employed, about five minutes' immersion of the seed in it is sufficient; when cold water is employed, a much longer time is necessary; and the time required to soften different varieties of seed, varies with the amount of moisture in the seed. After the seed is thus softened, it is passed through proper rollers, or subjected to gentle pressure in a press in small quantities. By this means the shell is broken, and the kernel is forced out. Both the kernels and shells of the seed are then dried in the sun, or by very low artificial heat. If the oil is to be used for culinary purposes, great care must be taken not to dry the kernels under a high heat. When dry, the kernels and seeds are separated from one another by sieves, and the oil is then expressed from the clear kernels by passing them between revolving pressure rollers, or any suitable oil pressing mill. The residuum, or skin, of the pure kernels form beau tiful oil-cakes for feeding cattle. The subjecting of the cotton seed to soften it, then afterwards separating the kernels perfectly free from the shell for the purpose described, constitutes the invention of Mr. Messer, and it appears to be one of importance to our cotton planters.

### Power of Steam under Great Pressure.

It has been remarked by very able chemists that gunpowder is one thousand times denser than the atmosphere. If, therefore, one thousand cubic inches of atmosphere were compressed into one inch, the one inch will be of the same strength as one cubic inch of gunpowder. Steam possesses about one-half the gravity (or weight) of the atmosphere; therefore, if 1,728 inches of steam, which can be generated from one single cubic inch of water, were compressed into one inch, it would become nearly twice the strength of one cubic inch of gunpowder. This fact will illustrate the great expansive force of steam. From these data approximately, according to the size, contents, and area of the boiler, its explosive power may be estimated; therefore we need not be surprised that those results ensue wherein tuns weight of material are driven to grea distances by the explosions of steam boilers.

#### Fumigating Paper.

There are two modes of preparing this article :--First, take sheets of light cartridge paper, and dip them into a solution of alum; say alum one ounce; water, one pint. After they are thoroughly moistened, let them be well dried. Upon one side of this paper spread a mixture of equal parts of gum benzoin and balm of tolu; or the benzoin may be used alone. To spread the gum and balm, it is necessary that they should be melted in an earthenware vessel, and poured thinly over the paper. Finally, the surface is smoothed with a hot spatula or iron. When required for use, slips of this paper are held over a candle, so

# Scientific American.

ignite. The alum in the paper prevents it, to a rapidly dries. Slips of this paper, rolled up certain extent, from burning.

steeped in a solution of saltpeter, in the proportion of two ounces of the saltpeter to one the agreeable perfume of the odoriferous gums. pint of water; to be afterwards thoroughly dried. Gum benzoin and tolu, alone or together, are to be dissolved, to saturation, in join and become as one. When cut into slips, rectified spirit or pale brandy, and with a brush they form what are called "Odoriferous Lightspread upon the paper, which, being hung up, ers."-[S. Piesse's Art of Perfumery.

as spills, are to be ignited and then blown out; Second, sheets of good light paper are to be the saltpeter in the paper causes a slow combustion to continue, diffusing, during that time,

If two of these sheets of paper be pressed together, before the surface is dry, they will

#### HEATH'S PATENT REAPER.



This figure is a perspective view of a reaper illustrating the improvements for which a patent has been granted to John E. Heath, assignor to Henderson & Caryl, Sandusky, Ohio. The nature of the improvements consist in the manner of suspending the cutter-bar by stirrups near the ground, in front or behind the driving-wheel, and in or near the same plane as the finger-board, in combination with an angular friction roller whereby the stability of the machine is increased and its draft diminished. It also consists in having an adjustable cutter-bar to regulate the pressure between the cutters and reaper, as may be desired.

a is a wooden back piece and b is a wooden side piece: c and d are cross pieces, securely fastened to an iron front piece, e, which extends across the whole width of the machine. There are standards rising from the cross pieces, c d, in which are placed the bearings of the axle or shaft of the driving wheel, f. The end of the tongue, g, is hinged to the standard on the piece c. On the top of the arm, i, an upright lever has its fulcrum pin. It projects upwards from the tongue, g, and has its forward end hinged to a strong staple, n, which rises from the front piece, e. The tongue passes through this staple, which is sufficiently high to allow the lever to elevate the front part of the machine over any obstacle, or over the cut grass when turning. Upon the tongue, g, in front of the staple is placed a gauge block, k, attached by a screw in a slot. This block serves to adjust the hight of the cutters according to the hight of the team or nature of the ground. A slit is formed in the periphery of the driving wheel, f, of such a form as to give a rapid reciprocating motion to the friction roller, m, when the machine is in motion. This roller plays loosely upon an arm projecting upwards and backwards at an angle of about 45 degrees from the horizontal cutter bar, n, which is suspended from the top of two standards by the hinged stirrups, g and r. By this arrangement, the friction of the cutter bar is reduced to a minimum, and run very near the ground. The power being transmitted from the driving wheel near its point of contact with the ground increases the stability of the machine and diminishes its draft. Upon the upper side of the cutter bar, n, are bolted the separate cutting teeth, t. These are placed close together and their cutting edges are beveled on their upper side-meeting at an acute angle in front. The fingers, u, are also made separate, and in a T form, with points in front. The portions which are opposed to the cutting edges of the teeth, t, are beveled on the under side and ground sharp. The rear portions of the fingers are of the same thickness as the cutter half of the width of the front piece, o, form a rebate in which the cutter bar traverses. From as to evaporate the odorous matter, but not to zontal pieces, r, to which bent pieces or jacks, the presence of a large crowd of spectators.

w, are secured by set screws. These jacks are connected by their forward extremities to an adjustable pressure bar, x, which bears upon the upper sides of the teeth, t, its front corresponding with the point of junction of the cutting edges of the teeth. This bar, with the jacks and set screws, serves to regulate the pressure between the cutters and fingers, as may be desirable. The rod is supported on the frame, and is rotated by a cord passing over a pulley on the driving shaft and another on the axis of the reel.

Messrs. Henderson & Caryl have manufactured a great number of these machines, and have been very successful in so doing, as they assure us that not one of them has yet been returned for repairs. They are now busy making about 1,500, to have them ready for the spring and summer sales. Mr. Heath has obtained several patents on harvesters, but this one embraces his most recent improvements.

More information relating to the sale and manufacture of these machines may be obtained by letter addressed to D. C. Henderson & Co., Sandusky, Ohio.

Quartz Ware. The Mount Alexander Mail, Australia, states that a miner at that place named Thomas Golightly, is about to apply for apatent for a process he has invented of obtaining castings of quartz resembling Chinaware in transparency. By chemical experiment, he has ascertained that the mineral may be fused and cast into any required shape. Of course, if this be true, it will no longer be necessary to crush it in order to wash out the gold from the fragments, for by simply melting it, the gold may be separated more easily, and to do this Mr. Golightly has invented a process. The quartz being melted, the casting into ware is intended to be then performed without the necessity of a melting for that especial purpose. Besides the transparency mentioned, the quartz ware would, it is said, equal in whiteness the purest alabaster. Such an invention would, of course, be of the greatest value to both Australia and California, and should it prove practical, the manufacture of quartz ware would probably soon become one of the most important branches of industry in both regions."

[We cannot discover anything new in the above alleged discovery. Quartz can be cast, and is now cast into a variety of forms,-cast glass articles for example.

Great Feat in Ascending an Inclined Rope. An Italian named Signor Caroni, and his wife, both beyond middle age, recently walked on tight ropes from the ground to the top of a four-story building, in San Francisco. The bar, n, and being firmly secured on the front hight was 64 feet, and the length of rope I75 feet. The ropes were an inch and a quarter in diameter, placed three feet apart, and steadied the rear of the front piece, e there project hori- by guys. The feat was performed with ease in The Dhoora or Indian Millet.

This plant bears a small kind of grain, much cultivated and extensively consumed in Indïa and Egypt, and the interior of Africa; it is quite equal in nutritive value to the average of English wheats, and yields a beautiful white flour. Prof. Johnston, recently deceased, analyzed it, and found that it contained 11 1-4 per cent. of gluten. Now, since gluten is the chief nutritive ingredient of all our grains, this comparison of the Professor exhibits, at once, a nutritive value for the Dhoora that surpasses some of the richest grains in use for the food of man or stock.

Some of this grain has been raised this year by Major R. A. Griffin, of Abbeville, S. C., and it has proven to be a valuable crop, as we learn by the Abbeville Banner. He planted it some time in April, four feet in the row, and fifteen inches in the drill, depositing five or six grains in a hill. He afterwards thinned down to one stalk, transplanting to hills that were deficient. This thinning is necessary, from the strong tendency of the plant to sucker and spread. The soil, such as would be selected for common corn, should be properly prepared and manured before planting; the yield is from 80 to 100 bushels per acre.

Extending his experiments recently to the green stalk of the Dhoora, Major G. discovered a cause of its being so much relished by stock, and its singular fattening effects, in addition to the excellent qualities of its grain. He found, on chewing the stalk, which he perceived was consumed in this way by the stock, that it was exceedingly rich in cane juice-but little inferior to the sugar cane itself.

During the last month, the Illinois Central Railroad Company has sold land to the amount of one million one hundred thousand dollarsnineteen-twentieths of which has gone into the hands of actual settlers.



Inventors, and Manufacturers

## ELEVENTH YEARS PROSPECTUS OF THE

SCIENTIFIC AMERICAN.

This work differs materially from other publications being an ILLUSTRATED PERIODICAL, devoted chiefly to the promulgation of information relating to the varibus Mechanic and Chemic Arts, Industrial Manufac tures, Agriculture, Patents, Inventions, Engineering, Millwork, and all interests which the light of PRACTICALSCIENCE is calculated to advance.

Every number of the SCIENTIFIC AMERICAN contains Eight Large Pages, of reading, abundantly illus trated with ENGRAVINGS,-all of them engraved ex

pressly for this publication. REPORTS OF U. S. PATENTS granted are also published every week, including Official Copies of all the PATENT CLAIMS. These Claims are published in the SCIENTIFIC AMERICAN in advance of all other pa-

Ders. The proprietors of the SCIENTIFIC AMERICAN will COMPANY PRIVES for the pay, in cash, the following SPLENDID PRIZES for the fourteen largest lists of subscribers sent in between the present time and the 1st of January, 1856; to wit:

			-		
For the largest List	-	-	-	\$	100
For the 2d largest List -	-	-	-		75
For the 3d largest List -		-	-		65
For the 4th largest List	-	-	-		
For the 5th largest List	-	-	•		50
For the 6th largest List				-	45
For the 7th largest List	100		-	-	40
For the Sth largest List	Ч. с. 1	-	-		35
For the 9th largest List	-	-	-	-	30
Forthe 10th largest List	-	-	-	-	25
For the 11th largest List	-	-	-	-	20
For the 12th largest List	-	-	-	-	15
For the 13th largest List	-		-	-	10
For the 14th largest List	-	-	-	-	5
Names can be sent in at differ	ent t	imes	and	from	differ-
-					

ent Post Offices. The cash will be paid to the order of the successful competitor immediately after the first of January, 1856.

TERMS := \$2 a.year ; \$1 for half a year, Southern, Western, Canada Money, or Post Office

Stamps taken at their par value for subscriptions. Letters should be directed (invariably post-paid) to

#### MUNN & CO. 128 Fulton street, New York

CLUB RATES. Five Copies for Six Months, **84** 88 Ten Copies for Six Months, -Ten Copies for Twelve Months. -\$15 Fifteen Copies for Twelve Months, 822 Twenty Copies for Twelve Months, 828