# WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY, AND MANUFACTURES.

Vol. XVII.--No. 22. [NEW SERIES.]

### NEW YORK, NOVEMBER 30, 1867.

#### Improved and Simplified Band Saw.

The endless or Band Saw has not heretofore received that degree of attention from our mechanics to which its merits entitle it. In England it is extensively used for wood work, and lately has been successfully employed on iron, especially for locomotive work. Visitors to the late fair of the Amer-

chine of which we give herewith illustrations, one being a perspective view of the machine complete, and the others of the saw guide.

With the exception of the table top, the machine is entirely of iron, the frame being strong while it is light. The standard, A, supports a frame, on which is an upwright sliding block and arm sustaining a horizontal shaft running in boxes. On this shaft is hung the upper wheel, B, which by means of the screw and hand wheel, C, can be elevated or lowered as the length of the saw demands. The lower portion of the frame under the table supports the lower shaft and wheel, which is driven by the pulleys, D. The two wheels have a flance against which the back of the saw bears, and the faces of the wheels are covered with vulcanized rubber resting on a bedding of strong cloth. This gives sufficient adhesion to the saw to insure its action as a belt without slipping.

From the front of the upper frame depends a vertical bar, E, sliding in boxes, to which it may be secured, at any hight required to accommodate the stuff to be sawed, by the thumb nuts, F. On the lower end of the bar is a guide, G, having four sides with recesses of varying depth to accommodate the various width of different saws. This guide is in two parts, held together by a screw bolt and graduated in the distance of their faces by means of the screw bolt and a four-pronged spring. The construction of the guide is better seen at H and I, the latter of which shows a section of the saw lying in one of the recesses. This guide can be turned quarter or half-way round to bring either of the different widths of recesses to engage with the saw.

The great advantage of the band saw over the reciprocating saw is, that there is no lost time in its operation, and no effort required to keep the work to the table, as the action of the saw tends to this result. Beside, there is no need of a pump or blower to clear away the saw dust, as it is carried continually downward. It was patented through the Scientific American Patent Agency, Aug. 28, 1866. Messrs. First & Pryibil, the patentees and manufacturers, state that the saw travels at

will do four times the amount of work performed with an orsilver solder, used in connection with a clamp made specially for the purpose, and the original temper of the plate is per- is formed. The inventor says: "The flanged cam takes the island of considerable extent outside of the beach was also fectly preserved.

All communications relative to the machine should be addressed to First & Pryibil, 175 and 177 Hester street, corner Mott, New York city.

#### Plan for Converting Reciprocating into Rotary Motion.

There have been quite a number of ingenious devices contrived to take the place of the crank, and avoid what are popularly supposed to be the defects in this method of converting motion. Whether this supposition is correct or not, it is probable that these attempts will be repeated indefinitely. That shown in the annexed engraving is one of the simplest, and the inventor says it has answered all his expectations. He has two engines of the same

dinary crank engine, and the other running with the spiral cam, the latter giving by far the best results.


The engraving presents a top view of the engine, A being the cylinder, B the steam chest, C the crosshead, and D the spiral cam. From the lower surface of the crosshead project | It can be applied in all cases where a reciprocating rectilinear two pins, seen at E, which engage with the sides of the cam | motion is to be converted into a rotary motion, and is used flanges and impart a rotary motion to the shaft on which the with great success on reaping machines in place of the crank.

The model or pattern of the cam may be formed by turning | pin in the crosshead passes the extreme outer end of the cam, a block of wood of the length of stroke required and of the same diameter. On both heads parallel lines are struck, and the ends of these lines connected by two other lines on the circumference, which, when the diameter of the block is, say, ten inches will be ten inches apart and parallel to each other.

L.SEITZOE

FIRST & PRYIBIL'S PATENT BAND SAW.

the rate of 4,000 feet per minute, and by actual experiment, | the diameter of the block, arcs are described from the opposite ends of the side lines. Then by opening the dividers to dinary up and down saw. Its work is very smooth, requiring the full half diameter of the block and describing two other less after labor in finishing. Certainly it is a simple and arcs, the thickness of the wings or flanges of the cam is deeconomical machine, as is evident from its construction and | termined. After repeating this operation on the opposite end operation. The manufacturers join the ends of the saw by of the block, the material is removed to the center of the block, leaving the parts between the arcs intact, and the cam



# HURLBUT'S SPIRAL CAM ENGINE.

dimensions, taking steam from the same boiler, one, the or- | place of the crank, and it has the great advantage that the | of hectares in wood had increased to over 9,000,000, or nearly power is applied always at the same distance from the center of the shaft, and under the most favorable circumstances, so that no dead center exists and a continuous revolving motion will be imparted to the shaft without requiring a fly wheel. cam is mounted, and through the pulley, F, to machinery. The cam is so constructed at its ends that when the outside

the inside pin, being at this moment the propelling power, does not pass the dead point until the outside pin has passed, when that becomes the propelling power until it reaches the opposite end of the cam."

Patented through the Scientific American Patent Agency ican Institute must have observed the operation of the ma- Then with a pair of dividers, opened somewhat less than half March 26, 1867, by William H. Hurlbut, who may be addressed relative to the invention at Mirabile, Cald-

well Co., Mo.

#### Preserve the Forests.

As compared with Europe, or with our own prairie States, New England and New York are regions of forest. There is scarcely any part of these States where the forest does not make a prominent feature of the landscape, and in most parts it predominates. Of course we do not mean the unbroken, primeval forest, but that succession of woodlands and treecrowned hills which reveal to the traveler at at once, as he comes from other countries, that he has reached a land where nature is still wild, and fuel cheap. But around the cities and along the seashore already wood begins to be scarce, and attention must be given to the planting of trees. Accordingly, in Barnstable, Nantucket, and Bristol counties, Mass., something has been done in this novel species of husbandry, as it would have seemed to our grandfathers. There can be no doubt that forests have a great influence on the moisture and fertility of the soil. It is traditional that whole regions in Spain which are now barren or only used for pasturage a part of the season, were, before the noble woods of the country were cut down, free from drouth and rich in crops. In France, the same tendency has been checked by legislation, which interfered, as early as 1669, to prevent the felling of forests without permission. The legislation is now very stringent, and in addition the Government exercises the right of compulsory plantation of trees on the land of citizens who will not be hired by the public money to plant for themselves.

The French law of 1859 forbids the cutting down of any wood larger than twenty-five acres, unless it shall appear to the proper authorities that such wood is not necessary to protect the soil on mountains or steep slopes, or against the encroachments of rivers; or to preserve springs and water courses from drying up, and the seashore from being blown or washed away; for the defence of the frontier or for the public health. It was found that to cut off the forests caused the hillsides to be stripped of soil, and the springs to dry up;

that torrents and freshets were much more injurious afterwards, and that the sea sand encroaches upon the arable fields as soon as the woods near the shore disappeared. Every one who has paid much attention to the subject knows that these changes take place, giving rise sometimes to remarkable phenomena. For instance, the long beach at Plymouth, when the Pilgrims landed there, was covered with trees, and an

> wooded. Since the trees have been cut the sea has washed the island away so that it is covered by every tide, and the beach has become so narrow in some parts that the heavy seas break through it, and needs to be strongly protected by artificial means. As the security of the harbor of Plymouth depends upon this beach, the folly of cutting down the trees is now manifest.

> The effect of the laws against cutting, and in favor of planting trees, in France, has been such, that of late years, instead of a steady decrease in the extent of woodland in the Empire, there has been a constant gain. In 1860 the wooded surface of France was 8.783.343 hectares, or less than 22,500,000 acres, the whole number of acres of land in France being at least 125,000,000. In 1865 the number

a million acres more than fifteen years. In a few of the other European countries preservation of wood has been undertaked, but nowhere with so much success as in France. Until within a few years, since coal has commanded a high price, the natural increase of wood in Massachusetts has kept pace with the amount cut off in each year.

But there is reason to believe that for the last year or two it has not been so, and in this part of the State especially,

there has been a great cutting down of firewood, the timber there having been used up some time ago.

It is true that planting has also been going on, but not on a large scale—not enough to prevent those changes in soil and climate which certainly follow the destruction of standing forests. It would be well, therefore, for our farmers and the owners of estates to consider whether they ought not to wood, which for fuel, for protection to the soil, and for ornament, will become of more and more value each year.

The countries in Europe, which most nearly resemble our own in respect to forests are Russia, in which there are 450,-000.000 acres of woodland out of a total of 1.000.000.000 acres: and the Scandinavian peninsula, where it is said three fourths | the geology of the country and its prospects as a mining reof the country is covered with wood. Canada and the extensive possessions of England to the north of Canada are counterparts in this hemisphere of Norway, Sweden, and northern Russia, and will be more and more drawn upon as our population increases and the woods recede. They are now of much value to Great Britain in this respect, for the English and Irish forests have almost entirely gone, and but few remain in Scotland.

England has thus far found in her coal mines a greater resource than anciently in her forests, but it is a great loss to ling the depth of fifty feet, and containing rude implements her to have parted with those entirely. Let her children in America profit by her example and preserve their woodlands. | mining tools. It would appear, from some of the indications, —Springfield Republican.

#### THE COPPER REGION OF LAKE SUPERIOR.

Attention was very early called to the remarkable deposits of native copper upon the shores of this great lake. The first mention of it appears to have been in the Missionary Reports of the Society of Jesus, for 1659-60. It is next spoken of by Claude Allouez, a Jesuit missionary, who visited this region in 1666. He speaks of having seen pieces of copper of ten or twenty pounds weight, which the savages reverenced as household gods, and of having passed the site of a great rock of copper, then buried in sand. In 1670 Father Dablon reports a marvellous story, which was told him by the Indians, concerning a copper island about fifty leagues from the Saut, which he interprets as a cause of poisoning from the metal, loose pieces of which the savages used in cooking their meat. Charlevoix, whose travels were published in 1744, corroborates these accounts, and mentions the fact that a brother of the order made chandeliers, crosses and censers of the copper which was there found.

About 1763, a practical Englishman, Alexander Henry, passed through this region. He narrowly escaped being massacred by the Indians, but in spite of his trouble he kept his eyes open to his own interest. In 1771, he commenced mining operations in the clay bluffs, near the forks of the Ontonagon river. The following year he transferred his workmen to the vein on the north shore, but being discouraged by the contraction of the lode from four feet to four inches, he became disgusted, and finally abandoned his workings.

In 1819, General Cass and Mr. H. R. Schoolcraft, passed through this region, and visited the famous mass of native copper on the Ontanagon. In 1823, Major Long and his party saw the scattered boulders of this formation. Nothing, however, came of all these observations, the general impression being that the wildness of the country and its distance from settlements rendered these enormous natural resources value less, at least for many years.

The first impulse to mining in this district was given by Dr. Douglass Houghton, State geologist of Michigan, who, in 1841, in his annual report to the legislature, gave an account of the geology of the country, and the first scientific description of the copper deposits. Subsequently, he devised an admirable plan for developing the resources of this region, and had commenced carrying it into practice when his sudden death by drowning put a stop to these important observations.

In 1843 was ratified with the Chippewas a treaty, which put the United States in possession of the territory as far west as the Montreal river, and southerly to the boundary of Wisconsin. The same year numbers of persons entered land in this neighborhood, by the provisions of a joint resolution of Congress in reference to the "lead lands" of Illinois, passed as far back as 1818. At first the applicant was allowed to select a tract three miles square, but afterward he was limited to one mile square. He was required to make selection within a year, to mark the corners, to leave a person in arge to point out the bounds, and to transmit to department a description and plat of the same. On the receipt of this plat, the applicant was entitled to a lease of three years, renewable for three additional years, on condition that he should work the mines with due diligence and skill, and pay the Federal Government six per cent. of all the ores raised.

As a natural consequence of these liberal provisions, a great influx of speculators and their agents took place into this territory. The first mining operations were commenced in 1844. Masses of native copper, containing silver, were found, and numerous veins were discovered. About a thousand permits were granted by the department, and nine hundred and sixty-one sites selected. Sixty leases for tracts three miles square, and one hundred and seventeen for tracts one mile square, were granted, and mining companies were organized under them. Most of the tracts covered by these were taken at random, and without any explorations whatever; indeed, a large portion of them were on rocks which do not contain any metalliferous veins at all, or in which the veins, when they do occur, are not found to be productive. The excitement reached its hight in 1846. Quantities of

stock were sold which represented no value whatever, and this reckless speculation injured the reputation of the mines.

In 1847 the country was almost deserted, only about half a dozen companies, out of all that had been formed, being engaged in mining.

In 1846, further grants of land were suspended as illegal, the resolution in regard to lead not covering copper lands, and take some greater pains to plant and preserve the growth of the following year Congress passed an act authorizing the sale of the lands and a geological survey. For the latter purpose, Dr. Charles T. Jackson was appointed, but after have ing spent two seasons in these explorations, he resigned, whereupon the work was confided to Messrs. Foster & Whitney, who have given a very full and satisfactory account of gion. Meanwhile, the actual miners had made considerable progress in their excavations, and as they purchased lands after thorough examination, confidence was gradually restored. By the time the United States Survey had been completed, and its results published, in 1850, copper mining had pecome an established business.

The report of Foster & Whitney contains some very interesting details of the discovery of ancient excavations for mining purposes. Some of these are quite extensive, reachfor boiling water, stone hammers, copper gads, and other that fire was the agent used to disintegrate the rock. Some idea of the extent of their operations may be formed from the fact that one of the explorers found a mass of native copper weighing six tuns, which had been detached by these ancient miners and supported on billets of oak, preparatory to remov al. The age of these works may be inferred from that of a pine-tree stump, growing out of one of the mounds of rubbish from the mine. This contained three hundred and ninetyfive annual rings, so that the exploration must have been made before Columbus started from Europe on his memorable voyage of discovery.—Piggot on Copper.

#### EXPANSION AND CONTRACTION OF STEEL.

Expansion and contraction belonging to this subject is the enlargement, or increase, or decrease, in the bulk of the steel, as the case may be, in consequence of a change in the particles by the process of hardening. It is pretty generally known to those who are employed in the process of hardening steel, and to those in the habit of fitting up various kinds of work requiring great nicety, that the hardening of steel often increases its dimensions; so that such pieces of work, fitted with nicety in their soft state, will not fit when hardened, and the workman has therefore to resort to the process of grinding or lapping to make the work fit.

The amount of the expansion (or the amount of the contraction) of steel cannot be exactly stated, as it varies according to the size of the steel operated upon, and the depth to which the steel hardens; also in the different kinds according to the amount of carbon combined, and even in the same steel operated upon at different degrees of heat. Steel which is the most liable to injury by excess of heat is the most liable to these expansions, and steel which is less liable to injury by heat is most liable to contractions. As, for example, the more carbon the steel contains, the greater will be the expansion of the steel; and the nearer the steel approaches to the state of iron, the less will be this increase of bulk.

Although the steel expands in hardening, it is not universal for pieces of all sizes to increase in dimsnsions; for sometimes it is smaller in dimensions after hardening. This, at first sight, appears anomalous; but I will endeavor to give an explanation of it.

Steel, like all other substances composed of particles, varies in its dimensions with a change in temperature. It follows that when the steel is at a red heat, the natural positions of its particles are in a measure displaced, and it is expanded to a greater bulk; and when immersed in water and suddenly cooled, such a change of its particles takes place as to make it hard and brittle. It also contracts to a smaller bulk by the loss of heat: but this cannot so rapidly occur at the central part, because it is protected by the surface steel. Consequently, large pieces of steel do not harden all through; or, in other words, do not harden properly to their centers, but toward the center the parts are gradually less hard, and will outer parts of the steel which harden properly, consequently it first of all to act upon the outer crust of the steel and then cooling it gradually toward the center. The outer crust being the first to part with its heat, it is of course the first to contract and become smaller. The outer crust in contracting is held in a state of great tension, by having to compress the central steel (the central steel at the time being expanded by the heat). While the surface steel is in this state of tension, and the central steel in this state of compression, the particles of the surface steel (by the strain) are displaced to a greater distance from each other, and the particles of the central steel (by the compression) are compressed into a denser state. The particles of the central steel being compressed into a denser state, it causes the central steel, after it has become quite cool, to occupy less space than what it did previous to hardening. The particles of the surface steel become hard while in this state of tension, consequently the hardened part of the steel becomes fixed, and cannot return to its original bulk; consequently, the hardened part of the steel occupies more space than what it did previous to hardening.

If the displacement of the particles of the outer steel predominates over the compression of the particles of the central steel, the piece of steel under operation will then be larger in Another hint deserves a place. I have found that articles

dimensions. If the con-pression of the particles of the central steel predominates over the displacement of the particles of the outer steel, the piece of steel under operation will then be smaller in dimensions. In other words, if the expansion of the outer steel amounts to more than the compression of the central steel, the piece of steel will increase in bulk; if the compression of the central steel amounts to more than the expansion of the outer steel, the piece of steel will then decrease in bulk. The expansion of the steel is greatest when it is heated to a high degree of heat before immersion. This effect is owing to the particles being displaced at a still greater distance from each other, and which may, in some measure, account for the brittleness of steel when overheated. This expansion is, in some measure, reduced by tempering; and this effect is caused by the hardness being reduced and allowing the particles to partly rëarrange themselves to their natural positions.

It is believed by some that the hardness of steel is caused by the compression of the whole of the particles into a denser state; in confirmation of this they say that steel after hardening always looks closer and finer in the grain. Now, if this were the only cause of steel becoming hard, how does the steel get larger in dimensions? Pieces of steel of all sizes would, according to this, universally become smaller. The compression of the particles of the central steel into a denser state certainly does take place, as I have before remarked, but the particles of the outer parts of the steel are displaced at a greater distance from each other, or the steel could not become larger in dimensions. It is believed by some that if a piece of steel (in hardening) increases in bulk in one part, that it must decrease in bulk in proportion in another part. Now, if this were the case, how is it that the specific gravity of some pieces of steel is reduced by hardening, and how is it that workmen have often to grind or lap pieces of sieel to make them fit the same places which they fitted previous to hardening. It may be said that the steel may be prevented from fitting the place it previously fitted by becoming crooked or oval in hardening; but if this were the only cause, how could it be made to fit its place again by grinding or lapping? It would be impossible (unless it were softened and upset) to make the lean or concave side of it fit its place again. I may also inquire, what is the cause of steel being whiter in color after hardening? As I have previously remarked that it is only those parts of the steel which harden properly that increase in bulk, it may perhaps be asked, how is it that a piece of bar steel becomes shorter in hardening? The answer is that the central steel is compressed by the surface steel endways as well as sideways, by the surface steel contracting shorter by the loss of heat. The central steel contracts after the outer crust is fixed, consequently an internal strain is caused; and, if the steel becomes shorter than what it was previous to hardening, it is because the force of this internal strain shortens the outer steel more than it expands in hardening.

It is quite reasonable to suppose, if the particles of the hardened parts of the steel are removed to a greater distance from each other, that the steel would look considerably more open and coarser in the grain; consequently, it may be inquired, if it is not the compression of the whole of the particles into a denser state, what is the cause of steel looking closer in its texture after hardening? The answer is, if we accept the theory that it is the crystallization of the carbon which causes the hardness in steel, that the carbon expands in the act of crystallization (in a similar manner that water expands by extreme cold in crystallizing into ice) and fills up every pore or crevice, and gives the steel the apbearance of being closer and more solid.

Such is a slight sketch of the expansion and contraction of steel; and, although a great deal more might be said, I have not thought it necessary to entangle the reader with a lot of theories, although it may be necessary for his amusement, and for the exercise of sound judgment, to occasionally glance at them in treating fully the purely mechanical op-

The expansion of steel is prevented in some measure by annealing the steel about three times previous to its being finished, turned, or planed; for instance, after the first skin is cut from the steel it should be annealed again, after which another cut must be taken from it and again annealed, and so the third time. This may appear to some like frittering sometimes admit of being readily filed; and as it is only the away time, but in many instances the time will be more than saved in lapping or grinding to their proper sizes after the is only those parts of the steel which harden that increase in articles are hardened, especially when it becomes necessary to bulk. When the steel is immersed in the water, the water lap or grind them by hand labor, for hardened steel works with great difficulty; therefore in some instances it becomes a matter of importance in hardening to keep the article as near as possible to its original size. I have myself had articles to harden which could not be lapped or ground to their finished dimensions in the turning lathe owing to their peculiar shapes, so that the workman has been compelled to adopt the slow process of lapping with a copper file and emery dust, mixed with oil. I have known those articles which were only once annealed, to take several hours to lap them to the finished dimensions after they were hardened; and I have known articles of the same kind, and of precisely the same dimensions (in their soft state), made from the same bar of steel and heated to the same temperature (as near as the eye could judge) and hardened in water of the same temperature which have been annealed three times, scarcely requiring to be touched with the copper file after they were hardened. As there may be some persons who may perhaps require an article to be after hardening as near its original size as possible, and who may not perhaps be provided with such things as buffs, laps, or stones, I presume therefore that this hint will not be out of place in making those acquainted with it.

made of steel which have been well forged will always keep truer and keep their original sizes better in hardening, and be less liable to break in hardening, than articles which are made of the steel in the state it leaves the manufacturer; for instance, if a very long screw tap, or reamer, etc., be required for any special purpose, it will be well to take a piece of steel sufficiently large to admit of being forged to the re quired dimensions. If for a long screw tap, three quarters of an inch in diameter, seven eights round-bar steel swaged down at a cherry-red heat to three-quarters and a sixteenth will suffice (the one-sixteenth is allowed for turning); but if the edges of seven-eighths square steel be hammered down so as to form eight squares and then swaged down to threequarters and a sixteenth, it will prove even better for the purpose than the seven-eighths round-bar steel, it must be obvious that if similar methods be adopted with larger articles, they will be less liable to break in hardening.—Ede on Steel.

### Correspondence.

The Editor are not responsible for the opinions expressed by their correspondents.

#### The Chicago Artesian Well.

MESSRS. EDITORS:-In two or three numbers of your paper I have read notices of this truly great and wonderful work, which, though originated and prosecuted upon theories outside of old fashioned mundane science, has proved more successful than anything of the kind ever attempted in this country. The history of the work, as detailed by its principal agent, Geo. A. Shufeldt, Jr., is briefly this: A gentleman named Abraham James, claiming to act by spiritual impressions, pointed out the locality where the well is now flowing, and insisted that at a certain depth artesian water could be had by boring. Upon the strength of his representations the work was commenced, and water in large quantities, and, for deep well water, of very pure quality, was struck within a few feet of the depth he had designated, and flows out at considerable hight above the surface, at the rate of 1,200,000 gallons per day. As Chicago, before this proof was given, was not known by most people to be situated over the bottom of a geological "basin," the whole matter is considered by its projectors a signal proof of spiritual intelligence and communication. But the work being finished,-no matter by what authority,-its details show clearly, that instead of its being wonderful that an artesian well is obtained there, it is one of the most beautiful proofs of the truth of the common theory of such wells; and to demonstrate this is the object of this paper.

It is supposed by Agassiz and others that the first rocks which appeared above the primeval ocean upon this continent—and perhaps on the earth—are those which constitute the Laurentian Range, bordering Lake Superior and running outwardly to the Atlantic. What we know is—for the rocks testify to it—that on the outward slope of this range, along the Mississippi river and its eastern branches, as we go downward geographically, or hydrostatically, we go upward geologically; that is, the different stratas of deposited rock—many of which outcrop along the river's bank—all lie like the tiles upon the roof of a house, overlapping and running under each other; but—to follow out the figure, the eave of the house is the highest; and, of course, the water falling upon it would run under instead of over the stratas.

The first deposit upon the Laurentian (which is an igneous rock thrown up by internal convulsions), is what has been called by some the St. Peter's Sandstone. This commences on the St. Croix river, one of the principal eastern branches of the Mississippi, at about one hundred miles south of the lake, and fifty or more from the ridge which forms the watershed between the lake and all the eastern branches of the upper part of that river. For thirty miles along the St. Croix this stone forms its banks, into which it has cut its way in ages past to a depth of one hundred feet or more leaving nearly perpendicular precipices upon each side.

This stone is impervious to water, and is probably the foun dation stone of all that part of northern Wisconsin which abounds in tumarack, cedar, and cranberry marshes. It is covered with a thick deposit of drift, forming low hills of loose, pebbly soil, between which are the swamps and lakes and some alluvial deposits. Following down the Mississippi river, this sandstone, which is called by the Iowa State Geologists the Potsdam Sandstone is last seen near the north line of that State, and there dips under the lower Magnesian limestone, which in about forty miles dips under another thin bed of sandstone, over which soon commences the thick and ex tended deposits of the Galena, or lead-bearing limestone, the latter the principal rock of the river bluffs for over one hundred miles. A little north of the latitude of Chicago commences a bed of Hudson river shale, which is overtopped by a thick deposit of Niagara limestone, which disappears under ground at a point on the river exactly west of Chicago. From this point the geological deposits going south and east rise with great rapidity up to the coal measures of central Illinois, through various stratas of limestone, mostly of a fine building quality.

well penetrated through all these stratas, which were not wanting, until it reached and went through the St. Peter's sandstone, and struck the water which fell upon the earth along the Southern Laurentian slope, and has run beneath that bed of rock, ready to spout from any hole which reaches it. This, if true, would account for the great purity of the water as compared with other artesian fountains, as it has encountered on its way no soluble mineral substances, and was originally strained through the sand drift of upper Wis-

The diary, kept apparently with great care during the boring of the second well, shows plainly that after going down about three hundred feet, through various limestones and marble, the drill struck the Niagara limestone, which forms the surface rock on the Mississippi, directly west of Chicago. It is described as a grey limestone, one hundred feet thick, with layers of flint. This description tallies exactly with the character of the stone exposed in the bluffs at this place. Underneath this was found a bed of shale, the same in character as that which lies below the limestone here, but which is still partially above the bed of the river. This proved to be about one hundred and fifty feet thick (here it has been bored into a great distance, but not through). From the bottom of this shale downward, the character of the rock is not so well defined in the diary. The Galena and lower beds of limestone seem to be wanting, and the drill appears to have reached the still lower sandstones, under which the water is stored.

The conclusions which I draw from the above are, 1st, That artesian water can be obtained at any point in this region by going deep enough to penetrate the St. Peter's or Potsdam sandstone; and 2d, That along the Mississippi river, as low down as the latitude of Chicago, it can be had at a depth several hundred feet less than at that place.

C. B.

Lyons, Iowa.

#### The Cave of the Puy de Dome.

MESSRS. EDITORS -- In your issue of Nov. 9th, I notice a communication from "M.A.D." requiring a solution of a natural phenomenon existing in the south of France. As you intimate, the facts are scarcely correct, as represented by "M. A. D." They are these: In the locality mentioned a spring issues from underneath a deposit of lava, which is remarkably cold, sometimes even covered with ice, in the hottest part of the summer; and in the winter has a temperature exceeding that of the air surrounding. Now there is nothing very extraordinary about this spring, excepting its excessive coldness (exhibited by the production of ice) in excessively hot weather, and this wonderful quality so much dwelt on and exaggerated possibly, by the guides who conduct tourists to the mountain (Puy de Dome), admits of a very simple explanation to the educated man, though a great mystery to the uneducated natives, and to some of those who ought to know better. This explanation consists in the fact that the rock through which the waters of this spring percolate, is of a very porous texture; in the hot weather a very rapid and abundant evaporation takes place, which reduces the temperature and causes the water to escape at or near the point of freezing. At my visit there, there was no ice in the spring, though I was assured that the occurrence sometimes took place. Under the circumstances, it is possible, and I believed the assertion for that reason, and not because one is told so In the winter, in cold weather, as a matter of course, the water would be warmer, and in certain states of the atmosphere would give off vapor, as other springs do under the same circumstances. This vapor is magnified into steam, and the double contrariety of cold in summer and heat in winter makes a pretty wonder for the uninstructed villager or trav eler. Possibly the wonderful evidences of intense volcanic action to be seen here, predisposes one to be rather too credulous as to mysterious phenomena. HENRY STEWART.

Norristown, Pa.

# Treatment of Kerosene Lamps.

MESSRS. EDITORS:—In your issue of Nov. 2, page 275, your correspondent "Experimenter" has given advice, which I cannot but think detrimental to the safety of the Kerosene burning public. He states that "if the wick fits the tube, it is impossible to drive the flame down into the lamp by blowinto the chimney," and further, recommends that method of extinguishing the lamp. Now your correspondent must be more fortunate in the possession of a good and perfect burner than nine-tenths of the people, for nine-tenths of all the burners used are made with vent holes along the side of the tubes, or in close proximity thereto, much larger in area, and much nearer the explosive mixture in the lamp than by way of the tube, with never so loose a wick as usually used.

The theory of lamp explosions, as I understand it, is this First, Kerosene of itself is not explosive, nor is the gas which rises from it, but it is the admixture of that gas with a large body of air that makes it dangerous. Kerosene, or coal oil, is a dense body, which gasifies slowly, requiring, during the process of combustion in lamps as used, air to take the place of the oil consumed this air passing down by the heater tube through the vent holes, as before stated, becomes warm, and by its heat eliminating a certain amount of gas, small in proportion to its own incoming body. The prolonged burning of the lamp, say for four or five hours, reduces the quantity of oil, enlarges the space for the explosive gaseous mixture, and imparts also a great heat to the contents of the lamp, which then gives forth vapor more freely, so as finally to produce the proportion of one part gas to nine of air, which I take it is the maximum point. This heat also increases the volume inside the lamp, causing this dangerous mixture to exude by these same vents, close beneath the flame, then catching from some deflection of the flame or its proximity thereto, explodes the lamp while standing on the table, and more often still when carried in the hand, or in going down stairs. Thus it will be seen that to blow the flame down is to invite destruction, unless the burner is properly constructed, as comparatively few are. The proper method is to draw the wick into the tube by means of the ratchet, which, while avoiding danger, will prevent any odor arising from the oil PENROSE CHAPMAN.

Brunswick, Me.

# Artesian Wells---Why the Water Flows---Is it Centrifugal Force?

Messrs. Editors:—A correspondent has published in a recent number of your journal, a theory of the nature of spouting water, in which he attributes the discharge of the water to the centrifugal motion of the earth—the tendency of matter to fly from the center. I have heard this opinion advanced before, and the existence of perennial springs, on the Adelsburg mountains in Switzerland, and in other places, adduced as evidence in support of the theory, but I do not believe it to be founded on fact.

I bored the Chicago Artesian; they are 711 feet in depth; they commenced filling with water at a distance of ten feet from the surface, and continued full of water all the way down. Why did not the centrifugal force throw this water out? and why was no water discharged until the drill had penetrated a particular subterranean stream? Before this point was reached there was plenty of water in the wells, and we could pump out an abundant supply; and this is true of hundreds of other artesian wells scattered throughout the country, they do not discharge the water above the surface, but plenty of it can be obtained by pumping. Why does not the centrifugal force throw the water out of these wells? And why do they not all become flowing wells, as would be the case if the theory were true? Or, in case of dry wells, why does this force not throw out the stones and chippings of the drill as well as the water? For these reasons I am inclined to adhere to the opinion that water, in flowing wells, comes from a higher source, and that the crust of the earth is everywhere penetrated by these underground streams to an extent of which at present we have no conception. For the benefit of another of your correspondents I here state that the temperature of the water in our wells is 57° Fah., and is uniform winter and summer. It was incidentally mentioned in your paper that the flow was intermittent: this is not the case; but it is without change in quantity or force all the year round. The form of the overflow resembles the white plume of a soldier, and is extremely beautiful. GEO. A. SHUFELDT, JR.

#### The Philosophy of the Soap Bubble.

MESSRS. EDITORS:—On page 291, No. 19, current volume of your famous journal I find a communication from Mr. Alfred O. Pope, detailing his experiment by which he imagines he has proved Sir David Brewster's theory regarding the color of soap bubbles. I do not find fault with the experiment, but with the deductions drawn from it. He does not tell us how his experiments prove that secretions were formed and until he demonstrates that they were formed he has not proved Brewster's theory. All admit that the thicker the film of the bubble the brighter the colors will be. Oleate of soda and glycerin in solution make a thicker film than a solution of common soap. Consequently, when the liquid begins to flow down the sides of the bubble and collect in drops at the bottom the top gets thinner and the colors then become paler and there being a constant change in the thickness of the film all over the bubble there is as constant a change of color until a deep blue or black makes its appearance at the top of the bubble which becomes so thin that the cohesive force is overcome by the weight of the sides and bottom, and the bub ble bursts. CHEMIST.

Cincinnati, Nov. 5, 1867

# Recipe for Making Boots Water Tight.

Messrs. Editors:—As the cold, muddy weather of fall is approaching, it may be of interest to many of your readers to know how to preserve their boots and make them at the same time pliable and water proof. It can be done in this way: In a pint of best winter-strained lard oil, dissolve a piece of paraffine the size of a hickory nut, aiding the solution with a gentle heat, say 130° or 140° F. The readiest way to get pure paraffine is to take a piece of paraffine candle. Rub this solution on your boots about once a month; they can be blacked in the meantime. If the oil should make the leather too stiff, decrease the proportion of paraffine, and vice versa.

I have used this for eight years past, and boots have lasted me two winters, the uppers always remaining soft, and never cracking. I have tried beeswax, rosin, tar, etc., but never found any other preparation half so good.

Dayton, Ohio.

ARTIFICIAL RUBIES, not mere copies in glass, but made veritably out of the same substance-alumina-of which the natural gems are composed, have been produced by M. Ebelsman of the Sevres Porcelain Works, near Paris. The process consists in employing a solvent, which shall dissolve the mineral or its constituent, and may thus, either upon its renewal or by a diminution of its solvent powers, permit the mineral to aggregate in a crystalline state. Certain proportions of alumina, magnesia, oxide of chromium, or oxide of iron, and fused boracic acid, are placed in a crucible made of refractory alumina enclosed in a second one, the whole being exposed to a high heat. The materials are first dissolved in the boracic acid, then as the heat continues, the latter evaporates, the alumina and coloring matter combine, crystallize, and present the exact appearance of the spinel ruby. In this way crystals of the same form, hardness, color, composition, specific gravity and effect on light, as the cymophane, and other precious stones are prepared.

WINE CONTAINING ZINC.—Dr. Wittstein has recently found that most European wines contain zinc in the form of salts, its presence being due to the fact that the isinglass used in purifying the wine is adulterated with about  $2\frac{1}{2}$  per cent of oxide of zinc.

#### THE CHEMISTRY OF METEORITES.

M. Daubrée, already so distinguished for his researches on metamorphism, has recently published the results of his Synthetical Experiments on Meteorites, and has thus brought before us, from an entirely different point of view, an inquiry into the nature and origin of the silicated magnesian rocks and minerals.

M. Daubrée first describes his experiments on the imitation of the meteoric irons. The most characteristic feature of these masses is the crystalline pattern, which is brought to view on a polished surface by the action of an acid. Simple fusion of the meteorite of Caille (Var) in a brasque of alumina (to avoid the contact of carbon, which would have combined with the iron), was insufficient to reproduce the appearance, although the resulting substance was certainly crystalline. Further experiments, in which soft iron was associated with some of the other substances that commonly accompany meteoric iron, such as nickel and protosulphide of iron and silicon. yielded a highly crystalline result, but not yet of the true character. If, however, to the soft iron was added phosphide of iron, in the proportion of from two to five or ten per cent, and, still better, if there was introduced at the same time nickel, and if a mass of as much as two kilogrammes in weight was operated on, there appeared, when the cooled lump was polished and etched, in the midst of dendritic patterns of great regularity, lines of a brilliant material dispersed in a reticulated form.

A third mode of attempting the imitation was that of melting down certain terrestrial rock substances, as peridote, lherzolite, hypersthene, basalts, and melaphyres. By this means specimens of iron were obtained which, both in composition and structure, bore strong resemblance to many of the siderolites. Especially was this notable in the metal obtained from the lherzolite of Prades (Eastern Pyrenes). These artificial irons were then found, like the natural meteoric ones, to contain nickel, chromium, and phosphide of iron, the latter in long needles recalling the appearance of the natural patterns.

Imitation of the Meteoric Stones.—Contrary to what might have been expected from the appearance of the black vitrified crust on the surface, the substance produced by the melting down of meteorites obtained from above thirty different falls, was in every case highly crystalline. Those of the common type present a group of metallic granules, disseminated in a stony mixture of peridote and enstatite, the former generally on the surface as a thin crystalline pellicle, the latter in the interior as long acicular crystals. A notable contrast was yielded by the aluminous meteorites, such as those of Juvinas, Jonzac, and Stannern, which produced, instead of crystalline, a vitreous mass.

But perhaps the more remarkable results were those obtained synthetically by melting down pieces of rocks characterized by the minerals peridote and enstatite. For this purpose peridote (olivine), from the basalt of Langeac (Haute Loire), and Iherzolite, from Vicdessos and Prades, were fused in earthern crucibles. They melted easily and yielded crystalline substances, the latter especially closely resembling the original rock. The proportion of enstatite (the bisilicate of magnesia) was found to be increased by the addition of silica.

When similar mineral substances were melted in presence of a reducing agent, the iron (which in the other case remained combined in the silicate) segregated itself in grains of various sizes, separable by the magnet. Thus a perfect analogy was established between the above rocks and the meteorites, as well in the stony minerals as in the iron, which always contained nickel.

Furthermore, some remarkable characters in the structure of the stony meteorites were found to have been imitated, especially the delicate parallel lines attributed to cleavage, which are visible when a thin slice is examined under the microscope, and the globular structure where the little spherules are sometimes smooth at the surface, at others drusy, or roughened with the points of minute projecting crystals, like the meteorite of Sigena, November 17, 1773.

When hydrogen was employed as the reducing agent, the results were very similar, and the reduction would take place at a temperature not exceeding red heat.

Again, another method of imitation, the reverse of the foregoing, was by oxidation. From silicide of iron, heated in a brasque of magnesia by the gas blowpipe, a substance was obtained extremely similar to the common type of meteorite. The iron was separated partly as native iron, partly as a silicate, forming peridote, some of it in the crystallized state. Further details of resemblance were attained by heating a mixture of silica, magnesia, and nickeliferous iron, phosphide and sulphide of iron. The stony gangue of the melted product, was found to be free from the latter three substances; and instead of the simple phosphide introduced in the experiment, there was observable the triple phosphide of iron, nickel, and magnesium, first noticed by Berzelius in meteoric irons.

The preceding experiments suggest some important deductions on the condition of the planetary matter from which the meteorites have been diverted to our own globe. M. Daubrée makes no attempt to enter the lists with Von Haidinger, Baron Reichenbach, Prof. Lawrence Smith, and others, on the questions attending the entry of these bodies in to our atmosphere, and the circumstances of their fall; but, considering that their surface alone is modified by these conditions, he infers that their interior mass remains the same as when it was wandering in space, and may to a great extent be taken as a sample of the material of the planetary bodies of which they are the fragments.


Seeing how nearly the composition and structure of the etor of the establishment at Auteuil has had his due share of fectly sound and malleable, which is a much more difficult meteorities are reproduced by the two methods of experiment, labor and anxiety in bringing the art to so high a degree of casting to make, on account of the thinness of the metal.

M. Daubrée refers by their aid to the original mode of formation of the bodies from which these meteorites come.

If they were produced from silicated minerals by reduction in which carbon was the reducing agent, it may be objected that the iron could scarcely have remained in the metallic state; and if hydrogen be supposed to have been the reducing agent, water ought to have been formed at the surface. whence it appears more simple and reasonable to recur to the idea of an oxidizing process. Allow that silicon and the metals existed at one time in the meteorites, not combined with oxygen as they now mostly are, and this by reason either of too high a temperature to allow them to remain in combination, or of too great a separation of their particles, then, as soon as, by their cooling down or by their condensation, the oxygen was able to act upon the other elements, it would at once combine freely with those for which it had most affinity and if not sufficient in quantity to oxidize the whole, or not enabled to act long enough, would leave a metallic residue. In fact; there would be produced the silicate of magnesia and iron, peridote or olivine, and granular portions of nickeliferous iron and of sulphides and phosphides of iron. These views, while applicable to a large proportion of the meteoric bodies, would require modifications for those rarer varieties which consist essentially of pyroxene and anorthite. While the magnesian silicates crystallize so readily after simple fu sion, these latter substances would only melt to vitreous and amorphous masses, and in order to become crystalline would have needed the presence of water.—Address to the Geological Society, 1867.

#### CLEMSON'S ADJUSTABLE SPRING-HELD SAW TEETH.

The engraving shows a saw tooth differing not only in form but in manner of being retained in place, from others. Its simplicity of shape and consequent ease of manufacture and management is one of its advantages, while the form of the slot as compared with that of the tooth is another. The tooth is dovetailed, or rather its edges conform to the slot, which



is of a V-shape. The tooth is curved the lower end, being struck on a circle. It is retained in place by a spring pressure as the curve of the slot in the plate differs slightly from that of the tooth, as seen at A. When partially worn the teeth may be moved outward from the center of the plate although still held by the spring of the tooth. When, however, worn quite short, the two halves of the holes, B, in the plate and tooth may be brought together and a pin or screw inserted. This is only necessary when the tooth is removed so far from the slot as not to be affected by the spring of the tooth against the plate. These half holes may be several in number, if required, but it is found in practice that one on the plate and one on the tooth and the slot in the plate amounts to about one-sixteenth of an inch.

The patent of Aug. 14, 1866 claims holding the teeth by elastic pressure, which is the peculiarity of the device, and others are being secured by a pending application through this office. Address for further information William Clemson Middletown. N. Y.

# COATING IRON WITH COPPER.

The Mechanics' Magazine furnishes the following account of simplified process of copper plating employed in the extensive electro-metallurgical establishment of M. Oudry, located in the village of Auteuil, three miles out from Paris. Such complete success has attended the introduction of this new method of depositing copper upon wrought or cast iron, that the inventor and founder of this establishment, relinquishng to his compeers the ordinary applications of copper ing which are limited to articles intended principally for purposes of interior decoration, produces chiefly such articles connected with the external decoration of stately and superb edifices, which are, therefore, exposed to all the destructive effects of air and water, to the deteriorating alterations of heat and humidity, and to the corroding action of gas and frost. To M. Oudry was entrusted the plating in copper of all the castiron monuments of the city of Paris, including the fountains of Venus and Diana in the Champs Elysees, that of Visconti in the Louvais square, that of the four seasons, and the monumental designs which embellish the Place de la Concorde. Among other works deserving notice is the reproduction in galvanoplastic of the bas-reliefs composing the Trajan column, exhibited at the Louvre, and the surface of which cannot be less than 700 square yards in extent.

Were people in general to know the price paid for success in any department of scientific knowledge and application, it is very questionable whether they would not be more inclined to pity than to envy the representative. The present proprietor of the establishment at Auteuil has had his due share of labor and anxiety in bringing the art to so high a degree of

perfection. For many years he was engaged in conducting experiments of a troublesome and complicated nature, in order to arrive at his end, which was copper plating of any required thickness upon cast and wrought iron by a direct operation. This was the only method, in his opinion, available for effectually resisting oxidation, when the specimens plated possessed a large area of surface, together with numerous details of tracery, graving, and ornament. Similarly, this was the only plan which promised success in plating bodies composed of several pieces and connected together by bolts or rivets, and which might be exposed to stain and friction, such as pistons, screws and armor plates. Under the same category may be included substances undergoing a heavy pressure, such as rollers. All these require not merely a plating of copper, as understood by the ordinary term, but absolutely a thick crust of copper upon them. To obtain this result it was necessary to immerse the objects in a bath of sulphate of copper, and to keep them there for several days in the presence of an electrical current. It was found that if the pieces were cleaned and plunged into a preliminary bath to obtain a superficial film, and then transferred to a bath of a stronger and more acid nature, the iron, owing to its impurities, having been but imperfectly cleaned, and consequently but very slightly crated, was at once attacked by the acid, and the result was the very reverse of what was desired. Instead of the object being plated, it was rapidly corroded and destroyed. After many attempts to succeed by the use of two successive baths of different strengths, M. Oudry was compelled to renounce the endeavor and to turn his attention to another plan of operation. The one he has finally adopted consists in discarding the preliminary bath and the cleaning, and replacing them by a fluid coating of an isolating and impermeable character. By this new process, the exact modus operandi of which is a secret, the monuments we have alluded to were plated, together with 20,000 gas lamps and fittings ordered from Auteuil for the city of Paris. These lamps are composed of a pedestal and shaft, the former of which is seldom retouched, but the shaft is generally adorned with garlands, and requires to be filed up. This having been done, the workmen cover the surface with a very thin film of benzine, and so soon as this coating is dry a second, and then a third, is applied, the whole three operations embracing a period of three days. Subsequently, the surface is rubbed over with charcoal powder, and then it is fit for the plating. Any part that is not required to be plated is covered with a paste of some conducting earthy substance. The objects having been duly prepared are transfeared to large wooden vats containing the baths, are tied together with copper wires, and surrounded with numerous earthern jars of a porous description, in which are placed plates of zinc furnished at the top with strips of copper, to which are attached the conducting wires encircling the objects to be plated. The contact of the copper and the zinc sets up the galvanic action which commences directly the earthern jars are filled with dilute sulphuric acid, and a saturated solution of sulphate of copper is introduced into the vats. The strength of the solution is maintained constant by supplying or feeding it with crystals of the sulphate of copper. Notwithstanding that the theory of the process depends upon these conditions being fulfilled, yet the beauty of the plating and the practical success is very much due to the thousand and one little devices and dexterous manipulations only to be acquired by long practice and experience. About three or four days suffice to render the operation complete, the thickness being the 1-25th part of an inch, and the objects are then taken out of the bath, washed in water slightly acidulated, brushed with a wire brush, and rubbed with green paper to relieve the dull tint the newly plated copper assumes. The finishing touches consist in brushing the objects with a brush steeped in a preparation of ammoniacal acetate of copper, which attacks the surface of the fresh coating, and imparts an agreeable greenish tint to it, and finally rubbing them with a hard brush well

Our readers will recognize in the battery adopted at the establishment of Auteuil, that of the well known Daniell's constant battery, the especial feature of which is to furnish regular currents of uniform intensity, by means of the partition separating the two liquids, and through the pores of which they come into contact. In all these substitutions for solid metal of the same nature as the superficial film, the question of cost enters largely, and a few remarks will be apropos to the subject. A gas lamp of the newest pattern, in Paris, weighs  $4\frac{1}{2}$  cwt., and costs, including casting, filing up, copper plating, and bronzing, exactly £8, being at the rate of fraction under fourpence per pound. The same article cast in bronze will only weigh, in consequence of the reduced thickness, 28 cwt., but owing to the price of that metal the cost would amount to a trifle over £30. It has been estimated that the difference between these two specimens for the whole city, amounts to a saving of nearly half a million pounds sterling. The Emperor of the French has marked his approbation of the energy, enterprise, and skill of M. Oudry, by presenting him with the cross of the Legion of Honor; and all those who have witnessed the success which has attended his efforts at the Exposition, will concur in the opinion that the honor had been well earned and deservedly

CASTINGS IN SOFT STEEL.—It is noted as a fact in casting steel to patterns, that Messrs. Vickers, Sons & Co., of Sheffield, Eng., have cast a hydraulic cylinder 8 inches in diameter and 2½ thick, perfectly sound and malleable. The Wm. Butcher Steel Works, Philadelphia, Pa., have recently cast a hydraulic cylinder 12 inches in diameter and but 1½ inches thick, perfectly sound and malleable, which is a much more difficult certific to make on account of the thinness of the metal

#### Artificial Grindstones,

We have already noticed in this journal the success which has attended the application of Mr. Ransome's beautiful process to the manufacture of artificial grindstones—a success which is so marked that there seems little doubt that the use of natural stones for grinding purposes will eventually become the exception instead of the rule. Among other firms, Messrs. Bryan Donkin & Co., the well-know engineers, of Bermondsey, have tried experiments which very decisively prove the advantages of the artificial over the natural stones. Messrs. Donkin were first supplied with a pair of Mr. Ransome's artificial grindstones in December last; and early in the present year they carefully tested these stones and compared their efficiency with some Newcastle stones at their works. Both the natural and artificial stones were mounted in pairs on Muir's plan—a system in which the peripheries of the two stones of each pair rub slightly against each other, with a view of causing them to maintain an even surfaceand the two sets of stones were tried under precisely the same circumstances, except that the Newcastle stones had a surface speed more than 20 per cent greater than that of the others.

The trials were made as follows: A bar of steel, 3 in. in diameter, was placed in an iron tube containing a spiral spring, and the combination was then arranged so that the end of the bar projecting from the one end of the tube barely touched one of the artificial stones, while the other end of the tube rested against a block of wood fixed to the grindstone frame. A piece of wood of known thickness was then introduced between the end of the tube and the fixed block, and the spiral spring, being thus compressed, forced the piece of steel against the grindstone. The same bar of steel was afterward applied in the same way, and under precisely the same pressure, to the Newcastle stone, and the times occupied in both cases in grinding away a certain weight of steel from the bar were accurately noted.

The results were that a quarter of an ounce of steel was ground from the bar by the artificial grindstone in sixteen minutes, while to remove the same quantity by the Newcastle stone occupied eleven hours, and this notwithstanding that the surface speed of the latter was, as we have stated, morethan 20 per cent greater. Taking the 20 per cent greater speed of the Newcastle stone into account, it will be seen that the 11 hours run by it were equal to 13% hours at the same speed as the artificial stone, and the proportional times occupied by the two stones were thus as 16 minutes to 13% hours, or as 1 to 52, nearly!

Such a result as this is something more than remarkable, and it is one which would scarcely have been credited, even by those who made the experiments, if it had not been fully corroborated by subsequent experience in the working of the artificial grindstones. Since the experiments above described were tried, Messrs. Donkin have set another pair of the artificial stones to work, and these, which are now in regular use, have given more satisfaction than those first tried. The saving in time, and consequently, in labor, effected by the use of the artificial grindstones is, in fact, so great that Messrs. Donkin have determined to use these stones exclusively in future; and we may add that the artificial stones are so much preferred by the workmen that those men, even, who are employed in shops at some distance from that in which the stones at present in use are situated prefer taking the trouble to go to them to using the Newcastle stones in their own shops. In addition to their great efficiency, the artificial grindstones possess the advantages of being able to be manufactured of any size, and of any degree of coarseness of grain, and they can thus be specially adapted to any particular class of work, while the process of their manufacture insures their being of uniform texture throughout, and free from the flaws and hard and soft places found in natural stones. Altogether, we believe that the general adoption of the artificial grindstones is merely a matter of time.—Engineering.


# Mutability of Species.

In a recent communication to the Geological Society of Paris, M. A. Gaudry pointed to some striking facts favorable to the theory of the mutability of species. The sand pits in the environs of Paris, and indeed all drift deposits in general, are very rich in remains of the mammoth or primitive elephant, and of the elephas antiquus. These remains chiefly consist of molar or back teeth, in which characteristic differences may be easily recognized. They consequently pertain to two different species, and in order to ascertain whether there exists any close parentage between them, M. Gaudry goes back to the pleistocene period, which lies between the upper tertiary or pliocene, and the drift strata. Now the pleistocene forest-bed of Norfolk contains a quantity of molars of each of the above species, but it also comprises others slightly differing from both, and also intermediate between those of elephas antiquus and elephas meridionalis, the latter ceasing to exist when the former and the mammoth begin. These again disappear after the drift, and are followed by other species. Here then we perceive a succession of species each of which have sprung from the preceding one. During the tertiary period there existed a breed of horses to which palcontologists have given the name of hipparion; they had small lateral fingers, thus forming a link between pachydermata and solipedes, which latter was considered perfectly dis tinct so long as the genus equus was characterized by a single finger at each foot. Now, Mr. Owen, on examining the horses' teeth found in the cavern of Oreston, discovered that the equus plicidens to which they belonged was intermediate between the hipparion and the present horse. In the equus plicidens the enamel of the teeth presents more folds than in the living breed but in the molars found in our gravel pits,

M. Gaudry has perceived gradations between those presenting many and those presenting fewer folds, whence he concludes that our horse is a descendant of the equus plicidens. A hippopotamus, the remains of which were discovered at Grenelle a few years ago, appears not to differ materially from the race that now inhabits the rivers of Africa; and yet at the time the owner of these venerable relics was disporting himself in the Seine, the climate was much colder here than it is now: so that Mr. Gaudry concludes with great plausibility that, if we had the whole skeleton, some differences would probably appear.

### HOUSE'S IMPROVEMENT IN TRUNKS.


Whether unjustly or not, the porters and baggage men employed at our hotels and railroad stations have been characterized as "baggage smashers," a term for which the trunk makers may be partially responsible. Wherever the fault may be it is certain that much damage and injury to



property, often of a fragile nature, ensues when one is compelled to travel. Almost invariably a severe blow on the corner of the trunk will break the back or burst the trunk. The object of the contrivance shown in the accompanying engravings is to prevent a portion, at least, of this damage by providing cheap but efficient guards. One of these is seen detached in Fig. 2, and its application to a trunk exhibited in Fig. 1.

A frame of malleable metal—either malleable iron or cast

brass-encompasses a triangular cup of thick vulcanized rubber, shown plainly at A, Fig. 2. This cup is formed with a flange which rests on the bars of the metallic frame. Each of the three prongs, B, of the frame have screw holes by which the shield is attached to the corners of the trunk. The appearance of the trunk or chest when these are attached



is clearly exhibited in Fig. 1 without the necessity of fur ther reference.

It is easily seen that these fixtures can be quickly secured to any trunk, chest, valise, etc., and while preventing the jar and breaking of the trunk or its contents, render both more secure. To those who travel—and everybody travels more or less nowadays-this simple device will recommend itself. The elasticity of the rubber and its resistance to abrasion insures great security.

It was patented Feb. 1866, by J. A. & H. A. House. For particulars J. C. Gillmore, agent, may be addressed at No. 26, Fourth Avenue, New York city: Mr. Gillmore sells either the trunks with improved attachment or furnishes the shields to trunk manufacturers.

# The First Steam Voyage Across the Atlantic.

The importance of the navigation of the ocean by steam first came to be fully realized in this country in the year 1818. Many scientific men doubted the feasibility of such navigation, but there were a few men of intelligence and enterprise who had the greatest faith in its practicability. Among this latter class was Mr. Scarborough, of Savannah, Ga., the senior partner of the firm of Scarborough & Isaacs, one of the lead- This gentleman proposes constructing large sheet iron cyliniug commercial houses in the South. In 1818 Mr. Scarborough, willing to show his faith by his works, came to New York and made purchase of a ship of about 350 tuns burthen which | tor has placed in a cylinder of the kind, wheat that had lain was then on the stocks, determinated with her to settle the mooted questions as to the ability of steam vessels to successfully navigate the ocean. The ship was named the Savannah. Mr. Scarborough then engaged the services of Captain Moses Rogers, a person we are informed "of great mechanical skill and ingenuity, who had been familiar and identified with the experiment of Fulton." Captain Moses Rogers was placed in charge of the engine and machinery of the Savannah. An able and faithful sailor was now wanted to navigate the vessel, and such a man was now found in Captain Stevens Rogers of this city. Under his command the Savannali, having been duly equipped with engine and machinery, steamed out of New York harbor on the 27th day of March, 1819, bound to Savannah on her trial trip, which was most successfully

On the 26th of May in the same year she left Savannah for Liverpool, making the trip in twenty-two days, during eight. | Company. Capital \$500,000.

een of which she was propelled by steam power. From Liv erpool the Savannah went to Copenhagen, Stockholm, St. Petersburgh, Cronstadt and Arundel, and from the latter port returned to Savannah, making the passage in twenty-five days.

The log book of the Savannah was sent to the Navy Department in 1848. Captain Stevens Rogers is yet living in this city. For a number of years past he has been collector of city taxes, but at the election in June last he was suspended. It has been often suggested that it would be no more than a simple act of justice on the part of the government to settle a pension upon the pioneer of ocean steam navigation, but no active steps have as yet been taken to accomplish the substantial recognition of his services.—New London Star.

### Editorial Summary.

THE GLACIAL F POCH.—At a late meeting of the New York Lyceum of Natural History, Mr. J. W. Reid presented a paper on the drift deposits of the United States. He accounted for the intense cold necessary to produce the immense glaciers of that period by the precession of the equinoxes, which, every 10,500 years, has the effect of transferring the great oceanic waters from one hemisphere to the other, the sun at that period remaining eight days longer in one hemisphere than in the other. At present, the winters of the southern pole are eight days longer than with us; an ice continent more than twice the area of Europe has formed there, and a map will show the great preponderance of water in the southern hemisphere. The extreme of cold at the Antarctic pole was reached in 1248, since which date the climate has been growing milder, while north of the equator it has been growing colder, and but ten thousand years remains before the temperature which twenty thousand years ago formed glaciers reaching to the top of Mount Washington, will be the prevailing one of North America.

ROSY AURORA.—Among the latest explanations of the red glow and splendor of sunrise and sunset, which has been given, is that of Dr. E. Lommel, in Poggendorff's Annalen, in which he shows it to be an effect of diffraction of light as viewed through a series of dark or partially dark screens. He lays it down as an axiom that a point of white light, viewed through a sufficient number of groups of screens, appears not merely reddish itself, but also is surrounded by a still more strongly red-colored aureole of diffracted light. The lower strata of the atmosphere is full of minute corpasaular bodies—dust, organic and inorganic, carbon or watery particles—which serve as dark screens, and when the sun is low, the rays traversing a long range of atmosphere, undergo diffraction, and by superimposition of adjacent points of light, the effect of redness is deepened. A mere red glow, without brilliance, is occasioned by solid particles, as we see the sun red when viewing it through smoke, aqueous vapor, when present in the air, makes a diffused reddish light.

A GRAND ENTERPRISE.—The French government contemplate a new and vast project, which if carried out will be of incalculable importance to that nation. This is to enlarge the Canal Deux Mers, so that large vessels may pass directly from the Atlantic ocean to the Mediterranean, without passing under the guns of the fort of Gibraltar. At present the canal connects with the Garonne river at Toulouse, and falls into the Mediterranean near Agde; the river reaching the ocean at Bordeaux completing the chain of communication. In order to fill the canal when it is enlarged, it is proposed to intercept the innumerable mountain streams, from the Pyrenees and mountains of Auvergene, and imprison them in huge reservoirs whence the water can be drawn as needed.

TESTING SWORD BLADES BY MACHINERY.—The Austrians fasten the sword by its haft into a frame and submit it with a known and adjustable velocity, to a certain number of strokes at the mid length of its edge against a block of beech wood. The sword is also subjected to a slanting or glancing blow at a given angle and velocity against the side of a cylinder of hard wood. The edge is tested by blows against a piece of wrought iron of a given breadth, and proof of the blade's elastic temper is obtained by bending and suddenly releasing it within certain limits. The peculiarity of these trials is that the nature and extent of every test is determinative and may be made adjustable.

Preserving Grain by storage in a vacuum is a plan recently recommended by an English gentleman, Dr. Louvel. ders, which are to be filled with the wheat or corn, and the air exhausted as far as possible by an air pump. The invenin a river for twenty-four hours, and become saturated with moisture. At the end of five days it was found in excellent condition, and made first rate flour and bread. A more practical application of this plan seems to be for the preservation of ship's biscuit from weevils and other parasites.

The insuring of steam boilers and other property affected from explosions is the object of a new company recently started at Hartford, Conn. Heretofore, there have been no companies in this country which have issued policies covering this class of risks, although in England they have been in successful operation for a number of years. We are very glad that manufacturers and others requiring the use of steam can now insure themselves against loss in event of an accidental explosion, if fire does not ensue from the result. The name of the new company is the Hartford Steam Boiler and Inspection THE ADVANTAGES OF A STOVE-PIPE HAT.—Every reformer and most of our writers have something to say condemnatory of the stiff high crowned hat and advocate the soft felt hat as a substitute. While the Hon. Charles Sumner was recently inspecting a sleeping car on a Michigan railroad the train suddenly started. This threw him forward and he struck the ground with his hat, damaging that article considerably, and inflicting a slight injury on his head and face. Had Mr. Sumner worn a felt hat, his head instead of its covering would have sustained serious injury. The stove-pipe hat will undoubtedly have one distinguished advocate at least after this

TEXTILE FROM HOP VINES.—Another discovery in the field of textile material, is that of a Belgian, who has shown that a second, most valuable, and heretofore useless product, can be furnished by the hop vine. After the hop blossoms have been gathered, the stems are steeped like hemp; when this operation has been completed the stalks are dried, beaten with a wooden beetle, and then the threads come off easily. After carding and working in the ordinary way, a very strong cloth is obtained. The thickest stalks also yield the material for several kinds of rope.

Where the Money Goes.—A letter from a lady in Paris, just received, says: "Never will so many Americans be in Paris at one moment again;" and she added, "what a deal of money they leave. I know some New York and Western ladies who have bought such quantities of laces. Every lady who comes to Paris must buy a real black lace shawl and silks. One lady bought twenty thousand dollars' worth of European luxuries, mostly for presents to friends, and one gentleman, on his way to his Western home, takes fifteen trunks filled with laces, silks, etc."

THE SPECTRUM TEST.—So delicate is the spectrum test in determining the presence of certain metals that it is possible to recognize in this way the 1-60,000th part of a grain of potassa or baryta; the 1-1,000,000th of a grain of lime or strontia; the 1-60,000,000th of a grain of lithic, and the 1-160,000,000th of a grain of soda. Dr. Letheby, a distinguished London chemist, has detected by this means the presence of blood in the stains of linen which had been laid away for seventeen years.

How to Preserve Eggs.—In 1791, Wm. Jayne, of Sheffield, England, obtained a patent upon the following method which he averred would preserve eggs in a good and fresh condition for two years or more:—Keep the eggs in a compound made of 1 bushel quick lime, 32 oz. salt, 8 oz. cream of tartar, with enough water to form a mixture so that an egg will swim with its top just above the liquid. If any of our readers should test this simple method we should be glad to hear the result.

For Polishing Steel.—A German engineer states that oxide of chromium is the best substance for polishing steel. The article can easily be prepared by heating bi-chromate of potash to redness. It is also used for painting on porcelain. One equivalent of chromic acid is reduced to oxide of chromium, and on well washing the residue of the ignition neutral chromate of potash is washed away and the oxide is left behind.

COLORING WOOLEN YARN.—An agricultural exchange asserts that yain, plain or mixed, can be colored a firm blue, even superior to that attained with indigo, by mixing common purslane (portulaca olcracea) macerated fine, and boiled for some hours with logwood chips, in the proportion of a half bushel of the former and quarter of a pound of the latter. Two ounces of alum is used as a mordant for every pound of wool.

THE AGE OF INVENTION.—It appears from the records of the Patent Office, that in 1864 the number of applications for patents was 6000; in the following year the number increased full fifty per cent; in 1866, 15,000 applications were filed, and this year will probably increase the number to 25,000. The number of caveats filed last year was twenty-seven hundred, and this year there will be upwards of four thousand.

How to Remove Foul Air from Wells.—Ebenezer Robinson, of Philadelphia, Pa., suggested, in 1793, a very quick and simple method of removing foul air from wells, cesspools, etc. He says he found the plan to succeed even where the air was so bad that neither flame nor life could be supported. His plan was to lower a leathern hose pipe into the well, and by means of a large bellows, inject fresh air.

THE MUD Crop of Paris. Among the many economies of municipal administration in Paris is the sale of the yearly "mud crop." In 1823 this yielded only \$15,000. It now brings \$120,000, and when left for some time in rotting tanks is sold for manure, at the increased valuation of \$600,000. If we could but make the mud crop of our American cities equally profitable!

MULTUM IN PARVO.—A very neat and convenient article in the shape of a pen holder has been introduced to the public by the Morse Ernser Company, of Philadelphia. It combines with a pen holder of ordinary shape and size, a pencil sharpener, eraser, and burnisher. Add to it a penknife, which can be easily done, and the article will be complete.

THE NEW PLANET recently discovered by Prof. Peters, of Hamilton College, N. Y., and at very nearly the same time by Prof. Tietjen, of Berlin, makes up the full number of these heavenly bodies now known to one hundred. The name of Undina has been given to the stranger.

A PARTY of capitalists recently visited Marsh,s Railroad, (an illustrated description of which was published in this paper before the enterprise was commenced), which is being built on the summit of Mount Washington, and a new company has been organized, fixing the capital at \$200,000. The Giant's Grove is being graded previous to erecting a large hotel on it, and the turnpike has been completed from that point to the railroad at the foot of Mount Washington. A little over a mile of the railroad has been constructed, and it is expected the balance will be finished next year.

THE MARITIME INTERNATIONAL EXHIBITION, which is to be held next year at Havre, promises to be interesting, as it will certainly be in many circumstances novel. The idea of it was suggested by the circumstance that the marine productions and objects connected with them have necessarily been only partially represented in the Champ de Mars. There are to be three classes of subjects: navigation and life-saving apparatus; various articles of commerce and manufactures; and matters connected with fishing and pisiculture. The whole is to be under the very highest patronage.

THE establishment of a National School of Mines is to be proposed in Congress at the coming session. It is estimated that \$10,000,000 per annum may be saved by the adoption of a better system in the working of our ores.

WE regret to hear of the death of Prof. McGauley, connected with the *Scientific Review*, the organ of the Inventors' Institute, London. Professor McGauley resided for a time in Canada, and his friends there will regret to learn of his death.

It is said that the only fruit which grows in every climate is the strawberry. It is the only fruit which somewhere on the earth is picked every day the year round.

#### THE NOVEMBER METEORS.

According to programme, the expected meteoric display came off early in the morning of the 14th inst., and so far as numbers are concerned, Prof. Loomis, of Yale College, pronounced the exhibition more remarkable than the one our European neighbors were favored with one year ago, and but little inferior to that seen in the United States in 1833. Reasoning from analogy in the case of the shower thirty-four years ago,—as we mentioned in our last issue,—astronomers confidently predicted this meteoric exhibition, and arrangements were made in most of our observatories for making systematic records of the shower. During the greater part of the night the task of mapping down on star charts the course and exact time of appearance of solitary meteors, was an easy one; but towards morning their appearance became so frequent that the observers ceased their efforts to time and man them, and only counted. The authority above quoted states that at New Haven the shower reached its greatest magnitude at 4.30 A. M., over five hundre I being then counted by one observer in an hour. And as one individual can watch but about one-sixth of the hemisphere, according to the usual method of computation, 3000, at least, were at this time visible in the whole heavens, and without doubt, twice that number actually came within the field of vision, but were eclipsed by the superior light of the full moon. From all parts of the country, have come reports of the beauty and brilliancy of the shower. Even the inhabitants of our Pacific States witnessed it, although, of course, it reached its full grandeur at an hour much earlier than with us. The display was not visible in England, or on the Continent.

The time when the shower attained its greatest brilliancy was, in this section, two hours later than that given by European observers of last year, and next year the display, if there be any, will not begin until ten o'clock A. M., Washington time, and will, therefore, be seen only in the Pacific Ocean.

# ${\bf MANUFACTURING,\,MINING,\,AND\,\,RAILROAD\,\,\,ITEMS.}$

The Foxdale mine in the Isle of Man, is already one of the richest lead and silver mines in Great Britain; but its value has been very much increased by the discovery of an ore hitherto unknown to exist in that country. The name of the ore is "Fahlerz" (tetrahedrite). It yields an immense amount

A steamer has leftHavre, having on board a large number of French locomotives, consigned to Russia. The report that the Creusot works had received an order for eighty locomotives—a report which has been freely published by our exchanges—it appears is a little premeture, the affair not as yet being definitely concluded. The pecuniary assistance proposed to be af forded by the Russian government this year, to the work of railway construction in that empire, is about \$15,000.000.

White chrome ore is found in Hanover, near Gettysburg, Pa., which yields about 55 per cent of iron. This ore is of the same kind as is now shipped from Havre de Grace, to Sheffleld Eng., to be used in the cutlery establishment of that place.

The first sleigh-bell ever made in this country was manufactured at Chatham, Conn., in 1780, and that town still retains a monopoly of this business. In the city of Dresden, albumenized paper is manufactured at the rate of upwards of 6,000 reams per annum, a quantity that would suffice to print more than 120,000,000 cartes de visite. The whites of 2,000,000 eggs are annually consumed in preparing this paper the yolks of which, are used by tanners for preparing the finer kinds of leather. 'After preparation, the paper is carefully assorted, and from ten to fifteen per cent is rejected for photographic purposes but is used by Dresden printers for color printing.

The Inventors Manufacturing company established one year at Terryville Conn., operate the largest shears and scissors factory in the country, and turned out last year about 60,000 dozen, worth from \$600,000 to \$700,000.

The "Lake Shore" railway lines between Buffalo, Cleveland and Toledo are about to consolidate with the Michigan Southern on the one hand and with the New York Central on the other, thus placing the whole route under one board of management. If effected, this combination will represent some \$150,000,000 of railroad capital.

At the head of Thunder Bay, on Lake Superior, two veins of native silver have been discovered; one seventeen the other eighteen feet in width, and one of them extending some three or four miles.

Jasper is now procured to almost any required extent at St. Gervaise, in Savoy. One quarry has a depth of 69 feet and a surface of at least 24,000 square yards.

The exports of iron and steel of British manufacture from the United Kingdom has undergone a wonderful expansion of late years. In 1847 these exports amounted to 550,000 tuns; in ten years this incressed to 1,500,000 tuns. Comparing 1866 with 1847 there is an increase of no less than 206.38 per cent. Last year appears to have been the best twelve months on record in valuation of exportations.

The Spanish journals state that the small-arms manufactory at Placentia is working night and day, executing an order given by the French Government for muskets of the new pattern. A French agent is on the spot, and has offered a premium of 30 reals for each Chassepot delivered before the time stipulated.

The failure of the great house of Decoqueville, whose iron founderies are to be sold by public auction on the 30th inst., is traced to the fatal effect of the Paris Exposition on French trade.

# Becent American and Loreign Latents.

Under this heading we shall publish weekly notes of some of the more promonent home and foreign patents.

SELF-SETTING GAME TRAP.—Alfred Wilkin, McConnelsville, Ohio.—This invention has for its object to furnish an improved trap which shall be durable, cleanly, entirely free from the odor of animals, requiring little care to keep it in working order and capable of destroying large numbers of animals at one setting.

BOLT FASTENING.—V. Lapham, El Paso, Ill.—This invention has for its ob ject to furnish an improved fastening for thill coupling bolts, clevis bolts, and other pivoting bolts which will hold the bolt securely in place and which can at the same time be easily and quickly attached and detached.

LAMP.—James Lee, New York city.—This invention has for its object to furnish an improved lamp so constructed and arranged as to guard against explosion by preventing the undue heating of the upper part of the oil reservoir and at the same time to guard against the lamp's being broken should it accidentally fall.

HAY RAKE AND TEDDER.—J. M. Law, Portlandville, N. Y.—This invention has for its object to furnish an improved attachment for hay rakes by means of which hay may be shaken out and stirred up or turned quickly, conveniently and thoroughly.

LEVELING ATTACHMENT FOR STEAM HARVESTERS, ETC.—Benjamin F Cook, Olema, Cal.—This invention relates to a new and improved leveling attachment to be applied to steam harvesters and other agricultural implements which are mounted on wheels for the purpose of keeping the main frame in a horizontal position in its transverse section when the machine is passing over inclined ground. The invention consists in interposing between the back axle of the machine and the bolster above it a wheel having its rim beveled or made inclined and connected with a windless or capstan in such a manner that the wheelmay be turned with facility and the main frame of the machine brought to or retained in a horizontal position when the wheels on which the machine is mounted are passing over inclined surfaces.

Hoisting Apparatus.—A. F. Crosman, Steamer Ossipee, North Pacific Squadron, U.S. Navy.—This invention is designed to facilitate the hoisting of small boats at the sides of ships and other vessels. The invention consists in a novel arrangement of the davit tackles whereby the tackle of both davits are operated and the boat hoisted or lowered by the manipulation of a single rope, The invention further consists in a novel means for releasing simultaneously both ends of the boat from the hooks of the tackle blocks when the boat is lowered so as to reach the water and thereby prevent the capsizing of the boat a contingency of not unfrequent occurrence when the water is rough.

DRYING ATTACHMENT FOR PAPER-RULING MACHINES.—R. J. Groshans, Buffalo, N. Y.—This invention consists in applying to paper-ruling machines a revolving fan in such a manner that the ink on the freshly ruled paper will be rapidly dried and the paper under the influence of the blast generated by therevolving fan bemade to drop evenly into the box or receptacle prepared to receive it.

Compositor's Copy Holder.—P.A. La France, Elmira, N. Y.—This invention relates to a new device for holding the manuscripts on printers' type cases and consists in the arrangement and construction of a platform which rests on suitable supports provided for that purpose on the type case and which can be easily moved laterally on the said type case to enable the compositor to reach all the types,

MACHINE FOR UPSETTING, CUTTING AND PUNCHING IRON.—J.J. Rose, Elmwood, Ill.—This invention has for its object to improve the construction of the machine patented by the same invention Aug. 1, 1863, and numbered 49,158.

BELT FASTENING.—David Wigger, New York city.—This invention relates to a new belt fastener which is so arranged as to be easily opened, and which, when closed, can be securely locked, and which is of great strength and durability.

FISHHOOK.—A. I. Lenhart, New Brunswick, N. J.—This invention relates to a new and improved fishhook of that class which are provided with a spring, a catch or fastening, and one or more supplemental hooks, which, when the fish seizes the balt, are released and spring so as to penetrate the fish and secure it. The invention consists in a novel construction of the device, or the arrangement of the parts, whereby the capture of the fish, when the latter nibbles or seizes the bait, is rendered almost certain.

BLEACHING PAPER STOCK.—S. T. Merrill, Beloit, Wis.—This invention has for its object the bleaching of paper stock in a more economical manner than hitherto, and consists in subjecting the stock to the action of chlorine gas while the former is undergoing the process of communition in what is known as the "rag engine," or the stock agitated in a close vessel.

RAILWAY TRAVELING HOOK.—Wm. R. Oatley, Rochester, N. Y.—This invention relates to a new and improved hook by which travelers in railway cars may suspend any hand luggage from the hat racks over the seats. The invention consists in connecting two hooks together by a swiveljoint, one hook being of sufficient dimensions to catch over a rail of the rack, and the other hook of such size that a strap, string, or cord may be readily suspended or fitted upon it,

COMBINED CHIMNEY AND VENTILATOR.—A. S. Whittemore, Willimantic, Conn.—This invention consists in combining a chimney or flue with a ventilator in such a manner that the compartments of a building may be thoroughly ventilated and the chimney or flue at the same time rendered perfectly fire proof.

PAPER RULING MACHINE.—Edmund A. Warren, Brooklyn, N. Y.—This invention relates to a new and improved machine for ruling paper, and it consists of a rotating cylinder provided with nippers to grasp and hold the sheets of paper to be ruled, and also provided with adjustable cams, the above parts being used in connection with a pen beam, and all constructed and arranged so as to operate in a perfect manner.

MOWER AND REAPER.—A. W. Tucker, Waxahachie, Texas.—This invention relates to a new mower and reaper, which is made adjustable so that the cutting apparatus can be set to a higher or lower level, and so that it can be thrown out of gear at pleasure; an endless apron is arranged directly in rear of the cutting apparatus, to receive the cut straw or grass, which can be discharged from the apron either in continuous succession or in swaths at suitable intervals.

Punching Machine.—Morris Seiferth, Morristown, N. J.—This invention relates to a new punching machine, for perforating plates or for stamping or notching the same, and consists in the use of an automatic cleaner, by which the plate, after a hole or depression has been punched, is lifted off the lower stationary punch, so that it can be easily adjusted upon the same, for the punching of the next hole or mark, while the die is moved up by the cam of the driving shaft.

HOUSE VENTILATOR.—Robert Boyd, Evansville, Ind.—This invention relates to an improved method of ventilating dwelling houses, halls, hospitals, and public buildings, whereby the fresh air from the outside may be conveyed inside, and the vitiated or foul air escape therefrom.

BRIDLE BIT.—A. H. Rockwell, Harpersville, N. Y.—Th's invention relates to a new bridle bit, which is an improvement on the ordinary four-ring bit, and which has on a flexible mouth piece two sliding bars, which are connected with a nose strap or face piece, in such a manner that by pulling the reins the said bars will be forced together, thereby pressing with great force against both sides of the upper jaw of the horse.

VACUUM AIR ENGINE.—J. R. Cameron, Pittsburgh, Pa.—The object of this invention is to form a vacuum by the expansion of air by heat, and by other appliances, by which the piston of a working cylinder may be driven by the simple pressure of the atmosphere, and power obtained thereby for driving machinery or other purposes.

SCREW DRIVER.—T. D. Voorhees, Easton, Pa.—This invention consists in making a portion of the ordinary screw driver just below the handle of a round form, and placing upon it a loose ferrule or thimble.

ROTARY STEAM ENGINE.—Edwin Chapman, Rochester, Minn.—This invention relates to a certain useful improvement in the class of steam engines known as rotary engines, and it consists principally in the manner in which the abutments are operated, and in the manner in which the steam is discharged with the cylinder, and exhausted therefrom.

CHEESE PRESS.—E. J. Crane, La Porte, Ind.—This invention relates to a new and improved method of constructing cheese presses, whereby the same are made self acting, and the invention consists in arranging two levers with suitable supports in such a manner that the cheese presses itself when properly arranged upon its table.

COMBINED SCHOOL DESK AND SEAT.—J.P. Scott, Lewisburg, Pa.—This invention relates to an improvement in the construction of a school desk, combined with a seat, and consists in such an arrangement and combination of parts that the seat and the desk may be separately adjusted in hight to suit pupils of different sizes, and that the seat and a lid of the desk may be folded up when not in use, and to be compact and out of the way when desired.

MACHINE FOR CUTTING PAPER STOCK.—Abijah L. Knight. Baltimore, Md.—In this invention the rags are fed to a vertically cutting knife, by means of a combination of smooth and fluted rollers, to which an intermittent motion is imported.

CARAXLE.—Samuel S. Burt, Marquette, Mich.—In this invention the axis boxes are fixed to a stout iron yoke, the ends of which pass over the wheels Each wheel runs on a short axle, independently of all the others.

GOLD SEPARATOR.—Wm. C. Stiles, Nevada City, Cal.—This invention is an improved instrument for panning or separating gold from earth. It consists of aninclined vibrating table, having a series of pannings, screens, and counter inclines, arranged along its surface, and operating in connection with gentle streams of water fed to it from different points above it.

LATCH FOR GATES.-ETC.-Mark J. Bria, Oxford, Ind.—This invention consists in a novel arrangement of a lever latch for gates, etc., whereby a person may open the gate from either side, without reaching over the top of the same.

LATCH FOR DOORS, ELC.—Edward King, Taunton, Mass.—This invention consists in a novel connection between the latch and handle, or knob spindle, whereby the action of the latch is made free and certain, and the same are rendered more durable.

SKATE.—George W. Shearer, Crown Point Center, N. Y,—This invention consists in a novel manner of connecting the runner or blade to the foot rest or block of the skate, through an arrangement of springs and levers, whereby an easy and elastic movement is imparted to the skater, and also of so grooving the under surface of the runner as to combine all the advantages of both a plain and grooved runner.

HAND DICE BOX.—Justus E. Zender, New York city.—This invention consists in making a hand dice box of metal, and of lining any hand dice box with feltcloth or its equivalent, whereby the same are made stronger and more durable, and whereby the noise occasioned by the shaking of dice is partly diminished, or prevented altogether.

DEVICE FOR SUPPORTING AND FASTENING WINDOW SASHES.—Amos Cutter, East Boston, Mass.—This invention consists in an attachment for the sash or window frame, so as to be susceptible of being brought against the window or sash frame, as the case may be, with a greater or less amount of force, by the simple turning in or out of a thumb screw, or its equiva-

Value or Traveling Bag -N. Groel, Newark, N. J.—This invention consists in an application to the corners of the leather constituting the sides of the bag or value, of metallic corner pieces, in such a manner as to partly stiffen and strengthen the same, and thus to increase their wear and durability.

TAG HOLDER.—A. Grushus, St. Paul, Minn.—This invention consists of a holder made of spring wire, in a pecualiar shape, whereby a tag may be fastened to and detached from the cloth, or other material, with great facility.

ADJUSTABLE WATCH KEY.—J.S. Birch, New York city.—This invention has for its object to furnish an improved key for watches, which may be so adjusted as to fit any watch, whether large or small.

ATTACHMENT FOR DOORS.—C. J. Fisher, Waukon, Iowa.—This invention has for its object to furnish an improved attachment for doors, which will prevent the knob or latch from injuring the wall, which will hold the door securely in any position to which it may be opened, and which will also securely fasten the door when closed.

SASH FASTENER.—George Brosius, Ranch's Gap, Pa.—This invention relates to an improvement in sash fasteners. The breaking of window weight cords, the difficulty and annoyance of putting in new, and the rattling of the guillotine window, have stimulated the invention of various devices dispensing with the sash weights and providing for the locking of the sash, and to this class of devices the present invention belongs.

Self Acting Sleigh Brake.—C. Gardiner, Esperance, N. Y.—This invention relates to a self-acting sleigh brake, and consists of a cross bar carrying two bent levers, one on each side of the sleigh; hinged in each lever is a pawl, which catches on the ice or snow when the cross bar is forced back. The bar is operated by means of a connecting rod, secured to a sliding on the tongue or pole, and fastened to the neck-yoke pin, or attached in some other suitable manner.

SHEEP TROUGH.—Frank Ketcham, Monongahela City, Pa.—This invention relates to an improved sheep through, and consists in a reversible trough so constructed that one trough is always dry and clean.

RAILEOAD SUPERSTRUCTURE.—J. A. Maxwell, Savannah, Ga.—This invention relates to an improvement in railroad superstructure, and consists in a combination of the cross-tie and stringer systems of laying the rails, whereby the advantages of both are secured.

TOBACCO PRESS.—T. N. Reed, Danville, Va.—This invention relates to an improved tobacco press. It consists of a box of iron, or some other suitable material, in which are two false sides, or boards, movable within the box frame in the direction of a line at right angles to their planes.

QUILTING FEAME AND CLOTHES HORSE—G. A. Mallory and J. J. Fish. Oxford, N. Y.—The nature of this invention consists in constructing a frame so arranged as to be adapted equally to use as a quilting frame and a clothes horse, and capable of adjustment for either purpose, as desired.

CARPENTER'S SQUARE.—O. H. P. Robinson, Belfast, N. Y.—The object of this invention is to enable carpenters and builders to lay out the mortises in framing houses with dispatch and accuracy. It consists in making a slot in the main bar of the square, for scribing the mortise directly within it, intead of measuring and scribing on the outer side of the square, in the ordinary manner.

vention relates to a new manner of constructing and arranging the sliding oke of a grain elevator, and consists, first, in making the yoke of cast iron a nstead of wood, as has heretofore always been done; and second, in the use adjustable guides between the yoke and the wooden frame, whereby unqualities arising from the expansion or construction of the rame or yoke, reither, can be regulated.

VOKE FOR GRAIN ELEVATOR - Eliza Jane Jewell Brooklyn N V - This in

PUNCH AND SHEARS.—J. C. Jordan, Watertown, Wis.—This invention relates to a machine wherein sheetiron and other metals can be cut or punched, as may be desired, and the invention consists in so shaping the main lever of the machine that it will at the same time force down a punch, by a cam, and operate the shears, one of the blades of which is secured to the said lever.

STRAW CUTTER.—Hiram Parks, Athens, N. Y.—This invention relates to a straw cutter in which a curved knife is used, and is secured to a revolving shaft, so as to make a drawing cut, and so as to cut a whole bundle of straw with the same facility with which the usual machines cut a small quantity.

BLACKING BRUSH—Chas. A. Paret, Nashville, Tennessee.—This invention relates to an improved blacking brush and consists in passing an endless elastic band crosswise through four staples upon the back of the brush stock to hold the box of blacking and in a groove along the side of the stock to receive a scraper.

MACHINE FOR SHAPING AND PRESSING HOODS.—Solomon and Henry Squire, Monson, Mass.—This invention relates to a machine for shaping and pressing hoods and consists of hollow metal block of the required shape into which a heater is inserted or the same may be heated by a gas jet or lamp. This block is hinged upon a stand midway between two uprights which work in grooves in the side of the frame and are surmounted by a yoke piece supported by springs a jointed presser is suspended loosely from the center of the yoke by an adjustable suspension rod and metal lip overlapping the plates

CULTIVATOR.—M. Barnett and Eli Wood, Hardinsburg, Ind.—This invention has for its object to furnish an improved cultivator, so constructed and arranged as to run lighter, be more durable, and less liable to get out of order than the cultivators now in common use.

WASHING MACHINE.—Allan Neilson, Allegheny City, Pa.—This invention relates to a washing machine in which two or more corrugated conical rollers, which are secured in such a manner in a swinging frame above a flexible washboard, that their axes cross each other, while their under surfaces are with their whole length on the said board, so that by oscillating the said frame, the rollers will rotate on their larger diameter and slip on their smaller end, and will thus at once beat and rub the clothes to be washed.

FRICTION CLUTCH AND PULLEY.—C. D. Palmite, Oswego, N. Y.—This invention consists in the employment of a pulley fitting loosely upon a shaft, and driven by a belt from any suitable power, in combination with an elbow-shaped friction lever, may, by the said wedge, be pressed against the inner circumference of the pulley rim, thereby connecting the pulley with the sleeve and shaft, and driving the latter.

EXCAVATOR OR DITCHINNG MACHINE.—Isaac V, Adair, Varick, N. Y.—This invention has for its object to furnish an improved machine designed especially for use in removing the earth from ditches after it has been loosened by a ditching plow.

PENCIL HOLDING ATTACHMENT FOR CARPENTERS COMPASSES.—W. G. Hillegass, Philadelphia, Pa.—This invention relates to a device by which carpenters steel pointed compasses can be provided with a pencil point, whenever desired so that the said pencil can be applied in a convenient manner; while heretofore the pencil had to be tied to one of the legs of the compass by means of a thread or string.

# Answers to Correspondents.

CORRESPONDENTS who expect to receive answers to their letters must, in all cases, sign their names. We have a right to know those who seek in formation from us; besides, as sometimes happens, we may prefer to ad dress the correspondent by mail.

SPECIAL NOTE.—This column is designed for the general interest and in struction of our readers, not for gratuitous replies to questions of a purely business or personal nature. We will publish such inquiries, however, when paid for as advertisemets at 50 cents a l ne, under the head of "Business and Personal."

\*\* All reference to back numbers should be by volume and page.

G. A. D., of Me.—" How can stains be removed from soap stone and the polish renewed?" It depends on the nature of the stains. If grease, soap will remove them.

R. R., of Canada:—"Do you know of a cheap composition to coatglassformaking mirrors; I have heard of such a thing being used in Europe?" We know of no process or material cheaper than those usually employed.

J. K. B., of Canada, desires to know the value of "magnetic or black sand," large deposits of which have been discovered near his place of residence. In reply we would state that the black band ore is in high repute for facility of reduction. The ore in the United States varies so greatly in quality that its mining is attended with uncertainty.

L. A. L., of —.—. "Is there any fluid or solid substance through which a magnet will not attract?" None known.

S. A. G., of Ind., wants to know what glistens in the small bits of stone he has sent us. It is mica, utterly valueless except when found in large masses. He asks, also, what to put in his platin; solution to make the gold or sillver deposit bright. You cannot deposit blacking on your boots and have it bright without brushing or burnishing; neither can you deposit metals by the galvanic battery and have the coating bright without burnishing.

H. C., of Mass.—The "skivers" or knives used by curriers in dressing the flesh side of skins have no edge similar to that of an ordinary cutting tool. The edge is quite "stunt," or of a short bevel, and the feather edge is turned by a "steel"—a round spindle—so that it forms an angle with the blade of nearly if not quite 180°. There is much art and experience required in its use.

P. McC., of N. J., says that mill picks should not be drawn at the edge, but should be forged thick and drawn back of the edge, the cutting portion being left as hard as water can make it.

F. G. W., of Mass., asks several questions relative to steam engine vacuums, condensation, pressure of the atmosphere, etc., all of which can be more readily answered by a treatise on natural philosophy or the life of James Watt than through these columns. We respectfully refer him to elementary works on steam engines.

A. F. F., of Ill., asks if he can construct an annealing furnace for sheet brass and do the work properly by means of an endless grate, or a grate attached to an endless apron. We see no reason why the plan is not practicable.

J. J. N., of Pa., asks for a rule to set the heads of a lathe when it is designed to turn a taper, the length of shaft and degree of taper being given. He offers for an example a piece one foot long the taper to be half an inch; "how far should I set the head from the taper line?" If the taper is to reach from end to end of the shaft the head should be set over just one quarter of an inch, in all cases one half of the taper required. But it may be he makes no allowance for the space taken up by the dog. We know of no absolute rule perfect under all circumstances. The experienced eye is the best rule for ever varying cases, always keeping in view that for every quarter inch the tail is thrown over double the taper is given, etc.

J. V., of Ala., sends a diagram and description of a flying machine which he thinks will work, and asks us to rublish it. We prefer to wait until we receive some account of a machine actually at work. We have piles of these suggestive and conjectural letters on aerial navigation, not one of which seems to us at all practical.

A. G., of Fla., replies to J. H. S., of O., that he can harden his cultivator plow without springing by chalking it well upon both sides, heating it to a cherry red and dipping it gradually into water.

E. B. Y., of Pa., asks "what acid or other substance will separate the carbon from carbonic acid or carbonic oxide so as to leave the oxygen only?" The information, if we could give it, would be acceptable not only to E.B. Y., but to the scientific world at large. We regret that we share in the universal ignorance of any means of accomplishing this end.

F. R., of N. Y., propounds a series of questions to which We reply: 1st; The article sold by druggists under thename of benzine is derived from petroleum, and is identical with naptha. 2d; Common petroleum or burning oil is better than benzine for preserving sodium. 3d; Napthaline is a solid camphor-like substance, found in gas tar. Gasoline is one of the most volatile liquid products of petroleum. 4th; Albumen is preserved on a large scale by drying. 5th; The atomic weight of oxygen is 16; the equivalent is 8. 6th; "Maynooth's iron battery" has not come into use. The inference you may draw is that its merits have been over stated. 7th Fressenius' Analysis and Miller's Chemistry are among the best authorities on chemistry.

E. C., of N. Y., referring to the instance given in our issue of the 16th inst of a piece of wood having imprinted itself upon a bar of iron states that he noticed recently in Fitchburg, Mass., a granite boulder, upon which was a representation of the bottom or end of a post which had been standing upon it for a number of years, the impression being about one-sixteenth of an inch deep. He calls upon some correspondent for a satisfactory explanation of this singular fact.

"Inquirer" calls for some table giving the percentage of alcohol in the various liquors, wines and brandies, more reliable than that of Brande, which is usually found in the books? Any such table can be only correct for particular samples, the percentage varying with the honesty of the distiller and age of the liquor. We refer Inquirer to an exhaustive article on alcohol in Muspratt, Chemistry.

B. F. E., of Ohio, replies to the inquiry of F. K., of Mo., for a simple recipe for softening hard water "that one quart of bran confined in a bag and boiled in ten gallons of hard water will bring the lime to the top which can then be skimmed off." This plan, he asserts, is superior to using sal-soda or wood ashes and is just the thing F. K. wants.

## Business and Lersonal.

The charge for insertion under ins head is 50 cents a line.

Pattern Letters and Figures for inventors, etc., to put on patterns for castings, are made by Knight Brothers, Seneca Falls, N. Y.

A metal-working shop, with two patents, for sale or exchange for Real Estate in city or country. Townsend & Sears, 218 Fulton st., room 7.

Manufacturers of Portable Saw Mills and Engines please send circulars and cash prices immediately. Address J. J. Hovell, Avon, Ill.

For sale low—the patent right of an improved Tag Holder—best out. Address A. Grushus, St. Paul, Minn.

Wanted—a Horizontal Face Plate Boring and Turning Lathe to swing 8 or 9 feet, new or second-hand. Address, with description and price list, T. H. Risdon, Mt. Holly, N. J.

Inventors Take Notice.—Having Spare Machinery, Power, etc., we would build light machinery, models, tools, or a patented article, requiring good machinists' work, Address Littlefield Brothers, Randolph, Mass.

Wanted!—Joshua Beal, Baton Rouge. La., wishes to communicate with Agents or Manufacturers of machinery used for the manufacture of cotton wrapping twine.

Parties desiring the services of a first-class inventor to get up new machinery, drawings, etc., address, with confidence, A. E. W., inventor and draftsman, 114 Fulton street.

Geo. W. Douglass, of New Haven, Conn., wants a heavy Power Press immediately.

We want a contract to build Sash, Blinds, and Doors; have New works. Address A. Woodworth, Cambridge, N. Y.

Wanted—A Second-hand Fire Dryer for Paper Making. Address S. D. Paddack, Elbridge. N. Y.
Sleigh Bells.—Manufacturers of Sleigh Bells will please send

their address to Wm. R. Oatley, Rochester, N. Y.

The Babbittonian Penholder has advantages over any in the

market, receiving pens of all sizes, holding them outward to prevent spattering, and having both the English and the famous French scales of measment. Babbitt Bros., 42 John street, New York, furnish them, postpaid, at 35 cents for the silver, and 15 cents for the white holder.

H. N. Winans, 11 Wall st., New York, Manufacturer of The Anti-Incrustation Powder, for removing and preventing Scale in boilers, desires the address of parties using Steam, that he may send circulars of interest on the subject.

Jones & Stelfor, Austin, Texas, wish to procure the best Tire Bending Machine, and Foot or Hand Punching Machine.

Stationary Engine For Sale, 10 Horse power, modern build, short stroke, with tubular boiler, 2½-inch tubes, was only used about six weeks. Price \$450 on board cars. Apply to Abram Logan, Tidiontc, Pa.

Wanted Immediately—Address of all Manufacturing Companies in United States—especially of Tin Plated Ware—for entirely new articles of Manufacture. Jno. I. D. Bristol, Detroit, Mich.

J. N. Bebont, Savannah, Ohio, wishes to communicate with makers of pumps suitable for operation by a wind mill.

# NEW PUBLICATIONS.

Astronomy. An Elementary Work on Physics, by W. T. Rolfe and J. A. Gillet, both teachers in the High School at Cambridge, Mass. Boston: Crosby & Ainsworth. New York: O. S. Felt.

The authors show how we know the earth rotates on its axis; that the earth and planets with their satellites revolve in elliptical orbits about the sun; and that the sun and the stars are moving through space, or about other stars. They have also endeavored to show how, by measuring a line a few miles in length on the surface of the earth, and a few angles, we are able to find the size of the earth, and to pass out into space and measure the distance from the earth to the sun, from the sun to the planets, and from the earth to the fixed stars—a distance so vast that the velocity of light is the only unit suitable for expressing it.

ELEMENTS OF NATURAL PHILOSOPHY. By the same authors and publishers as above.

This work is designed as a first book in physics, to be used in grammar and district schools. The work consists of three sections: the first treating o pressure; the second of motion; and the third of machines and sources o mechanical power. Under the latter are taken up the so-called "mechanica powers," and the sources of mechanical power—namely, hand power, horse power wind power water power, and steam power; and an account is given of the most important machines by which each of these is made to do work. Under water power are included the subjects usually put under hydraulics. This work, as well as the work on Astronomy, is profusely illustrated.

# EXTENSION NOTICES.

Samuel G. Lewis, of Kellyville, Pa., having petitioned for the extension of a patent granted to him the 14th day of February, 1854, and reissued the 22d day of October, 1867, for an improvement in making thick paper, for seven years from the expiration of said patent, which takes place on the 14th day of February, 1863, 1t is ordered that the said petition be heard at the Patent Office on Monday, the 27th day January next.

#### Device for Regulating the Amount of Water fed action of the sulphites of lime, hyposulphite of magnesia, F, leads the oil up into this wick holder. The spiral spring to a Boiler.

Not a few of the boiler explosions that occur are directly attributable to lowness of water, and often this state of water cannot be detected by the gage, on account of some fault either of construction or operation. Under such circumstances an automatic, absolute, and reliable device for regulating the amount of water fed to the boiler is a desideratum. The inventor of the device shown in the accompanying engraving is confident that this is what is needed. A is the boiler to which is connected the water reservoir, B, which is a coneshaped vessel supported by the standards, C. The water is fed into this reservoir by the pipe, D, and to all intents and purposes the reservoir is a portion or extension of the boiler,

being connected with the steam space-seen above the dotted water line in A-by the pipe, E, and with the water space by the pipe, F, both of which are furnished with cocks. Inside this reservoir is a lever shown by the dotted lines, G, having at the large end of the cylinder a float, H, which rests upon the water, and is secured to a transverse shaft at the other end which has keyed to it the arm, I, that is slotted, as is also the valve arm, J, and both are connected and adjusted by a bolt, K. In the pipe, D, is a valve worked by the float, H, through the medium of these arms, I and J. L is a waste pipe with cock for drawing off the water when desired. The dome, M. attached to the steam pipe, E, contains a coil of copper wire intended by the inventor for the purpose of preventing incrustation in the reservoir.

The operation is apparent. As the water lowers in the boiler the float, which rests on its sur-

and permits a greater inflow of water from the pump, arrested decomposition, and by so doing allowed the animal while the contrary result occurs when the water to recover by the recuperative power existing in its own conrises. Of course, if the accuracy of the apparatus is at stitution. The author thought his observations conclusive all to be depended upon, this is a perfect regulator of the as to the excellent influence of the sulphites on the septic diswater in a boiler. The inventor also introduces in the lower end of his pipe a ball valve, which, when the pump is attached to the reservoir into which the hot water or condensed steam passes, prevents all the thumping experienced when pumping hot water.

This device was patented Sept. 24, 1867, through the Scientific American Patent Agency by R. J. Jordan, assignor to himself and E. Darling, of Elkhart, Ind. Address for particulars the former at Elkhart, Ind., Box 264.

# Public Improvements in Paris.

Mr. Wales, in a recent, private letter, thus speaks of the progress in public and private improvements now going for ward in Paris :-


"A new cattle market has just been opened in the outskirts of Paris, which covers a space of nearly three-fourths of a mile square. It is solidly built in dressed, cream-colored stone, and enclosed by strong walls, with a very handsome entrance. Every accommodation that modern experience has suggested is provided,-offices, fountains, water for the cattle, stalls, pens, and storehouses. A railway connects with the circular one that runs around the city, so that cattle from any point in France can be brought straight in without transhipment. The whole space is covered by a roof, but open at the sides. From 5000 to 6000 cattle, 20,000 sheep, 2500 calves, and as many pigs, can easily be accommodated. A communication by bridges connects the market with the new slaughter houses on the opposite side of a canal. No animals for slaughter are ever seen in the streets of Paris, and the streets are always kept perfectly clean. The SCIEN-TIFIC AMERICAN recently published an elaborate account of the Paris markets, which certainly surpass those of any other city in the world. The municipal government exercises the most rigid inspection over every article exposed for sale, and no poor, half-decayed meat or vegetables are allowed to be sold or offered for sale.

"Nothing in Paris so much impresses an American as its splendid public buildings, and the perfect order that prevails in its busy thoroughfares. At this moment a new opera house is nearly completed, which is the most elegant building of the kind in the world. It will cost forty million francs, the expense being equally divided between the Imperial Government and the municipality of Paris. It is also a great mistake to assert, as many do, that the private residences of New York are finer than those in Paris. During the ten years past Paris has improved wonderfully in this respect, so that now she outrivals all other modern cities. I wish the authorities in New York could be induced to copy some things which are so valuable to the people of Paris."

# Antiseptic Properties of the Sulphites.

At the recent Dundee meeting of the British Association Dr. Polli communicated a paper bearing on this subject containing facts which he had obtained as the results of extended observations. Sulphurous acid was said to be the most active agent in preventing or arresting all organic fermentation.

phite. These substances were found to possess all the propaction was more uniform and certain and constant. In ex- | H permit the oil to flow into the lower part of the tube. From perimenting on animals and himself, he found that large doses could be taken without risk. On killing animals treated with sulphites, and others not so treated, he found that the former were most slow to decompose, and, indeed, remained quite fresh when the others were putrescent and the tube, F, to feed the wick. Before this vessel can fill, the offensive. Another series of experiments showed that in one class the administration of the sulphites, was sufficient to tion indicated by the arrows, to the reservoir. effect a more or less rapid cure in cases where blood poisoning was present, as in fevers, but this fact he did not attribute to the flame of the lamp, can never become heated, thus pre-




#### JORDAN'S STEAM BOILER REGULATOR.

face, descends, opens the valve in the feed pipe, D, any curative power in the sulphites, but to the fact that they him at Constableville, Lewis county, N. Y. eases, and remarked that it was for the purpose of thus benefitting others that he had brought his researches under the attention of the scientific world.

# HOFFMANN'S IMPROVEMENT IN LAMPS.

The intention of the inventor of this lamp is to construct one not liable to explosion if kerosene or similar fluids are



used, to keep the outside of the lamp perfectly clean, to save much of the labor of filling and trimming, and to prevent the evaporation of the oil by heating. It may be constructed either of metal or glass. A is the oil reservoir, the oil being poured in at the cap, B. Into this reservoir is fixed a tube which supports the lamp or wick holder, C. This is also secured upright by the braces, D. From the upper vessel de-As the acid, however, was not sufficiently applicable in ex seend two tubes, E and F, one of which, E, returns any excess however, is conclusive on this point. To whomsoever it may

sulphate of magnesia, sulphide of soda, and granulated sul- in A sustains the upper cup in position. In the tube are two loose valves. G and H, held to the seats by transverse bars or erties of sulphurous acid, with the advantage that their snugs, and packed with rubber. The apertures seen under these references to the engraving-which, it will be noticed, is sectional—it will be seen that the internal details form a pump. By pressing down the upper vessel, the valves, G and H, are worked, and the oil in the reservoir is forced up through oil will flow over into the pipe, E, and pass back in the direc-

By these arrangements the oil, being so far removed from

venting the generation of gas from the oil; not a particle of oil can escape from the inside of the lamp to soil the outside, and all danger of explosion from the communication of the flame to the oil is avoided.

The arrows in the engraving show plainly the course of the oil from the reservoir to the upper vessel, and its return, if too much is pumped up. By a change in the wick tube any burning oils or fluids may be used in this lamp. The lamp, or the oil reservoir may be filled while the lamp is lighted without danger, and it is believed that this separation of the lamp proper from the oil reservoir will entirely prevent explosions.

Patent papers for this invention were obtained through the Scientific American Patent Agency, Oct. 1, 1867, by Peter Hoffmann; who desires to sell rights to vend and manufacture.

Makers of lamps, and others interested, will please address

# Machine for Extracting Tannin from Hemlock Bark.

Mr. Langley, at the November meeting of the Massachusetts Institute of Technology, described a machine for the above purpose, now in process of construction at the South Boston Iron Works, under his superintendence, and from his designs. By this machine much time and labor will be saved, and the old tedious process of long contact of the coarsely ground bark with the skins to be tanned considerably shortened.

The hemlock bark, in pieces of half an inch to an inch thick, and several inches long, is soaked for about fifteen minutes in water at 200° Fah.; it is then fed into a hopper, which conducts it to a three-rolled machine, something like the rollers of a sugar or cane mill, through which it passes, coming out lacerated and compressed: it then falls into a vat of hot water, where it is agitated by a wheel, that the tannin from the crushed cells may be dissolved in the water; it is then raised by a series of buckets on an endless chain, somewhat in the manner of a grain elevator, to another hopper, whence it is fed to another series of three rollers; here it receives its final compression, and comes out in flakes or sheets, like coarse paper, and almost free from tannin. The buckets are made of coarse wire, that the water may drip through during the elevation. In order to avoid the blackening action of iron, wherever this metal is brought into contact with the solutions, it is thickly coated with zinc.

The extracts thus obtained are of a fine crimson color. highly concentrated—indeed almost saturated solutions of tannin; they require to be largely diluted, being from three to six times too strong for application to the skins; thus the tanning principle of a cord of bark, which the machine can treat in an hour, is concentrated into a barrel of the extract. Even supposing that the tanning process cannot be shortened, as far as the best quality of leather is concerned, any one will see the immense advantage of taking a machine to the hemlock woods, and bringing back tanning extract by the barrel instead of so many loads of bark. This process will open an immense and profitable commerce between this country and others where tanning materials are not indi-

# The Spread Locomotive Truck.

In No. 17, current volume, page 263, a reply to J. P. J., of Pa., states that the locomotive truck was invented in 1831, and that Wm. Mason, of Taunton, the well known inventor and manufacturer, improved it by spreading the wheels to admit of the use of a cylinder on a level with the center of the driving wheels. This referred to outside cylinders, of course.

A correspondent from Massachusetts states that he was in the employment of Mr. Mason when he delivered his first engine, and that previously he had superintended the construction of spread truck locomotives in another establishment.

We knew only that the Mason engines achieved a deservedly wide-spread popularity mainly for this and possibly for other minor improvements, and had always supposed he was the first builder to spread the truck sufficiently to allow of the cylinders on an "outside" engine to be leveled to the centers of the drivers. The statement of our correspondent, periment, Dr. Polli had undertaken an investigation as to the of oil in the upper vessel back to the reservoir, and the other, be accredited it was a long step in the right direction.





### MUNN & COMPANY, Editors and Proprietors.

PUBLISHED WEEKLY AT NO. 37 PARK ROW (PARK BUILDING), NEW YORK,

O. D. MUNN. S. H. WALES. A. E. BEACH.

\*\*The American News Company," Agents, 121 Nassau street, New York

\*\*The New York News Company," 8 Spruce street.

TF Messrs. Sampson Low, Son & Co., Booksellers, 47 Ludgate Hill, London. England, are the Agents to receive European subscriptions or advertisements for the Scientific American. Orders sent to them will be promptly attend-

Messrs. Trubner & Co., 60 Paternoster Row London, are also Agents for the Scientific American.

VOL. XVII., No. 22....[New Series.].... Twenty-first Year.

NEW YORK, SATURDAY, NOVEMBER 30, 1867.

#### Contents:

(Illustrated articles are marked with an asterisk.)

### HAND-TOOLING ... ITS ADVANTAGES TO THE MACHINIST.

With the improvement in automatic or self-acting tools the acquirement of skill in manipulation has not preserved the importance to which it is justly entitled. The hand tool for turning does not preserve the high position which it formerly occupied, yet its use is exceeding valuable, and even necessary, in many instances. There is an extensive class of work in machine building on which it can be advantageously employed; yet we are not aware that in this country its use is generally taught as a part of the apprentice's education. It ranks next in importance to the file, and a machinist who can handle it with facility is always an important hand in a shop.

Curved and irregular forms, which must be turned, may be finished much more readily by the hand tool, if judiciously and properly used, than by the fixed lathe tool. For instance, common iron washers, which are placed under the head of a screw or a nut, may be turned and water polished by the hand tool very rapidly. We can hardly imagine any other method of finishing them. The washer is driven on an arbor with just sufficient force to retain it in place, then the arbor put upon the lathe centers, with a dog to engage with the face plate, and revolved as rapidly as a drill--almost as rapidly as a piece of wood to be turned. A diamond pointed tool, made from a triangular file, will speedily remove the scale, when another tool, used with water, will give a splendid finish, the washer so treated presenting an elegant appearance. So in "skinning" or lightly turning a small shaft or arbor the hand tool is invaluable; and in finishing out curves and bevels on a shaft.

The formers for brass musical instruments, which taper for much of their length and then expand by a gradual but varying curve into the "b $\epsilon$ ll" can be more easily and rapidly finished to the gage by the hand tool than by any automatic lathe however perfect and complicated.

The heads of steam engine cylinders are often beaded and ornamented by projecting rings. No ordinary engine lathe with its fixed tool, however handy the operator, can so rapidly and elegantly finish these ornaments as the hand tooler with his simple implements. So in hundreds of cases a practical knowledge of the hand tool is an immense advantage to the workman and profit to his employer.

Sometimes it is necessary to "chase" a screw thread instead of finishing it with the ordinary tool in a screw lathe. By the use of the chaser—which is but a modification or another application of the common hand tool—a screw thread can be finely finished and all its irregularities and roughness removed. Screws of odd sizes may thus be cut which would otherwise perhaps require dies made for that special purpose and occasion.

Skill in the use of the hand tool can be easily acquired; judgment and discretion are as necessary to its successful use as practice. The tools required are cheaply and easily made; the small tools being formed either from old files or bars of steel, and the shoulder tool being merely a stock of wood with a handle transversely attached, and carrying in a groove a straight steel bar properly shaped at the point and held by ascrew. Machinists of foreign education at present excel in this specialty, but there is no reason why our American mechanics should not become adepts in hand tooling.

# ECONOMY IN COKE MAKING---THE UTILIZATION OF THE WASTE GASES.

The only use that has heretofore been made of the gases driven off from bituminous coal during the press of coking has been to supply the heat necessary to make the coke. It will require but a glance to show that even with a coal with but a small proportion of gaseous matter in its composition, only a portion of its gas is really necessary to give the heat required to completely perform the operation of coking. The only attempt that we are aware of that has been made to utilize all the gases driven off is by the process of Messrs. Carver & Co., of St. Entienne in France, and they issued a small pamphlet which was given to visitors to the show of articles made from the gases driven off incoking exhibited by the Société de Carbonization de la Loire in the Paris Exhibi tion. This pamphlet was explanatory of their process which is eminently successful. The gases from the coking coal are collected and drawn off through pipes, and cooled sufficiently to condense the tar, ammonical liquids. etc., contained in them; this purifies the gas and it can be used for the same purposes as that made by the ordinary illuminating gas works. From the tar and liquids thus condensed, benzine, napthaline, sulphate of ammonia, a number of artificial manures, and a number of dye stuffs, are made; fabrics are also exhibited colored by these dyes. All these valuable products are, therefore, made from the gases which are permitted to be wasted by the usual process.

This company estimate that the profit they net from these substances is 21 francs for each tun of coal coked. And to give an accurate estimate of the profits which accrue from this source it is only necessary to say that the coking ovens of the company, and which have been in operation for over nine years, use annually upward of 80,000 tuns of coal in making coke. The pamphlet of Messrs. Carver & Co. contains a calculation that some three and a half million tuns of coke are made annually in France; this amount corresponds to some four millions of tuns of coal, a large portion of the volatile constituents of which are wasted and from this it is estimated that between twelve and thirteen million of francs are lost annually by the ordinary wasteful method. On the whole this is one of the most eminently successful examples of the application of practical chemistry to the arts that we have had the pleasure to record. It is a striking example of the benefits of the technical and industrial education which has been followed for many years in France, and indeed on the continent generally. We trust that before many years our practical men may enjoy equal advantages with respect to the application of theory to practical operations connected with the industrial arts not only as regards chemistry alone but in all other branches. To effect this we must have schools of a decidedly practical nature, and text books devoid of speculation and so clearly composed that the facts that they are written to convey may be clear to the average understanding of those seeking instruction from them. A traveller in Europe with any mechanical perceptions, cannot fail to be impressed with the importance of the continental system of technical instruction by the superb engineering and the wonderfully perfect metallurgic operations to be seen on every

# THE PETROLEUM FUEL---WILL IT SUPERSEDE COAL?

The petroleum excitement reached its climax immediately after the trials with the retort apparatus on the U.S.S. Palos, in Boston Harbor. The results after these experiments were proclaimed on all sides as eminently successful; "the days of coal were numbered," so said one of the experts at a Babylonian banquet given in Boston in honor of "the great event of the age." A commodore in the U. S. Navy was so impressed with these trials that he forthwith petitioned the Department to order an extended trial at sea. There is a point in connection with the Palos matter that should not be ommitted, and that is that the report of the Board of Naval engineers, who were ordered to attend the trials and to strictly investigate them, has not, to our knowledge, been made public. It would seem that if this report was a favorable one, it would have been placed before the public long ago, and that too in a very conspicuous manner; if this had been the case it is pretty clear that it would have carried much more weight, and would also have influenced stock subscriptions to an extent considerably greater than the parade of the after-dinner speeches of the savans, sailors, and engineers who made an excursion on the Palos in Boston Har-

Since this event in the petroleum world the excitement has been gradually subsiding and the dying embers are only kept at a dull-red heat by skillful letter-writing by the correspondents of the New York press, in other cities. The Cunard line have not adopted it, neither is it used on railroads and it would seem that if the petroleum companies themselves have any confidence in the wares they are trying to persuade the public to buy, they would be introduced practically so that there might be a fair comparison with coal, particularly as it is claimed by them that the apparatus can be put in any furnace with very little labor.

# The Dental Vulcanite Question.

We recently published a judicial decision in the vulcanite question which was adverse to the dentists. A meeting of dentists was held at Cincinnati, on the 7th inst., to take into consideration the dental vulcanite question, and the following resolution was adopted:

the same fact held true in the case of glaciers, and has made experiments in an artificial grotto some three hundred feet deep, in the Grindenwald glacier. The ice wall was nearly fifty feet thick, the solar light that penetrated through was resolution was adopted:

Resolved, That we approve of the action of the executive erous aspect almost alarming. On looking toward the entry committee and all they who have been active for the dental at a certain distance, the cavern appeared to be lit up with a

profession of the West, in contesting the claims of the Goodyear Dental Vulcanic Company against the profession, and that we request them to continue the defense to the ultimatum, believing, notwithstanding the decision of Judge Wilson, of New York, that the importance of the subject demands full and final investigation by the best tribunal in the country

#### ANTI-FRICTION METAL FOR RAILWAY AXLES.

Nothing interferes more with the success of mechanical inventors than the element of friction. Not even the law of gravitation offers such obstacles to the intentions of inventors. To overcome the resistance of friction, especially on shaft journals, there have been devised several combinations of different metals which together should give the greatest resistance to pressure and heat. One of the most notable successes in this line has been that of the well-known Babbitt metal, which even now holds a high place in the estimation of mechanics.

But, it is claimed that there are compositions which far surpass this in the points which are sought to be obtained. There is reason for this claim in the case of one, at least, and we are doing but an act of simple justice to call the attention of our railway men to the advantages of the "Star Metal," which is manufactured largely by the Star Metal Company at their establishment in Brooklyn, N. Y., and Chicago, Ill.

We lately visited the former concern and witnessed the various processes of manufacture, except the actual mixing of the metals, which is preserved a profound secret. The basis, however, of the Star metal is spelter or zinc. In this foundery are employed, at present, seventeen furnaces, in constant operation. The patterns are molded in ordinary furnace sand in iron flasks. The metal box is held in a shell of brass, as by experience it was found preferable to a box made entirely of the Star metal. The metal is run into the brass shell, with which it is united by partial fusion. The box is then cleaned and dressed to exact size by the file. The bearing is trued and polished by vulcanite emery rollers which form the half circle to a gage so that the bearings are as perfect as they could be made by boring or turning. The use of emery for this purpose will prove at once to the practical mechanic that this metal differs greatly from Babbitt, which if ground with emery would become filled with the flinty particles. The metal is, in reality, very hard, instead of being soft, and is so brittle that it does not clog the file any more than iron and much less than hard brass. This quality of hardness may seem to be an objection, as it is commonly believed that bearing metal should be soft, but the manufacturers claim that this very quality is one of the peculiar advantages of the metal. Its resistance to heat is remarkable, its melting point being but a trifle lower than that of ordinary brass, and it is very difficult to heat it by friction. It will not cut the journal when hot, as brass does, and it will outwear either brass or the Babbitt composition.

These boxes are in use on a large number of our most extensive railroads in the country, and have received in all cases the most unqualified commendation. The company say in their circular that "in the examination of the actual comparative wear between Star metal and other (solid brass or Babbitt) bearings, upon the roads in this country testing Star metal, we find, taking the difference in wear and in weight into the calculation, that those roads should pay but  $14\S$  cents per pound for their (solid brass or Babbitt lined) bearings, to compete in price with Star metal bearings. We therefore claim that those roads lose, per pound, in using brass or Babbitt lined bearings, the amount they pay for same over 145 cents per pound; that it is more economical to use Star metal bearings costing 37 cents per pound than others, even at 145 cents, on account of less wear upon the journal by the Star metal, and for the reason of its not cutting the same when hot; that it requires less power to draw a train running with Star metal bearings from the fact that where the journal and bearing wear least, there is less friction."

When tested against the brass or Babbitt lined boxes the Star metal bearings have invariably proved superior in the relation of from 40 to 75 per cent. The tests have been made by placing equal numbers of the Star metal boxes and of others under the same car, so that each should have the same amount of wear, and travel the same distance.

# New Facts in Spectrum Analysis.

A very curious observation, on the spectrum of a terrestrial flame closely resembling that of certain yellow and red stars, has been communicated to the Italian society—called the Forty—of Modena, by M. Secchi. This flame is that which proceeds from a converter in which Bessemer steel is being made and at the time when the iron is completely decarbonized. The spectrum presents a series of very fine and very numerous lines, similar to those of a Orionis and a Herculis only reversed. This results from the great number of metals burning in the flame, and is the only flame comparable with the colored stars. There is nothing improbable in this fact when we consider the composition of ærolites in which as is well known, iron predominates.

M. Secchi had formerly ascertained that the spectrum of the color of sea water is deprived successively of its red, yellow and green as its depth increased, and at the greatest depths it appears of a violet blue. He tried to ascertain if the same fact held true in the case of glaciers, and has made experiments in an artificial grotto some three hundred feet deep, in the Grindenwald glacier. The ice wall was nearly fifty feet thick, the solar light that penetrated through was of a fine blue tint, so that human countenances had a cadaverous aspect almost alarming. On looking toward the entry

red light, undoubtedly the effect of contrast. The thickness of the superposed mass was not enough to show a greater effect than the almost complete absence of the red, and a great diminution of the yellow. The ice was perfectly compact, limpid, and with few air bubbles.

#### Origin of the Connecticut Clock Business.

Bishop, in his "History of American Manufactures," says that the wooden clock manufacture was commenced in Waterbury, Conn., by James Harrison, in 1790, on whose books the first is charged January 1, 1791, at £3 12s. 8d. In East Windsor the brass clock manufacture was carried on by Dariel Barnap. Specimens which are still preserved are said to be nowise inferior in workmanship to the best English clocks of that or any later period. Clocks were also made in East Hartford by a Mr. Cheeny. In 1793, Eli Terry who had been instructed by Burnap in the business as practiced by him and Cheeny, removed from East Windsor, where he had carried on clock-making, to Plymouth, in Litchfield County. His subsequent enterprise and improvements in the art in that place entitle him to be considered the parent of the manufacture in Connecticut. At that time, Thomas Barnes, of Litchfield, and Gideon Roberts, of Bristol, were also known as clock-makers. The kinds of clocks made by these were brass and wooden clocks, with long pendulums, and their price was, for a wooden clock and case, from \$18 to \$48, the higher priced ones having a brass dial and dial for seconds, and the moon's age, and a more costly case. Brass clocks with a case, cost from \$38 to \$60. So limited was the sale at those prices, that three or four hundred constituted a stock in trade, and they were carried out for sale by the maker on horseback, the case being procured by the purchaser at from \$5 to \$30, according to his taste. Terry made both kinds, using a hand engine for cutting the teeth of the wheels and pinions, and a foot lathe for the turned work. In November, 1797, he patented an improvement in clocks, watches, and time-pieces, covering a new construction of an equation clock, showing the difference between apparent and mean time. In 1802, in which year Willard of Boston took a patent for his time-pieces, Terry began the business on a larger scale by water power, and, five or six years after, his success in making them by the thousand, which had been ridiculed as chimerical, enabled him greatly to extend the manufacture, which others now commenced on the wholesale system. In 1814 he introduced a new era in the business by commencing on the Naugatuck river the manufacture of the shelf or mantel clock, which he patented in 1816. The cheapness of these created a wide demand. Several improvements made by him in the mechanism, and the later progress in machinery generally, have increased the annual production in that State to hundreds of thousands, and given to every household a clock, equal to the old ones, at a cost of \$2 and upward. His descendants have been engaged in the business to the present time, and his pupil, Chauncey Jerome, since 1821.

Apart from the importance of horological machines in every department of life, and especially in relation to science and business, there are few of the mechanic arts which have furnished more numerous and striking examples of great and useful inventions among its members than the clock and watchmaking business. Many, both in Europe and America, have first exercised in this way their ingenuity, which has afterward conducted to discoveries of universal utility. Rittenhouse, Fitch (also a native of Connecticut), Whittemore, who, before any of the above, also constructed without a model, an efficient wooden clock, Dr. Franklin, and others, might be named. Clock-makers are said to have been the first who employed special machines for their manufactures, the wheel-cutting engine having been invented by Dr. Hooke about 1655, and the screw-cutting lathe by Hindley, a clockmaker of York, England, in 1741. The fusee engine and slide rest, the value of which are known to all mechanician's who use metal, are of later introduction, although the latter, in an imperfect form, was used at Rome in 1648, and attained its present form in 1772.

The Assembly of Connecticut, in October, 1783, awarded a patent for fourteen years to Benjamin Hanks, of Litchfield, for a self-winding clock. It was to wind itself by the help of the air, and to keep more regular time than other machines. The principle was made use of in New York and elsewhere

# Practical Application of the Transparency of Metals.

Metals have generally been considered as opaque bodies, not permitting the passage of light through their substance. very easy to show, by the use of an extreme thin film, as of gold or silver deposited upon glass, that light passes quite freely through it, and this property has latterly been turned to very good advantage. One of the earliest applications was as a substitute for the ordinary soot-blackened or colored glass, used in observing the sun during an eclipse, or at other times; and the silvering of the objective glass of the great telescope of the Paris Observatory has permitted an investigation of the sun's disk such as could not otherwise be prosecuted. Viewed through a lens, or even a plane glass thus silvered, the sun appears of a soft, blue'sh color, very sharply defined against a black background, formed of the sky. All the peculiarities of the solar image, the different spots and foci in their variations of intensity, and the less luminous marginal regions, are shown with the greatest clearness, and even the filmiest clouds and vapors which seem to sweep over the disk can be readily perceived. The examination can be kept up any length of time without strain to the eyes. The physiological influence is very different from that of colored glasses, the use of which is sometimes very objectionable. Since all the different rays of light pass through the metal (although greatly tempered) except the outermost life. The incision in the windpipe was, however, kept open

rays, the silver must be deposited in the usual galvanoplastic or chemical manner, so as to form a very delicate film. Gold and platinum may also be used, but silver possesses several advantages.

This property, in the part of metals, of greatly subduing the rays of light without extinguishing them to any extent, and of excluding almost entirely the rays of heat, is now applied to other practical purposes. Weak eyes can use spectacles thus prepared to the greatest advantage, where colored glasses are not to be thought of. For persons whose business keeps them before a glowing fire, such glasses are invaluable, since the sight is not strained by the light, nor the everball injured by the heat, which is measurably excluded. Screens of glass, to be placed before fires, have also been made on the

By inserting plates of glass thus treated in the panels of doors, or using them as window panes, it will be easy to observe from within all that is going on outside, while it will be impossible to see into the room unless there be another window on the opposite side, so as to show through. The application of the silver to the glass converts it into a mirror, which reflects the light, and to the observer is as opaque as mirrors are generally. The use of such windows wherever an observer within has occasion to notice persons outside without being seen, will be readily understood in the case of prisons, workshops, stores, etc., where, however, as already remarked, there must be but the one opening. The platinized glass has been found most convenient for this pur-

These few illustrations of a general principle, capable of a great variety of practical applications, show, at the same time, how often the man of science, seeking for the solution of some problem in his theoretical investigations, reaches a result capable of a thousand uses in every day life, which are eagerly caught up and turned to profitable account.—Phil.

#### Brunel's Mishaps.

Although Brunel died at the comparatively early age of fifty-three, it is even matter of surprise that he lived so long. He had more perilous escapes from violent death than fall to the lot of most men. We have seen that at the outset of his career, when acting as assistant engineer to his father, in the Thames Tunnel, he had two narrow escapes from drowning by the river suddenly bursting in upon the works. Some time after, when inspecting the shafts of the railway tunnel under Box Hill, he was one day riding a shaggy pony at a rapid pace down the hill, when the animal stumbled and fell, pitching the engineer on his head with great violence; he he was taken up for dead, but eventually recovered. When the Great Western line was finished and at work he used frequently to ride upon the engine with the driver, and occasionally he drove it himself. One day, when passing through the Box Tunnel upon the engine at considerable speed, Brunel thought he discerned between him and the light some object standing on the same line of road along which his engine was traveling. He instantly turned on the full steam and dashed at the object, which was driven into a thousand pieces. It afterwards turned out to be a contractor's truck, which had broken loose from a ballast train on its way through the tunnel. Another narrow escape which he had was on board the Great Western steamship, where he fell down a hatchway into the hold, and was nearly killed. But the most extraordinary accident which befell him was that which occurred while one day playing with his children. Like his father, Sir Marc, he was fond of astonishing them with sleight-of-hand tricks, in which he displayed considerable dexterity; and the feat which he proposed to them on this occasion was the passing of a half-sovereign through his mouth out at his ear. Unfortunately, he swallowed the coin, which dropped into his windpipe. The accident occurred on the 3d of April, 1843, and it was followed by frequent fits of coughing, and occasional uneasiness in the right side of the chest; but so slight was the disturbance of breathing that it was for some time doubted whether the coin had really fallen into the windpipe. After the lapse of fifteen days, Sir B. Brodie met Mr. Key in consul tation, and they concurred in the opinion that most probably the half-sovereign was lodged at the bottom of the right bronchus. The day after, Mr. Brunel placed himself in a prone position on his face upon some chairs, and bending his head and neck downwards, he distinctly felt the coin drop towards the glottis. A violent courh ensued, and on resuming the erect posture he felt as if the object again moved nward into the chest. Here was an engineering difficulty, the like of which Mr. Brunel had never before encountered. The mischief was purely mechanical; a foreign body had gone into his breathing apparatus, and must be removed, if at all, by some mechanical expedient. Mr. Brunel was, however, equal to the occasion. He had an apparatus constructed, consisting of a platform which moved upon a hinge in the center. Upon this he had himself strapped, and his body was then inverted, in order that the coin might drop downward by its own weight, and so be expelled. At the first experiment the coin again slipped towards the glottis, but it caused such an alarming fit of convulsive coughing and appearance of choking that danger was apprehended, and the experiment was discontinued. Two days after, on the 25th, the operation of tracheotomy was performed by Sir Benjamin Brodie, assisted by Mr. Key, with the intention of extracting the coin by forceps, if possible. Two attempts to do so were made without success. The introduction of the forceps into the windpipe, on the second occasion, was attended with so excessive a degree of irritation that it was felt the experiment could not be continued without imminent danger to

red rays, which are excluded, together with the dark heat by means of a quill or tube, until May 13, by which time Mr. Brunel's strength had sufficiently recovered to enable the original experiment to be repeated. He was again strapped to his apparatus; his body was inverted; his back was struck gently, and he distinctly felt the coin quit its place on the right side of his chest. The opening in the windpipe allowed him to breathe while the throat was stopped by the coin, and it thus had the effect to prevent the spasmodic action of the glottis. After a few coughs the coin dropped into his mouth. Mr. Brunel used afterwards to say that the moment when he heard the gold piece strike against his upper front teeth, was perhaps the most exquisite in his whole life. The half-sovereign had been in his windpipe for not less than six weeks!

OFFICIAL REPORT OF

#### **ULAINS** PATENTS AND

#### Issued by the United States Patent Office,

FOR THE WEEK ENDING NOVEMBER 12, 1867. Reported Officially for the Scientific American

PATENTS ARE GRANTED FOR SEVENTEEN YEARS the following

eing a schedule of fees:—	
On filing each Caveat	310
On filing each application for a Patent, except for a design On issuing each original Patent. On appeal to Commissioner of Patents. On application for Excession of Patent On application for Excession of Patent	.\$15
On issuing each original Patent	\$20
On appear to Commissioner of Patents.	4:30
On application for Extension of Patent	#30
On granting the Extension. On filing a Disclainer.	\$50
on filing a Disclaimer	\$10
On filing application for Design (three and a half years) On thing application for Design (seven years) On thing application for Design (fourteen years).	\$10
On filing application for Design (seven years)	815

In addition to which there are some small revenue-stamp taxes. Residents ct Canada and Nova Scotia pay \$500 on application.

Pamphlets containing the Patent Laws and full particulars of the mode of applying for Letters Patent, specifying size of model required, and much other information useful to Inventors, may be had gratis by addressing MUNN & CO., Publishers of the Scientific American, New York.

70,675.—MEAT MANGLER.—A. T. Adams, Indianapolis, Ind. I claim the combination of the two jaws with the plates, II, bars, mm, and springs, nn, all arranged and operating as and for the purpose specified, 70,675.—MOTH-PROOF CASE.—James W. Aikm and John H.

Stone, Philadelphia, Pa.

We claim a sheet metal moth-proof case for a lady's furs, having the perforated central cylinder A, and the recess, b', in combination with the cylinder, B and the elastic band ring, b''', the said parts being constructed, arranged, and combined to operate together substantially as and for the purpose described.

pose described.

70,677.—NEEDLE MACHINE.—Walter Aiken, Franklin, N. H.

I claim the machine or combination, substantially as described, for the purpose set forth, that is, as composed of the rotary cutted, A, the grooved rest, E, the series of rotary arbors, K, their carrier or wheel, I, and operative mechanism, the shaft, F, and the mechanism for revolving and moving it longitudinally, and the bolt, s, and mechanism for operating such bolt, substantially as explained. ubstantially as explained.

70,678.—MACHINE FOR MAKING THE TONGUES OF MACHINE

70,678.—MACHINE FOR MAKING THE TONGUES OF MACHINE KNITTING NEEDLES.—Watter Aiken, Franklin, N. H.
I claim the combination of the carriags, C, the feeder, G, the bowl-forming dies, w v, and the flattening dies, d"e', all provided with mechanism for operating them, substantially as described.

£4 laso claim the combination of the carriage, C, the feeder, G, the nicking and bowl-forming dies, n' o' w' v', and the flattening dies, d'e', all provided with mechanism for operating them, substantially as set forti.

I also claim the combination of the carriage, the feeder, the bowl-forming dies (or the latter and the nicking dies), and the punch, I', and punch die, g', all provided with mechanism for operating them, substantially as set form.

I also claim the combination of the carriage, the feeders, the bowl-forming dies (or the latter and the nicking dies), the punch and punch dies, and the rounding dies, h' i', all provided with mechanism for operating them, substantially as specified.

Lalso claim the Combination of the carriage, the feeder, the bowl, the punching dies (or the latter and the nicking dies), the punch and punch die, and the rounding dies, and the separpting dies, k' i', all provided with mechanism for operating them, substantially as explained.

70,679.—Hott Air Furnace—Biddle Arthurs, Pittsburgh, Pa.

for operating them, substantially as explained.

70,879.—Hot Air Furnace—Biddle Arthurs, Pittsburgh, Pa.

I claim the drum or heater of sheet or plate iron, with an opening in its bottom and front, connecting with a fire space, c, of brick, the edges of the heater or drum around such opening having flanges, i, built into the furnace walls, constructed and arranged substantially as described for the purposes specified.

specified.
70,580.—SAW.—James E. Atwood, Trenton, N. J., assignor to himself and Cyrus H. McCormick, New York city.
I claim the tooth. A, when held in its position by ratchet, ccc, for the purpose herein described.
60,681.—CARRIAGE WHEEL—Charles C. Ayers, Chelsea, assigner to himself and Henry A. Breed. Lynn. Mass.

signor to himself and Henry A, Breed, Lynn, Mass.

I claim the combination as well as the arrangement of the metallic annulus or inner tire, D, with the wooden felly and the pokes and hub, as exed. so claim the combination as well as the arrangement of the metallic an-sor inner tire, D, with the wooden felly, the hub, spokes, and outer the scribed.

nature of inner tire, D, with the wooden felly, the hub, spokes, and outer the as described.

I also casim the combination as well as the arrangement of the metallic annulus, D, the wooden felly, the springs and chambers therein, the spokes, and the hub, as described, the hub, under such a combination of the spokes with it and the felly, being suspended from the upperhalf of the felly and on springs, while the wheel may be in revolution and use.

70,682.—CONSTRUCTION OF SALVERS.—Seth C. Babbitt, Meriden, Conn, assignor to the Meriden B itannia Company.

I claim the mode or process of siffening the fine or outer edge of a softmetal or Britannia salver, substantially a described.

I claim a Britannia or soft-metal salver constructed substantially as described.

scribed.
70,583.—Truss.—Charles A. Baker, Auburn, N. Y.
I claim the front pad or plate, E. provided with the rod, A, auxiliary pad, B, and straps, D G and H, all constructed and arranged substantially as and for the purpose set forth.

70.584.—Chalk-line Reels.—James Bathgate, Cincinnati.O. I claim the combined arrangement of the reel, Cc, chalk recepticle, D, cap, E, apertures, G, and line, H, all constructed and employed as and for the purposes specified.

70,685.—MACHINERY FOR LAYING AND TWISTING ROPE.—

Stephen Bazin and James A. B <sup>12(1)</sup>. Canton, Mass. We claim the sliding gride pulley, N, in combination with the crane, M, and the winding red; O, operating su-stantially as described for the purpose

set forth.

We also claim the rolls, v, so arranged as to revolve simultaneously, in combination with the fleeters, b', and the guide pieces, a', or their equivalen s, for the purpose of insuring the equal delivery of the strands, substantially as described.

70,686.—Tapering Drill.—Jason A. Bidwell, East Boston,

70,686.—TAPERING DRILL.—Jason A. Bidwell, East Boston, Mass.
Iclaim, 1st, A twisted reamer, c, which is adapted to serve, in conjunction with a spirally grooved drill, a, for making tapering holes in metal, substantially as described.

2d, The construction of a cutting shoulder, e, upon the shank c', of a twisted reamer, c, substantially as described and for the purpose specified.

70,687.—Bed Bottom.—Albert Bingham (assignor to Wm. T. Mudget), Newtonville, Mass.
What I claim as my invention in a spring bed bottom is as follows, that is to say, having its bolster piece, D, its series of pins, c, and slats, g, supported by springs, f, so as to be movable vertically together thereon, and so that each slats may move independently of the bolster piece and its guide pins, the whole being substantially as described.

I also claim the improved spring bed bottom as constructed, not only with each of its slats, supported at its foot or lower end on a stationary cross bar, but as having a bolster piece, D, series of pins, e, and slats, g, supported by springs, f, so as to be movable vertically together thereon, and so that each slatmay move on its spring independently of the bolster piece and its guide pins, the whole being substantially as specified and represented.

70,688.—MACHINE FOR FINISHING WOOLEN CLOTH.—Edwin Birkenshaw. Ashuelot, N, H.

70,688.—MACHINE FOR FINISHING WOOLEN CLOTH.—Edwin Birkenshaw. Ashuelot, N.H.
I claim my improved arrangement of the two teasling cylinders, the shearing mechanism, and their two sets of feed rollers, one teasling cylinder under such arrangement of the series of rollers. D.D. etc., with the shearing mechanism, the feed rollers, and the two teasling cylinders, a ranged in manner as described and represented.
I also claim the combination, as well as the arrangement of the bridge, F, the series of rollers, D.D. etc., the shearing mechanism, the feed rollers, and the two teasling cylinders, arranged as described, the said feeding cylinders arranged as described, the said feeding cylinders arranged as described, and the rotar shade well as the said feed and the road and the rotary shearer brush and the teasling cylinders arranged with the n, as described, and the rotary shearer brush and the teasling cylinders being provided with mechanism for operating them, substantially as hereinbefore explained. before explained. 70,689.—Car Coupling.—Luther Boyd and Philip Krieg-

baum, Springfield, Ohio.
We claim the movable head, B, as constructed in combination with stationary head, C, sides, e.e, and springs, dd, all arranged and operating in the manner and for the purpose herein set forth and described.

70,690.—Evaporation and Vaporization.—M. S. Bringier

70,690.—Evaporation and Vaporization.—M. S. Bringier Ascension Parish, La.

I claim, 1st, The application of one or more series of tubes of small diameter to the external surface of boilers, kettles, or other yessels, as herein described for the purpose set forth.

2d. The use of a revolving coil of wire gauze, or the equivalent thereof, inside steam-boilers, as herein described for the purpose set forth.

3d. The combination of one or more series of small tubes externally applied to boilers, with an internal revolving coil or cylinder of wire gauze, or its equivalent, as herein described for the purpose set forth.

70,691—PROCESS FOR EXTINACTING SACCHARINE MATTERS FROMSUGARCANE.—M. S. Bringier, a scension Parish, La.

I claim, 1st, Extracting saccharine matter from sugar cane, or other vegetables containing it, by maceration and disintegration, as herein described, or any other which is substantially the same in its mode of operation.

2d, The combination of the receiving-toller, A, steam pipe, B, pipes H, C, and D, with the shaft, E, when the latter is provided with the disintegrating appliances herein described, for the purpose set forth.

70,692.—Mop Wringer.—Oscar M. Brooks and Elisha J. Mat-

70,692.—MOP WRINGER.—Oscar M. Brooks and Elisha J. Matteson, Janesville, Wis.

We claim, 1st, The inclined supports, e and h, when pivoted at opposite ends of the horizontal vokes, H, and used to support two parallel and similarly operating rolls, B B, substantially as described.

2d, The combination and arrangement of a treadle, F, pivoted at the ends of two horizontal yokes, H, with the connecting links, f and g, springs, i, inclined supports, e and h, and horizontal yokes, H, when the whole are constructed, arranged a d used substantily as described.

70,693.—WASHING MACHINE.—Alexander R. Campbell, Cheltenbur Mo.

tenham, Mo. I claim the rock shaft, e, semi-circular corrugated dasher, E, corrugated dash board, g, smooth desh board, h, shatts, k, cross bar, M, braces, n, cover, o, st indards, d, deve-tailed slots, q, and the corrugated circular and square ends of a washing machine, all in combination, when constructed and operating substantially as shown and specific. 1.

70,694.—Mode of ATTACHING FERRULES TO HANDLES.—Asa I. Carrier. Washington. D. C.

L. Carrier, Washington, D. C.
I claim the ier ule, b, constructed and applied to tool handles, umbrellas and canes, substantially as described and operating as and for the purposes

set forth.

70,695.—HORSE HAY FORK.—William Carroll, Hillsdale, Mich., assigner to himself and S. H. Rhodes, Clyde, Ohio.

I claim the toggle joint. E, springs, D, and nibs, I, in combination with the tubular shaft and rod, substactially as and for the purpose set forth.

70,696.—CAR TRUCK.—S. A. Chase (assignor to himself and Stephen Smith). Booton Mass.

Stephen Smith), Boston. Mass.

I claim, 1st, The combination with the main axles and wheels of a car truck of the upper rollers when supported in elongated bearings, substantially as and for the purposes described, 24, The combination with the journals, c c, of their elongated bearings and lubricating chambers, substantially in the manner and for the purposes set forth.

set forth.

70,697.—Journal Box for Cars.—G. H. Clemens, Baltimore, Md., assignor to himself and Henry A. Chadwick, Washington, D. C. I claim, 1st, The hollow box, E, having the blocks of wood arranged therein, said box being formed spherical on is upper surface to permit of its adjusting itself to the journal, as herein described.

2d, In combination with the box, E, constructed as described, I claim the case composed of the parts, G and H, constructed as set forth.

70,698.—CHAIR.—Harrison Cole, Cincinnati, Ohio.
Lelaim the three-legged chair standard, A in combination with the brace.

I claim the three-legged chair standard,  $\Lambda$ , in combination with the brace A, and the lags, C C C and C C C C, for attaching it to the floor and chair bottom, substantially as shown.

bottom, substantially as shown.

70,699.—Door And Window Fastener.—Washington J. Corthell and Philip Richards, Boston, Mass.

We claim the combination and arrangement of the knob and shank, d and e, the projection, f, a d the spring, h, with the bolt, b, constructed with its recess, e, moving back and forth in the case, a, substantially in the manner and for the purpose above set forth.

70,700.—HORSE HAY FORK.—J. S. Culver, Springport, N. Y.

70,700.—HORSE HAY FORK.—J. S. Culver, Springport, N. Y. I claim the attaching of shoulder pieces to the main stem of the hay elevating fork, substantially as and for the purpose deleribed.
70,701.—BRACKET FOR LAMPS.—Robert Devereux (assignor to himself and Bernard H. Muehle), Buffalo, N. Y. Iclaim the circular rim, A. having an opening, D, for the purpose and substantially as herein set forth and described.
70,702.—BLIND STAPLE.—Frank Douglas, Norwich, Conn. I claim as a new article of manufacture a blind staple of corrugated wire, as herein described.
70,703.—BLUING PAPER FOR LAUNDRY PURPOSES.—Theodore Dreidel, Cincinnati, Ohio.
I claim the prepared bluing paper for laundry purposes, substantially as set forth.

(10,704.—Mode of Producing Hydrogen Gas.—Cyprier Marie Eessié Du Motay and Charles Raphael Ma. échal, Metz, France. We claim the method of and means for producing or generating hydrogen as, substantially as herein set forth and described.

gas, substantially as herein set forth and described.
70,705.—Mode of Producing Oxygen Gas.—Cyprier Marie Eessié Du Motay and Charles Raphael Maréchal, Metz, Franco. We claim the method of and means for obtaining oxygen gas from atmospheric air, substantially as and for the purposes herein set forth and described.

70,706.—Cloth-folding Machine.—Henry Dunphy, New York city.
I claim, 1st, The arrangement for holding the folders in the machine consisting of the clamps, c, in combination with the cheeks a a, of the holders, B, the whole constructed and operating substantially as described and spec

11led. 2d, The rollers, F.F., provided with narrow rings of leather, rubber, of other similar material, in combination with the folding apparatus, substan

other similar material, in combination with the folding apparatus, substantially as described and specified.

3d, The hinged ironer, D, in combination with the folding apparatus, substantially as described and specified.

4th. The laterally and back-and-forward adjusting, retaining, and stretching apparatus consisting of the roller, n, bar, p, and traversing blocks, o and r, in combination with this apparatus, substantially as described and specified.

5th, The roller, n, tapering toward both ends for spreading and stretching the cioth in combination with the laterally and back-and forward adjusting mechanism and the folding apparatus, substantially as described and specified.

10.0707:—STEAM ENGINE.—Charles E. Emery, Brooklyn, N. Y. I claim, 1st, Lining the interior surfaces of the cylinders of engines operated by steam or heated gas with gias, porcelain, enamel, or equivalent substance, in manner substantially as described to produce the results specified.

ded. 2d, The combination of the cylinder. X, with the cylinder, N, or its equiv ent. 3d, The elongated piston, A, in combination with the lining or protecting

nal, xx.
The combination of the pipe, b, with the piston rod or trunk, all sub-ally as and for the purposes herein set forth. 70,708.—PAPER FILE.—William Fallon, Washington, D. C. I claim the combination of a folding extension back to file binders with flap in front, and india-rut ber strap with reinforce on each end and clasps for same, as described herein.

same, as described herein.
70,709.—SALT SIFTER.—William A. Fenn, Wolcott, N. Y.
1 claim, 1st, The araangement of the plate, C, in combination with the
botile or case, A so as to operate in the manner described.
2d, In combination with the above, I claim the arrangement of a spring so
as to return the place, substantially as herein set forth.
70,710.—MOLDS FOR CASTING STEEL INGOTS.—John E. Fry,

Johnstown, Pa.
I claim the series of iron ingot molds, e.e., in combination with the sand ore, a, constructed substantially as hereinbefore described for the purpose core, a constructed substantially as hereinbefore described for the purpose set forth.

70,711.—Belt Cutter.—Moses C. Goodale (assignor to him-

40, 11.—BELT OUTTER.—MOSES C. GOOGAIC (ASSIGNOR to Inim-self and Louis Godder), Lowell, Mass.
I claim the arm, f, whin its punch seat, h, when arranged to operate sub-stantially as described and fully set forth.
Also the arrangeme t and construction of the knife, b, awl, n, and punch, e, in combination with the pliers, k and m, all for the purposes substantially as herein described.

12.—APPARATUS FOR BURNING HYDROCARRON OILS.—athew T. Gosnell. Baltimore MA Mathew T. Gosnell, Baltimore, Md.

I claim the combination and arrangement of a tube or pipes B B, a perforated hearth, B, a valve or valves or inlets (for admission of atmospheric air), D D. with a boiler, A, and furnace, E, or their equivalents, in the manner and for the purposes set forth.

70,713.—DEVICE FOR THE ADJUSTMENT OF LOOKING GLASSES.

N. Deresting Cases.—Alfred A. Gray and William C. Hyde, Detroit, Mich. W. claim the hinge and movable hinge plate, the thumb screw, or screw that secures the hinge plate, and the mode of adjustment, substantially as and for the purpose set forth.

70,714.—Sash FASTENER.—E. Herbster (assignor to himself,

70,714.—Sash Fastener.—E. Herbster (assignor to himself, T. Tripp and E. F. Brown), Chicago, Ill.

I claim, ist, The combination of wheel, D, having holes, b b etc., with pin, E, arranged to operate in sleeve, F, having slots, h and n, for the purpose of locking sash, substantially as herein set forth.

2d, The combination of wheel, D, spring, C, pin, E, sleeve, F' and key, T arranged to wind said spring up and to fasten sash, substantially as and for the purpose set forth.

70,715.—PAPER-RULING MACHINE.—William O. Hickok, Harrisburg, Pa.

I claim the application thereto of a stationary table, G, so that it will operate in combination with the web, E, cords, F, and feed rolls, D D', substantially in the manner described and set forth for the purpose specified.

70,716 —Wrapper for Needles.—Jason Hill, Astwood,

near Redditch, England.
I claim, in combination with a wrapper in or on which needles are placed or stuck, an incision or flap at or near the upper left hand corner for forming a cover for and for gaining access to the tops of the needles, substantially as and fer the purpose described.

70,717.-CLUTCH FOR HAY ELEVATORS.-N. D. Hinman,

70,717.—CLUTCH FOR HAY EMENATORS.—IT. E. Manday, Stepney Depot, Conn.
I claim, 1st, The arrangement described of the levers, L and N, with the yoke, R, and quiley, E, when constructed so as to operate in the manner and for the purpose substantially as set forth.

2d, The combination of the levers L M and N, when constructed so as to operate as and for the purpose specified.

70,718.—POCKET CUTLERY.—Peter S. Hoe, New York city.
I claim the combination, in a single instrument, of a knife, pincers and

bodkin arranged to open and shut like a pocket knife, substantially as described and specified.
70,719.—SCRAPER.—William J. Horner, Cincinnati, Ohio.

70,719.—SCRAPER.—William J. Horner, Cincinnati, Ohio. I claim, in combination with the divided and hinged beam, A B C, shovel, D, and handles, E, the tongue, F, self-locking catch, G, and trigger, L, substantially as and for the purposes set forth.

70,720.—HAY OR COTTON PRESS.—Frank Horton (assignor to himself and Albert Horton), Silver Creek, N. Y.

I claim, 1st, Attaching the draft chains, C, to the follower, R, at points inside of the press frame, A' (the sides of the press box being slotted longitudinally for the passage of the chains) for the purpose described.

2d, Leading the raft chains, C, when placed within the press box over the sheaves, C', and obliquely to or nearly to the center of the windlass shaft, D, in the manner and for the purpose described.

3d, The locking device applied to the top covers, F and G, and side door, I, composed of the lever, H, hinged loop, hI, and staple or hook, h2, substantially as described.

70,721.—MODE OF PREVENTING THE EXPLOSION OF LAMPS.

70,721.—Mode of Preventing the Explosion of Lamps.

70,721.—MODE OF PREVENTING THE EXPLOSION OF LAMPS.—Edward Howard, Redhill, England,
Iclaim the application of the long tube. A, before named and the substitution for the usual openings of a groove in the collar of the vase, C, so that by no opening can the flame of the lamp reach the gas in the vase.
70,722.—INVALID BEDSTEAD.—S. P. Johnson (assignor to himself an 1 Charles B. Whittemore), Portland, Me.
I claim, 1st, The double-swinging lever, g, as and for the purposes set forth.
2d, The arrangement of the folding legs, 1 2 3, etc., having the pins on their inner sides, with the folding braces having the longitudinal and transverse slots, as and for the purposes described.
3d, The arrangement and combination of the rod, k, lever, j, ratchet, n, and pin, m, as and for the purposes set forth.
70,723.—CORN-POPPER.—Edward G. Kinsley, Stoughton, Mass.

Mass.
I claim the corn-popper, as made with the perforated divisional partition, a, extended a cross its box, A, of woven Wire, substantially as described, and as the purpose as energited.

for the purpose as specified. 70,724. — WATCH ESCAPEMEN'T.—William . H. Lamb, San Francisco, Cal.

I claim, Ist, The construction of an escapement for timepieces, in such a manoer as to pass the teeth upon opposite sides of the balance staff, thereby giving an impulse on both the right and left vibration, substantially as herein described.

2d Trubed to be the construction of the const

giving an impulse on both the right and left vibration, substantially as here-in described.

2d, Unlocking pin, g, from the teeth, n, of the escape wheel, by the the lib-erating pin, on the balance staff coming in contact with the end of the detent lever, d, substantially as described; and,

3d, The combination of the wheels, D and E, operating on each, side of the balance staff by means of the noticed rollers, b and c, or their equivalent, and the liberating pin, i, operating on the end of the detent lever, d, and the the pin, g, the whole operating as and for the purpose herein specified and described.

-Churn.-C. H. Lee, Oskaloosa, Iowa.

I claim the churn, A, provided with a turret. in combination with a mouth piece, B, so constructed as to admit a free circulation of air in the churn, and at the same time prevent the cream from escaping, substantially as herein set forth and described. -BLIND FASTENING.—Goodrich Lightfoot (assignor to 70,726.

Aug. 20.—DLIND FASIERING.—Gooding In Inglithout (assigned to himself and Joseph B. Lighthoot), Elgin, Ill. I claim the jointed rot, L, in combination with hinges, e and e", when con-structed and operated substantially in the manner and for the purpose speci-

70.727.—Insulator for Lightning-rods.—Thomas J. Lockhart and Josiah Looke, Pittsburg, Pa.
We claim the application to lightning rod insulators of the metallic shank, c, as herein described, or any other substantially the same, and which will roduce the intend of effect.

produce the intend d effect.
70,728.—Saw.—James K. Lockwood, Alpena, Mich.
1 claim a circular saw, constructed with more or less slots, D, upon radial lines from the eye toward the periphery, and terminating in holes, C, in combination with the obloag holes or s.ots, E, for the purposes substantially as set forth.

set forth. 70,729.—CAR COUPLING.—Samuel L. Loomis, Byron, N. Y. 70,729.—CAR COUPLING.—Samuel L. Loomis, Byron, N. Y. Claim, in a draw-head or bumper of a railroad car, a spring so constructed and arranged as to serve the purposes of sustaining the pin until the link enters, and holding the link horizontal for the purpose of coupling, substantially as described.

And, in combination with a spring constructed and arranged as above claimed, I claim a coupling-pin with a shouldered end or point, as and for the purposes set forth.

And, in combination with a pin having a shoulder near the point, I claim a projection or plate, H, in the bumper or draw-head.

70,730.—HARVESTER.—Charles W. Marsh and William W. Marsh, Shahbona, Ill.

Marsh, Shabbona, Ill.

We claim, 1st, Ine arran ement of the several pulleys, C. E., and G. with tightening or adjustable pulley, D., so that drive-belt, H. may give motion to both drums, K and L., of band of rakes, M, and revolving platform, N, substantially as and for the purpose described.

2d, We claim the adjustable pulley, D, on slide, d, working in groove in platform addegatibed.

plate, f, as described.

3d, We claim the adjustable frame, A, when used in connection with the tightening or adjustable pulley, D, substantially as and for the purpose specified. 70 731.—Railroad Track.—Henry McCan, Hanover, Ohio.

I claim the construction and arrangement of the base and tread rails, A B, in combination with the chairs and ties, D E, and adjusting bolts, F, in the manner substantially as set forth.

70,732.—Mode of Obtaining Motive Power from Petro-

LEUM AND OTHER OILS—Robert D. McCreary, Oil City, Pa.
I claim, ist, The process herein described of producing motive power from oil without wholly destroying its lubricating or Illuminating properties, or its value for refining or for other purposes.
2d, I further claim the combined process of partially evaporating oil to obtain motive power, without destroying its valuable properties, and using the resultant gages for intel or illumination after their expansive force has been or partially so spent in driving the engine.

or partially so spent in driving the engine.

70,733.—Pump.—John H. McGowan, and Theodore H. McGowan, Cincinnati, Ohio.

We claim a suction pipe coupling, E E', in connection with a pump cylinder or cylinders A, so constructed as that, when attached to the pump, it will form a reservoir, which will maintain a constant supply of water, and in which the pump cylinder is partly or wholly submerged, substantially as described, and for the purpose specified.

70,734.—Cowl or Chimney Cap.—Charles G. Miller, Cincinnati, Ohio.

nati, Ohio. I claim the parts, B D E F II I, upon the top of a chimney, arranged substantially as described. 70,735.—DROPPER FOR HARVESTERS.—Lewis Miller, Akron.

Ohio.

I claim, 1st, An apron for holding the falling grain, that is wound up and unwound by a traveling roller, and rack and pinion attachments, substantially as described.

2d, Also, in combination with a traveling roller, and an apron wound up and unwound by it, a holding bar or board, that is thrown into and out of action by the roller, substantially as and for the purpose described.

70,736.—FAN-BLOWER.—Warren P. Miller, San Francisco,

Cal.

I claim a blower, consisting of two or more wheels, constructed and operated in manner as described.

Cal.

I claim a blower, consisting of two or more wheels, constructed and operated in manner as described.

70,737.—PRESERVATIVE BLACKING FOR LEATHER.—William

B. Moore, Winchester, Mo.

1 claim a blacking and leather preservative, composed of the ingredients hereinbefore named, and compounded in the manner and in the proportions substantially as described.

70,738.—MACHINE FOR SETTING UP STAVES IN BARRELS.—

James A. Morrell, Chicago, Ill.

I claim, 1st, The buttons, c, provided with the springs, e, substantially as and for the purposes specified.

3d, The adjustable truss-hoop supporter, D E, constructed and operating substantially as set forth.

3d, The hoop or band, C, for keeping in place and supporting the lower ends of the staves, substantially as specified.

4th, The lock or stop, a, for holding the truss hoop supporters in place, substantially as described.

5th, The standard or cylinder, A, base, B, and buttons, c, in combination with the truss supports, D E, and truss-hoop, F, substantially as and for the purposes specified.

70.730.—I.AND ROLLER.—E. F. Olds, Lyon, Mich.

purposes specified. 70,739.—LAND ROLLER—E. F. Olds, Lyon, Mich.

70,739.—LAND ROLLER—E. F. Olds, LyOn, MICH.
I claim, 1st. Hanging the rollers by means of their shafts or gudgeons to a
central adjusting frame, so constructed and arranged that said rollers may
be weighted more or less on either side by means of said frame, and the rollers rendered self-adjustable to the surface of the ground, as and for the purpose substantially as set forth.
2d, The central adjustable frame, E, constructed so as to be weighted, in
combination with the rollers, B, substantially as and for the purpose set
forth.

orth. 3d, The caster-wheels, L, and springs, M, in combination with the frame 3, and rollers, substantially as and for the purpose set forth.

70,740.—Flask for Casting Tweers.—Beneville C. Painter, Mechanicsburg, Pa. 1 ct aim, lst. In combination with the sections, AB, of the flask, the partitions, I K, and false or removable bottom, D, arranged as and for the purpose

escribed. 2d, Also, in combination with the previously made tube, G, the ferrule, c. nd slide, F, in the section, B, for the purpose of molding In the tube, and emoving the finished casting from the flask, substantially as described. 70,741.—LIGHTNING CONDUCTOR.—William G. Pike, Phila

10,741.—In HTMING CONDUCTOR.—WITHIRM G. TIRE, I mindelphia, Pa.

I claim, 1st. A lightning conductor, consisting of a cylindrical or flattened tube or gasket of woven, praided, or plaited wire, terminated at its upper end by a solid point, substantially as shown and described.

2d, The angular rod, e, for connecting separate branches of the tubular conductor, constructed substantially as set forth.

3d, The combination of the wire tube, a, solid point, b, inserted rod, c, and insulators, d, arranged and constructed in the manner and for the purpose substantially as set forth.

20,749.

Marrange and County Depunys County Name Lorent P. Pitch. 70,742.—MIXING AND DRYING CYLINDER.—Leman B. Pitch-

(0), (42.—MIXING ARE CALLED CONTROL OF THE CONTROL OF T

70,743.—STEAM ENGINE CUT-OFF.—George W. Rawson, Cambridgeport, assignor to himself and Michael Hittinger, Somerville, Mass. I claim the combination of the slide valve, the two gates, their openings

and mechanisms, substantially as described, for operating such gates in manner as specined.

I also claim thesaid mechanism or combination, substantially as described, for operating the gates of the slide valve through the agency of a governor, and the mechanism for producing the longitudinal movements of the slide valve, such mechanism or combination inst mentioned consisting of the tripper, p the notched slide bars, g g, the pawls or catches, m m, the springs, k k, the arm; if, and the stude, r s, the whole being arranged a displied to the sleam cliest and the slide valve, substantially in manner and so as to operate as hereinbefore specified.

70,744.—HARVESTER.—George Riemer, Fayette, N. Y. I claim the combination with the slide bar, H, and grooved wheel, G, provided with the rim, a, and made removable from its staft, of the friction roller, I, arranged and operating in the manner and for the purpose herein

70,745.—Bridle Bit.—A. H. Rockwell, Harpersville, N. Y.

I claim, 1st, The mouthpiece, A, when composed of three links, de, and e', and when combined with the sliding ba's, ff', and with the rings, g g', or their equivalents, all made and operating substantially as herein shown and their equivalents, all made and operating successived.

2d. The bars, f and f', when made to slide on a flexible mouthpiece, when connected with the nose strap, B, and when made and operating substantially as and for the purpose herein shown and described.

70,746.—Steam Generator.—Robert E. Rogers, and James Blood Philadelphia. Pa.

70,746.—NTEAM GENERATOR.—1.000.

Black, Philadelphia, Pa.
We claim the boiler, A, having the enlargement, a, formed so as to project at or about a right angle with the body of the boiler, in combination with the circulating tubes, B, when the upper ends of said tubes are inserted straight into the enlargement, a, and the lower ends of said tubes are bent and inserted into the lower portion of the body of the boiler, A, substantially

70,747.—HAND CORN PLANTER.—McCollum Russell and Al-

70,747.—HAND CORN PLANTER.—McCollum Russell and Alfred G. Burdick, Mill Rock, Iowa.
We claim, 1st, The plunger, E. provided with a pocket, e, regulating slide, J, and metallic end. K, in combination with the opening in the bottom, D, of the seed chamber, brush, d, and sp. ings or scrapers, B B C C, suostantially as and for the purpose set forth.

2d, The cell or pocket, e, in combination with the regulating slide, J, and brush, d, substantially as and for the purpose described.

3d, The combination and arrangement of the stop, 1, strap, H, pin, h', button, L, and plunger, E, substantially as and for the purpose specified.

70,748.—Construction of Butt Hinges.—D. C. Sage, Mid-

70,748.—UONSTRUUTION OF LOCAL detown, Conn.
I claim 1st, The attachment of butt hinges to door casings and doors by means of hooks and plates, substantially as described.
2d, The construction of the leaves of hinges with hooks, a a, or their equivalents, upon them, for being received by perforated plates, B, substantially as described.

alents, upon them, for demg received by periodic a place, B. saturday as described.

3d, The washers, d, of hardened metal, and detached from the pintle of the hinge, applied in recesses at the joints of the hinge, substantially in the manner and for the purpose described.

70,749.—COAT AND HAT HOOK.—J. B. Sargent, New Haven,

Conn.
I claim a contand hat hook, consisting of the plate, C, and hook or hook, A or B, or oth, on which the knob, D, is secured by a rivet or screw passing therethrough, in the manner described.

70,750.—SNAP HOOK.—J. B. Sargent, New Haven, Conn.
I claim. ist, The double tongue, D, in combination with the hook, A, when constructed so as to operate substantially as described.

2d, The thumb-piece, E, in combination with the tongue, D, of a snap hook, so as to lock and secure the snap when closed.

So as to lock and secure the snap when closed.

70,751.—Saw Set.—Amos M. Shafer, Camden, Ohio.

I claim, 1st, The screw standard, H h, and hand nut, I, in combination with the spring, F, constructed and operating substantially as and for the purpose set forth. set torth. 2d, Preserving the parallelism of the sliding rest, P, with the anvil, and at the same time changing its relative hight with said anvil, by sliding the inclined edge of the said rest in brackets, M O Q M' O' Q', substantially as described

ceribed.

70,752.—Cog Chain.—Thos. Shaw, Philadelphia, Pa. 1 claim the chain link, as constructed, for the purpose specified.

70,753.—Corn Planter.—William H. Shepherd, College

70,753.—Corn Planter.—William H. Shepherd, College Corner, Ohio.

I claim, 1st, The grain-dropping frame consisting of the cross beam, I, and grain slides, JJ, arranged substantially as shown.

2d, The blocks, O, to inducate the position of the fills, as set forth.

3d, The provision of side beams, FF, pin, f, slot, i', and screw, e, for the purpose stated.

4th, The provision for liberating the hinged piece, L'allowing of the spouts M, to swing clear of the ground, as stated, and for the purpose set forth.

5th, The arrangement of the parts, h'h''', for the purpose set forth.

70,754.—Mode of Separating Vegetable Matter From Animal Fibers.—Henry Sherwood, London, Great Britain.

I claim, 1st, To disaggregate vegetable fibers or substances by means of their exposure to gaseous sulphuric anhydride, and to anhydrous chlorohydric gas, each used alone or together, or in mixture with other eases not being the elements of water; but I do not claim the use of vapors produced by evaporating the sulphuric or muriatic acids of commerce, except the oxygen of the aqueous particles contained in those vapors be first eliminated, or caused to enter into chemical combination with some other clement to form an oxide.

2d. I claim. In an instrument necessary for making use of gaseous agents,

of the aqueous particles contained and conta

70,755.—Machine for Tempering Files, Saw Blades, and

OTHER ARTICLES. John Small, St. Louis, Mo.
I claim, 1st, in a machine which is adapted for tempering files or plates and confluing them between clamps during the tempering process, constructing the box containing said clamps wholly or partly of glass, substantially as described

the box containing said clamps wholly or partly of glass, substantially as described.

2d. The construction of the grated clamps, D D' with bracing ribs upon their backs, in combination with double-acting screw shafts for moving these clamps, substantially as described.

3d, The arrangement of the clamps, D D', in inclined planes within a bath or box, A, and upon double-acting screw shafts, E, operated and operating substantially as described.

4th, The hinged plate or apron, J, applied to the jaw, D, in combination with movable nooked rods, g, substantially as described.

5th, The standard, H, provided with pulleys, hiv, upon its upper end, over which ropes or chains pass, which are attached to the hinged apron, J, and also to the cross head of hooked rods, g, substantially as described.

70,756.—SPRING ROCKINGCHAIR.—Edmund Smith, Jr., Worcester, assignor to Albert Goodspeed, Hubbardston, Mass.

1c alm, in combination with the irame and seat of a chair, the springs, a a' a', with their opposite ends fastened respectively towards the front and rear of the chair, all arranged and combined substantially in the manne: and for the purposes above set forth and described.

70,757.—STEAM GENERATOR.—Jas. T. Smith and John Walter, Baltimore, Md.

70,757.—STEAM GENERATOR.—Jas. T. Smith and John Walter, Baltimore, Md.
We claim, Ist, The interior series of boilers, A, connected with tubes, n, and supplied with caps, s, at each end, the whole constructed and operating substantially as set forth.
2d, The mud-silis, E, pibes, H, in combination with the outside tier of boilers, A, operating as and for the purpose substantially as herein described.
3d, The gooseneck branch pipes, L, in combination with the central tier of boilers, A, constructed as and for the purpose substantially as set forth.
70,758.—Low-water Indicator.—L. Franklin Smith, Philadelphia Pa

70,758.—LOW-WATER INDICATOR.—L. FIGHERM.
delphia, Pa.
I claim, 1st, I'he arragement of the water gage, O, chambers, P and P', and
three-way cocks, M and Q, in relation to the boller, and with reference to the
expanding tube, C, and fixed rod, G, substantially as described and for the
purposes specified.
2d, The arrangement of the weight, N with the lever, H, and arm, h, for
closing the valve, K, substantially as described.
70,759.—CASKET HANDLE.—William M. Smith (assignor to

10, 19.—CASKET IANDLE.—WIHRAM M. SMITH (ASSIGNOT to himself and the Meriden Britannia Company), west Meriden, Conn. I claim the employment of attachments, D, or their equivalents, having tags, E, in combination with the depressions formed in the plates, B, substantially as and for the purpose described.

70, 760.—SASH STOP.—Henry Soggs, Columbus, Pa. Lelaim 1st. The combination and surveyence at of the pinjon. E, and winch

I claim, 1st, The combina tion and arrangement of the pinion, E, and winch, F, applied to the jamb, with the rack bar, D', and friction rollers, I', applied to the sash in the manner and for the purp se set forth.

2d. The spring cacch, G, in combination with the winch, and operating in the manner and for the purpose.

70,761.—PROCESS OF PREVENTING DECAY IN WOOD.—J. H.

Taylor, New York city.

I claim, ist. The chemical combinations of the above-named agents, in the manner described, for the purpose of preserving wood and other fibrous materials from decay.

2d. The combination of these potent antiseptics in the form of vapor, acting in accordance with known chemical laws, in the manner and for the purpose described.

—GATE.—G. L. Templeton, Pierceton, Ind.

I claim the cam, H, made of round wire, or similar material, and secured to the inner wing, E, in combination with the outer slotted wing, F, roller, I, gate, A, and frame, B, having a slot, J', arranged and oper aing substantially as and for the purposes set forth.

as and for the purposes set forth.

70,763.—CARRIAGE JACK.—Isaac Varney, Kenebunk, Me. I claim the arrangement and combination of the arm. D, toothed slide, C, gear, b, casing, a, centrally-pivoted pawl, e, and spring pawl, tr.on the nollow cylinder, B, substantially as and for the purposes set forth.

70,764.—WELL TUBE.—Joseph Wagner, Newcastle, Pa.

I claim, 1st, The perforated stem, C, of the point, b, encased within the tube, A, in combination with the slot, a, and pin, b, substantially as and for the purpose described.

2d, the combination of the point, B, constructed as described, with the perforated stem, C, perforated tube, A, slot, a, and pin, b, substantially as and for the purposes described.

70,765.—Follynatin Pen.—Michael Wagner (assigner to him.

70,765.—FOUNTAIN PEN.—Michael Wagner (assignor to himself and Herman Witte), Cincinnati, O. Talaim the winged bristle socket, J K, sheath, C D F, scallops, &, slot, L, and stud, H, slot, G, combined, arranged, and operating as and for the pur-

pose specified.
70,766.—MANGLE.—H. Wehdeking, Edgerton, O.
1 claim, 1st, Tightening the linen bed and shortening the same, by the ar

with the stationary arms, Bosoberanan, In the stationary arms, Bosoberanan, In and shown.

2d, The construction and arrangement of the legs or lower part of the mangle, in combination with the rods, i, i, substantially in the manner and for the purpose as aerein described and shown.

3d, The arrangement of the wooden spring, J, rubber springs, I I, rods, i i, rollers, F and H, in combination with the arms, A a A A, and arms, B B, and the legs of the mangle, substantially in the manner and for the purpose as herein described and shown.

70,767.—Composition for Inking Rollers and Pads.—J.

M Wilder Cleveland. O.

70,767.—COMPOSITION FOR INKING ROLLERS AND M. Wilbur, Cleveland, O.

I claim the composition for ink rollers or pads consisting of the ingredients in about the proportions herein given, as and for the purpose specined.

70,768.—HOBSE POWER.—Wm. H. Wiley, Fredonia, N. Y.

I claim, 1st, Extending the frame of the machine laterally across and beyond the circular track travelled by the horses, and providing the same with sildes for the reception of a drag saw cross head and with bed pieces for the horizontal shaft pillow blocks, in the manner and for the purposes described.

2d, Securing the pinion spindles, D, to the table, C, at varying distances from the center thereof, so that different sizes of pinions to gear with cogrim, F, and spur wheels to gear with pinion, b', may be used, as and for the purpose set forth.

70.769.—EGG STAND AND BOILER.—Edward P. Woods and

Daniel Sherwood (assignor to Woods, Sherwood & Co.,) Lowell, Mass. We claim, as a new article of manufacture, an egg stand and boiler, contructed substantially as described and for the purposes specified. 70,770.—MACHINE FOR MAKING WIRE DISH STANDS, ETC.—

Edward P. Woods and Daniel Sherwood, (assignors to Woods, Sherwood & Co.,) Lowell, Mass.
We claim, 1st, The spiral grooved head or former constructed substantially

we claim, ist, the spiral grooved head or former, constructed substantially as described and specified.

2d, The combination of the spiral grooved head or former with the bar, G, substantially as described and specified.

3d, The combination, with the spiral grooved head or former, of the slots, cc c c, substantially as described and specified.

70,771.—MORTISING MACHINE.—Charles L. Zeidler, Cincin-

c c c c, substantially as described and specified.

70,771.—Mortising Machine.—Charles L. Zeidler, Cincinnati, Ohio.

I claim, 1st, The arrangement of continuously vibrated bell crank, D, having the arm, G, and wrist, g, connected on one side by pitman, H. to the chisel bar, and on the other side to a wrist, K, actuated by an obliquely slotted slide, L, under control of the operator, constructed and operating substantially as and for the purpose set forth.

2d, The arrangement of fast and loose sleeves, Q and R, upon the chiselshaft or stem, engaging and releasing pawls or catches, S and T, cord, U, and pulley, V, in combination with the catch or trigger, H, and tappet, I', rack and pinion, v'l, and actuating and balancing springs, W and N, constructed and operating substantially as and for the purpose set forth.

70,772.—DITCHING Machine.—Isaac V. Adair (assignor to himself and Peter Wyckoff,) Varick, N, Y.

I claim, 1st, The arrangement of the wheels. A, axles, B, frame, C, pulley, B', band, A', endless chain of buckets, U, frame, S, adjustable brace bars, C' and D, and frame, F, with each other, substantially as herein shown and described and for the purpose set forth.

2d, The frames, F and C, when connected together by the adjustable bar, R, and draft chain, P, substantially as herein shown and described and for the purpose set forth.

70,773.—Prinyting Press.—Edwin Allen, Norwich, Conn.

I claim the combination of the adjustable or sliding taper rollers. L, with inking roll shaft, k, hung and controlled essentially as described, and disk, K, for operation together, substantially as and for the purpose or purposes herein set forth.

70,774.—Steam Engine.—Ernesto Ansaldi, Leghorn, Italy. 70,774.—STEAM ENGINE.—Ernesto Ansaldi, Leghorn, Italy. I claim the arrangement of the steam ports, passages, valves, and chests, as described, with the piston of two steam cylinders and their connections, to act in combination with each other, for the purpose of mutually assisting each other for overcoming the dead points of their strokes when accomplished by the means substantially as described and illustrated in the drawings. 70,775.—Belt Lacing.—Holland C. Babcock, Cincinnati, O. I claim the belt lacing provided with a pointed or stiffened tip, B or B', a slit, C, and secured for packing in a coiled form by tag, D, or its equivalent, substantially as and for the object stated. 70,776.—CAR COUPLING.—Peter Baker, Oakland, Md. I claim, 1st, The coupling pin, B, provided with the flange, e, in combination with the hinge, E, and lever, C, when arranged to operate substantially as herein described and for the purpose set forth. 2d. The draw head, A, when arranged to be adjusted vertically in combination with the frame, G, substantially as herein described. 70,777.—Elevator.—Jas. S. Baldwin, Newark, N. J. I claim, 1st, The use of the apron, B, and the apron, C, or equivalent yield-

70,777.—ELEVATOR.—Jas. S. Baldwin, Newark, N. J. I claim, 1st, The use of the apron, B, and the apron, C, or equivalent yielding edges, substantially as set forth.

2d, The secondary platform, F, and its apron, D.

3d, The balancing of said aprons in the manner set forth.

70,778.—ATTACHING BOLSTERS TO KNIVES.—Henry Barber, Greenfield, Mass.

I claim attaching the bolsters upon the tang by means of projections, a a' and b b', upon each side of the bolsters, the projections being clinched on the top and bottom sides of the tang, substantially as and for the purpose shown.

70,779.—Cultivator.—Morgan Barnett and Eli Wood, Har

70,779.—CULTIVATOR.—Morgan Barnett and Eli Wood, Hardinsburg, Ind.
We ciaim, 1st. The plough frames formed by the combination of the beams, G, standards, E, and adjustable brace bars, I, with each other, substantially in the manner herein shown and described and for the purpose set forth.
2d, Pivoting the beams, G, upon the forward side of the axle, B, by means of the rods or bolts, J, and clips, K, substantially as herein shown and described and for the purpose set forth.
3d, The combination of the locking keys, P, with the forward ends of the beams, G, and with the rods or bolts, J, substantially as herein shown and described and for the purpose set forth.
4th, The combination of the guide frames, M, with the beams, G, and rods or bolts, J and N, substantially as herein shown and described and for the purpose set forth.
5th, The combination of the levers, L, with the beams, G, and guide frames, M, substantially as herein shown and described and for the purpose set forth.
6th, The combination of the graduated stop-lever, O, with the beams, G, and guide frames, M, substantially as herein shown and described and for the purpose set forth.
70,780.—HAM-SLICING HOLDER.—John Baumgartner and

70,780.—HAM-SLICING HOLDER.—John Baumgartner and

Lawrence Angster, Newark N. J.
We claim the guard or arm. B. the brace, F. G. the lever, and rack, E. operating together in manner substantially as and for the purposes described and set forth. 70,781.—Seeding Machine.—R. Baxter, French Camp, Cal

I claim, ist, The seed box, constructed as described, and provided with a rod and prongs, so located that a part of the several prongs only is in the box, and that at the front side thereof, as and for the purpose described.

2d, The elbow lever, operated by a pin on the plow wheel and operating the rod with its prongs, in combination with the said rod, in the manner and for the object set forth. for the object set forth.
70,782.—Beehive.—James M. Beebe, Casadaga, N. Y.

I claim the series of frames, C C, constructed and bound together, as de scribed, when said frames are used within the casing, A B, formed, as here it set forth, with honey boxes, F F, space, bottom board, I, and openings, ed the whole constructed, arranged, and used in the manner and for the purpo ses set torth. 70,783.—Horseshoe.—Jacob Behel and John Perrine, Rock-

70,783.—HORSESHOE.—Jacob Behel and John Perrine, Rockford, and John M. Buell, Ogle county, III. We claim, 1st, The movable clips, at and a2, when constructed and attached substantially as set forth. 2d, The combination of the movable clips, a1 a2, and shoe, A, having bevelled rec:sses. x, to receive the same, substantially as described. 3d, The combination of the movable clips, a1 a2, and the shoe, A, constructed with corresponding recesses, x, and projections, c c, substantially as described.

scribed.
4th, The combination of the movable clips, a1 a2, and shoe, A, constructed with stationary clips, v, and projections, c and k, substantially as described.
70,784.—STEAM ENGINE SLIDE-VALVE.—E. H. Bellows, Wor-

cester, Mass.

1 claim, 1st, A four post balanced valve, E, constructed and operating substantially as and for the purposes set forth.

2d, The combination with the steam chest, A, having a projection or flange, c, of the valve, E, substantially as set forth.

2d, The combination with valve, E, of cap, H, and projections or flanges, c of fr and ears, e, substantially as and for the purposes set forth.

70,785.—CULTIVATORS.—Alfred C. Belt, Goresville, Va.

70,785.—CULTIVATORS.—Alfred C. Belt, Goresville, Va. I claim, 1st, The reversad arrangement of the alternate teeth of the cultivator, as described.

2d. The cultivator teeth arranged in reversed positions, as described, in combination with the adjustable colter.

3d. The grooved or recessed beam, in combination with the flanged teeth secured theoretic accombination.

combination with the adjustable colter.

3d. The grooved or recessed beam, in combination with the flanged teeth secured thereto, as described.

4th. The forward tooth, provided with the perforated sifter mold board, in combination with a following tooth having the reversed arrangement described, for the purpose set forth.

70,786.—POTATO PLANTERS.—John E. Bendix, New York city, and Morris Dietsch, Westchester, N. Y.

We claim, 1st, A carrier wheel, C, provided at its circumference with cups or buckets, d, in combination with a suitable hopper and tubular seeding stock, substantially as and for the purpose specified.

2d. The lever, J, and vertical holding post, K, arranged and operating in relation with each other, and with the sliding bar, G, of the covering blade, substantially as and for the purpose specified.

3d. The sliding bearing, f, arranged in relation with the shaft which carries the cupped or bucketed carrier wheel or wheels, C, and the gearing connecting the said shaft with the driving axle, whereby the movement of the carrier wheel or wheels, with reference to the hopper and seeding stocks, may be stopped without interfering with the progressive motion of the machine, substantially as herein set forth.

70.787.—A DJUSTABLE WATCH KEYS.—J. S. Birch. New York

70,787.—Adjustable Watch Keys.—J. S. Birch, New York

city.

I claim, 1st, Slitting the barrel, A, of a watch key, diagonally, substantially as herein shown and described, and for the purpose set forth.

2d, Forming the lower part of the barrel, A, cone or pyramid shaped, that is to say, decreasing in size towards the shank or stem, a, substantially as herein shown and described, and for the purpose set forth.

3d, The combination of the sleeve or slide, B, and nut, C, one or both, and whether made in one or two pieces, with the slit barrel, A, of the watch key, substantially as herein shows and described, and for the purpose set forth.

70,738.—Grinding Machine for Circular Saws.—Thos. Birch, covington, Ky., and Adam Sowden, Cincinnati, Ohio, assigners to Riuser, Hogan and Sowden, Cincinnati, Ohio, assigners to We claim, 1st, The provision, in a machine for grinding circular saws, of a

pair of driving friction pulleys, adapted to grasp the saw at a shifting point diametrically opposite, or nearly so, to the point of impact of the grindstone, and having a corresponding approach toward and recession from the saw's center in the act of crinding, substantially as and for the purpose set forth.

2d, The arrangement of the saw carriage and driving pulley carriage, caused to automati ally advance and rece d with une qal velocities in paths parallel to the grindstone's axis, for the purpose explained.

3d, The arrangement of the paired iriction driving pulleys, Z Z', made to grasp the saw on epposite sides thereof by means of pressing springs, b b', and set screws, c c', for the purpose set forth.

4th, In combination with the said friction driving pulleys and accessories, we claim the arrangement of travelling gearing and shaft, Y Y', e e e', and stationary gearing, e'', as represented.

70,789.—BARREL COVER — Calvin Bird, Dorchester, Mass. I claim the combination of the flush handle with the strengthening cleat

I claim the combination of the flush handle with the strengthening clean and guard plate substantially as described.

10,790.—SETTING STEAM BOILERS.—C. T. Boardman, Paw-

70,790.—SETTING STEAM BOILERS.—U. 1. DOBTUING, I am tucket, R. I.

1 Claim in combination with the cylindrical boilers, B. B. tubular boiler, G. and walls, A. of a setting, the pler, H., and horizontal partitions. J. J., arranged substantially as specified.

70,791.—GALVANIC BATTERIES.—Charles Boulay (assignor to Jean David Schneiter), Paris, France.

1 claim putting each of the electro motive metals of each element in direct contact with any suitable exciting matters or mixtures of them in the dry or slightly moistened and more or less coarsely pulverized state, which exciting matters or mixtures of them are to act on their respective electro motive metals, or other electro motive bodies embedded in them, by attracting mosture from any suicable exciting liquid or solution, from which they are kept separate by a suitable porous partition or a diaphagm, substantially in the manner and for the purposes described, and illustrated in the annexed drawings.

HOWER MANNEY ANDRE — Robert BOVG. EVansville,

70,792.—House Ventilators.—Robert Boyd, Evansville

Ind.
Iclam, 1st, A ventilator so constructed that pure air may pass into the room, and foul or impure air may be passed therefron, substantially in the manner herein shown and described.
2d, The onter cylinder, B, with the openings, G, H and J, and the frame, A, combined and arranged substantially as described.
3d, The inner cylinder, C, or its equivalent, arranged and operating substantially as and for the purpose set forth.

stantially as and for the purpose set forth.

70,793.—RAILWAY-AXLE BOX.—C.B. Boynton, St. Paul, Minn.
I claim the arrangement and combination of the rubber, A, under the washer of bolt, B, the inside construction of cover, C, also the flange, E, fitting on to the shouldes at the top of box, D, as herein described and for the purpose set forth.

purpose set forth.
70,794.—GATE LATCH.—Mark J. Briar, Oxford, Ind. roper Male Datch.—Right J. Brigh, Uxford, Ind. I claim a latch for gates, etc., composed of latch lever, I, link piece, K lever handle, L, grranged together substantially us and for the purpose described.

70,795.—Sash Fastener.—Geo. Brosius, Ranch's Gap, Pa. 1 claim the combination of the cam lever, D, spring, E, or its equivalent lover, F, arm, K, bolt, L, and cord, G, in the manner and for the purposes substantially as above set forth and described.

70,796.—APPARATUS FOR DRAWING TIRES FROM ENGINE-

Driving Wheels.—Wm. H. Bryant, Chicago, Ill. I claim the apparatus for drawing tire from wheels, herein described, constructed and operating substantially as her in set forth. 70,797.—CARRIAGE-TOP BUTTON HOLES.—S. A. Budd, Cleve-

70,797.—CARRIAGE-TOP BUTTON HOLES.—S. A. Dudu, Oreveland, O. I claim the combination of the spring, a, washers. A D. and disk or cap, C, with the curtain, substantially as and for the purpose set forth.
70,798.—HARVESTER.—John Burke, Sycamore, Ill.
I claim, 1st, The combination of slotted plates, F F', provided with notches attached to the front end of gear frame, A, with standard, D, provided with corresponding notches at back end of said gear frame, so that said gear frame may be thus raised or lowered equally at both ends, and parallel with main frame, substantially as set forth.
2d, 1 claim the combination of slotted plates with rachet, consisting of plates F F', and dogs, G G', substantially as described and for the purpose specified.

FF' and dogs, GG', substantially as described and for the purpose specified.

3d, I claim the dogs, GG', for the purpose specified.

70,799.—CAR AXLE.—Samuel S. Burt, Marquette, Mich.
I claim the yoke, D, in combination with the axle boxes, CC, axle, BB, and car wheels, AA, substantially as and for the purpose described.

70,800.—AIR ENGINES.—John R. Cameron, Pittsburg, Pa.
I claim, 1st. The combination of the vacuum chamber, A, and the hot air chamber, C, when constructed and arranged as described.

2d, The fire box, B, with its blast pipe, d, and the water cistern, E, in combination with the vacuum chamber, A, constructed and operating substantially as herein set forth.

3d, The inner lining, b', for the purpose of forming more rapidly a vacuum in A, and also the bellows, D, in combination with the vacuum chamber, A, substantially as herein described for the purpose specified.

70,801.—CREEPING ROBES FOR INFANTS.—M. M. Cashman, Boston, Mass.

Boston, Mass.
I claim forming a creeper, by uniting a skirt, A Ai Aii, with a wrapper, Aiv Aii Aii, authantially as shown and for the purpose set forth.
70,802.— ROTARY ENGINES.— Edwin Chapman, Rochester,

Minn.

I claim, ist, The arrangement of the steam chamber, e, aperture, g, and packing, r, with reference to the piston, D, and shaft, E, as herein described for the purp see specified.

2d, The construction of the piston, D, provided with the opening for discharging steam into the cylinder, and opening, f. for exhausting the steam through the shatt, substantially as herein shown and described.

through the shatt, substantially as herein shown and described.

70,803.—MOTOR FOR OPERATING SEWING MACHINES.—Wm.
Z. W. Chapman, New York city, H. C. Goodspeed, Plainfield, N. J., and Edwin Reed, Bath, Me.
We claim a sewing machine motor, in which is a barrel enclosing the coiled spring, the equalizing fly wheel, the train of gears, regulating cone pulleys, c. c', connected by a band which is operated by a sliding rack and pinton, all constructed and combined as described, and for the purpose set forth.

In like combination we claim the arrangement of the cover of the table, provided with an aperture, which while shut will expose the arm and plate, and when open will neither disturb the machine nor carry any part thereof with it.

-LEVELING ATTACHMENTS TO AGRICULTURAL IMPLE-

70,804.—LEVELING ATTACHMENTS TO AGRICULTURAL IMPLEMENTS MOUNTED ON WHEELS.—Benj. F. Cook, Olema, Cal.

I claim the application of a wheel, F, provided with a rim, a, bevelled so as to form inclined planes, and interposed between the rear axle and bolster of the machine, substantially as and for the purpose set forth.

I also claim the combination of the wheel, F, and the capstan or winch, H, substantially as and for the purpose specified.

I further claim the brake, e, arranged in relation with the drum, dx, of the capstan or winch, H, and connected to the lever, Gx, when said parts are used in combination with the wheel, F, for the purpose set forth.

70,805.—Roofing.—Geo. Cook, Paris, Ill.

I claim, 1st, Atile, B. of earthenware, stoneware, or other suitable material, having the parts, D E F G H, substantially as shown and described.

2d, In combination with the tile, B, I claim the cap, G, having a groove, g, as and for the purpose set forth.

3d, In combination with the tile, B, I claim the hasp, C c c', as and for the purpose stated.

purpose stated.

4th, In combination with the elements, DEFH. I claim the bead, I, and grooved comb, J, for the different sides of the roof peak, as and for the purpose set forth. SILENT BOLT FEEDER.—Jacob Cornwell, Kalama-

70,806.—SILENT DOLL FEEDER. 300. Mich.
200, Mich.
1 claim, 1st, The revolving platform, m, provided with scraper, f, in combination with the revolving platform, n, substantially in the manner set forth.
2d, in combination with the subject matter of the above, I claim lever, L, and band, s, substantially as described.
70,807.—Low WATER DETECTOR.—Clemoire F. Cosfeldt, Jr.,

70,807.—LOW WATER DETECTOR.—Clemoire F. Cosleidt, Jr., Philadelphia, Pa. 1 claim, 1st. The arrangement within the boiler of the valve seat, B, support, E, and the independent slotted valve, CD, having shank, b, and rod, d, as and for the purpose described.

2d, The regulating screw, d, one end protruding through the slot, c, and the other end resting on the support, E, substantially as and for the purpose described.

described.
70,808.—CLOTHES WRINGER.—E. Hall Covel, New York city

1 claim, 1st, The double slotted standards, A A, in combination with the onical box, N, and levers, H H, substantially as and for the purpose herein ecited. 2d. The double bail or semi-circular levers, H.H., jointed together, and form

ing thereby a fulcrum for each other, with the boxes, N, attached thereto, or cast theron, and having the springs and adjustable nut on the ends, as and for the purpose described.

the purpose described.

70,809.—APPARATUS FOR CARBURETING AIR.—William F. Cozzens and J. H. Jones (assignors to themselves and Leopold Bouvier), St. Louis, Mo.

We claim, 1st, The combination of the condensing or forcing apparatus, A, with the carbureter, B substantially as set forth.

20. The combination of the trays, B2 and B3, and the injection pipes, b5 and apertures b4, when arranged as and for the purposes set forth.

70,810.—CHEESE PRESS.—E. J. Crane, Laporte, Ind.
I claim the platform, A, the studs, B B' and C, the connecting bar, E, the levers, D D', the pressing stud. F, and the table, G, arranged, comoined and operating substantially as shown and described for the purposes herein set forth.

70,811.—Construction of Sheet Metal Boxes.—Martin H.

Crane (assignor to Crane, Breed & Co.), Cincinnati, O.
I claim the mode of stiffening and ornamenting vessels made of sheet metal by the use of composite ribs or mouldings of wood and metal, soldered to the exterior or interior surface of the vessel, substantially as set forth. 70.812.—VENTILATING DEVICE FOR RAILROAD CARS.—Wm.

G. Creamer, Brooklyn, N. Y.
I claim the construction and attachment of ventilating plates to the sides of railroad cars, to admit air and exclude rain and cinders, and present a flush surface, substantially as specified.

70,813.—BOAT HOISTING APPARATUS.—A. F. Crosman, Steam-

er Ossipes, U.S.N.
I claim, 1st, The drums, D.D., upon the shaft, E, secured to the side of the vessel between the davits, and provided with a rope, G, passing through the side of the vessel, all arranged as described, whereby the manipulations of the rope, G, operate the tackle ropes, a a, simultaneously, as herein shown and described.

2d. The arrangement of the links, J. K, shooks, L, ruetallic mousings, M, hooks, N, and vertically sliding bar, f, for detaching the boat from the tackle blocks, as herein shown and described.

70.814.—METHOD OF STARTING AND STOPPING CARS.—Alonzo

70,814.—METHOD OF STARTING AND STOPPING CARS.—Alonzo G. Crossman, Huntington, N. Y.
I claim, 1st, The cylinder, L, and piston, K, in combination with the wheels, D, E and F, and suitable connections, the whole operating in conjunction with the axle, G, substantially as set forth.
2d, The combination with the cylinder, L, piston, K, and wheels, D, E and F, of the clutches, a and b, substantially as and for the purpose specified.
3d, The combination, with the piston, K, and cylinder, L, of the rack, R spur wheel, S, and crank, T, substantially as and for the purpose set forth.
70,815.—FAUCET FOR STOVE RESERVOIRS.—John B. Crowley (assignor to himself and Chamberlain & Go.), Cincinnati, O.
1 claim, 1st, The provision, in a stove reservoir, or boiler, of the spout, B, having within the reservoir a plug or valve, D, whose stem extends and is operated above the top of the reservoir, substantially as and for the purpose set forth.
2d. The arrangement in a stove reservoir of the spout, B, having within the

operated above the top of the reservoir, substantially as and for the purpose set forth.

2d, The arrangement in a stove reservoir of the spout, B, having within the reservoir the upturned seat or inlet, C, and self-closing valve or plug, D, whose stem or handle extends through an orifice, e., in the reservoir lid, and is confined in lugs or guides, G H, substantially as set forth.

70,816.—CORN HARVESTER.—John P. Culp, Quincy, Ill.

I claim, 1st, The wheels. D E F H I I', the shipper, G, cutter, K, and reel, L, arranged as described, in combination with the sustaining wheels, B, and shaft, a, of a corn cutting machine, as set forth.

2d, The jointed arms, c c, in combination with the cutter, K, and reel, L, arranged and operating substantially as and for the purpose set forth.

3d, The combination of the latch, O, and the trap-falls, N N N', in the bed or a corn cutting machine, when arranged and operating substantially in the manner and for the purpose described.

4th, The roller, P, with its arm, i', and the latch, m, when combined with the frame and bed of a corn cutting machine, and arranged and operated substantially as and for the purpose set forth.

70,817.—Ash Sifter.—J. Warren Custer, Trappe, Pa.

I claim the arrangement of the wire sieve, D, having a wire around its circumference, when secured within a circular box, A, by means of the jaws, E E, formed in said box, and the spring, G, in the manner and for the purpose set forth.

70,818.—Sash Supporter and Fastener.—Amos Cutter

Sash Supporter and Fastener.—Amos Cutter,

East Boston, Mass.
I claim the combination of the arms carrying the rollers or wheels holder, f, and thumb screw, G, or its equivalent, substantially as and for the purpose described. 70.819.—Gates.—Orlean Doud (assignor to himself and Isaiah

Rowe), Dansylle, New York.

Rowe), Dansylle, New York.

I claim, 1st, The combination of the rail, A', with the pin, b, and post, B', with cap, a, and metal plate, C, with the gate, A, having a segmental bar, D, all constructed, arranged and operating in the manner and for the purposes set forth.

set forth.

2d. The latches, d.d., rod., i, lever, e, spring, g, used in connection with the gate, A, and post, B, with its pins, x.x., for the purposes set 1 oth.

70,820.—CAPSTANS.—Jacob Edson, Boston, Mass.

70,820.—CAPSTANS.—Jacob Edson, Boston, Mass.
I claim, 1st, Constructing the base of two cone-shaped disks, or shells, one of which is reversed so as it or give double bearings, B, and B'B', for the standard or spindle, H.
2d, The unguent receptacle at the top of the base, and surrounding the staneard or spindle, H, made substantially as and for the purpose set forth.
3d, The extending of the fleeting cleats above the joint which separates the head from the body of the capstan, substantially as described and for the purpose set forth.
4th. Combining with the body of the capstan the head and cap, N, made in one piece, substantially as and for the purpose set forth.
5th, In placing the upper bearing of the capstan in the top of the cap or head, N, substantially as and for the purpose set forth.
6th, The combination of the draining pipes, L L, with the receptacles, K K, substantially as described and for the purpose set forth.
70,821.—Wheel Barrow.—David B. Ellis, Ypsilanti, Mich. I claim the diagonal brace, bracing and strengthening both the body and legs of the barrow against lateral and perpendicular strain and pressure, substantially as described.
70,822.—Marble Shooter.—Wm, F, Falls, Boston, assignor

substantially as described.

70,822.—MARBLE SHOOTER.—Wm. F. Falls, Boston, assignor to Ira Steward, Millord, Mass.

I claim a marble shooter having its parts constructed and arranged to operate and adapted to the projection of marbles of varying size, substantially as set forth.

70,823.—Door Holder.—C. J. Fisher, Waukon, Iowa.

I claim the combination of the cam lever, E, frames or plates, B and C, and bumper, F, with each other, substantially as herein shown and described and for the purposes set torth.

70,824.—CROOK FOR MUSICAL INSTRUMENTS.—Isaac Fiske,

and for the purposes set forth.

70,824.—CROOK FOR MUSICAL INSTRUMENTS.—Isaac Fiske, Worcester, Mass.

I claim a crook for musical instruments made of one piece of metal and formed into shape substantially as set forth.

70,825.—WORK BOX.—James S. Fletcher, South Bend, Ind.

I claim a revolving or turning work box with apartments within it for containing sewing articles accessible as set forth, and constructed as described and represented, out of solid rings, C.c., as set forth and explained.

70,826.—COMPOSITION FOR COATING SHIPS' BOTTOMS.—Geo.

A. F. Fowke, Westminster, Great Britain.

I claim the composition, in its forms, I. II. and III., and in its application and use, as hereinbefore in this specification described, for the purpose of coating the bottoms of iron, and woo den ships, floating docks, and other similar structures and submarine works, and thereby preventing them from fouling and the ravages of the worm.

70,827.—SLEIGH BRAKE.—C. Gardiner, Esperance, N. Y.

I claim, 1st, The pawls, G. their upper ends wedge shaped and pivoted in the corresponding wedge-shaped mortice in the bent lever, E., whereby the pawl is permitted to yield to the beckward movement of the sleigh, all arranged and constructed as herein set forth for the purpose specified.

2d. The connecting rod, e. embracing the bar, A'; and the tongue, A', connected by the plin working in the slot in the tongue, its lower part extending to the neck yoke, all constructed and arranged as described, in such a manner that the length of the stock of the pawl, G, shall be coverned by the length of the slot in the tongue, as herein set forth for the purpose specified.

70,828.—RAILROAD GATE.—E. K. Gardiner, Orville, Ohio.

I claim the gates, D D, levers, m m and n n, arms, i i, and movable rails, C c, all combined substantially in the manner and for the purpose specified.

70,829.—CAR COUPLING.—Samuel Gissinger, Lawrenceville, Pa.

1 claim the pates of the part of the partice with the part of the purpose specified.

Pa. I claim the pivoted buffer, A, provided with link opening, O, pin opening, 2, plate, R, and locking pin, f, when used in combination with lever, g and r, chain, m, and springs, n and s, constructed, arranged, and operating substantially as herein described and for the purpose set forth.

70,830.—Tool Rest.—Wm. Gleason, Rochester, N. Y.

70,830.—Tool Rest.—Wm. Gleason, Rochester, N. Y.

1 claim, 1st, The employment of the triple screw system, substantially as heren set forth, for the purpose of adjusting vertically the cutting tool of engine lathes without loosening it.

2d, The arrangement of the eccentric clamping shaft, Y, in connection with the clamping screw, S, and rest, D, substantially in the manner herein shown and described and for the purpose set forth.

70,831.—METAMORPHOSCOPE.—E. A. Goodes (assignor to himself, E. L. Miller, and W. H. Morford), Philadelphia, Pa.

1 claim, 1st, The combination of two or more endiess belts of different lengths, furnished with sections of figures or pictures, substantially as and for the purpose specified.

2d, The combination of the endless belts furnished with sections of figures or pictures, the rollers, A\* a b c, and the top plate or cover, e, formed with an opening, f, substantially as and for the purpose specified.

70,832.—TRAVELING BAGS AND VALISES.—Nicholas Groel, Newark, N. J.

Newark, N. J.

I claim as an article of manufacture the struck-up metallic corner pieces, D, when constructed and applied in the manner described to valless and raveling bags, for the purpose specified.

Taveling bags, for the purpose specified.

70,833.—DRYING ATTACHMENT FOR PAPER RULING MACHINES.—R. J. Groshans, Buffalo, N. Y.
I claim, 1st, The application of a revolving fan to paper ruling machines for the purpose of dryling the piper, and causing the same to be discharged smoothly into the box prep ired to receive it, substantially as set forth.

2d, The manner of constructing the fan, substantially as shown and described, to wit, having the fan composed of pasteborrd, tar-board, or an equivalent material fitted on pins, c, in the shaft, and retained in position by springs, B, substantially as shown and described.

70,834.—TAG HOLDER.—A. Grushus, St. Paul, Minn.
I claim the tag holder made substantially as herein described.

70,835.—TREADLE FOR SEWING MACHINES.—Thomas J. Hallgan, New York city.

1835.—TREADLE FOR DEWING PROCESSING AND STATE AND STATE OF THE PROCESSING AND STATE OF

unison and whereby said shafts are made the one to support and protect the other, essentially as herein set forth.

2d. The combination of the treadle shafts, C.D. arranged as described, with their treadles, A.B. driving arms or levers, E.F., pitmen.: G.H. and double-throw crank, I, of or to the revolving shaft, K, substantially as shown and described.

throw crank, 1, 01 or 10 bills for the bills. Griffen B. Halsted, N. Y. city, 70,836.—Stovepipe Damper.—Griffen B. Halsted, N. Y. city, the spurred 10,350.—STOVEPIPE DAMPER.—Grillen B. Haisled, N. I. City. I claim, 1st, The notched friction ring, in combination with the spurred shaft of the damper, substantially as and for the purpose specified. 2d, The friction ring constructed with a cam-like surface, whereby the compression of the pipe may be increased by turning the triction ring with reference to the damper shaft, substantially as and for the purpose specified. 3d, The damper, B. constructed with the angular groove, e, and the lips, f, arranged in relation with each other substantially as described, whereby the damper may be readily attached to its spurred shaft, as set forth.

70,837.—Loom.—Marion McDonald Hankins, Vandalia, Ill. I claim, 1st, The combination of the straps, C C, and rollers, D E, for operation substantially as specified, to work the pickers by the action of the

lay.

2d. The arrangement of the picker levers, B B, constructed as described, springs, F, or their equivalents, and the lay, substantially as herein set forth 3d, In combination with the levers, B B, the connecting straps, G G, rollers pickers, H H, and check straps, I I, for operation with each other and the lay, as shown and described.

4th, The means, substantially as herein described, for operating the treadle roller, T, consisting of rods, J J, lever, K, shaft, L, spring, N, rod, O, and clutch and lever, Q P, essentially as specified.

70.838.—MEDICAL COMPOUND.—John Harrigan, East Bos-

70.838.—MEDICAL COMPOUND.—Join Harrigan, East Boston, Mass.
I claim the above described medicine, compounded as described and for the purpose set for th.
70.839.—AMALGAMATOR.—F. G. Hesse, San Francisco, Cal.
I claim, 1st. The narrow annular analgamaling chamber, A, formed by a revolving cylinder, b, and an in-ener cylinder, either stationary or revolving with D, constructed for very high speed, and in combination with a hydraulic device to cause a current of air topass through said chamber, for the purpose substantially as described.

- 2d. The use of an extra current within the chamber, A, for the purpose of distancing pulp without interfering with the amalgamating current, substantially as described.
- stantially as described.

  3d. The manner of producing this current by means of a centrifugal head and guide blaces, substantially as described.

  70,840.—PENCIL HOLDER FOR COMPASSES.—Wm. G. Hille-
- 70,840.—FENCIL HOLDER FOR COLARY AND A STATE OF THE PRINCIPLE OF THE PRINC

- its pin, E. extending into a recess in said piston, in the manner substantially as and for the purposes specified.

  70,842.—PUMP.—John M. Hirlinger, Red Rock, Pa.

  I claim the slide valves, a and d. constructed as described, in combination with the stock and piston, arranged as and for the purpose specified.

  70,843.—MENSTRUAL RECEIVER.—S. L. Hockert, Chicago, Ill., assignor to himself and Jared Thompson, Sr., Milwaukee, Wis.

  I claim the construction and combination of ring, a, sack, b, and arm, c, for the purposes and in the manner substantially as hereinbefore shown.

  1 also claim the combination of ring, a, sack, b, arm, c, and cord, for the purposes and in the manner as hereinbefore set torth, or their equivalent.

  I also claim a combination of ring, a, sack, b, arm, c, cord, i, pad, c, projection, a, set serew, d. belt, if, and buckle, g, for the purpose and in the manner hereinbefore set forth.

  70,844.—Ture Wells.—D. Cyrus Holdridge, Lodi, Wis.
- ner hereinbefore set forth.

  70844.—TUBE WELLS.—D. Cyrus Holdridge, Lodi, Wis. I claim the tubular point, B, and screw, f, in combination with the pipe, A, when arranged to operate as described and for the purpose set forth.

  70,845.—Machine for Making the Links for Cables and other chairs.—Alfred Homfray, Witley Lodge, England.

  I claim, 1st, The sliding shaft or ram, and mandrel which it carries, in combination with the anvil and the jaws for holding the link, and tappets for closing said jaws, substantially as and for the purposes herein shown and described.
- scribed.

  2d. The combination with the sliding shaft or ram and its mandrel, of the welding ram or hammer and die, arranged and mounted in the frame of the machine, substantially as and for the purposes set forth.

  3d. The combination of the mandrel, its shaft, and the welding hammer and die, with the anvil, link-holding jaws, and tappets by which said jaws are closed. substantially as herein shown and specified.

  70.846.—Door Fastening.—Nelson Hornaday, West Elkton,
- Ohio.

  I claim the combination of hooks, A A C, bar, B, with the catches, D E O, when the several parts are constructed, arranged, and operating conjointly in the manner and for the purpose specified.

  70,847.—MOLDING-FACING MACHINE.—Robert Howdon (assignor to Crane, Breed & Co.), Cincinnati, Onio.

  I claim, 1st, The construction of the dies of a molding facing machine in two or more adiustable parts, for the purpose set forth.

- I claim, 1st. The construction of the dies of a molding facing machine in two or more adjustable parts, for the purpose set forth.

  24. The arrangement of frame, A, movable dies, CC'C", and set screws, D, or their equivalents, for the purpose set forth.

  3d. The auxiliary die, I i, in the described combination with the rear die C, of a two or more part molding facing apparatus, for the purpose explained.

  70,848.—SELF-ADJUSTING THILLS.—Arah H. Howe, Brookfield, Vt.

  1 claim, 1st. The independent shafts, B B, connected together by the strap, C, and to axle, A, by means of the rod, a, whereby one of said shafts may be used independent of the other, as specified.

  2d, The arrangement of the shafts, B B, low-fraft whiffle, D, rods, a a, and connecting straps, in the manner substantially as and for the purposes set forth. 70,849.—Machine for Filling Marshes.—George Howell
- 70,349.—MACHINE FOR TILLING MARSHES.—George Howell, Philadelphia, Pa. I claim, ist, An excavating boat constructed for partial and varied submergence, having the chamber, B, pipe, G, side plate, a, and with or without the inner plates, J, substantially as described and for the purpose set forth.

  2d. In combination with such a boat, I claim the air-tight reservoirs and phose connected therewith, substantially as and for the purpose set forth.

  3d. I claim in combination with such a boat, the st.rrer, e, on the shafts, F, sabstantially in the manner described and for the purpose specified.

  70,850.—Automatic Tight-Rope Dancer.—Wm. Humans
- 70.850.—AUTOMATIC TIGHT-ROPE DANCER.—Wm. Humans (assignor to himself and Charles Williams, Jr.), Boston, Mass. I claim, 1st, A jointe figure, balanced as shown, in computation with a pulley wheel, o, provided with cranks or arms, d, through which motion is imparted to the legs of the figure as the pulley passes over a cord, on which it is supported, substantially as described, 2d, Telaim the combination of the hinged arm or detent, e, and cord, g, or its equivalent, attached to the arm of the figure, substantially as and for the purpose set forth.

  70.851.—Paddle Wheel constructed with radial arms, B, and floats, D.
- 70,851.—PADDLE WHEEL.—Wm. Hunter, Detroit, Mich. I claim a paddle wheel constructed with radial arms, B, and floats, D, which are rigidly attached to the end of one arm, and, extending in front thereof, are secured on the opposite edge of the next preceding arm, or to the rim, C, in such manner as to form an acute angle at itsupper edge, and form a diagonal bracing for the arms, substantially as described.
  70,852.—PAPER FLOUR SACK.—John M. Hurd, Auburn, N.Y. I claim, 1st, Crimping or softening a strip or band around near the top of the paper flour sack, as and for the purpose specified.
  2d, The combination of the plain rolls, G H, or their equivalents, with two or more sets of crimping rolls, when all are used for the purpose above specified.
- or more sets of crimping rolls, when all all above the processing of the combination with the pivoted arm, B, substandially as and for the purpose specified.

  2d The combination of plates, k k', arms, D D, sleeve, C, and arm, B, as and for the purpose set forth.

  3d, Spring, I, wheel, d, sleeve, C, and arm, B, all combined substantially in the manner and for the purpose described.

  70,854.—SHRINKING TIRE.—J. B. Jackson and M. R. Jackson,
- Rochester, Iowa.

  Rochester, I
- 70,855.—Yoke for Grain Elevators.—Eliza Jane Jewell,
- 70,805.—YOKE FOR GRAIN ELEVATORS.—EIIZA JARC Jewell, Brooklyn, N. Y., administratrix of the estate of T. E. Jewell, deceased. I claim, 1st, Making the yokes of grain elevators of cast iron, constructed stantially as and for the purpose herein shown and described.

  2d, The adjustable guide arrangement at the ends of a metal yoke, when consisting of the flanges, c, plates, e, gibs or guides, f, and set screws, g, all made and operating substantially as described, in combination with the tenons, b, on the uprights of the stationary frame, A, arranged as described. 70,856.--LAMP.-Melvin Jincks, Dansville, N. Y.
- I claim the employment of a gas tube which shall extend from the mouth of the wick tube to the first floor of the shell, for the purpose of rataining and consuming the gas generated in the lamp, when arranged in combination with non-conductor, B, shell, A, and extinguisher, E, as herein set forth and described.
- and described.
  70,857.—Compound Tool for Punching and Shearing. J. C. Jordan, Watertown, Wis.
  I claim the combination of the frame, A, lever, C, cogged segment, D, pinion, E, handle, F, shears, B G, cam, H, box, L, mandrel, I, punch, M, and die, f, all alranged and operating substantially as herein described and represented
- sented. 70.858.—Fireplace.—Israel Kepler, Corry, Pa. I claim in connection with the common corrugated grate back, the corrugated extension plate or back, H, projecting over the fire and condinuing up to the throat of the flue, as and for the purpose herein described and repre-
- 70,859.—Sheep Trough.—Frank Ketcham, Monongahela
- City, Pa.

  I claim the sheep trough of the form and configuration substantially a and for the purposes herein shown and described.
- and for the purposes herein shown and described.

  70,860.—Door LATCH.—Edward King,

  I claim the combination of the hub, F, to knob spindle, having extensic arm, H, in combination with a latch bolt carrying pawl, I, when all arrange together for operation substantially as and for the purpose described.
- 70,861.—SHEEP SHEARS.—Brainerd Kingsley, Sharon, Mich. I claim ist, The bands, G. G., and handle, I., arranged to hold and operate cutters, J., substantially as set forth.

  2d, The combination of cutters, J. J., and m m., with levers, B. C., bar, A., bands, G., and handle, I, as set forth.

  3d, The plate, E', bar, A., posts D and E, arranged to support bands, G. G., and lever, C., substantially as described.
- -Nut-Tapping Maching.-Jas. Kirkley, Chicago, Ill I claim 1st, The arrangement of a gang of die boxes, a gang of taps, a gang of rotating and vertically sliding spindles, in the relation shown to gears, and a shaft, O, the parts above named being constructed and operated substantially as herein described.
- stantially as he win described.

  2d, The arrangements of the oil receiver, G., oil-supply reservoir, F. pipes, de, and forcing-pump, a, in combination with the die bed and vertically sliding and rotating spindle carrying taps, substantially in the manner and for the purpose herein described.

  3d, The combination, with the nut tapping machine, constructed and operating substantially as herein described, of an automatic lubricating and oil-elevating apparatus, constructed and operating substantially as herein described.
- scribed.

  4th, The arrangement of the levers, R, weight, W, links, R', treadles, S, and vertically-sliding and horizontally-rotating spindles, carrying taps, H, in relation to one another and to the die-bed, D, substantially in the manner and for the purpose described.
- 70,863.—MACHINE FOR CUTTING PAPER STOCK.—Abijah L
- 70,863.—MACHINE FOR CUTTING PAPER STOUR.—AUJan L. Knight, Baltimore, Md.
  I claim 1st, The combination of the crank shaft, G, pitman, F F, knife-block H, ende-frame, I, and knives, I and C, substantially as and for the purpose 2d. The combination of the crank shaft, G, pitman, F, having the pin, e. 12d. The combination of the crank shaft, G, pitman, F, having the pin, e. 12d. The combination of the value of the crank shaft, G, pitman, F, having the pin, e. 12d. The papers to the combined and arranged substantially as and for the purpose set for th.

  3d. The papers tock cutting machine above described, consisting of the parts spect. 12d in clauses one and two of this claim, combined and arranged together substantially as described, for the purpose of cutting and preparing baper stock.
- 70,864.—Machine for Molding Pulleys.—Thos. Knowles,
- Robert Knowles, and Samuel Knowles, Jersey city, N. J.

  We claim a machine or apparatus for moldingwheels or other work of curvilinear character, having for its elements a piliar or post, A, horizontally swinging and radially adjustable ram, D, carrying a vertically adjustible ram or pattern-holder, I, and dividing gear for adjusting the swing of the horizontally as specified.

- 70,865.—Compositor's Copy Holder.—P. A. La France, Elmira, N. Y. assignor to himself and H. R. Kendall, New York city.

  I claim 1st, The board, A, when provided with the extension, b, and roller, c, or their equivalents, and with the spring finger-bar, C, for holding the manuscript, substantially as and for the purpose herein shown and described.

  2d, The board, A, when provided with the extension, e, or its equivalent, and with the indicating sliding bar, D, substantially as and for the purpose herein shown and described.

  3d, The board, A, when provided with grooves, h h, or their equivalents, and with slotted plate or plates, E, or their equivalents, substantially as herein shown and described.
- and with slotted plate or plates, E, or their equivalents, substantially as herein shown and described.

  4th, The board, A, when arranged as described, so that it can be moved laterally on the type-case, B, and when provided with the spring finger-bar, C, sliding indicator-bar, D, and extension bars, E, or equivalents, all made and operating substantially as and for the purpose herein shown and described.

  70,866.—Bolt Fastening, D, formed by the combination of the hinged parts, d1 and d2, pivoted catch, d3, and rubber spring, d4, or equivalent, with each other and with the bolt, C, substantially as herein shown and described and for the purpose set forth.
- 70.867.—LAMP.—James Lee. New York city.
- 70,867.—LAMP.—James Lee, New York city.

  I claim 1st, The combination of the wooden case, B, with the oil reservoir, A, substantially as herein shown and described and for the purpose set forth.

  2d, The interposition of a wooden connection, b2, between the neck, a', of the oil r-servoir, A, and the cap, C, substantially as herein shown and described and for the purpose set forth.

  3d, Forming air passages, D, in the neck of the lamp, leading beneath the cap, C, from the external air to the interior of the oil reservoir, A, substantially as herein shawn and described and for the purpose set forth.

  4th, The adjustable extension pedestal, formed by the combination of the parts F and G, springs, f, and stop, g', with each other, and with the case, B, substantially in the manner herein shown and described, and for the purpose set forth.
- pose set forth. 70.868.—Fізнноок.—A. I. Lenhart, New Brunswick N. J. 70,808.—FISHHOOK.—A. I. Lennart, New Brunswick N. J. I claim the hook, B, pivoted to the bar, A, provided with the shoulder, b, and having the spring, d, bearing against it, in connection with the slide, c, having the spring, D, a tached, and the hook or hooks, C, all arranged substantially as and for the purpose set forth.

  70,869.—SHAFT COUPLING.—W. E. London, (assignor to J.A.
- 70,869.—SHAFT COUPLING.—W. E. London, (assignor to J.A. Fay & Col., Cincinnati, Ohio.

  I claim a shaft coupling constructed as herein specified, to wit: one half keyed on firmly in the usual manner, the other half provided with an adjustable clamping device, as herein specified and for the purposes described.

  70,870.—HORSE RAKE AND HAY SPREADER COMBINED.—J.M. Low, Portlandville, N. Y.

  I claim 1st, The arrangement of the revolving toothed shaft, M, and its supporting frame, K, the axie, A, and frame, C, of the rake substantially as herein shown and described and for the purpose set forth.

  2d, The combination of the gear wheels, N and O, shaft, P, gear wheels, Q, and R, one or more shafts, S, and the gear wheels, T and U, with each other, and with the drive wheels, B, frame, K, and tedder-shaft, M, substantially as, herein shown and described and for the purpose set forth.

  3d, The combination of the toothed reciprocating clearer shaft, B, with the revolving toothed tedder-shaft, M, and with the frame, K, substantially as herein shown and described and for the purpose set forth.

  4th, Operating the reciprocating clearer shaft, B, from the shaft, P, by means of the eccentric wheel, E, or its equivalent, and the pitman, D', substantially as herein shown and described and for the purpose set forth.

  70,871.—QUILTING FRAME AND CLOTHES DRYER.—Geo. A. Mallory, and J. J. Fish, Oxford, New York.

- Mallory, and J. J. Fish, Oxford, New York.
  We claim the adjustable slotted standards, A.A., cross-rail, B, arms, C.C., and cross-rois, g.g., constructed and arranged to serve as a quilting frame and clothes horse combined, substantially as described.
  70,782.—PREPARING WOOD TO BE USED IN THE MANUFACTURE OF PAPER AND FOR OTHER PURPOSES.—C. K. Marshall, New Orleans, 1.9.
- TORE OF PAPER AND PURCHASE TO THE TORE OF TARK AND ADDRESS OF THE TORE OF THE
- the manufacture of paper.

  70,873. FURNACE FOR DESULPHURIZING AND REDUCING ORES.—Jabez Maunton, (assignor to himself and Wright Duryea, Wm. Ennis, J. H. Van Riper, A. P. Cummings, and J. Wendell Cole), New York
- Ennis, J. H. Van Riper, A. P. Cummings, and J. Wendell Cole), New York city,
  I claim 1st, The combination with a reversible draft in or through them, essentially as specified, of the fuel chambers, E. E., and intermediate reducing chamber, F, said chambers being chargeable from above, and communicating with each other at or near the base, substantially as and for the purpose or purposes specified.

  2d, The combination with a reversible draft, operating as described of regenerators, D. D, fuel chambers, E. E., and intermediate reducing chamber, F, said fuel and reducing chambers connecting with each other at or near the base, and chargeable form above, essentially as herein set forth.

  3d, The vertical regenerators, D. D, with their draft inlets or others, e, arranged below, in combination with the fuel chambers, E. E, and intermediate reducing chamber, F, for action as described.

  4th, In combination with the vertical regenerators, the spray water pipes, K, essentially as and for the purpose specified.

- K, essentially as and for the purpose specified.
  70,784.—FURNACE FOR HEATING PURPOSES.—Jabez Maun-
- ton, (assignor to himself. Wright Duryea, Wm. Ennis, J. H. Van Riper, A. P. Cumming, and J. Wendell Cole, New York city. I claim the combination of the fuel chamber, C. C', arranged to connect or combustion at the base, and regenerators, F. F', in connection with said nambers at or near their tops, for operation with a reversible draft substandly as specified.
- tially as specified. 70,875.—RAILWAY SUPERSTRUCTURE.—J. Audley Maxwell, 70,870.—KALLWAY SOLDANDESS SAVANDAR, Ga.

  Savannah, Ga.

  I claim in the construction and arrangement of the superstructure of railroads, the combination of the ties, A A and B, string pieces, C, chair, H, and knees, K, in the manner and for the purpose herein described.

  77,876.—MACHINE FOR PLANING METALS.—Wm. McPherson,
- 77,876.—Machine for Planing Metals.—Wm. McPherson, New York city.

  I claim ist, The cross-traversing screw, G, or its equivalent, and driving gear, as herein specified, so arranged to the cross-cutting tool in a planing machine asto operate relatively to the cutting tool, A, and table, W, substantially in the manner and for the purpose herein specified.

  2d, I claim in combination with the longitudinal and transeverse feeding mechanism of the planer, the adjustable uprights, E E, arranged to operate substantially as and for the purposes herein set forth.

  3d. The hinged braces, 2 and 4, in line with the axis of and in combination with the adjustable inclined uprights, E, and bed of the planer, substantially as and for the purposes herein specified.

  70,877.—HAND LOOM.—S. C. Mendenhall, Richmond, Ind. I claim 1st. The ambication to hand looms of the endless metal-eyed belt
- I claim 1st, The application to hand looms of the endless metal-eyed belor the metallic chain, B b, in combination with the spurred pulleys, C, b, the whole being arranged and combind for the purpose of driving the cam shart
- A.

  2d, The described arrangement of endless metal-eyed belt or metallic chain, Bb, spurred pulleys, C and D, pitmen, PP, and batten, Q.

  3d, The described arrangement of the endless metal-eyed belt or metallic chains, Bb, spurred pulleys. C and D, pitman, PP, and batten, Q, and the crank, D', when said crank has such a position on its pulley as to give and time the motions of the batten, and the cam shaft, a and for the purposes set forth.
- 4th, I claim the reversible plate, S, with its slot, u, or its equivalent, for the purposes set forth and described.
- purposes set forth and described.
  70,878.—BLEACHING STOCK FOR PAPER.—S. T. Merrill, Beloit, Wis.
- Iolin, wis.

  I claim the introduction into a close-covered rag engine or other close vessel, provided with an agitator, of chlorine gas, or the disengaging of the latter from a chlerine solution contained within the box of the engine or other vessel, for the purpose of bleaching paper stock, substantially as set forth. 70.879.—Slide for Extension Table.—Elisha Mets. (as-
- signor to himself and A. Cram), Rochester, N. Y.

  I claim in combination with the oblique grooves, substantially as herein shown and described, the bent coupling or locking irons, h, for the purposes set forth -Awning.-S. Miller, and J. S. McClellan, Cham-
- paign County, Ohio.
  We claim ist, The two rollers, B B, in combination withroller, F, canvas, H, arms, G, boards, K K, and cord, I, constructed and operating as described, and for the purposes set forth.

  2d, The arranging boards, K K, so as to form a shelter to roller, F, in combination with roller, F, canvas, H, arms, G, boards, K K, and cord, I, constructed and operating as described, and for the purposes set forth.
- 70,881.—Machine for Tempering Skirt Wire.—J.H.Monk
- Brookin, N. Y.

  I claim a pair of grooved rollers, adjusted substantially as specified, in combination with the pot or bath for melted metal for tempering wire for skirts, etc., in the manner set forth.

  70,882.—WASHING MACHING.—Allan Neilson, Allegheny
- City, Pa.

  City, Pa.

  I claim, 1st, The corrugated conical rollers, E, when arranged with level lower surfaces and when secured to a swinging frame, C, the axes of which rollers cross each other, substantially as and for the purpose herein shown
- and described.

  2d. The flexible was bloard, G. consisting of laths that are secured together by strings or wires, a a, operated by a treadle, F, substantially as set forth.

  3d. The combination of the treadle, F, cords, a, box, H, and flexible board, G, with each other and with the rollers, E, all made and operating substantially as herein shown and described. -DISH WASHER.-Edwin Norton and J. S. B. Norton,
- Boston, Mass.
  We claim the combination as well as the arrangement of the revolving rame, E E; with the crib, K K, made substantially as described and for the urpose set forth.
- purpose set forth.
  70,884.—Hook for Travellers.—William R. Oatley, Rochester, N. Y.
  I claim the two hooks, A. B, connected by a swivel joint, and constructed not arranged substantially in the manner as and for the purpose set forth.
- and arranged substantially in the manner as and for the purpose set forth.

  70,885.—FANNING MILL, GRAIN AND SEED SEPARATOR.—
  Harrison Ogborn, Richmond, Ind.

  I claim, 1st, The trough, 13, situated under and at the lower end of the upper grain board with a removable side, 13, substantially as and for the purposes described.

  2d. The combination of the adjustable trough, 13, with the upper grain board, 11, forming the bottom of the front part of the shoe, I, and the adjustable screen, J, substantially as and for the purposes described.

  3d, The combination of the upper grain board, 11, with the adjustable side, 13, of the trough, 13, substantially as and for the purposes described.

  4th, A hopper consisting of the side boards, E, with converging grooves, e, the sliding board, F, and adjustable swinging board, H, substantially as and for the purposes described.
- for the purposes described.
  5th. The combination of the swinging board, H, lever, E, provided with a

- spur or tooth, e1, and the rack, e2, substantially as and for the purposes de scribed.
  6th, The vertical circular rim B
- spur or tooth, el, and the rack, e., substantially as and for the purposes accribed.

  6th, The vertical circular rim, R, secured to the fannings, Q, substantially as and for the purposes described.

  7th, The rod, p, with its bent part, p', and the lever, n, substantially as and for the purposes described.

  8th, The rod, p, in combtnation with the linked rods, m and m', wrist, v and wheel, V substantially as and for the purposes described.

  9th, The belt wheel. W, pivoted loosely on the pin, w, and provided with three sets of holes, K K 1 and K2, for the purpose of giving either circular, side or end motion to the shoes, substantially as and for the purposes described.
- side of end motion to the shoes, substantially as and to the part soribed.

  10th, The arm, 1, rigidly attached to the shoe by means of which motion is transmitted to the shoe, substantially as and for the purposes described.

  11th, The combination of the arm, 1, rigidly attached to the shoe, pulleys. V W, and belt to give circular motion to the shoe, substantially as and for the purposes des ribed.

  12th, The combination of the arm, 1, pulleys, V W, and rod, v', to give either side or end motion to the shoe, substantially as and for the purposes described.
- described.

  13th, The pins, g2, on the cleats of the sliding doors, G', substantially as and for the purposes described.

  70,886.—RAILWAY CHAIR.—Nathaniel F. Page (assignor to
- 70,889.—RAILWAY CHAIR.—Nathaniel F. Page (assignor to himself and Elijah Whitney), Rutland, Vt.

  I claim as my layention the combination as well as the arrangement of the cap, C, with the par, A, made with the two lips, a b, to receive the rail and the cap, substantially as specified.

  I also claim the arrangement of the recess of the lip, b, at an obtuse angle with the rail-supporting surface of the chair, such char being provided with two lips, a b, and a cap, C, as set forth.

  70,887.—CARD HOLDER FOR TRUNKS.—William L. Paine, Boston, Mass
- Boston, Mass.
  I claim the within-described card holder for trunks consisting of the strips or plates, BC, in combination with points or projections, or their equivalent, for holding the card securely in place, substantially as set forth.
  70,888.—FRICTION CLUTCH PULLEY.—C. D. Palmiter (assign-

- 70,888.—FRICTION CLUTCH PULLEY.—C. D. Palmiter (assignor to S. A. Webb), Oswego, N. Y.
  I claim, ist. The device herein shown and described of connecting the pulley, B, with the shaft, A, consisting of a movable wedge, I, and an eccentric pivoted riction pad, j, which are made and operated substantially in the manner herem shown and described.

  2d. The hinged lever, C, spring, h, statonary arm, C, and sliding wedge, I, in combination with each other and with the shaft, A, and pulley B, all made and operating substantially as herein shown and described.

  3d. The combination and arrangement of the arm, C, having arm, d, elbow-shaped bar, D, pivoted thereto, and having the arms, fg, and pad, j, spring, h, set screw, I, wedge, I, sliding sleeve, E, palley, B, and shaft, A, as herein described for the purpose srecified.

  4th, The pad, J, when attached to the arm, D, at the point of connection of the arm, fg, and out of line with the axis, A c, whereby the revolutions of the pulley, B, in one direction clamps the edge of the pad in line with the axi, A, e, and increases its bite, and the revolutions of the pulley, B, in one direction clamps the edge of the pad in line with the axis, A, e, and increases its bite, and the revolutions of the pulley in the opposite direction turn the pad out of the line of said axis and releases its bite, as icrein described for the purpose specified.

  70,889.—Blacking Brush.—Charles A. Paret, Nashville, Tenn.
- Tenn.

  I claim the arrangement of the staples, D D, loop, F, elastic band, E, scraper, B, spring, C, and groove brush stock, A, as herein described for the purpose speccified.

- scraper, B, spring, C, and groove brush stock, A, as herein described for the purpose speccified.

  70,890.—Ash Sifter.—Daniel E. Paris, Troy, N. Y. city.

  I claim, 1st, A bail to an ash sifter used separately from an ash pan or constructed with hooks or lugs at either end of the bail so as to engage with an ash pan surrounding or inclosing the sifter and so that both sifter and pan can be moved by the bail or the sifter separately.

  2d, A double self-acting lifter to an ash pan or ash sifter so constructed with hooks or other means of moving the pan or sifter but not attached or attachable to them except while in actual use or in vertical position, as herein described and explained.

  70,891.—Straw Cutter.—Hiram Parks, Athens, N. Y:

  I claim the notched feed bar, K, when provided at its front with teeth in combination with the pin, b, on the oscillating lever, I, all made and operating substantially as herein shown and described.

  70,892:—Blacking Box Holder.—Thomas King Payson, New York city.
- New York city.
  I claim the box holder, A, with its lid carrier, B, provided with set screws, f, or other equivalent means for securing the box and its lid and setting the same relatively to each other, also facilitating the accommodation of different sized boxes in the one holder, substantially as shown and described.
  70,893—INKSTAND.—Stephen Perry and Joseph John Perry,

- 70,893—NKSTAND.—Stephen Perry and Joseph John Perry, London, England.
  We claim, 1st, The employment of a hollow stopper formed of vulcanized india-rubber, or other suitable elastic material, in combination with the reservoir, A, tube. D, and cup, Dl, for the purpose and substantially in the manner set forth.

  2d, The tube, D, formed with the protuberance, D2, and fitted into the stopper, C, for the purpose and substantially in the manner set forch.

  3d, Forming a stopper, cup and tube, in one piece of hard and soft rubber combined, substantially as described.

  70,894.—EDGE PLANE.—J. E. Plummer, Binghamton, N. Y. I claim the construction and use of a "reversible edge plane," substantially as described and represented for the purpose set forth.

  70,895.—BOLT FOR DOOR.—George A. Pridham, Newark, N. J. I claim the plate, A, as constructed and used in combination with the bolt, E, provided with screws, G and F, as and for the purpose set forth.

  70,896.—GRAIN DRILL.—Hiram Pulse, St. Paul, Ind.

  I claim, 1st, The upper box or hopper, F, having the two doors, g g', and throats, H G', for optional discharge of the grain either through the screen or otherwise, as set forth.

  2d, The slides, O and Q, adjusting lever, P, clamp, p, and slotted bar, p' combined and arranged substantially as and for the purposes set forth.

  3d, The cross bolt, B, and nuts, 123466, in the described combination with the purpose
- 3d, The cross bolt, B, and nuts, 123456, in the described combination with the beams, A A', sheaths, C C' C", and draft rod, Y, for the purpose-specified
- specified.

  4th. The slotted brackets, r, and slotted segmental arcs, r', in combination with the rear wheel, R, and driving belt or chain, S, as and for the purpose practice.
- specified.

  5th, The notched spouts, D, in combination with the valves, n, and winged shares, N n', for the purpose decribed.

  6th, in the described combination with the screen, I, and screen chamber, F', or my grain drill, I claim the removable drawer, J, for the purpose speci-
- F, of my grain diff., I could not spring, f, for the purpose specifie.

  7th, The notched rod, W w, and spring, f, for the purpose specifie.

  8th, The caster wheel, T, slotted bracket, U, and bolt, V, for supporting the front end of the implement in combination with the adjustable rear wheel, R, as and for the purpose set forth.

  70 000 Decompositing Horses FROM Vehicles.—John
- Tront end of the purpose set forth.

  70,897.—DISCONNECTING HORSES FROM VEHICLES.—John Rancevan, Carthage, Ohio.

  I claim, 1st, The socket, C, provided with the spring backing, e, in combination with the bolt, c, stay strap eye, d, and cords, l and G, arranged and constructed substantially as described and for the purpose specified.

  2d, The pivoted hammer, f, guard, f''' revolving lever, F, spring double tree strap, E, and double tree, D, arranged as described upon the tongue or other desirable part of the vehicle, and operated substantially as described and for the purpose set ferth.

  70,898.—COMBINED HARROW AND SEEDER.—Benjamin Randall, Adams, N, Y.
- Adams, N. Y. I claim, 1st, The shatt, J, in the seed box, I, provided with the radial arms b, and rotated by means of suitable gears from one of the wheels, B, when the same is in combination with the scattering board or plate, M, and all arranged substantially as described and for the purpose set forth. 2d, The slide, K, perforated with the V-shaped holes, e, and fitting in the seed box, I, in combination with the perforated bottom, L. of the seed box which is perforated with representations of the seed box and for the purpose specified.
- M. the whole being constructed, arranged and operating substantially as and for the purpose specified.

  3d, The combination of the harrow connected with the truck or mounted frame and the distributing apparatus applied to said frame, all arranged substantially in the manner as and for the purpose set forth.

  70,899.—APPARATUS FOR TETHERING ANIMALS.—David W

- 70,899.—APPARATUS FOR TETHERING ANIMALS.—David W Rawson, Croydon, N. H.

  I claim the band, m, with the hook or hooks, b, and the flange, d, on the cap, c, to be applied to any tether in which a cap or socket turning on an upright stake or bar is used.

  70,900.—Tobacco Press.—Thomas N. Read, Danville, Va. I claim, 1st, The shrouding box, A, provided with false sides, A A, substantially as and for the purpose described.

  2d. The hinged cross head, C, when combined with the screw, E, as and for the purposes and operating in manner substantially as specified.

  3d. The truncated conical body, G G, in combination with socket. f, toe, e, and band, H, substantially as and for the purposes above set forth and described. 70,901.—Carpenters' Square.—C. H. P. Robinson (assignor
- to himselfand John B Robinson) Bellport, N. Y. Iclaim a carpenters' square provided with a slot, a, in the manner and for the purpose described. 70,902.—Compound Tool for Cutting, Punching, and Up-

- 70,902.—COMPOUND TOOL FOR CUTTING, PUNCHING, AND UPSETTING IRON.—John J. Rose, Elmwood III.

  I claim, 1st, The curved lever, F, pivoted in the frame, A, in combination with the slide, E, and lever, B, whereby the latter in its downward
  movement presses upon the inner end of the lever, F, whose outer end
  forces the slide inward to upset the iron held by the clamps, C D.
  2d, The combination of the eccentric, L, upon the eccentric lever head,
  H, yoke, K, and slotted side piece, al, with the plunger, J, and punch, I,
  as herein described, for the purpose specified.

  3d. The construction and arrangement of the main lever, B, pivoted between side plates, at 2, at their rear encs, lever, F, slide, E, clamps, C D, and
  hand lever, H, with flange, K' as herein shown, for the purpose specified
  70,903.—Door SPRING.—Cyrus W. Saladee, Newark, Ohio.
  I claim the combination of the box, A, mandrel, C, spring, E, and plates
  D and K, with an arm, B, and stirrup, F, constructed and operating substantially as described, and for the purposes set forth.

  70,904.—School Desk and Seat.—J. P. Scott, Lewisburg,
  Pa.
- 70,904.—ECHOOL DEER AND PART.

  Pa.

  I claim, 1st, The arrangement of the school desk, B, supported on the sliding standards, A A, and the seat, C, hinged to the slide pieces, b b, and supported by the segment arms, c c, constructed, combined, and operating, as and for the purposes herein described.

  2d, The Ild, f, hinged to the desk, B, in combination with the folding brackets, g g, in such manner as to fold on the top or close the hollow receptacle for books in the desk, arranged as herein set forth.

  PROPERTY STREET METAL.—MOTTIS.
- 70,905.—Apparatus for Punching Sheet Metal.—Morris
- Seiferth, Morristown, N. J.
  I claim, 1st, Securing the punch. C, in the bed plate, B, by means of the holder, G, and screw, e, and making it adjustable up and down by means the screw, b, substantially as herein shown and described.
  2d, The application to the punching machine herein described of the auto-

matic lifter, i, by which the plate is raised off the punch, substantially as and for the purpose berein shown and described.

2d, The bar, li, lever, i, and spring, k, in combination with the cam, g, on the shart, D, and with the stationary punch, C, all made and operating substantially as herein shown and described.

70,906.—Siate.—G. W. Shearer, Crown Point Center, N. Y.

I claim the combination of the levers and springs between the blade and for the purpose described.

I claim the combination of the levers and springs between the blade and for the purpose described.

70,997.—MAIL BAG.—Luther M. Sims, Lincoln, Ill.
I claim the cise, C, constructed and used with the bag and its flap, a, substantially in the manner and for the purpose set forth.

70,998.—CARRIAGE JACK.—Joshiah B. Small, Boston, Mass.
I claim my improved carriage jack, as constructed with its notched lifter or slider, arranged with guide posts in manner as described, and as having two toggles and a forked lever, and a stop, h, thereof, arranged and combined togener, and with one of the posts, in manner as specified.

70,709.—COOLING AIR AND OTHER SUBSTANCES.—Daniel E. Semes, Washington, D. C.
I claim, 1st, Atomizing liquids, by means of a fan-blower, substantially as described.

described.

2d, Cooling air or liquids, substantially as set forth.

3d, The devices or their equivalents, substantially as set forth, for cooling

air and liquids.
70,910.—ELASTIC PACKING FOR THE JOINTS OF DOORS, LIDS,

70,910.—ELASTIC PACKING FOR THE JOINTS OF DOORS, LIDS, AND THE LIKE.—Daniel E. Somes, Washington, D. C.
I claim, Ist, An elastic tube, having a flange, lug, or plate, or more than one of either, or their equivalents, substantially as herein described, and for the purpose set forth.

2d, An elastic tube, prepared by splitting, as in fig 9, or by making holes, f, as in fig, 12, or in any equivalent manner, for the purpose set forth.

70,911.—CAR BRAKE.—Charles Spofford (assignor to Charles Spofford, Walter E. Hawes, Charles Hersey, and Francis C. Hersey), Boston, Mass.

I also claim the eccentric-gear, M N, when used with mechanism for operating the brakes of railroad cars, etc., substantially as described.

I also claim the friction wheel, T, in combination with a slotted bar, w, and shipper, 7, for taking the power from the per phery of a car wheel, C, to wind up the brake, substantially as set forth.

70,912.—MACHINE FOR PRESSING BONNETS.—Solomon Squier, and Horace Squier, Monson, Mass.

and Horace Squier, Monson, Mass.
We claim, 1st, The combination of the jointed presser, F f, pressure-bars, pressing-frame, A C D E, block, B, heater, b', suspension rod, G, lip plates; in and supplementry heaters, h h, as herein described, for the purpose

specified.

2d, 1 ne block, B, when attached to the frame, A, by a slide hinze, b, so that different sized blocks may be used to press hoods of varying proportions, by the same machine, without changing the jointed presser, as herein set forth.

70,913.—Fish HOOK.—Elisha Sterling, Cleveland, Ohio.

I claim the combination with the hook, A B, shding extension hook, a, and

I claim the combination with the hook, A B, shiding extension hook, a, and the counter extension hook, b, constructed substantially in the manner and for the purpose set forth. 70,914.—Gold Separator.—William C. Stiles, Nevada City,

Cal.

I claim, 1st, The instrument seen in figs. 5 and 6, letter, C, in combination with a boot or shoe.

2d, I also claim the extra insole, with its spring or springs, in combination with the valve, as seen in tig. 6, letter, C, substantially as described, and for the purposes set orth in the specification.

70,915.—Grinding Mill.—Giles M. Stone, St. Louis, Mo. 1 claim the adjustable roller, B, operating in connection with the front edge of the chute, T, or the purpose of grinding the lumps which pass between the upper rollers before reaching the second rollers, as herein shown and described.

70,917.—Machine for Flanging and Wiring Metallic Plates—Orson W. Stow. Pleatering and 6, letter, C, in combination with a best properly of the second of the control of the con

70,917.—Machine for Flanging and Wiring Metallic Plates—Orson W. Stow, Plentsville, Conn.

I claim the combination, as well as the arrangement, of the adjusting screw bearing, L, with the rocker-shaft, K, and the roller-shaft, C, its shoulder, h, and camp-nut, M, or their equivalents.

I also claim the combination and arrangement of the set nut, T, the rocker-shaft, K, and the adjusting bearing, L, applied to the shaft and the case or frame of the machine, substantially as specified.

I also claim the application of the front box, of the shaft, C, to such shaft and the case or frame, I, so as to be capable of being moved in one arc with the shaft, and endwise with such shaft, as described.

I also claim the case or frame, I, as made and applied to the rocker shaft journals and he bearings of the two shafts, and so as to encase the gears, substantially as de cribed and represented.

70 918.—Harvester.—A. W. Tucker, Waxahachie, Texas.

I claim suspending the finger bar and its appendages from a curved beam.

I claim suspending the finger bar and its appendages from a curved beam. D, pivoted to the rear of the frame of the machine, and adjustable in any desired position, as set forth, so as to set the finger bar at any desired besired bight, it combination with the pivoted extension, E', of the finger bar, and the chain and lever, I, all being constructed, arranged, and operated in the manner and for the purpose set forth.

70,919.—FAUCET.—John E. Tucker, Boston, Mass.

I claim a faucet, composed of pipe, B, with stem, C, and plug, D, with its grooves, e, pipes, G and A, and packing-ring, E, all constructed, arranged, and operating in the manner us and for the purposes set forth.

and operating in the manner as and for the purposes set forth.

70,920.—Mode of Preparing Cloth for Receiving Lithogoraphic and Other Impressions.—Charles Volkmar, Jr., New York city, assignor to himself, Wm. P. Myers and Thomas Hediem, Baltimore, Md.

I claim the process for preparing cloth for receiving lithographic, photographic, or other impressions, substantially as described.

70,921.—Self-Closing Hinge.—Caspar Vetter (assignor to himself and Peter Schneider), Cincinnati, Ohio.

I claim, Ist. The combination, with a self-closing door, or shutter hinge, operating by gravitation and by a spring, substantially as shown, of the angular or non-circular top or head, B, and socket, K, permitting the door, when mounted, to gravitate to any desired position, as described.

2d, In combination with the spring, J, I claim the inclined edges upon collar, C, and socket, G, having depressions, g g', and prominences, c c', substantially as shown and described.

79,922.—Guides or Clamps for Harness Frames.—Adolph S, Villee Lancaster, Pa.

79,922.—GUIDES OR CLAMPS FOR HARNESS FRAMES.

S. Villee, Lancaster, Pa.

I claim the protecting guides, formed of strips, AB, with blocks or ends, C, arranged substantially as shown and described, for the purpose specified.
70,923.—SCREW DRIVERS.—T. D. Voorhees, Easton, Pa.

I claim the rotating thimble, C, with the flange, D, when applied to a screw driver, substantially as and for the purpose set forth.
70,924.—GRATE COMBINATION.—John Wallace, Louisville, Ky.
I claim the semi-circular tile, B, and grate, A, when the same are constructed and combined substantially as described and for the purpose set forth.
70,925.—PAPER RULING MACHINE.—Edmond A. Warren, Brooklyn, N. Y.

70,925.—PAPER RULING MACHINE.—Edmond A. Warren, Brooklyn, N. Y.
I claim, 1st. The rotating cylinder, C, provided with shafts, D D, having fingers, E, to grasp the sheets of paper to be ruled in connection with the penbeam, O, provided with pens, Q, and all arranged to operate in the manner substantially as and for the uniterest set for the cylinder, C, in connection with the arm, M, on the shaft, I, provided with integers, K, for presenting the sheets to the cylinder, C, substantially as shown and described.

3d, The adjustable cams, T, at one end of the cylinder, C, in connection with the arm, S, on shaft, P, having the pen-beam, O, attached, substantially as and for the purpose specified.

4th, The cords, U U', arranged in relation with the cylinder, C, and working respectively over the rollers, Z Z' W Y Y', to operate substantially in the manner as and for the purpose set forth.

70,926.—W AGES INDICATOR.—Windsor N, White, Winchendon, Mass.

70,926.—WAGES INDICATOR.—Windsor N. White, Winchendon, Mass.

I claim the said wages indicator, or combination and arrangement of the cylinder, divided and marked substantially as described, with the slotted case or its equivalent, and the scale applied to such case, as set forth.

70,927.—CHIMNEYS—A. S. Whittemore, Willimantic, Conn.

I claim the combination of a tile chimney or flue, A, with an air pipe, C, the latter encompassing the former, and communicating with the external air and the compartments within the building, substantially as and for the purpose specified.

I further claim the elastic bands, B, fitted in the annular recesses, f, in the flanges at the ends of the tiles, substantially as and for the purpose set forth.

I further claim the elastic bands, B, fitted in the annular recesses, f, in the flanges at the ends of the tiles, substantially as and for the purpose set forth. 70,928.—AXLES AND AXLE BOXES.—David Wigger, New York city.
I claim, Ist, The rings, cd, fitted within the journal box, in combination with the collars, e, f, on the Journal, Ax, substantially as and for the purpose spectified.
2d, The arrangement of the packing ring, n, within the annular nut, C, and in relation with the journal, Ax, packing rings, h, and flange, g, substantially as and for the purpose specified.
70,929.—SELF-SETTING GAME TRAP.—Alfred Wilkin, McConnellsville, Ohio.

70,323.—SELIT SELITAL CONTROL CONNEL SHIP SELITARY CONNEL SHIP SELITARY CONTROL SHIP SEL

weight, arms, D, short lever, E, and lever, V, The Section of Setting and tripping the trap, substantially as herein shown and described of the combination of the quadrant, I, and spear, K, with the arms, D, of the shaft, B, substantially as herein shown and described, for the purpose of killing the animal.

3d, The combination of the curved pivoted piece, L, connecting rods, N, elbow levers, O, and hinged platform, R, with each other and with the arms, D, of the shaft, B, substantially as herein shown and described, for the purpose of throwing the dead animal out of the way-4h, The combination of the lever, T, and hooks, U and V, with the elbow levers, O, and quadrant, I, substantially as herein shown and described and for the purpose set forth.

70.930.—BELT FASTENER.—David Wigger, New York city, I claim, 1st, The plates, B B', when firmly secured to the ends of the belt, and when shaped as described, so that they can only be disengaged by moving the ends of the belt aside, substantially as herein set forth.

2d, The plates, B and B', when made as set forth, in combination with the bolt, a, the same beling made and operated substantially as and for the purpose herein shown and described.

70.931.—Lantern.—Moses B. Wright, Meriden, Conn.

pose herein shown and described.
70,931.—LANTERN.—Moses B. Wright, Meriden, Conn.
I claim the perforated metal cap, D, top, a, chimney, C, shell, B, and perforated metal band, d, all combined in the manner substantially as set for th.

To,932.—Dice Box.—Justus E. Zender, New York city.
I claim, 1st, As a new article of manufacture, a hand dice box made of metal, substantially as and tor the purpose described,
2d, I also claim a hand dice-box, lined with cloth, or any equivalent material therefor, whether such dice-box be made of metal or any other suitable material, substantially as and for the purpose specified.

### REISSUES.

2,797. — MACHINE FOR BOLTING AND CLEANING CLOVER-

2,131.— MACHINE FOR BOLITING AND CLEANING CLOVER-SEED.—John C. Birdsell, south Bend, Ind.

I claim, 1st, The combi ation in a machine for threshing and hulling clover seed, of the bolts, A.A. with the cranks, D. E. guide rods, F. F., arms, G. G. H. H., and connecting rods, B. B., or their equivalents, in the manner and for the purpose set forth.

2d, I claim the combination, in the machine above described, for threshing and hulling clover seed, the trough, I, with the endless conveyer, J, in the manner and for the purposes specified.

2,798.—PITMAN CONNECTION FOR HARVESTERS.—Hiram L.

wanger, New York city.

I claim, 1st, Connecting the pitman, B, to the pitman wheel, A, of a harvester, by means of a round or polygonal pin, a, having a necentric projection, d, and made substantially as and for the purpose herein shown and described.

scribed.
2d, The tapering pin, a, when arranged in combination with the pin, d, the washer, e, and nut, b, all made and operating substantially as and for the purpose herein shown and described.

3d, I claim the pin, i, in combination with the packing, k, all made and operating substantially as and for the purpose herein shown and described. [Note.—Fifty-one patents in the above list were obtained through the Home Office of the Scientific American.—Eds.]

#### PENDING APPLICATIONS FOR REISSUES.

Application has been made to the Commissioner of Patents for the Reissue of the following Patents, with new claims as subjoined. Parties who desire to oppose the grant of any of these reissues should immediately address MUNN & Co., 37 Park Row, N. Y.

-CLOTHES WRINGER -C. H. Knox, Mount Pleasant,

00,5 2.—CLOTHES WRINGER.—C. H. KHOX, MOURT Pleasant, Iowa. Dated July 2, 1867. Application for reissue received and filed Oct. 13, 1867. It caim the double cog wheel, P, and double pinion, S, substantially as set forth.

2d, The combination of Cog wheel, P, and pinion, S, with rollers, D D, substantially as and for the purpose set forth.

3d, The arrangement and combination of lever, M, hinged to box, A, roller, L, rods, K, levers, I, and plate, G, arranged to operate upper roller, D, as set forth.

26,327 -Nursing Bottle.-Milo S. Burr (assignee by mesne

26,327—NURSING BOTTLE.—Milo S. Burr (assignee by mesne assignments of Francis J. La Forme), Boston, Mass. Dated Nov. 29, 1859. Application for reissue received and tiled Oct. 10, 1857. I claim my said improved nursing bottle, having its body, A, composed of glass or other suitable material, and provided with an elastic nipple or mouth piece, f, and a flexible or pendulous tube, C, applied thereto substantially in manner and so as to operate as and for the purpose set forth.

I also claim in a nursing bottle otherwise properly organized, the use or employment of a flexible or pendulous tube, substantially as and for the purpose set forth.

I also claim the application of a gravitating tip or tube. c, to the lower end of the flexible tube, C, substantially as and for the purpose set forth.

68,398.—Overshoe.—Henry G. Tyer, Andover, Mass. Dated Sept. 3,1867. Application for reissue received and filed Oct. 30, 1867. I claim a boot or shoe constructed with an elastic gore or gores of vulcanizable material, when the said gore is inserted into the shoe before vulcanization and during the process of construction, and the whole completed by vulcanization substantially as set forth.

63,770.—CENTRIFUGAL MACHINE FOR DRAINING SUGAR AND OTHER STEBSTANCES.—David M. Weston, Boston, Mass. Dated April 9, 1867. Application for reissue received and filed Nov. 2, 1867. ist, in the construction of centrifugal machines for separating liquids rome.

1st, In the construction of centrifugal machines for separating liquids from other substances, I claim suspending such machines at the top by flexible connections operating substantially as described.

2d, The combination of the spindle, D, and its accessories, with the socket, R, and its india-rub er bushing, C, or other equivalent spring connection, to form a flexible and elastic bearing for the shatt, E, by which the cylinder may be suspended substantially as described.

3d, The employmentima centrifugal machine of a hollow shaft, and a spindle or axle on which it runs, to support the cylinder or basket, substantially as described.

4th, So forming and arranging the driving pulley, F, upon the shaft, E, that it shall surround the spring bearing, substantially in the manner and for the purpose described.

5th, The construction of the openings, I, in the bottom of the cylinder, in such machines and the valve, J, for the purpose of closing the same, substantially as described.

6th, The combination of the cylinder, G, the hollow shaft, E, the driving pulley, F, the spindle, D, its elastic bushing, C, and socket, B, to form the operative part of a centrifugal machine, substantially as described.

57,006.—GAS MAINS.—I. N. Stanley, Brooklyn, N. Y. Dated Aug. 7,1866. Application for reissue received and filed Nov. 2, 1867. I claim as an improvement in hydraulic mains for gas works, the combination with the main C, of the external supply tubes D, cast with or made separately from and attached to the main, and communicating with the same be-

water or fluid therein, substantially as an i for the purpose herein

34,088.—BASKET.—Lansing Marble and Townsend North, Vassar, Mich., assignees of Lassing Marble aforesaid. Dated Jan. 7, 1862.

Application for reissue received and filed Nov, 2, 1867.

1st, I claim a basket formed of two series of overlapping splints, A A', substantially as described, and fastened in any suitable manner.

2d, Fastening hoops, a a D and C C, in combination substantially as and for the purpose described.

the purpose described.

2,847, whole No. 33,851.—GANG PLOW.—Wm. B. Ready, Sacramento, Cal. Dated Dec. 3,1861. Application for reissue received and filed Nov. 1867.

1st, I claim the curved beams, A, when used in connection with a gang plow, or a series of plows connected together by cross bars, B B B, constructed and operating as and for the purposes herein set forth.

2d, The arrangement of the arms, G, wheels, I, and lever, J, when attached to the right hand arms, G, and connected to the central beam, A, as and for the purposes set forth.

3, The arrangement and application of the draft at any point or place below the top of the standard of the plow, as specified and described and for the purposes set forth.

56,189.—Horse Rake.—George Deal, Wilmot, Ohio. Dated July 10, 1866. Application for reissue received and filed Nov. 6, 1867. I claim the combination and arrangement of the hinged arm; 11, adjusting screws, H H, or their equivalen, tooth roller, D, and rake teeth, L L, substantially as and for the purpose herein specified.

NOTE.—The above claims for Reissue are now pending before the Pat ent Office and will not be officially passed upon until the expiration of 30 days from the date of filing the application. All persons who desire to oppose the grant of any of these claims should make immediate appli-MUNN & CO., Solicitors of Patents, 37 Park Row, N. Y.

# Advertisements.

The value of the Scientific American as an advertising medium cannot be over-estimated. Its circulation is ten times greater than that of any similar journal now published. It goes into all the States and Territories, and is read in all the principal libraries and reading rooms of the world. We invite the attention of those who wish to make their business known to the annexed rates. A business man wants something more than to see his advertisement in a printed newspaper. He wants circulation. If it is worth 25 cents per line to advertise in a paper of three thousand circulation, it is worth \$2.50 per line to advertise in one of thirty thousand.

# RATES OF ADVERTISING.

Back Page, for engravings......\$1.00 a line. Inside Page......40 cents a line. Inside Page, for engravings.....60 cents a line.

# AMERICAN EMERY.

RROWSIC EMERY, Manufactured at Bath, Me. All numbers from fouran to one hundred and twenty. The only real mine in the world, excepting in Turkey. For sale in quantities to sult, at reduced prices, by STANWOOD, MCLELLAN & FULLER, 24 Central street, Boston.

From Stanly Rule and Level Co., New Britain, Conn. "We have been using some numbers of your Emery on steel, and it gives good satisfaction. If it proves to work as on trial, thus lar, we shall use nothing else. For some reason, London emery does not give us good satisfaction

Bristol, Conn.:
Our men, who work by the job, say your Emery is better than any English or American Emery they ever used.

Mackintosh Hemphill Co., Pittsburgh, Pa.:

The quality of your Emery Cloth is excellent.

22 9\*\*

FIFTY Persons in every town wanting the best Fireside Monthly, full of good Ficaring, Instruction, Amusement, "Gayeties and Gravities," should send for the "Household Messenger," London Ridge, N. H. Specimen & CENTS.

A vol., postpaid, only fifty

OOK! LOOK!! Best Stencil Dies, fifty TOOK! LOOK!! Best Stenen Dies, may two sizes and styles. A chance for any one to engage in a paying business requiring but small capital.

Enstructions Free. H. N. COON, Jr., Burington, Vt.

500 AGENTS WANTED TO SELL Howe's Never Failing Ague Cure and Tonic Blood, Liver, Skin, etc. Large Profits—100 per cent. For particulars, inclose a 8 c. stamp to proprietor, C. B. HOWE, M.D., Seneca Falls, N. Y.

WANTED. AAn Inventor of a New and Improved Traction and A gricultural Engine wishes to correspond with parties interested in their manufacture and introduction.
Address R. K. MOMURRAY, Engineer, 22 2 2 1 2 and 4 N. Greene st., Baltimore, Md.

PRATT, WHITNEY & CO.,

HARTFORD, CONN.

Make Hand and Encine Lathes, Crank and Gear Planers, Drills, Screw and Milling Machines, Water Motors, etc., unsurpassed for nice construction, strength, unsurpassed for nice construction, strength, 22 13

ENOIR GAS ENGINES, From half-Horse to three Horse-power, for sale at COMPANY'S OFFICE, No. 26 Pine st., Room 8, New York. 22 5

WANTED—A Second-hand Low Press-ure Engine of about Sixty Horse power. Address 22 5 MODELS and all kinds of Brass Work

made at J. GAIR'S, 8 Gold st., near Maiden Lane. INVENTORS having Patents to sell will

M. find it to their advantage to visit the rooms of GEO. M. DANFORTH & CO., Inventors' Exchange, 512 Broadway, New York, opposite St. Nicholas Hotel. Send stamp for circular. 22 3\*

ABRICATION OF VINEGAR. Prof. H. DUSSAUCE, Chemist, is ready to furnish the most recent methods of manufacturing Vinegar by the slow and quick processes, with and without alcohol, directly from corn. Also, process to manufacture vinegar and acetic acid by distillation of wood. Methods of assaying vinegars. Address

1\*1

New Lebanon, N. Y.

A RTIFICIAL EARS FOR THE DEAF,
Can be Concealed. Send to E. HASLAM, 266
Broadway, New York, for a descriptive pamphlet. 22 4\*

YOU CAN SOLDER your own tin ware without a soldering tron by buying one bottle of or Wilson's Prepared Solder. Samples sent on receipt of 25 cents, with price list. Agents wanted everywhere. Direct to Wilson & CO., No. 19 Lindall st., Boston. 22 2D

TO SOAP MANUFACTURERS.—Prof. H.
Dussauce, Chemist, is ready to furnish processes to
manufacture every kind of lyes and soaps, with the plans
of manufactories and drawings of apparatus. Also, anlysis of soaps and crude materials. New Lebanon, N. N.

HUTCHINSON & LAURENCE, 8 Dey street, New York. Steam Engines and Boilers, Iron and Wood-working Machinery, New and Second-hand Machinists' Supplies, etc., General Agents for Judson's, and other improved Governors.

NCRUSTATIONS REMOVED And Prevented by The Winans Anti-Incrustation Powder. 11 Wall st., New York. Success guaranteed. 1\*

IBERAL ARRANGEMENTS WILL BE made with parties who wish to build the Ohio Reaper and Mower, by J. A. SAXTON, Canton, Ohio. 22 ti

To PATENTEES.—Metal Small Wares of all descriptions made and introduced to the Trade. Press and Drop Work, Metal Spinuing Dies, Tools, Castings, etc., to order. J. H. WHITE, Newark, N. J. 1\*

# $WIRE\ ROPE.$

JOHN Annafactured by
JOHN A. ROEBLING.
Trenton, N. J.

FOR Inclined Planes, Standing Ship Rigging, Bridges, Ferries, Stays or Guyson Derricks and Cranes, Tiller Ropes, Sash Cords of Copper and Iron, Lightning Conductors of Copper. Special attention given to hoisting rope of all kinds for Mines and Elevators. Apply for circular, giving price and other information. If 23

POSITIVE STEAM PUMP, WM. HARSEN, Patentee and Manufacturer, Gre-oint, L. I., costs one third less than any other First-cl Pump of the same capacity. J. W. COLE, Manufacturer's Agent, No. 205 Broad way, Room 3,

POWER PUNCHES, ROTARY SHEARS,
Vertical Drills, etc. Address
GREENLEAF & CO., Indiagencle, Ind.

THE STONE'S RIVER UTILITY Works, of Murfreesboro', Tenn., manufacture large quantities of Red Cedar Ware and Moth-proof Cedar Clothes Chests. Agents Wanted. Send for Catalogue, 22 tf] D. H. C. SPENCE, Sup't.

The Holiday Journal.
OF Parlor Plays, Magic Sports, Games, Experiments, Problems, Puzzles, etc., Will be Sent Free, Address ADAMS & CO., Publishers, Boston. 22 1-D.

Painting. Full directions for mixing and applying Paints and Varnishes will be found in Painter, Glider, and Varnisher's Companion, price \$1.50 by mail.free of postage. HENRY CAREY BAIRD, Industrial Publisher, 406 Walnut st., Philadelphia.

BOILER FELTING SAVES TWENTYfive per cent of Fuel.
JOHN ASHCROFT,
50 John st., New York.

PAINTER, GILDER, and VARNISH-ER'S COMPANION.—Tenth Edition, with import-ant additions, just ready, price \$1 50 by mail, free of post-ag. HENRY CAREY BAIRD, Industrial Publisher, 406 Walnut st., Philadelphia, Pa.

THE Excelsior Wind Mill and the Genuine Concord Axles manufactured by 26\*] D. ARTHUR BROWN & CO., Fisherville, N.H.

The very highest prize, THE CROSS OF THE LEGION OF HONOR, was conferred on the repreentative of the Grover & Baker Sewing Machines, at the Exposition Universelle, Paris, 1867, thus attesting their great superiority over all other Sewing Machines. Salesrooms 495 Broadway, New York.

PATENT IMPROVED ENDLESS OR BAND SAW MACHINES, where saw breaking is entirely prevented; they run one-third faster than any other band saw. Also, a narrower saw, than usual, can be used and produce from three to five times more work than any of the best up-and-down saws in use; save much power and stock. Refer nees can be given from almost any part of the country. Machines for cutting boards are in process of building. We also manufacture well designed oval and other wood turning lathes, double adjustable spindle boring machines, chrcular saw mandrik, snafting pulleys, flanges, etc.

FIRST & PRYIBIL.

20 6°]

175 and 177 Hester st, New York city.

# PAT. ERASER

PATENT INK ERASER, BURNISHER, Pencil Sharpener, and Pen Holder combined. Sells at sight. Agents wanted. Can make \$50 a week. Sample, post paid, 25 cents, or two styles for 40 cents. Address MORSE ERASER CO., 22 41 404 Library st., Philadelphia, Pa.

CARPENTERS SEND for New and Practical Architectural Works, enclosing stamp. 20 tf) A. J. BICKNELL, Troy, N. Y.

HOUSEKEEPERS DO YOUR OWN
Painting. Full directions for mixing and applying
Paints and Varnishes will be found in Painter, Gilder, and
Varnisher's Companion, price \$150 by mail, free of postage. HENRY CAREY BAIRD, Industrial Publisher, 406
Walnut st, Philadelphia.

PAPER COLLAR MACHINES.-Experimental Machinery and Models—the latest improved machine for Platting Linen Bosoms and Collars. Patterns, Drawings, and Letters at the corner of Union and Fulton sts.. Troy, N. Y. W. H. TOLHURST. 21 2\*

OACH PAINTERS will find Practical O'NCH FAINT END WIT HIM THACKAN

Directions for Coach Painting and Varnishing in
tenth edition of Painter, Gilder, and Varnisher's Companion, now ready, price \$150 by mail, free of postage,
HENRY CAREY BAIRD, industrial Publisher, 406 Waknut street, Philadelphia.

WILL SELL ENTIRE OR STATE Rights for my Hay Gatherer, illustrated in No. 19, Scientific American. Every farmer needs one. Address 19 4\*] JAS. SWINNEETON, Marion, O.

DUNHAM'S Improved Nut-Forging Machine is uncounsed in simplicity and durability, and the most perfect working machine in use. Rights for sale, Address [15 8\*] GEO. DUNHAM. Unnonville, Conn.

GOOD BUSINESS AT YOUR OWN A GOOD BUSINESS A1 TOOM'S Patent Ventilating Damper. No one using Stoves would long be without them after their sale was commenced. Retail for \$1.50\$. Agents get half. Hotels take twenty to and every house in proportion. Apply to fifty, and every house in proportion. Apply to 1\*] J. C. FELLOWS, Box 5548, P.O., New York.

### SUBMARINE BLASTING.

Important to

#### ENGINEERS AND CONTRACTORS

On Submarine Work.

The superiority of Ehrhardt's Patent Powder over all other compounds for submarine blasting has been fully proved, after severe tests, in the work now progressing in Boston Harbor, as the following correspondence will

Boston, Oct. 3, 1867.

Gen. J. G. Foster, U. S. A. . Sir:—I beg leave to submit the following report of work done on Tower Rock, (in Boston Harbor,) under your supervision. I commenced work August 9, 1867, with the best powder heretofore used, and continued to blast till Sept. 18, 1867, and succeeded in removing about 20 tons of rock, using about 22 kc. 28.

On Sept. 18, commenced blasting with Dr. Ehrhardt's Patent Powder, and with four (4) cases, and in six days, removed the rock (about 150 tuns) to the required depth. My great success with the Ehrhardt Powder, warrants me in recommen ding it in blasting Corwin Rock, as I am confident that within o ther powder can I accomplish the work without great loss of time and increase of cost.

Your ond't servant.

GEO. W. TOWNSEND,
Submarine Engineer.

Submarine Engineer.

Boston, Oct. 10, 1867.

Dr. Ehrhardt. Dear Sir:—I enclose to you a communication received from Mr. Geo. W. Townsend, Coultractor, relative to the merits of the powder invented by you. I agree with Mr. Townsend, that for submarine blasting it is the best powder we have as yet tried, and I would recommend its use under similar circumstances.

Very respectfully, your obd't serv't,

J. G. FOSTER, ir. Major Gen. U. S. A.

Parties wishing to purchase the Powder, or rights for States, can get satisfactory information of its great ad vantages over all o her Blasting Powder, at the Compa ny's Office, No. 38 City Exchange, Boston

GEO. E. LINCOLN. Treasurer

PORTABLE RAILROAD.—The advantages of the patented Portable Railroad are manifold. Its aves both time and money; it is particularly adapted for excavating and filling, constructing railroad beds, milldams, levees, etc., for working in mines, quarries, brick yards, and peat bogs. Sold or restud in 20-foot sections, from one to a thousand. Also, Cars suitable for the work to be done. Contracts for excavations, etc., promptly attended to. For rarticulars or pamphlet, address box 222, Mechanics Exchange, or A. PEI ELER & CO., New Brighton, Richmond county, N. Y. 20 3\*

PAINTER, GILDER, AND VARNISH ER'S COMPANION, Tenth Edition, contains the best practical directions for Glass Staining, Sign Funthing, Imitation of Woods, Marbies, Tottoise Shell, etc., price \$1.50 by mail, free of postage. HENRY CAREY BAIRD, Industrial Publisher, 406 Walnut st., Philadelphia.

TO CAPITALISTS, MANUFACTURERS of Machinists' Tools, etc.—The Patent for the United States, having 15 years to run, of a very valuable Machinists' Tool, a large number of which have been sold, and which has been thoroughly tested during the past 18 mos., is offered for sale because the owner has not sufficient capital to properly push their mianufacture and sale. Any company largely manufacturing machinists' tools, brany capitalists who may wish to invest in the business, tenclear on the investment in this machine, heavy percentages annually.

It will be sold for cash, or part cash and part stock in any Compary purchasing the Patent; or a partner with capital and character will be accepted. The English, French, and Belgian Patents, also, for sale.

For particulars, address

MACHINIST, Fair Haven, Conn.

# AGENTS WANTED.

Y AGENTS say there is more Money and and better satisfaction given, selling my Patent Door Springs, etc., than any other agency business known. Descriptive circulars sent to any person inclosing a 3 c ent stamp.

19 ti]

A. E. TAYLOR, New Britain. Conn.

# WOODWARD'S COUNTRY HOMES.



150 Designs and Plans for HOUSES of moderate cost. \$150 post-paid.

Geo. E. Woodward, Publisher and Geo. E. Woodward,
Publisher and Importer of
ARCHITECTURAL BOOKS 191 BROADWAY, NEW YORK.
Complete Catalogue sent free. [21 tf

THE AMERICAN TURBINE WATER WHEEL, Patented by Stout, Mills, and Temple, possesses new and valuable improvements, and remedies defects which exist in all other Turbine wheels. For cent of power guaranteed to be equal to any overshot wheel. For descriptive circulars address OLIVER & CO., 32 tf Agents, 55 Liberty street, New York.

BALLAUF, MODEL MAKER, No.
Orders for Certified Duplicates of Patent Office Models
and Original Models for Inventors.

16 13\*

A MONTH IS BEING MADE with our IMPROVED STENCIL DIES, by Ladies and Gentlemen. Send tor our free Catalogue containing Samples and Prices. Address 9 tf-R. S. M. SPENCER & Co., Brattleboro, Vt.



PLATINUM—For all Laboratory and Man utacturing purposes. Platinum Scrap and Ore Purchased. H. M. RAYNOR, Office 748 B'dway, N. Y. 8 10\*ec

PICE CAN AND BLACKING BOX
Makers, send for circular of Painter's Parent Rivering device, dispensing with solder. Great economy, 30
Machines in use.

45 Holliday street, Baltimore. Makers, send for circular of Painter's Patent Riverdevice, dispensing with solder. Great economy, 30
chines in use. W. PAINTER & CO.,
3 eow5\*] 45 Holliday street, Baltimore.

TINNER'S TOOLS—Good Second-hand set for sale. GEO. G. ATWOOD, Geneva, N. Y.

WOOD-WORKING MACHINERY, The SUBSCRIBER is Agent in New York for J. A. F. & Co., C. B. Rogers & Co., Ball & Williams, Richards Merriam & Co., H. B. Smith, Gray & Woods, Lane & B. ley, D. Doncaster, and all other manufacturers of Working Wachines. S. C. HILLS, No. 12 Platt st.

# OIL! OIL!! OIL!!!

FIRST PREMIUM.....PARIS, 1867.

# **EXPOSITION UNIVERSELLE!**

PEASE'S IMPROVED OILS! Acknowledged the Best in the World! The Highest Award over all others!

Grand Silver Medal and Diploma! The Only One to the United States awarded to F. S. PEASE,

For the Greatest Excellence in Oils for Lubricating and Burning.

WORLD'S FAIR—TWO PRIZE MEDALS Awarded to F. S. PEASE for Improved Engine, Signai, Lard, and Premium Petroleum, as the Best inade!

These Improved Oils cost no more than many of the common oils in market, while they are en 'orsed by the greatest experience and highest authority in the United States and Europe, and offered to the public upon the most thorough, reliable, and practical tests as the Best Oils made to

Railroads, Steamers, and for Machinery and Burning.
F. S. PEASE, Oil Manufacturer,
Nos. 61 and 63 Main street. Buffalo, N. Y.
N. B.—Reliable orders filled for any part of the world
10 tf

PROPOSALS FOR THE SALE OR
Lease of the PROPERTY OF THE BALTIMORE
WROUGHT IRON PIPE AND TUBE COMPANY, are
invited until November 20th, 1867.
The works are large and fitted up with the most approved schinery for the manufacture of Gas Pipe and
and Boiler Flucs, Flues with Foundery, Machine Shop,
and Galvanizing Shop attached.
Its reputation is established, and the demand larger
than the supply.
Plans of the premises, and tull particulars, may be had
on application to the Secretary, at No. 91 Holliday st.,
20 3!

LEAST OF THE SALE OR
HENRY J. DAVISON,
No. 200 Water st., New York.

#### IMPORTANT TO SMOKERS.

THE Patent on the neat little device illustrated on page 120 of this volume of the control of th trated on page 120 of this volume of the Soientific American, for perforating cigars, is offered for sale on most reasonable terms. Every cigar store, or bar room, or boarding house should have one of the instruments. They are also adapted for individual smokers. The manufacture of them must be very profitable. For rights to manufacture, address OLIVER GUINAND, Patentee, 20 20s 1is]

AINTER, GILDER, AND VARNISH-ER'S COMPANION.—Tenth Edition, with import-ant additions, just ready, price \$1.50 by mail, free of post-age. HENRY CAREY BAIRD, Industrial Publisher, 406 Walnut st., Philadelphia.

FOR SALE—Mineral Land—Missouri Pine and Mineral Land. For sale, my one-third interest in a tract of 4,000 acres, with two Steam Saw Mills and Lead Mines now in course of development. Send for description and map. THOS. ALLEN, 722 South Fourth street St. Louis, Missouri. 21 6\*

POR SAI E CHEAP—A Fifty-six inch in-scrted tooth Circular Saw, made by Woodrough & McParlin, Cincinnati, Ohio. Address 20 3\*1 H, A. & S. G. WIGHT, Detroit, Mich.

ROGINE LATHES, Hand Lathes, Foot Lathes, and Tapping Machines, of the best design and first-class workmanship. Also, special machinery, small tools, etc. Patent articles made to order. 18 5\*] FLATHER & CO., No. 11 Riverst., Nashua, N. H.

PLANE AND MATCHER for \$350, a good, new machine. S. C. HILLS, 12 Platt st. N. Y.

THE FUEL SAVING FURNACE CO., No. 205 BROADWAY N. Y.

STEAM ENGINES—
Superior in Construction, with Sault's Patent Frictionless Slide Valve, the most complete and economical Engine for Manufacturing purposes. Address
10 18\*]
M. & T. SAULT, New Haven, Conn.

WANTED, an Agent—One chance in each town, worthy the attention of an active business man, to take the agency for the sale of Bradstreet's Rubber Molding and Weather Strips, applied to the sides, bottom, top, and center of doors and windows. The sale is beyond anything ever offered before to an agent, and from \$10 to \$25 per day can be made. Send for agent's circular. The first who apply secure a bargain. Terms for Molding, cash. J. R. BRADSTREET & CO., Boston, Mass. 16 13\*

FOR SALE—Very superior upright Drills, first class. Send for cut, 2 t BULLARD & PARSONS, Hawtford, Conn

TODD & RAFFERTY, Manufacturers and DEALDR'S IN MACHINERY.
Works, Paterson, N.J.: Warerooms, 1 Dey st., New York.
Steam Engines and Boilers, Steam Pumps, Machinists'
Tools Also, Flax, Hemp, Tow, and Rope Machinery,
Snow's and Judson's Governors, Second-hand Machinery.

BABCOCK & WILCOX'S

PATENT STATIONARY STEAM ENGINES, Built by the
Hope Iron Works, Providence, R. I.
Warranted Superior to any other engine in the market, for economy of fuel, regularity of speed, and non-liability to derangement. [17 tt] JOS. P. MANION, Agt.

Patent Stretched, Patent Jointed, and Patent Riveted Leather Banding. These Bands are warranted to run straight and maintain a perfect bearing on the pulleys. They are made from the center part, only, of the hide, tanned whole for the purpose, in the best of oak bark, and stretched, both wet and dry, by power machines.

12 14\*1 HOYT BROTHERS, 28 & 30 Spruce st., N. Y.

TUEL Economized and Power Increased by CARVALHO'S PAT. STEAM SUPER HEATER. Guaranteed to remedy "priming," save a large percentage of fuel, and turnish pure, dry steam, of any required temperature. Is easily attached to boilers, very durable, and pays for itself in a few months. Address HENRY W. BULKLEY, General Agent, 70 Broadway, N. Y. 13 12\*

WANTED—Ladies and Gentlemen everywhere, in a business that will pay \$5 to \$20 per no book, patent right, or medical humbug, but a standard article of merit, wanted by everybody, and sold at one third the usual price, with 200 per cent profit to our agents. Samples and circulars sent by mall for 25 cents. 21 tf-D] WHITNEY & SON, 6 Tremont st.. Boston, Mass.

AW'S PATENT SHINGLE and HEAD-L ING MACHINE—The simplest and best in use. Stave Cutters, Jointers, Equalizers, etc. Send for illustrated circular. Address TREVOR & CO., 17 6\*) Lockport, N. Y.

S TOCKS, DIES, AND SCREW PLATES, Horton's and other Chucks. JOHN ASHCROFT, 50 John st., New York.

TURBINE WATER WHEELS.— Luther's Direct and Reacting Turbine Wheels man ufactured and for sale by the NOVELTY IRON WORKS Foot of East 12th 8t., N. Y. Send for Circular. 13 25\*

SETS, VOLUMES AND NUMBERS. Entire sets, volumes and numbers of Scientific ER Can (Old and New Series) can be supplied by ad-ssing A. B. C., Box No. 773, care of MUNN & CO., New

UN AND SEWING MACHINE Screws
of all kinds and sizes on hand and made to order by
LAMB KNITTING MACHINE MF'G CO.,
Successors to the
20 tf ]
Mass. Arms Co., Chicopee Falls, Mass

THE BEST BOLT CUTTER IS MERRI
MAN'S PATENT—Which cuts a full, smooth thread
at once passing over the bolt. The dies revolve, are instantly adjustable to the slightest variation, and open to
release the bolt. Foreign Patents for sale. Send for circulars.

H. B. BROWN & CO.,
New Haven, Conn.

PAPER-BAG MACHINES, and STATE Rights to use, for sale by B. S. BINNEY, 64 Kilby st., Boston, Mass.

SHCROFT'S LOW WATER DETECT ASHCROFT, 50 John st., New York. 21 12

PORTABLE STEAM ENGINES, COMbining the maximum of efficiency, duranility, and economy with the minimum of weight and price. They are widely and favorably known, more than 600 being in use. All warranted satisfactory or no sale. Descriptive circulars sent on application. Address

J. C. HOADLEY & CO., Lawrence, Mass.

1 tf

DOUGLASS MANUFACTURING CO. Exclusive Manufacturers of COOK'S PATENT BORING IMPLEMENTS.

#### Also, a complete assortment or MECHANICS' TOOLS



Framing Chisels, Socket Firmer Chisels and Goures, Socket Paring Chisels, Drawing Knives, Screwdrivers Augers and Bits, Bung Borers, Boring Machines, Gimlets, Firmer Chisels and Googes, Hollow Augers, Corkscrews, etc.

Warehouse, 70 Beekman street. New York. 10 tf

MODELS, PATTERNS, EXPERIMENT-AL and other Machinery, Models for the Patent Office, built to order by HOLSKE MACHINE CO., Now. 528, 530, and 532 Water street, near Jefferson. Refer to Scientific American Office.

WATER WHEELS.—
The Helical Jonval Turbine is manufactured by
J. E. STEVENSON, 40 Dey street, New York.

CHARLES A. SEELY, CONSULTING and Analytical Chemist, No. 26 Pine street, New York. Assays and Analyses of all kinds. Advice, Instruction, reports, etc., on the useful arts.

A IR SPRING FORGE HAMMERS ARE A made by CHAS. MERRILL & SONS, 556 Grand street, New York. They will do more and better work, with less power and repairs, than any other Hammer. Send for a circular.

ROLLING MILL
MACHINERY AND CASTINGS.
Address [194\*] GREENLEAF & CO., Indians, polis, Ind.

THE

# HARRISON BOILER

Is the only one now offered for sale entirely FREE from DESTRUCTIVE EXPLOSION.

Twenty thousand horse-power have been made and put in operation within the last three years, with a constantly increasing demand. For descriptive cfreulars and price apply to the Harrison Boiler Works, Philadelphia, Pa., or to J. B. HYDE, Agent, 19 tf] Offices 9 and 10, No. 119 Broadway, N. Y.

A PRIZE MEDAL of The Paris Exhibition was awarded to SHAW & JUSTICE

#### for their DEAD STROKE POWER HAMMER.

The great satisfaction given by these Hammers whereever introduced, warrants the Patentee in asserting them
to be THE BEST, as well as the most economical Hammer in use. They are made of sizes suitable for forging
Iron from 10 in. to ½ in. square, and are employed in
manufacturing axless for locomotives as well as carriages;
also, for axes, hatchets, hoes, shovels, agricultural implements, table cuttery, and die work generally, with equal
success. For State Rights (not sold) and Hammers, address the Fatentee, [17 tf] PHILIP S. JUSTICE,
14 Zorth 5th street, Philadelphia, or 42 Cliff st., New York.

DATENT SHINGLE, STAVE, AND
Barrel Machinery, Comprising Shingle Mills, Heading Mills, Stave Cutters, Stave Jointers, Shingle and
Heading Jointers, Heading Rounders and Planers, Equallzing and Cut-off Saws. Send for Illustrated List.
FULLER & FORD,
17 tf] 252 and 284 Madison street, Chicago, Ill

REAT ECONOMY IN FUEL.—

The Washington Iron Works' New Steam Engine, with Variable Cut-off, worked by the Governor patented by Wm. Wright, Oct. 1866, is the most perfectly simple and economical Engine, yet introduced, saving 50 per cent in fuel. This engine takes the lead of all others, and is being put in in different parts of New England, this city, Philadelphia, and in the principal manufacturing districts of the country. For information address WASHINGTON IRON WORKS, WASHINGTON IRON WORKS, Or apply at the office of the Company, 57 Liberty st., New York City. Circulars sent to order.

22 tf

CTEAM ENGINES.—COOK, RYMES & Co.'s celebrated first-class stationary, portable hoisting engines constantly on hand, at their warero 107 Liberty street. New York.

AN I OBTAIN A PATENT?—For Advice and instructions address MUNN & CO., 37 Park Row New York for TWENTY YEARS Atterneys for American and Foreign Patenta Caveats and Patents quickly prepared. The Scientific American § 3 a year. 30,000 Patent cases have been prepared by M. & Co.

FOR ENGINE BUILDERS' AND STEAM Fitters' Brass Work, address
10 26\*1 Cincinnati Brass Works.

WHEELER & WILSON, 625 BROAD-way, N. Y.—Lock-stitch Sewing Machine and But tonhole do.

SHEET AND ROLL BRASS, BRASS AND COPPER WIRE, GERMAN SILVER, ETC. Manufactured by the THOMAS MANUFACTURING CO.,

Thomaston, Conn.
Special attention to particular sizes and widths for Type
Founders, Machinists, etc. 2 26\*

VOODWORTH PLANERS A SPE-proved style and workmanship. Wood-working Machine-ry generally. Nos. 24 and 26 Central, corner Union street, worcester, Mass. 12 15\*tij WITHERBY, RUGG & RICHARDSON.

DUERK'S WATCHMAN'S TIME DETECTOR.—Important for all large Corporations and Manutacturing concerns—capable of controlling with the utmost accuracy the motion of a watchman or patrolman, as the same reaches different stations of his beat. Send for a Circular.

J. E. BUERK,
N. B.—This detector is covered by two U. S. patents,
N. B.—This detector is covered by two U. S. patents,
Parties using or selling these instruments without authority from me will be dealt with according to law.

819\*

MPORTANT.

MOST VAJUAFILE MACHINE for all kinds of irregular and straight work in wood, called the Variety Moloing and Flaning Machine, indispensable to competition in all branches of wood-working. Our improved guards make it self to operate. Combination collars for cuttery, saving 100 per cent, an feed table and connection, for waved moldings and planing, place it above all others. Evidence of the superiority of these machines is the large numbers we superiority of these machines is the large numbers we superiority of these machines is the large numbers we superiority of these machines is the large numbers we superiority of these machines is the large numbers we superiority of these machines is the large numbers we superiority of these machines are consumed to the superiority of these machines are superiority of these machines are superiority of these machines, and parties large numbers we superiority of these machines are to state of the superiority of these machines are tested before defined and Planing Machine Company, Post-office Box 3290, New York. All our machines are tested before defined and planing was a superiority and warranted.

O IRON FOUNDERS.--

By using the waste heat from a Cupola Furnace, connected with a Harrison Boiler, a saving of the entire cost of fuel for the blast can be guarenteed.

As thus applied, it may be seen daily in operation from 2 to 50 clock, b. m., at the Harrison Boiler works, Gray't Ferry Road, Philadelphia Pa. J. B. HYDE, Agent, 17 ti

PABCOCK & WILCOX'S PATENT
STATIONARY STEA & ENGINES,
From 25 to 1,000 horse-power, built in the best manner and at the shortest notice by the
South Brooklyn Steam Engine & Boiler Works
Imlay, Summ; and Van Brunt, sts., Brooklyn, N. Y.
Prover 4,000 horse-power of these engines are now running and contracted for.

17 tf]
D. McLEOD, Proprietor.

RICHARDSON, MERIAM & CO.,

Manuracturer: and Dealers in

DANIELL'S AND WOODWORTH PLANERS.

Boring, Matching, Molding, Mortsing and Tenoning Mschines, Scroll, Cut-off, and Slitting Saws, saw Mills, Saw

Arbors, Spoke and Wood-turning Lahles, and other wood

working Machinery. Warchouse, 107 Liberty street, New

York. Manufactory, Worcester Mass.

DATENT POWER AND FOOT-PUNCH-ING PRESSES, the best in market, manufactured by N. C. STILES & CO., West Meriden, Conn. Cutting and Stamping Dies made to order. Senafor Circulars. 1413\*tf

OR FIRST-CLASS SHAFTING WITH Patent Selt-oiling Boxes and adjustable Hangers, also Mill Work and special machinery, address I tf BULLARD & PARSONS, Harword, Conn.

WOOD, LIGHT & CO.—MANUFAC-turers of Machinists' Tools and Naysmyth Ham-mers, Lathes from 4 to 30 feet long, and from 15 to 100 inches swing. Planers from 24 to 60 inches wide and from 4 to 46 feet long. Upright Drills Milling and index Milling Ma-chines. Frofile or Edging Machines. Gun Barrel Machines Shatting, Mill Gearing, Pullers and Hangers, with Patent Self-oiling Boxes. Works, Junction Shop, Worcester, Mass. Warehouse at 107 Liberty street, New York. 15 th

PRESSURE BLOWERS.—Equal in Force to Piston Blowers, and a perfect substitute for both Fan and Pistons—running more easily than either. Adapted for Blast, and Cupola, and Heating Purposes, Forges Steamships, Boilers. Ventilation, etc., etc. Prices according to sizes, ranging from \$25 to \$1.590. Addrss, for Circular B. F. STURTEVANT, 12 Sudbury street, Boston, Mass.

THE CELEBRATED "SCHENCK" WITH NEW AND IMPORTANT IMPROVEMENTS,
Manufactured by the
SCHENCK MACHINE O., MATTEAWAN, N. Y.
JOHN B. SCHENCK, President,
T. J. B SCHENCK, Treas.

14 tf

RON PLANERS, ENGINE LATTIES, Drills, and other Machinists' Tools, of Superior Quaity, on hand and finishing. For Sale Low. For Description and Price, address NEW HAVEN MARUE ACTURING CO., New Haven, Ct.

A NDREWS'S PATENT PUMPS, ENGINES, etc.-GINES, etc.— CENTRIFUGAL PUMPS, from 30 Gals. to 40,000 Gals per minute, capacity.
OSCILLATING ENGINES (Double and Single), from

OSCILLATING ENGINES (DOUBLE and CHRISE), 10-22 to 26 horse-power, con 2 to 50 horse-power, con 2 to 50 horse-power, con 2 to 16 horse-power, con 2 to 16 horse-power. TEAM HOISTERS to 16 horse-power. These machines are all first-class, and are unsurpassed for compactness, simplicity, durability, and economy of working. For descriptive pamphlets and price list address the manuscrurers, W.D. ANDREWS & BEO., 1 tf No. 419 Water street N. X

PHOENIX IRON WORKS-

PHOENIX IRON WORKS

Established 1834.

GEO. S. LINCOLN & CO.,

Iron Founders and Manutacturers of Machinists' Tools

54 to 60 Arch street, Hart. ord, Conn.

We are prepared to furnish first-class Machinists' Tools
on short notice. Samples may be seen in our Wareroom.

Also, we keep constantly on hand our Patent FRICTION
PULLEY, Counter Shafts for Lathes, etc.

MASON'S PATENT FRICTION
CLUTTHES, for starting Machinery, especially
Heavy Machinery, without sudden shock or jar, are man
ulactured by VOLNEY W.MASON,
14tf ]
Providence, R. I.

RAY'S PATENT WATER-PROOF Roof-ing Paper, etc. Send red stamp for Circular and sample of Paper. 12 13'] Second and Vinestreets, Canden, N. J.

DORTABLE AND STATIONARY Steam
Engines and Boilers, Circular Saw Mills, Mill Work
Cotton Gins and Cotton Gin Materials, manufactured
by the ALBERTSON & DOUGLASS MACHINE CO.,
New London, Conn. 14 tf

MACHINE CARD CLOTHING.—

Manufacturers of Cotton, Wool, and Flax Machine Card
Clothing of every variety. E. S. LAWRENCE,
Supt., Worgester, Mass. Sargent & Co., Agents, 70 Beck,
unan street them York.

NITRO-GLYCERIN.—
UNITED STATES BLASTING GIL CO.—We are now prepared to fill all orders for Nitro-Glycerin, and respectfully invite the attention of Contractors, Miners and Quarrymen to the immense economy in the use of the

JAMES DEVEAU, Sec., SZ. Place street, New York

RICSSON CALORIC ENGINES OF GREATLY IMPROVED CONSTRUCTION.—Ten years of practical working by the thousands of these engines in see, have demonstrated beyond card their superiority where less than ten borse-power is required. Portable and Stationary Steam Engines, Crist and Saw Mills, Cotton Gins' Air Pumps, Shatting, Pulleys, Gearing Pumps, and General Joibling. Orders promptly filled any kind of Machinery. JAMFS A. ROBINSON, 1tt—D] 164 Duane street, cor. Hudson, New York.

BALL & CO., SCHOOL STREET, WORCESTER, MASS., MEANIFICTURES OF WOODWORTH'S, Daniell's, and Gray & Wood's Planers, Sash Molding, Tenoning, Mortising, Upright and Vertical Shaping, Boring Machines, Scroll Saws and a variety of other Machines and articles for working wood.

Send for our Illustrated Catalogue. ATHE CHUCKS-HORTON'S PAT-ATITE OTTO A to 36 inches Also for car wheels, Manufacturer's address, E. HORTON & SON, Windsor 1 23\* Locks, Conn.

EMPLOYMENT! \$10 a day and Expenses paid, Circulars free. O. T. GAREY, Biddeford, Mc



# ATENTS

will give him all the directions needful to protect his rights.

Messrs. MUNN & CO., in connection with the publication of the SCIENTIFIC AMERICAN, have been actively engaged in the business of obtaining patents for over twenty years—nearly a quarter of a century. Over Fifty thousands inventors have had benefit from our counsels. More than one third of all patents granted are obtained by this firm

than one third of all patents granted accounts of the firm.

Those who have made inventions and desire to consult with us, are cordially invited to do so. We shall be happy to see them in person, at our office, or to advise them by letter. In all cases they may expect from us an honest opinion. For such consultations, opinion, and advice, we make no charge. A pen-and-ink sketch, and a description of the invention should be sent, together with stamps for return postage. Write plainly, do not use pencil nor pale ink; be brief.

All be smess committed to our care, and all consultations.

ink; be brief.
All business committed to our care, and all consultations, are kept by us secret and strictly confidential. Address MUNN & CO., 37 Park Row. New York.

tions, are kept by us secret and strictly confidential. Address MUNA & Co. 37 Park Row. New York.

Preliminary Examination,—In order to obtain a Preliminary Examination, make out a written description of the invention in your own words, and a rough pencil or pen-and-ink sketch. Send these with the fee of \$5\$ by mail, addressed to MUNN & CO. 37 Park Row, and in due time you will receive an acknowledgment thereof, followed by a written report in regard to the patenta bility of your improvement. The Preliminary Examination consists of a special search, which we make with great care, among the models and patents at Washington to ascertain whether the improvement presented is patentable.

In Order to Apply for a Patent, the law requires that a model shall be furnished, not over a foot in any dimensions,—smaller, if possible. Send the model by express, pre-paid, addressed to Munn & Co., 37 Park Row, N. Y., together with a description of its operation and merits. On receipt thereof-we will axamine the invention carefully and advise the party as to its patentability, free of charge.

The model should be neatly made of any suitable materials, strongly fastened, without glue, and neatly painted. The name of the in ventor should be engraved or paintenance of the invention, of ull working more of the whole machine will not be necessary. But the model must be sufficiently perfect to show, with clearness, the nature and operation of the improvement.

New medicines or medical compounds, and useful mixtures of all kinds, are patentable.

When the invention consists of a medicine or compound, or a new article of manufacture, or a new composition, samples of the article must be turnished, neatly put up. Also, send us a full statement of the ingredients, proportions mode of preparation, uses, and merits.

tions mode of preparation, uses, and merits.

Relssues.—A reissue is granted to the original patentee, his heirs, or the assigneds of the entire interest, when by reason of an insufficient or defective specification the original patent is invalid, provided the error has arisen from inadvertence, accident, or mistake without any fraudulent or deceptive intention.

A parentee may, at his option, have in his reissue a separate patent for each distinct part of the invention comprehended in his original application, by paying the required fee in each case, and complying with the other requirements of the law, as in original applications.

Each division of a reissue constitutes the subject of a separate specification descriptive of the part or parts of the invention claimed in such division; and the drawing may represent only such part or parts. Address MUNN & CO., 37 Park Row, for full particulars.

Interferences.—When each of two or more persons

Loc., 37 Park Row, for full particulars.

Interferences,....when each of two or more persons claims to be the first inventor of the same thing, an "interference" is declared betwe n them, and a trial is had before the Commissioner. Nor does the fact that one of the parties has aiready obtained a patent prevent such an interference; for, although the Commissioner has no power to cancer a patent aiready issued, he may, if he linds that another person was the prior inventor, give him also a patent, and thus place them on an equal footing before the courts and the public.

Caveats,—A Caveat gives a limited but immediate protection, and is particularly useful where the invention is not fully completed, or the model is not ready, or further time is wanted for experiment or study. After a Caveat has been filed, the Patent Office will not issue a patent for the same invention to any other person, without giving notice to the Careator, who is then allowed three months time to file in an application for a patent. A Caveat, to be of any value, should contain a clear and concise description of the invention, so far as it has been completed, illustrated by drawings when the object admits, in order to file a Caveat the inventor needs only to send us a letter containing a sketch of the inventor, with a description in his own words. Address MUNN & CO., 37 Park Row, N. Y.
Additions can be made to Caveats at any time. A Caveat runs one year, and can be renewed on payment of \$10 a year for as long a period as desired.

Quick Applications.—When, from any reason,

Quick Applications.—When, from any reason, par as are desirous of applying for Patents or Caveats, in GP at maste, without a moment's loss of time, they have only to write or telegraph us specially to that effect, and we will make special exertions for them. We can prepare and mail the necessary papers at less than an hour's notice, if required.

prepare and mail the necessary papers at less than an hour's notice, if required.

Foreign Patents,—American Inventors should bear in mind that, as a general rule, any invention that is valuable to the patentee in this country is worth equally as as much in England and some other foreign countries. Five Patents—American, English, French, Belgian, and Prussian—will secure an inventor exclusive monopoly to his discovery amone one huxdred and the world. The tachities of business and steam communication are such that patents can be obtained a broad by our citizens almost as easily as at home. The majority of all patents taken out by Americans in foreign countries are obtained through the Scientific Americans for information and a Sunopsis of the Patent Laws of various countries will be furnished on application to Messrs. Munn & Co.

For Instructions concerning Foreign Patents, Reissues, Interferences, Hints on Selling Patents, Rules and Proceedings at the Patent Office, the Patent Laws, etc., see our Instruction Book. Sent free by mail on application. Those who receive more than one copy thereof will oblige by presenting them to their friends.

MUNN & CO.,

# MUNN & CO.,

No. 37 Park Row, New York City. Office in Washington, Cor. F and 7th streets.

Patents are Granted for Seventeen the following being a schedule of fees:-	Years
On filing each Caveat	\$10
On filing each application for a Patent, except	for a \$1:
On issuing each original Patent.	\$20
design. On issuing each original Patent On appeal to Commissioner of Patents On appelation for Reissue. On application for Extension of Patent. On granting the Extension.	\$30
On application for Extension of Patent	\$50
On filing a Disclaimer	\$50 \$10
On filing a Disclaimer On filing application for Design (three and a	half
years) On filing application for Design (seven years)	\$10 \$15
On filing application for Design (fourteen years).	
In addition to which there are some small revenu taxes. Residents of Canada and Nova Scotia pay	e-stamp
application	ψουσ οι

PATENT CLAIMS.—Persons desiring the claim of any invention, patented within thirty years, can obtain a copy by addressing a note to this office, giving name of patentee and date of patent, when known, and inclosing \$1 as a fee for copying. We can also furnish a sketch of any patented machine to accompany the claim, at a reasonable additional cost. Address MUNN & CO. Patent Solicitors, No. 37 Park Row, New York.

### Advertisements.

A limited number of advertisements will be admitted in this page on the following terms: Seventy-five cents a line, each insertion, for solid matter; one dollar a line for space occupied by engravings.

## GREAT ECONOMY IN WATER POWER.

EFFEL'S DOUBLE TURBINE WATER

Our wheels are as well adapted to low as high falls. Some of them are running successfully under three feet fall.

Danville, Vermillion Co., Ill., Aug. 16, 1867.

Messrs. Jas. Leffel & Co., Springfield, Ohio.—

Gents:—In answer to your inquiries of the 13th inst., we would say, your wheel, that we are now running in our factory (in the place of the overshot wheels), is only six inches in diameter, and one inch wide, and draws two and a quarter square inches of water. We have never used over one-third of a gate, or about three-quarters of a square inch, to drive all our machinery, our fall being forty (40) feet. Our overshots were each twenty feet in diameter, placed one above the other, and connected by a pinion between them. Your wheel runs one set of cards, one jack of one hundred and eighty-four spindles, two looms, etc., with scant one-third gate. We can do double i he amount of work with your wheel that we could with the two overshots it displaced, and we Delieve that there was never better overshots built than the ones we had.

Our Springs afford only eighty-four gallons of water

that there was never better overshots built than the ones we had.

Our Springs afford only eighty-four gallons of water per minute, and as the quantity has never varied scarcely one cubic foot per day for years, and as we have known exactly how many pounds of wool we could work with our overshots, it is clearthat we have the best means of judging of the comparative merits of your wheel and the overshots. As to the durability, we have now been running it over four months constantly, although the wheel makes near fourteen hundred revolutions per minute, there has not been the least perceptible wear in any of its par's. We think that the workmanship cannot be surpassed, for it seems to us that it is perfect. We are perfectly satisfied with the change we have made, and give you the above to do as you think proper with.

Yours Truly,

Monitowne Wis 22th pit 1867

Manitowac, Wis., 22th ult., 1867.
We, the undersigned, have in use at our Mills, in the town of Cato, one of Leffel's double Turbine Water Wheels. To say that we are pleased with it would express but little of the satisfaction we feel. It more than meets our expectations, and does all that the manufacturers claim for it.

It gives double power; is small in size; no leakage; cannot be trozen up; and will run with a very low head of water.

Iowa City, Iowa, Oct. 3, 1867.

Mess rs. Jas. Leffel & Co.,
Gents:—From a sense of duty we subjoin the following:
We this summer put in three (3) of your 40 inch, and one
of your 48-inch wheels, which are running under from five
to six feet head. The 48-inch wheel is driving one run of
4½ burrs, and one fourfeet, grinding from 18 to 20 bushels
per hour.
We consider them far beyond any other wheel in point
of steadiness and convenience, heartily recommending
them as the best we have ever used, and conclude they
cannot be surpassed by any other wheel.
Yours Truly.
CLOSE BRO.

Lucius W. Pond,

# Iron and Wood Tools. And Machinery,

TURBINE WATER WHEELS.

Works at Worcester, Mass. Sale Rooms S5 Liberty st., (2 doors West or Broad-

way), New York. 22 tf os

METTAM'S GALVANO ELECTRO ME-talic Insoles, Belts, and Armlets, for the cure of Rheumatism, Gour, Neuragia, Cold Feet, and all diseases of the blood and nerves. Send for circular. LORIN BROOKS & SONS, Boot and Shoe dealers, 434 Broadway, New York, General Agents. 22 10s

WANTED—To buy a No. 1 Patent Right.
Address J. K. ROSS, Noblesville, Ind. os 1\*

#### WHITE LEAD.

THE MANHATTAN WHITE LEAD CO. are now granting licenses under their Letters Patent. Their process is simple, cheap, and rapid. Their product is equal in whiteness and superior in body to any other White Lead. The cost fof manufacture is several cents per pound less than the old process. For terms apply at the office of the Company.

22 os2\*] ABRAHAM BELL'S SON, 25 Park Row.

#### TURBINE WATER WHEELS.



REYNOLUS PATENT
embodies the progressive spirit of the age. Simplicity, Economy, Durabili
ed. The only Turbine that
excels Overshots. Awarded the Gold Medal by American Institute.
Shafting, Gearing and Pulleys furnished for all kinds
of Mills, made on Mechancal Principles, under my personal supervision, having
had long experience. Circulars sent free.

GEORGE TALLCOT, No.96 LIBERTY STREET, NEW YORK.

JOSEPH A. MILLER'S Improvements in OSEPH & MILLER'S Improvements in steam Boilers cause greater economy in fuel than any other inventions of the Age. They double the capacity of most boilers, save at least 33 per cent in fuel, insure perfect safety from explosion, and give perfectly dry steam. 6,000 horse-power put up this year in the largest and best esablishments in the country, such as A. & W.Sprague, R. I.; Merchants'Mf'g Co., Fall River; American Frint Works, do., Middlesex Bleachery, Boston; Manchester Print Works, N. H.; Prov. Drying, Bleaching, and Call. Co.; Clyde Print Works, River Point, R. I.; Fales, Jenks & Sons. Pawtuckett, R. I.; W. H. Dudley, Keyport, N. J., etc., etc. For circulars and information apply to J. E. STEVENSON, 40 Dey st., N. Y.; Wesson & Phillips, Prov. R. I.; Horace McMurtrie & Co., 38 & 85 North st., Boston; E. S. Frazer, Boardmens' Ins. Co. Cincinnati, O. 20 4\* os

WHEATON'S OINTMENT cures the Itch WHEATON'S OINTMENT will cure Salt Rheum WHEATON'S OINTMENT cures Old Sores. WHEATON'S OINTMENT cures all diseases of the Skin Price 50 cents;—by mail 60 cents. All Druggists sell it WEEKS & POTTER, Boston, Proprietors, [14 13 os tf-N

# SLATE SLABS.

Any size, shape, and thickness for sale by HUDSON RIVER SLATE CO. Samples, Plain and Marbleized, shown at their office 21 408\*]

A GENTS WANTED—\$10 to \$20 a day, to introduce onr new patent Star Shuttle Sewing Machine. Price \$20. It uses two threads, and makes the genuine Lock STATOR. All other low-priced machines make the Chain Stitch. Exclusive territory given. Send for circulars. W. G. WILSON & CO., Manufacturers, Cleveland, Ohio. GENTS WANTED-\$10 to \$20 a day

BEFORE BUYING TURBINE WATER WHEELS—Sendfor Circulars of PEEKSKILL MANUFACTURING CO., Peekskill, N. Y.

# AGENTS WANTED.

MY AGENTS Say there is more Money made and better satisfaction given selling my Patent Door Springs, etc., than any other agency business known. Descriptive circulars sent to any person enclosing a 3 cent stamp.

19 tros

VALUABLE PATENT RIGHT FOR SALE.—The weighing and measuring cup, patented Nov. 1867. An article long needed by every family in the land. Thoroughly practical, extremely simple, yet very accurate, and so cheap as to be within the reach of all; by means of which housekeeepers can prepare the ingredients for pastry, preserves, etc., etc., and that too by a utensil useful for many other purposes, simply a dipper.

of the tension useful for many observables.

Rights for the Eastern, Southern, and Western States, for sale, at reasonable rates. Reliable agents wanted to introduce the "Cup" everywhere. Jobbers supplied to any extent required. Samples furnished for 50 cents. For further particulars address

GODES, MILLER & MORFORD,

Patentees and Manufacturers.

21 2\*]

No. 653 Franklin street, Philadelphia.

PUBLIC SALE OF VALUABLE FOUNdery, Maciane, and Stove Works, Nov. 21, 1867, with water power, situated in Frederick, Md. For plat description and list of patterns, apply to M. C. YOUNG, Frederick, Md.

RAWING INSTRUMENTS

Swiss, German Silver, and French, separate and in cases—
DRAWING BOARDS, DRAWING PAPER, WATER
COLORS, TRANSITS, LEVELS, COMPASSES, etc.
And all supplies for Engineers, Architects, or Machinists.
A Priced and Illustrated Catalogue sent free on application.

WILLIAM Y McALLISTER,
14 120s\*] 728 Chestnut street, Philadelphia Pa.

EUROPEAN AGENCY for the Exhibition BLANCHARD & McKEAN,

No. 3 Rue Scribe, Paris, France,
Will attend personally and promptly to all business relating to the interests of American Inventors and Manufacturers in Europe. Corresponce solicited.
GEO. A. BLANCHARD.] 15 to 6 [J. A. McKEAN.

OACH PAINTERS will find Practical Directions for Coach Painting and Varnishing in tenth edition of Painter, Gilder, and Varnisher's Companion, now ready, price \$1.50 by mail, free of postage. HENRY CAREY BARD, Industrial Publisher, 406 Walnutst, Philadelphia.

STEAM AND WATER GAGES, STEAM Whistles, Gage Cocks, and Engineer's Supplies.
21 12 JOHN ASHCROFT, 50 John st., New York.

GOOD CHANCE FOR BUSINESS IN A the Best Manuracturing City in New England. The subscriber offers for sale his Corlis Engine and Reynolds Patent Boiler, now running in his factory. The purchaser can also rent or buy the building. For further particular inquired. plars inquire of N. C. STILES, West Meriden, Conn.

T. TRIMMER'S Smut Machines and Separators, manufactured at the Rochester Agricultural Works, Rochester, N. Y. 21 13\* T. TRIMMER'S Smut Machines and

WANTED—AGENTS EVERYWHERE to sell the Magic Cleansing Cream. Sample doz., terms, show cards, etc., sent on receipt of \$2.

D. CUMMINGS & CO,
21 4] 42 South Market street, Boston.

A. BAGLEY & CO., Manufacture ed from the bar, and of extra quality, and case-hardened to order, and used in the construction of all kinds of machinery. Orders solicited. Send for price list and circular.

E. A. BAGLEY & CO.,

Worcester, Mass.

FOR SALE—2 Shapers,  $6\frac{1}{2}$  stroke, and one Lathe, 18 Swing, 9 ft. Bed. All kinds of machinery made to order. LOUIS DUVINAGE, 580 Hudson st., N.Y.

WROUGHT-Iron Pipe for Steam Gas and Water; Brass Globe Valves and Stop Cocks, Iron Fittings, etc. JOHN ASHCROFT, 50 John st., N. Y. 21 12

PAINTER, GILDER, AND VARNISH-ER'S COMPANION, Tenth Edition, contains the best practical directions for Glass Staining Sign Painting, Imitation of Woods, Marbles, Tortoise Shell, etc., price \$15 by mail. free of postage. HENRY CAREY BAIRD, Industrial Publisher, 406 Walmut st., Philadelphia.

UST PUBLISHED—THE INVENTOR'S JUST PUBLISHED—THE INVENTOR'S and MECHANIC'S GUIDE—A new book upon Mechanics, Patents, and New Inventions. Containing the U. S. Patent Laws, Rules and Directions for doing business at the Patent Office; 112 diagrams of the best mechanical movements, with descriptions; the Condensing Steam Engine, with engraving and description; How to lavent; How to Obtain Patents; Hims upon the Value of Patents; How to sell Patents; Forms for Assignments; Information upon the Rights of Inventors, Assignees and Joint Owners; Instructions as to Interferences, Reissues Extensions, Caveats, together with a great variety of useful information in regard to patents, new inventions and scientific subjects, with scientific tables, and many illustratons. 108 pages. This is a most value able work. Price only 25 cents. Address MUNN & CO. 37 Park Row. N. Y.

A MESSIEURS LES INVENTEURS—
Avis important. Les inventeurs non familiers avec
la langue Anglaise, et qui préféreraient nous communiquer leurs inventions en Français peuvent nous addresser dans leur langue natale. Envoyez nous nu dessin et
une description concise pour notre examen. Toutes
communications serons reçus en confidence.

MUNN & CO., Norte MESSIEURS LES INVENTEURS-

MUNN & CO., Scientific American Office, No. 37 Park Row, New York



# 🔁 Scientific American.

THE

BEST NEWSPAPER IN THE WORLD.

# Published Twenty-Two Years.

This paper differs materially from other publications being an Illustrated weekly paper containing 16 large pages, devoted to the promulgation of information relating to the various Mechanical and Chemical Arts. Photography, Manufactures, Agriculture, Patents, Inventions Engineering, Mill Work, etc.

Every number contains several beautiful engravings of new machines.

All the most valuable discoveries are delineated and described in its issues, so that, as respects inventions, it may be justly regarded as an Illustrated Repertory, where the Inventor may learn what has been done before him in the same field which he is exploring, and where h may bring to the world a knowledge of his own achiev

The contributors to the SCIENTIFIC AMERICAN ar among the most eminent scientific practical men of the

nics, Inventors, Engine ers. Chemists. rers, Agriculturists, and people in every walk of life, will find the Scientific American to be of great value in their respective callings. Its counsels and suggestions will save them hundreds of dollars annually, beside affording them a continual source of knowledge.

An official list of all Patents granted, together with the claims thereof, is published weekly.

The form of the Scientific American is adapted fo binding and preservation; and the yearly numbers make two splendid volumes of nearly one thousand quarto

Published Weekly, \$3 a year, \$1.50 half-year, 10 copies for 1 year, \$25. Specimen copies sent gratis. Address

#### MUNN & CO., No. 37 Park Row, New York.

JUST PUBLISHED—THE INVENTOR'S AND MECHANIC'S GUIDE.—A new book upon Mechanics, Patents, and New Inventions. Containing the U.S. Patent Laws, Rules and directions for doing business at the Patent Office; 112 diagrams of the best mechanical movements, with descriptions; the Condensing steam Engline, with engraving and description; How to Obtain Patents; How to sell Patents; Forms for Assignments; Information upon the Rights of Inventors; Assignments; Information upon the Rights of Inventors; Assignments and Joint Owners; U.S. Census by Counties, together with a great variety of useful information in regard to patents, new inventions and sci.ntific subjects, with scientific tables, and many illustrations. 108 pages. This is a most valuable work. Frice only 25 cents. Address MUNN & CO. 37 Park Row, New York.

# CIRCULAR SAWS,



# WITH

# EMERSON'S PATENT MOVABLE TEETH.

These Saws are meeting with

UNPRECEDENTED SUCCESS.

GREAT SUPERIORITY  $\begin{array}{cccc} And & their \\ OVER & EVERY & OTHER & KIND, \\ Both & as & to \end{array}$ EFFICIENCY AND ECONOMY

Is now fully established. Also,

EMERSON'S PATENT PERFORATED

CROSS CUTTING, CIRCULAR, AND LONG SAWS.

(All Gumming Avoided.) And

EMERSON'S PATENT ADJUSTABLE SWAGE,

For Spreading, Sharpening, and Shaping the Teeth of all Splitting Saws. Price \$5. Manufactured by the

AMERICAN SAW COMPANY,
Office No. 2 Jacob street, near Ferry street, New York.
Send for New Descriptive Pamphlet and Price List. 21 tf